

Objective:

To develop a website using HTML5 tags and apply styles to the website using advanced CSS3 properties such as rounder corners, border images, multiple backgrounds, gradients, shadows.

Description:**Rounded Corners**

- The CSS border-radius property defines the radius of an element's corners.

border-radius: 25px

- Four values - border-radius: 15px 50px 30px 5px; (first value applies to top-left corner, second value applies to top-right corner, third value applies to bottom-right corner, and fourth value applies to bottom-left corner):

Border Image

The CSS border-image property allows you to specify an image to be used instead of the normal border around an element. The property has three parts:

1. The image to use as the border
2. Where to slice the image
3. Define whether the middle sections should be repeated or stretched

border-image: url(border.png) 30 round

border-image: url(border.png) 30 stretch

Multiple Backgrounds

CSS allows to add multiple background images for an element, through the background-image property. The different background images are separated by commas, and the images are stacked on top of each other, where the first image is closest to the viewer. The following example has two background images, the first image is a flower (aligned to the bottom and right) and the second image is a paper background (aligned to the top-left corner):

```
#example1 {
```

```
background-image: url(img_flwr.gif), url(paper.gif);
```

```
background-position: right bottom, left top;
background-repeat: no-repeat, repeat;
}
```

Background Size

The CSS background-size property allows you to specify the size of background images. The size can be specified in lengths, percentages, or by using one of the two keywords: contain or cover. The following example resizes a background image to much smaller than the original image (using pixels):

```
#div1 {
  background: url(img_flower.jpg);
  background-size: 100px 80px;
  background-repeat: no-repeat;
}
```

Pseudo classes

Use pseudo-classes focus, required, valid, hover to enable CSS in the <input> elements.

```
input:focus{
  border: 3px solid red;
  background-color: green;
}
input:required{
  border: 3px solid blue;
  background-color: yellow;
}
input[type="email"]:invalid{ color:red; }
input[type="email"]:valid{ color:blue; }
<table ><tr><td class="itemName">item1</td>
  <td class="itemImg"></td></tr> </table>
.itemImg{ opacity :0.2;      }
.itemName:hover + .itemImg{   opacity: 1;  }
```

Hint: itemName and itemImg are adjacent sibling. On hover of itemName select its adjacent sibling itemImg.

Set different colors for odd and even rows and change the background color on mouse over. [hint: nth-child(odd) and nth-child(even)].

Sample web page design:

