BLAUPUNKT

BLAUPUNKT Brand established 1924 GERMANY

EV CHARGING **CABLE**

TYPE 2 to TYPE 2 Cable



SPECIFICATIONS:	1-PHASE	1-PHASE	3-PHASE	3-PHASE
Model No.:	**A1P16AT2**	**A1P32AT2**	**A3P16AT2**	**A3P32AT2**
Working Voltage:	220V ~ 250V	220V ~ 250V	380V ~ 450V	380V ~ 450V
Rated Current:	16A	32A	16A	32A
Insulation Resistance:	>1000MΩ	>1000MΩ	>1000MΩ	>1000MΩ
Resistance Voltage:	2000V	2000V	2000V	2000V
Contact resistance:	Less than 0.5mΩ	Less than 0.5mΩ	Less than 0.5mΩ	Less than 0.5mΩ
Insertion and Extraction Force:	80N<F<100N	80N<F<100N	80N<F<100N	80N<F<100N
Main Material:	Thermo Plastic/ SiliconRubber/ Copper Alloy	Thermo Plastic/ SiliconRubber/ Copper Alloy	Thermo Plastic/ SiliconRubber/ Copper Alloy	Thermo Plastic/ SiliconRubber/ Copper Alloy
Cable Spec.:	3*2.5mm²+2*0.5mm²	3*6mm²+2*0.5mm²	5*2.5mm²+2*0.5mm²	5*6mm²+2*0.5mm²
Cable Length:	8m	8m	8m	8m
IP-class:	65	65	65	65
Fire rating:	UL94 V-0	UL94 V-0	UL94 V-0	UL94 V-0
Operating Temperature:	(-30°C ~ 50°C)	(-30°C ~ 50°C)	(-30°C ~ 50°C)	(-30°C ~ 50°C)
Net Weight:	1.8 kg	2.5 kg	2.8 kg	3.5 kg

DISTRIBUTED BY:

BLP EV SYSTEMS APS - EDITHS ALLÉ 8, 5250 ODENSE SV, DENMARK