# SWARM SYSTEM FOR DISASTER RESPONSE

*Comprehensive Review Structure & Implemented Technical Specification*

*Authors: Abin Varghese, Alan Biju, Alen Varghese, Akshay Santhosh | Guide: Ms. Resmi V*

| Section | Subsections and Implemented Technical Details |
|---|---|
| **I. INTRODUCTION** | 1. Background & Context: Disasters (earthquakes, landslides, floods), critical golden 72-hour search window, limitations of human search teams and terrestrial vehicles.<br>2. Problem Statement: Single-drone limitations (battery endurance, narrow FOV, single point of failure); centralized swarm bottlenecks (telemetry loss, base station failure).<br>3. Key Contributions: (a) INT8 YOLOv8 on Raspberry Pi 4 edge (16.8 FPS, 81.6% mAP@0.5); (b) Market-based distributed auction with dynamic Voronoi partitioning; (c) Sub-420 ms heartbeat fault recovery. |
| **II. REVIEW METHODOLOGY** | 1. Systematic Criteria: Search taxonomy across IEEE Xplore, ScienceDirect, ACM Digital Library (2018-2026).<br>2. Problem Formulation: Discretized 500m x 500m disaster area, fleet N UAVs, coverage objective C(t) -> 100%, redundancy minimization R < 5%.<br>3. Comparative Analysis: Centralized vs decentralized vs hybrid swarm architectures. |
| **III. UAV SWARM ARCHITECTURE & SYSTEM DESIGN** | 1. Hardware Stack: Holybro S500 airframe, Pixhawk 4 autopilot (PX4 v1.14), Raspberry Pi 4 (4GB RAM) companion, Sony IMX219 camera, ESP32 mesh radio.<br>2. Software & Communication Stack: ROS 2 Humble, PX4 micro-XRCE-DDS bridge, ESP-NOW ad-hoc mesh protocol (2.4 GHz), 5.8 GHz telemetry.<br>3. System Architecture Diagram: Autonomous swarm edge architecture connecting vision sensors, Raspberry Pi 4 edge autonomy, and PX4 flight control (Fig. 1). |
| **IV. SENSING, LOCALIZATION, & ON-DEVICE PERCEPTION** | 1. Edge Detection Pipeline: INT8 quantized YOLOv8 model running on ARM Cortex-A72 at 59.5 ms/frame (16.8 FPS).<br>2. Geolocation Projection: Pinhole camera back-projection model mapping pixel coordinates (u, v) to world GPS coordinates (lat, lon, alt) with < 2.0m RMS accuracy.<br>3. Algorithm 2: Real-Time INT8 YOLOv8 Detection & Geolocation Projection Pipeline.<br>4. MATLAB Benchmark: Precision-Recall curves across FP32, FP16, INT8 and geolocation error vs altitude (Fig. 2). |
| **V. PATH PLANNING & SWARM TASK ALLOCATION** | 1. Sector Decomposition: Dynamic Voronoi partitioning weighted by individual UAV battery state.<br>2. Algorithm 1: Distributed Market-Based Dynamic Task Allocation Auction Protocol (marginal utility bidding, 50ms auction window).<br>3. MATLAB Simulation: 4-UAV search trajectories, lawnmower sweep patterns, casualty targets T1-T12, debris zones (Fig. 3).<br>4. MATLAB Auction Analysis: Utility bidding convergence in 3-4 rounds and 26.2% fleet energy savings (Fig. 4). |
| **VI. COMMUNICATION, COORDINATION, & FAULT TOLERANCE** | 1. Gossip Heartbeat Protocol: 5 Hz broadcast containing node status, pose, and active tasks.<br>2. Algorithm 3: Heartbeat Failure Detection & Decentralized Swarm Re-Auctioning (400 ms timeout).<br>3. Dynamic Self-Healing: Mid-flight failure at t = 180s automatically triggers decentralized re-auction and sector reallocation. |

| | |
|---|---|
| | 4. MATLAB Fault Simulation: Coverage recovery from 74.8% plateau to 99.8% and scalability latency vs swarm size (Fig. 5). |
| **VII. SIMULATION, EXPERIMENTS, & BENCHMARKING** | 1. Gazebo Multi-UAV Simulation: Full physics simulation with PX4 SITL and simulated disaster terrain.<br>2. Real Benchmark Tables: Table I (Hardware Specs), Table II (Quantization), Table III (Coverage vs Fleet Size), Table IV (Edge Boards), Table V (Fault Recovery Latency).<br>3. Performance Highlights: 11.4 min 100% search time, 3.4% path redundancy, 419.1 ms fault recovery. |
| **VIII. CHALLENGES & OPEN DIRECTIONS** | 1. Environmental Obstacles: Rubble occlusions, weather interference (fog, rain, dust), GPS multipath degradation.<br>2. Networking Bottlenecks: RF shadow zones in collapsed steel buildings, packet drop mitigation.<br>3. Future Work: Autonomous battery docking stations, cooperative multi-drone lifting of emergency medical supplies. |
| **IX. CRITICAL EVALUATION & LESSONS LEARNED** | 1. Edge vs Centralized Trade-off: Onboard inference eliminates video telemetry bottlenecks while maintaining 81.6% detection accuracy.<br>2. Auction Efficiency: Distributed market auction converges within 23.8 ms for 4 drones, requiring negligible bandwidth.<br>3. Resilience Validation: Swarm achieves 99.8% coverage even when individual aircraft suffer sudden hardware dropouts. |
| **X. CONCLUSION** | 1. Summary of Deliverables: Autonomous, decentralized, edge-AI multi-UAV swarm framework.<br>2. Core Achievements: 38.2% faster search completion, 26.2% energy savings, sub-420 ms failure recovery.<br>3. Real-World Readiness: Ready for deployment with first responders and disaster management authorities. |

## Recommended Tables and Figures Matrix

| Item | Section | Description / Metrics Included |
|---|---|---|
| Table I: Swarm Hardware Specifications | Section III | Raspberry Pi 4, Pixhawk 4, Holybro S500, Sony IMX219, ESP32 |
| Table II: Object Detection Precision | Section IV | YOLOv8 FP32 vs FP16 vs INT8 (mAP@0.5, FPS, size, Pi 4 latency) |
| Table III: Swarm Coverage Performance | Section VII | Fleet N=1 to N=8 (100% coverage time, path overlap, energy) |
| Table IV: Edge Hardware Benchmark | Section VII | Pi 4 vs Jetson Nano vs Coral TPU vs NCS2 vs Pi 3B+ |
| Table V: Fault Recovery Latency | Section VII | Heartbeat timeout (400ms) + Re-auction (12.8ms) = 419.1ms total |
| Fig. 1: Swarm Edge Architecture Diagram | Section III | Hardware, Raspberry Pi 4 edge ROS 2 nodes, and communication topology |

| | | |
|---|---|---|
| Fig. 2: MATLAB Detection Benchmark | Section IV | Precision-Recall curves and geolocation error vs altitude |
| Fig. 3: MATLAB Swarm Trajectories | Section V | 4-UAV 500m x 500m lawnmower search paths and survivor targets |
| Fig. 4: MATLAB Auction Convergence | Section V | Bidding convergence across rounds and fleet power profiles |
| Fig. 5: MATLAB Fault Recovery | Section VI | Swarm coverage recovery dynamics under node failure and scalability |