

```
#include<stdio.h>
void main()
{
int pid;
pid = fork();
if(pid > 0)
{
printf (" Iam parent\n");
}
else
{
printf("Iam child\n");
}
}
```

The parent process prints the first statement and the child prints the next statement.

3. exec

New programs can be run using exec system calls. When a process calls exec, the process is completely replaced by the new program. The new program starts executing from its main function.

A new process is not created, process id remains the same, and the current process's text, data, heap, and stack segments are replaced by the new program. exec has many flavors one of which is *execv*.

execv takes two parameters. The first is the pathname of the program that is going to be executed. The second is a pointer to an array of pointers that hold the addresses of arguments. These arguments are the command line arguments for the new program.

4. wait

When a process terminates, its parent should receive some information regarding the process like the process id, the termination status, amount of CPU time taken etc. This is possible only if the parent process waits for the termination of the child process. This waiting is done by calling the wait system call. When the child process is running, the parent blocks when wait is called. If the child terminates normally or abnormally, wait immediately returns with the termination status of

Reference Books:

1. W. Richard Stevens, Bill Fenner, Andy Rudoff, UNIX Network Programming: Volume 1, The Sockets Networking API, 3rd Edition, Pearson, 2015
2. Lisa Bock, Learn Wireshark: Confidently navigate the Wireshark interface and solve real-world networking problems, Packt Publishing, 2019
3. Teerawat Issariyakul, Ekram Hossain, Introduction to Network Simulator NS2, 2nd Edition, Springer, 2019

Experiment 1

Getting started with Basics of Network configurations files and Networking

Commands in Linux.

The important network configuration files in Linux operating systems are

1. /etc/hosts

This file is used to resolve hostnames on small networks with no DNS server. This text file contains a mapping of an IP address to the corresponding host name in each line. This file also contains a line specifying the IP address of the loopback device i.e, 127.0.0.1 is mapped to localhost.

A typical hosts file is as shown

```
127.0.0.1 localhost
127.0.1.1 anil-300E4Z-300E5Z-300E7Z
```

2. /etc/resolv.conf

This configuration file contains the IP addresses of DNS servers and the search domain.

A sample file is shown

```
# DO NOT EDIT THIS FILE BY HAND -- YOUR CHANGES WILL BE OVERWRITTEN
nameserver 127.0.1.1
```

3. /etc/sysconfig/network

This configuration file specifies routing and host information for all network interfaces. It contains directives that are global specific. For example if NETWORKING=yes, then /etc/init.d/network activates network devices.

4. /etc/nsswitch.conf

This file includes database search entries. The directive specifies which database is to be searched first.

The important Linux networking commands are

1. ifconfig

This command gives the configuration of all interfaces in the system. It can be run with an interface name to get the details of the interface.

```
ifconfig wlan0
```

```
Link encap:Ethernet HWaddr b8:03:05:ad:6b:23
inet addr:192.168.43.15 Bcast:192.168.43.255 Mask:255.255.255.0
inet6 addr: 2405:204:d206:d3b1:ba03:5ff:fead:6b23/64 Scope:Global
inet6 addr: fe80::ba03:5ff:fead:6b23/64 Scope:Link
inet6 addr: 2405:204:d206:d3b1:21ee:5665:de59:bd4e/64 Scope:Global
UP BROADCAST RUNNING MULTICAST MTU:1500 Metric:1
RX packets:827087 errors:0 dropped:0 overruns:0 frame:0
TX packets:433391 errors:0 dropped:0 overruns:0 carrier:0
collisions:0 txqueuelen:1000
RX bytes:1117797710 (1.1 GB) TX bytes:53252386 (53.2 MB)
```

This gives the IP address, subnet mask, and broadcast address of the wireless LAN adapter. Also tells that it can support multicasting.

If eth0 is given as the parameter, the command gives the details of the Ethernet adapter.

2. netstat

This command gives network status information.

```
Netstat -i
```

Iface	MTU	Met	RX-OK	RX-ERR	RX-DRP	RX-OVR	TX-OK	TX-ERR	TX-DRP	TX-OVR	Flg
eth0	1500	0	0	0	0	0	0	0	0	0	BMU
lo	65536	0	12166	0	0	0	12166	0	0	0	LRU
wlan0	1500	0	827946	0	0	0	434246	0	0	0	BMRU

As shown above, the command with -i flag provides information on the interfaces. lo stands for loopback interface.

3. ping

This is the most commonly used command for checking connectivity.

```
ping www.google.com
PING www.google.com (172.217.163.36) 56(84) bytes of data.
64 bytes from maa05s01-in-f4.1e100.net (172.217.163.36): icmp_seq=1 ttl=53 time=51.4 ms
64 bytes from maa05s01-in-f4.1e100.net (172.217.163.36): icmp_seq=2 ttl=53 time=50.3 ms
64 bytes from maa05s01-in-f4.1e100.net (172.217.163.36): icmp_seq=3 ttl=53 time=48.5 ms
64 bytes from maa05s01-in-f4.1e100.net (172.217.163.36): icmp_seq=4 ttl=53 time=59.8 ms
64 bytes from maa05s01-in-f4.1e100.net (172.217.163.36): icmp_seq=5 ttl=53 time=57.8 ms
64 bytes from maa05s01-in-f4.1e100.net (172.217.163.36): icmp_seq=6 ttl=53 time=59.2 ms
64 bytes from maa05s01-in-f4.1e100.net (172.217.163.36): icmp_seq=7 ttl=53 time=68.2 ms
64 bytes from maa05s01-in-f4.1e100.net (172.217.163.36): icmp_seq=8 ttl=53 time=58.8 ms
^C
--- www.google.com ping statistics ---
8 packets transmitted, 8 received, 0% packet loss, time 7004ms
rtt min/avg/max/mdev = 48.533/56.804/68.266/6.030 ms
```

A healthy connection is determined by a steady stream of replies with consistent times. Packet loss is shown by discontinuity of sequence numbers. Large scale packet loss indicates problem along the path.

Experiment 2

To familiarize and understand the use and functioning of System Calls used for Operating system and network programming in Linux.

Some system calls of Linux operating systems

1. Ps

This command tells which all processes are running on the system when ps runs.

ps -ef

UID	PID	PPID	C	STIME	TTY	TIME	CMD
root	1	0	0	13:55	?	00:00:01	/sbin/init
root	2	0	0	13:55	?	00:00:00	[kthreadd]
root	3	2	0	13:55	?	00:00:00	[ksoftirqd/0]
root	4	2	0	13:55	?	00:00:01	[kworker/0:0]
Root	5	2	0	13:55	?	00:00:00	[kworker/0:0H]
root	7	2	0	13:55	?	00:00:00	[rcu_sched]
root	8	2	0	13:55	?	00:00:00	[rcuos/0]

This command gives processes running on the system, the owners of the processes and the names of the processes. The above result is an abridged version of the output.

2. fork

This system call is used to create a new process. When a process makes a fork system call, a new process is created which is identical to the process creating it. The process which calls fork is called the parent process and the process that is created is called the child process. The child and parent processes are identical, i.e, the child gets a copy of the parent's data space, heap and stack, but have different physical address spaces. Both processes start execution from the line next to the fork. Fork returns the process id of the child in the parent process and returns 0 in the child process.

```
#include<stdio.h>
void main()
{
int pid;
pid = fork();
if(pid > 0)
{
printf (" Iam parent\n");
}
else
{
printf("Iam child\n");
}
}
```

The parent process prints the first statement and the child prints the next statement.

3. exec

New programs can be run using exec system calls. When a process calls exec, the process is completely replaced by the new program. The new program starts executing from its main function.

A new process is not created, process id remains the same, and the current process's text, data, heap, and stack segments are replaced by the new program. exec has many flavors one of which is *execv*.

execv takes two parameters. The first is the pathname of the program that is going to be executed. The second is a pointer to an array of pointers that hold the addresses of arguments. These arguments are the command line arguments for the new program.

4. wait

When a process terminates, its parent should receive some information regarding the process like the process id, the termination status, amount of CPU time taken etc. This is possible only if the parent process waits for the termination of the child process. This waiting is done by calling the wait system call. When the child process is running, the parent blocks when wait is called. If the child terminates normally or abnormally, wait immediately returns with the termination status of

Reference Books:

1. W. Richard Stevens, Bill Fenner, Andy Rudoff, UNIX Network Programming: Volume 1, The Sockets Networking API, 3rd Edition, Pearson, 2015
2. Lisa Bock, Learn Wireshark: Confidently navigate the Wireshark interface and solve real-world networking problems, Packt Publishing, 2019
3. Teerawat Issariyakul, Ekram Hossain, Introduction to Network Simulator NS2, 2nd Edition, Springer, 2019

Experiment 1

Getting started with Basics of Network configurations files and Networking

Commands in Linux.

The important network configuration files in Linux operating systems are

1. /etc/hosts

This file is used to resolve hostnames on small networks with no DNS server. This text file contains a mapping of an IP address to the corresponding host name in each line. This file also contains a line specifying the IP address of the loopback device i.e, 127.0.0.1 is mapped to localhost.

A typical hosts file is as shown

```
127.0.0.1 localhost
127.0.1.1 anil-300E4Z-300E5Z-300E7Z
```

2. /etc/resolv.conf

This configuration file contains the IP addresses of DNS servers and the search domain.

A sample file is shown

```
# DO NOT EDIT THIS FILE BY HAND -- YOUR CHANGES WILL BE OVERWRITTEN
nameserver 127.0.1.1
```

3. /etc/sysconfig/network

This configuration file specifies routing and host information for all network interfaces. It contains directives that are global specific. For example if NETWORKING=yes, then /etc/init.d/network activates network devices.

4. /etc/nsswitch.conf

This file includes database search entries. The directive specifies which database is to be searched first.

The important Linux networking commands are

1. ifconfig

This command gives the configuration of all interfaces in the system. It can be run with an interface name to get the details of the interface.

```
ifconfig wlan0
```

```
Link encap:Ethernet HWaddr b8:03:05:ad:6b:23
inet addr:192.168.43.15 Bcast:192.168.43.255 Mask:255.255.255.0
inet6 addr: 2405:204:d206:d3b1:ba03:5ff:fead:6b23/64 Scope:Global
inet6 addr: fe80::ba03:5ff:fead:6b23/64 Scope:Link
inet6 addr: 2405:204:d206:d3b1:21ee:5665:de59:bd4e/64 Scope:Global
UP BROADCAST RUNNING MULTICAST MTU:1500 Metric:1
RX packets:827087 errors:0 dropped:0 overruns:0 frame:0
TX packets:433391 errors:0 dropped:0 overruns:0 carrier:0
collisions:0 txqueuelen:1000
RX bytes:1117797710 (1.1 GB) TX bytes:53252386 (53.2 MB)
```

This gives the IP address, subnet mask, and broadcast address of the wireless LAN adapter. Also tells that it can support multicasting.

If eth0 is given as the parameter, the command gives the details of the Ethernet adapter.

2. netstat

This command gives network status information.

```
Netstat -i
```

Iface	MTU	Met	RX-OK	RX-ERR	RX-DRP	RX-OVR	TX-OK	TX-ERR	TX-DRP	TX-OVR	Flg
eth0	1500	0	0	0	0	0	0	0	0	0	BMU
lo	65536	0	12166	0	0	0	12166	0	0	0	LRU
wlan0	1500	0	827946	0	0	0	434246	0	0	0	BMRU

As shown above, the command with -i flag provides information on the interfaces. lo stands for loopback interface.

3. ping

This is the most commonly used command for checking connectivity.

```
ping www.google.com
PING www.google.com (172.217.163.36) 56(84) bytes of data.
64 bytes from maa05s01-in-f4.1e100.net (172.217.163.36): icmp_seq=1 ttl=53 time=51.4 ms
64 bytes from maa05s01-in-f4.1e100.net (172.217.163.36): icmp_seq=2 ttl=53 time=50.3 ms
64 bytes from maa05s01-in-f4.1e100.net (172.217.163.36): icmp_seq=3 ttl=53 time=48.5 ms
64 bytes from maa05s01-in-f4.1e100.net (172.217.163.36): icmp_seq=4 ttl=53 time=59.8 ms
64 bytes from maa05s01-in-f4.1e100.net (172.217.163.36): icmp_seq=5 ttl=53 time=57.8 ms
64 bytes from maa05s01-in-f4.1e100.net (172.217.163.36): icmp_seq=6 ttl=53 time=59.2 ms
64 bytes from maa05s01-in-f4.1e100.net (172.217.163.36): icmp_seq=7 ttl=53 time=68.2 ms
64 bytes from maa05s01-in-f4.1e100.net (172.217.163.36): icmp_seq=8 ttl=53 time=58.8 ms
^C
--- www.google.com ping statistics ---
8 packets transmitted, 8 received, 0% packet loss, time 7004ms
rtt min/avg/max/mdev = 48.533/56.804/68.266/6.030 ms
```

A healthy connection is determined by a steady stream of replies with consistent times. Packet loss is shown by discontinuity of sequence numbers. Large scale packet loss indicates problem along the path.