

```
int main() {  
    int* ptr;  
    *ptr = 5;  
    cout << *ptr << endl;  
    return 0;  
}
```

print value

Run C++ Save

```
1 #include<iostream>  
2 using namespace std;  
3 int main(){  
4     int x=5;  
5     int* ptr=&x;  
6     cout<<*ptr<<endl;  
7     return 0;  
8 }
```

Your INPUT here. Give only values (e.g., 10, not a=10)

5

```
using namespace std;

int main() {
    int sum = 0;
    for (int i = 0; i < 5; ++i) {
        sum += i * i;
    }
    cout << "Sum: " << sum << endl;
    return 0;
}
```

printValue

Run C++ Save

```
1 #include<iostream>
2 using namespace std;
3 int main(){
4     int sum=0;
5     for(int i=0; i<5; i++){
6         sum+=i * i;
7     }
8     cout<<"Sum: "<<sum<<endl;
9     return 0;
10 }
```

Your INPUT here. Give only values (e.g., 10, not a=10)

Sum: 30

```
int main() {  
    int arr[5];  
    for (int i = 0; i < 5; ++i) {  
        arr[i] = i;  
    }  
    for (int i = 0; i < 5; ++i) {  
        cout << arr[i] << " ";  
    }  
    cout << endl;  
    return 0;  
}
```

Run C++ Save

```
1 #include<iostream>  
2 using namespace std;  
3 int main(){  
4     int arr[5];  
5     for(int i=0; i<5; i++){  
6         arr[i]=i;  
7     }  
8     for(int i=0; i<5; i++){  
9         cout<<arr[i]<<" ";  
10    }  
11    cout<<endl;  
12    return 0;  
13 }
```

Your INPUT here. Give only values (e.g., 10, not a=10)

0 1 2 3 4

```
void printValue(int& value) {  
    cout << value << endl;  
}  
  
int main() {  
    int num;  
    printValue(num);  
    return 0;  
}
```

Run C++ Save

```
#include<iostream>  
using namespace std;  
void printValue(int& value){  
    cout<< value << endl;  
}  
int main(){  
    int num=0;  
    printValue(num);  
    return 0;  
}
```

5

0