

GE23131-Programming Using C-2024

Quiz navigation

[Show one page at a time](#)[Finish review](#)

Question 1

Correct

Marked out of
3.00

[Flag question](#)

Status	Finished
Started	Monday, 23 December 2024, 5:33 PM
Completed	Tuesday, 19 November 2024, 6:09 PM
Duration	33 days 23 hours

Write a program to read two integer values and print true if both the numbers end with the same digit, otherwise print false. Example: If 698 and 768 are given, program should print true as they both end with 8. Sample Input 1 25 53
Sample Output 1 false Sample Input 2 27 77 Sample Output 2 true

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int a,b,c,d;
5     scanf("%d%d",&a,&b);
6     c=a%10;
7     d=b%10;
8     if(c==d)
9     {
10        printf("true");
11    }
12    else
13    {
14        printf("false");
15    }
16    return 0;
17 }
```

Flag question

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int a,b,c,d;
5     scanf("%d%d",&a,&b);
6     c=a%10;
7     d=b%10;
8     if(c==d)
9     {
10        printf("true");
11    }
12    else
13    {
14        printf("false");
15    }
16    return 0;
17 }
```

	Input	Expected	Got	
✓	25 53	false	false	✓
✓	27 77	true	true	✓

Passed all tests! ✓

Question **2**

Correct

Marked out of
5.00 [Flag question](#)

Objective

In this challenge, we're getting started with conditional statements.

Task

Given an integer, n , perform the following conditional actions:

- If n is odd, print **Weird**
- If n is even and in the inclusive range of **2** to **5**, print ***Not Weird***
- If n is even and in the inclusive range of **6** to **20**, print ***Weird***
- If n is even and greater than **20**, print ***Not Weird***

Complete the stub code provided in your editor to print whether or not n is weird.

Input Format

A single line containing a positive integer, n .

Constraints

- $1 \leq n \leq 100$

Complete the stub code provided in your editor to print whether or not *n* is weird.

Input Format

A single line containing a positive integer, *n*.

Constraints

· $1 \leq n \leq 100$

Output Format

Print Weird if the number is weird; otherwise, print Not Weird.

Sample Input 0

3

Sample Output 0

Weird

Sample Output 0

Weird

Sample Input 1

24

Sample Output 1

Not Weird

Explanation

Sample Case 0: $n = 3$

n is odd and odd numbers are weird, so we print **Weird**.

Sample Case 1: $n = 24$

$n > 20$ and n is even, so it isn't weird. Thus, we print **Not Weird**.

```
1 #include<stdio.h>
2 int main()
3 {
4     int a;
5     scanf("%d",&a);
6     if(a%2!=0)
7     {
8         printf("Weird");
9     }
10    else if(a%2==0&&a>=2&&a<=5)
11    {
12        printf("Not Weird");
13    }
14    else if(a%2==0&&20>=a&&a>=6)
15    {
16        printf("Weird");
17    }
18    else
19    {
20        printf("Not Weird");
21    }
22    return 0;
23 }
24 }
```

	Input	Expected	Got	
✓	3	Weird	Weird	✓
✓	24	Not Weird	Not Weird	✓

Passed all tests! ✓

Question 3

Correct

Marked out of
7.00[Flag question](#)

Three numbers form a Pythagorean triple if the sum of squares of two numbers is equal to the square of the third. For example, 3, 5 and 4 form a Pythagorean triple, since $3^2 + 4^2 = 25 = 5^2$. You are given three integers, a, b, and c. They need not be given in increasing order. If they form a Pythagorean triple, then print "yes", otherwise, print "no". Please note that the output message is in small letters. Sample Input 1 3 5 4 Sample Output 1 yes Sample Input 2 5 8 2 Sample Output 2 no

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int a,b,c;
5     scanf("%d %d %d",&a,&b,&c);
6     if(a*a+b*b==c*c || b*b+c*c==a*a || a*a+c*c==b*b)
7     {
8         printf("yes");
9     }
10    else
11    {
12        printf("no");
13    }
14    return 0;
15 }
```

Input	Expected	Got
-------	----------	-----

```
9     }  
10    else  
11    {  
12        printf("no");  
13    }  
14    return 0;  
15 }
```

	Input	Expected	Got	
✓	3 5 4	yes	yes	✓
✓	5 8 2	no	no	✓

Passed all tests! ✓