BELLOMASSI

INFRASTRUCTURE AND DEVOPS

Backup and Disaster Recovery Plan

Bellomassi Order-to-Delivery Management Platform

Document ID BM-INF-009

Document control

Field	Value
Document title	Backup and Disaster Recovery Plan
Document ID	BM-INF-009
Version	1.0
Status	Draft — for client review
Category	Infrastructure and DevOps
Related module(s)	All modules
Document owner	DevOps Engineer
Prepared by	Project documentation team (AI-assisted draft prepared from source-code analysis)
Reviewed by	*Pending — not yet reviewed*
Approval	*Not approved — awaiting client review (no approval has been given)*
Created date	2026-11-12
Last updated date	2026-11-12

> **Status labels used in this document:** VERIFIED (confirmed in the current source code or existing documents) · PROTOTYPE (works in the React/LocalStorage prototype with mock or simulated behaviour) · PROPOSED (recommended production design, not built) · PENDING CONFIRMATION (needs a client decision) · NOT IMPLEMENTED · NOT VERIFIED.

Purpose

Define backup scope, frequency, retention, recovery objectives and the restore procedure.

Scope

PROPOSED. Prototype data lives in each browser's LocalStorage and has no backup except manual export (NOT IMPLEMENTED as a backup feature).

Definitions

Other terms: see **BM-GLO-001** (Project Glossary).

References

- **BM-INF-003** (Infrastructure, Network Architecture and Server Specification)
- **BM-DAT-005** (Data Retention Policy (Draft))
- **BM-DEP-005** (Rollback Plan)

1. Objectives (proposed, PENDING CONFIRMATION)

Objective	Target
RPO (max data loss)	15 minutes
RTO (max downtime)	4 hours
Backup retention	Daily 35 days; monthly 12 months

2. Backup scope

Item	Method	Frequency	Location
PostgreSQL	Managed snapshots + continuous WAL (PITR)	Daily + continuous	Same region + copy to second region
Object storage (POD, documents, invoices)	Versioning + cross-region replication	Continuous	Second region
Configuration / IaC	Git	Every change	Git hosting
Secrets	Secrets manager with backup / export policy	On change	Provider
Redis	Not backed up (cache / transient)	—	—

Diagram: DGM-18 in **BM-DGM-001** (Diagram Catalogue and Visual Documentation).

3. Restore procedure (summary)

1. Declare incident; decide on PITR target time.
2. Restore database to new instance at target time; verify row counts and latest orders.
3. Point staging-like DR environment (IaC) to restored database and replicated bucket.
4. Run smoke tests; switch DNS / load balancer.
5. Reconcile: deliveries and OTPs created after the restore point are re-checked with drivers.
6. Post-incident review.

4. Testing

Restore test quarterly (database to a scratch instance) and a full DR rehearsal yearly. Results recorded — none performed yet (NOT VERIFIED).

Revision history

Version	Date	Author	Description
1.0	2026-11-12	Documentation team	Initial draft prepared from analysis of the bellomassi-premium-ui source code and existing project documents.