BELLOMASSI

DEPLOYMENT AND RELEASE

Deployment Guide and Runbook

Bellomassi Order-to-Delivery Management Platform

Document ID BM-DEP-002

Document control

Field	Value
Document title	Deployment Guide and Runbook
Document ID	BM-DEP-002
Version	1.0
Status	Draft — for client review
Category	Deployment and Release
Related module(s)	All modules
Document owner	DevOps Engineer
Prepared by	Project documentation team (AI-assisted draft prepared from source-code analysis)
Reviewed by	*Pending — not yet reviewed*
Approval	*Not approved — awaiting client review (no approval has been given)*
Created date	2026-11-12
Last updated date	2026-11-12

> **Status labels used in this document:** VERIFIED (confirmed in the current source code or existing documents) · PROTOTYPE (works in the React/LocalStorage prototype with mock or simulated behaviour) · PROPOSED (recommended production design, not built) · PENDING CONFIRMATION (needs a client decision) · NOT IMPLEMENTED · NOT VERIFIED.

Purpose

Step-by-step instructions to run the prototype (VERIFIED) and to deploy the production platform (PROPOSED).

Scope

Part A prototype; Part B production. Commands in Part A were executed on 2026-11-12.

Definitions

Other terms: see **BM-GLO-001** (Project Glossary).

References

- **BM-INF-005** (Environment Configuration and Environment Variables Reference)
- **BM-INF-006** (Docker Architecture and Deployment Guide)
- **BM-INF-007** (CI/CD Pipeline and Git Workflow)
- **BM-DEP-005** (Rollback Plan)

- **BM-DEP-006** (Post-Deployment Verification and Smoke Test Checklist)

1. Part A — Prototype (VERIFIED)

Requirements: Node.js 20+ and npm.

```
npm install             # install dependencies
npm run dev             # development server (http://localhost:5173)
npm run build           # production bundle in dist/
npx vite preview        # serve dist/ (http://localhost:4173)
npm run lint            # oxlint
```

Hosting: copy `dist/` to any static web host; configure SPA fallback (all routes → `index.html`). Optional variable `VITE_INTEGRATION_GATEWAY_URL` at build time. Data is seeded into each browser's LocalStorage on first visit (APP_DATA_VERSION 8); a new version migrates existing browser data. Clearing site data resets the demo.

Demo accounts are listed on the sign-in screen (prototype only — never use them in production).

2. Part B — Production deployment (PROPOSED)

2.1 First-time setup

1. Provision infrastructure with IaC (network, database, Redis, storage, container service, load balancer, DNS, TLS).
2. Create secrets in the secrets manager (**BM-INF-005** (Environment Configuration and Environment Variables Reference)).
3. Build and push images (`bellomassi-web`, `bellomassi-api`, `bellomassi-worker`).
4. Run database migrations job (`python manage.py migrate`).
5. Create the first Super Admin (management command), roles and permissions seed.
6. Load master data (**BM-DAT-004** (Data Migration Strategy)).
7. Deploy API, channels, workers, beat, web.
8. Configure providers (maps keys, SMS / WhatsApp, email) and verify webhooks.
9. Run smoke tests (**BM-DEP-006** (Post-Deployment Verification and Smoke Test Checklist)).

2.2 Routine release

1. Confirm release approval (**BM-DEP-001** (Release Management Process)).
2. Announce maintenance window if migrations are not backward compatible.
3. Take on-demand database snapshot.
4. Run migrations job (backward-compatible migrations first).
5. Deploy new version to the idle (green) environment; health checks pass.
6. Switch traffic; monitor errors and latency for 30 minutes.
7. Smoke tests; publish release notes.
8. If rollback criteria are met → **BM-DEP-005** (Rollback Plan).

2.3 Mobile app

Build signed artefacts (EAS / Fastlane), upload to internal testing, pilot drivers verify, promote to production track.

Revision history

Version	Date	Author	Description
1.0	2026-11-12	Documentation team	Initial draft prepared from analysis of the bellomassi-premium-ui source code and existing project documents.