

**Head Office:** Refrigeration & Oxygen Co. Ltd.

P.O. Box 501 Safat 13006,

Kuwait

**Dubai Office:** Emirates Industrial Gases Co. LLC.

P.O. Box 3763, Dubai, UAE

Qatar Office: Qatar Oxygen Co. W.L.L

P.O. Box 22386,

Doha, Qatar

**Bahrain Office**: Bahrain Medical & Industrial Gas Plant

P.O.Box 80738, Kingdom of Bahrain Email Id: info@rocq8.com

Web Address: www.airtecgulf.com

**Emergency Phone** 

Kuwait +965 1844 844 Dubai +971 8005414

Qatar +974 44114603/4/5

Bahrain +973 17400469/473

**Facsimile Phone** 

Kuwait+965 2484 3020Dubai+971 42664168Qatar+974 44114350Bahrain+973 17400391

#### 1. CHEMICAL PRODUCT

PRODUCT NAME: NITROGEN SYNONYMS: Cryogenic Liquid Nitrogen, LIN

### 2. COMPOSITION, INFORMATION ON INGREDIENTS

### **Exposure Limits (PPM)**

| Ingredient <u>Name</u> | ormula | CAS#      | <u>Concentration</u> | ACGIH TLV | OSHA PEL | MAC | Other STEL |
|------------------------|--------|-----------|----------------------|-----------|----------|-----|------------|
| NITROGEN               | N2     | 7727-37-9 | 99+%                 | S/A       | S/A      | S/A | S/A        |

Note: NE = NONE ESTABLISHED S/A = SIMPLE ASPHYXIANT

### 3. HAZARD INDENTIFICATION

\* \* \* EMERGENCY OVERVIEW \* \* \*

Extremely cold liquid and gas under pressure.

Can cause rapid suffocation.

### **POTENTIAL HEALTH EFFECTS**

**ROUTES OF ENTRY: Inhalation** 

ACUTE EFFECTS: Material acts as a simple asphyxiant by displacing air necessary for life. Symptoms include rapid respiration, muscular incoordination, fatigue, dizziness, nausea, vomiting, unconsciousness, and death.

CHRONIC EFFECTS: None known

MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE: None known

OTHER EFFECTS OF OVEREXPORSURE: None

CARCINOGENICITY (US ONLY):

NTP - No

IARC MONOGRAPHS - No OSHA REGULATED – No

| Document Code: PR-DS-006 | Rev:01, 01/10/2014 | Page <b>  1</b> of <b>4</b> |
|--------------------------|--------------------|-----------------------------|
|                          |                    |                             |



### 4. FIRST AID MEASURES

INHALATION: Immediately remove victim to fresh air. If breathing has stopped, give artificial respiration. If

breathing is difficult, give oxygen.

EYE CONTACT: None SKIN CONTACT: None INGESTION: None

IN EVENT OF EXPOSURE, CONSULT A PHYSICIAN

NOTE TO PHYSICIAN: None

### 5. FIRE FIGHTING MEASURES

FLASH POINT: Nonflammable

AUTOIGNITION TEMPERATURE: N/Ap FLAMMABLE LIMITS: Nonflammable

LOWER: UPPER:

EXTINGUISHING MEDIA: Use what is appropriate for surrounding fire.

SPECIAL FIRE FIGHTING INSTRUCTION AND EQUIPMENT: Wear self-contained breathing apparatus and full protective clothing. Keep fire exposed cylinders cool with water spray. If possible, stop the product flow.

HAZARDOUS COMBUSTION PRODUCTS: None

UNUSUAL FIRE AND EXPLOSION HAZARDS: Cylinder rupture may occur under fire conditions.

## 6. ACCIDENTAL RELEASE MEASURES

CLEAN UP PROCEDURES: Evacuate and ventilate area. Remove leaking cylinder to exhaust hood or safe outdoor area. Shut off source if possible and remove source of heat.

SPECIALIZED EQUIPMENT: None

#### 7. HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING: Secure cylinder when using to protect from falling. Use suitable hand truck to move cylinders.

PRECAUTIONS TO BE TAKEN IN STORAGE: Store in well ventilated areas. Keep valve protection cap on cylinders when not in use.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS: Provide adequate general and local exhaust ventilation to avoid asphyxiation.

EYE / FACE PROTECTION: Safety glasses

SKIN PROTECTION: None

RESPIRATORY PROTECTION: In case of leakage, use self-contained breathing apparatus.

OTHER PROTECTIVE EQUIPMENT: Safety shoes when handling cylinders.

| Document Code: PR-DS-006 | Rev:01, 01/10/2014 | Page   <b>2</b> of <b>4</b> |
|--------------------------|--------------------|-----------------------------|
|--------------------------|--------------------|-----------------------------|



### 9. PHYSICAL AND CHEMICAL PROPERTIES

**APPEARANCE: Colorless** 

**ODOR: Odorless** 

PHYSICAL STATE: Cryogenic Liquid

VAPOR PRESSURE: N/Ap
VAPOR DENSITY (AIR=1): 0.967
BOILING POINT (C): -195.5

SOLUBILITY IN WATER: cm3/100cm3 H2O 1.485

SPECIFIC GRAVITY (H2O=1): Gas EVAPORATION RATE: Gas ODOR THRESHOLD: None

#### 10. STABILITY AND REACTIVITY

STABILITY: Stable under normal storage conditions.

CONDITIONS TO AVOID: Storage in poorly ventilated areas. Storage near a heat source.

MATERIALS TO AVOID: Nitrogen reacts with Li, Nd, and Ti at high temperatures.

HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION: None

## 11. TOXICOLOGICAL INFORMATION

LETHAL CONCENTRATION (LC50): None established

LETHAL DOSE 50 (LD50): N/Ap

TERATOGENICITY: N/Ap

REPRODUCTIVE EFFECTS: N/Ap

MUTAGENICITY: N/Ap

#### 12. ECOLOGICAL INFORMATION

No adverse ecological effects are expected.

#### 13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Dispose of non-refillable cylinders in accordance with federal, state and local regulations. Allow gas to vent slowly to atmosphere in an unconfined area or exhaust hood. If the cylinders are the refillable type, return cylinders to supplier with any valve outlet plugs or caps secured and valve protection caps in place.

## 14. TRANSPORT INFORMATION

CONCENTRATION: 99+% DOT DESCRIPTION (US ONLY)

| Document Code: PR-DS-006 | Rev:01. 01/10/2014 | Page   <b>3</b> of <b>4</b> |
|--------------------------|--------------------|-----------------------------|
| DOCUMENT CODE, PN-D3-000 | NEV.U1. U1/10/2014 | F 4 2 F 1 3 U1 4            |



PROPER SHIPPING NAME: Nitrogen, Refrigerated Liquid

HAZARD CLASS: 2.2(nonflammable)
INDENTIFICATION NUMBER: UN1977
REPORTABLE QUANTITIES: None

LABELING: NONFLAMMABLE NITROGEN LIQUID

ADR / RID (EU Only): Class 2,1a

SPECIAL PRECAUTIONS: Cylinders should be transported in a secure upright position in a well ventilated truck.

#### 15. REGULATORY INFORMATION

OSHA: Process Safety Management: Material is not listed in appendix A of 29 CFR 1910.119 as highly

hazardous chemical.

TSCA: Material is listed in TSCA inventory.

SARA: The threshold planning quantity for material is 10,000 lbs.

EU NUMBER: 231-783-9

NUMBER IN ANNEX 1 OF DIR 67/548: Not listed in annex 1.

**EU CLASSIFICATION: N/Av** 

R: As S: 9, 23

### **16. OTHER INFORMATION**

OTHER PRECAUTIONS: Protect containers from physical damage. Do not deface cylinders or labels. Cylinders should be refilled by qualified producers of compressed gas. Shipment of a compressed gas cylinder which has not been filled by the owner or with his written consent is a violation of federal law (49 CFR).

ABBREVIATIONS: N/Ap - Not Applicable N/Av - Not Available SA - Simple Asphyxiant NE - None Established

### Use proper connections; do not use adapters. Do not force fit!!

#### **DISCLAIMER**

The information and recommendations in this Material Safety Data Sheet relate only to the specific material mentioned herein and do not relate to use otherwise ie.in combination with any other material or in any process.

The information and recommendations herein are taken from our extensive experiences and the data contained in recognized references and believed by us to be true. Refrigeration group of companies make no warranties either expressed or implied with respect there to and assume no liability in connection with the use of such information and recommendation.