REC-CIS GE23131-Programming Using C-2024

Quiz navigation Show one page at a time Finish review

Question 1 Correct Marked out of 1.00 ▼ Flag question

Status Finished Started Sunday, 29 December 2024, 7:42 PM **Duration** 38 mins 12 secs

Completed Sunday, 29 December 2024, 8:20 PM You are given a two-dimensional 3*3 array starting from A [0][0]. You should add the alternate elements of the array and print its sum. It should print two different numbers the first being sum of A 0 0, A 0 2, A 1 1, A 2 0, A 2 2 and A 0

> A00 A10 A 2 0

> > 6 7 8

9

10

11 •

12

13

14 15

16 17

18 19 int odd=0, even=0;

for(int i=0 ;i<3;i++){</pre>

else

for(int j =0;j<3;j++){</pre>

if((i+j)%2!=0)

odd+=arr[i][j];

even+=arr[i][j];

printf("%d\n%d",even,odd);

1, A 1 0, A 1 2, A 2 1.

Input Format

Output Format

A01

6

A11

5

A 2 1

A 0 2

A12

A 2 2

First and only line contains the value of array separated by single space.

First line should print sum of A 0 0, A 0 2, A 1 1, A 2 0, A 2 2 Second line should print sum of A 0 1, A 1 0, A 1 2, A 2 1 **SAMPLE INPUT** 123456789 **SAMPLE OUTPUT** 25

20

Answer: (penalty regime: 0 %) 1 #include <stdio.h> 2 v int main(){ int arr[3][3]; 3 for(int i=0;i<3;i++){ 4 • 5 for(int j=0;j<3;j++){</pre> scanf("%d",&arr[i][j]);

Expected Got Input 1 2 3 4 5 6 7 8 9 25 25 20 20 2591 21 422 423 443 586 645 657 846 904 2356 2356 Passed all tests! < Microsoft has come to hire interns from your college. N students got shortlisted out of which few were males and a few females. All the students have been assigned talent levels. Smaller the talent level, lesser is your chance to be

selected. Microsoft wants to create the result list where it wants the candidates sorted according to their talent levels, but there is a catch. This time Microsoft wants to hire female candidates first and then male candidates. The task is to create a list where first all-female candidates are sorted in a descending order and then male candidates are sorted in a descending order. **Input Format** The first line contains an integer N denoting the number of students. Next, N lines contain two space-separated integers, ai and bi. The first integer, ai will be either 1(for a male candidate) or 0(for female candidate). The second integer, bi will be the candidate's talent level.

Question **2**

Marked out of

Correct

5.00

▼ Flag

question

Constraints $1 <= N <= 10^5$ 0 <= ai <= 1

1 <= bi <= 10⁹

Output Format Output space-separated integers, which first contains the talent levels of all female candidates sorted in descending order and then the talent levels of male candidates in descending order. SAMPLE INPUT 5 03 16 0 2 07 1 15 SAMPLE OUTPUT

7 3 2 15 6

2

6

7 8 9

10 11

12 13

14 15 •

16

17 🔻

Answer: (penalty regime: 0 %)

int main() {

int n;

#include <stdio.h>

#define MAX_N 100000

scanf("%d", &n);

int ai, bi;

int female_talent[MAX_N], male_talent[MAX_N];

if (ai == 0) { // Female candidate

female_talent[female_count++] = bi;

int female_count = 0, male_count = 0;

for (int i = 0; i < n; i++) {

scanf("%d %d", &ai, &bi);

} else { // Male candidate

male_talent[male_count++] = bi; 18 19 20 21 22 // Sorting female talent levels in descending order for (int i = 0; i < female_count - 1; i++) {</pre> 23 🔻 24 • for (int j = 0; $j < female_count - i - 1$; j++) { 25 • if (female_talent[j] < female_talent[j + 1]) {</pre> 26 int temp = female_talent[j]; 27 female_talent[j] = female_talent[j + 1]; 28 female_talent[j + 1] = temp; 29 30 31 32 33 // Sorting male talent levels in descending order 34 • for (int i = 0; i < male_count - 1; i++) {</pre> 35 • for (int j = 0; $j < male_count - i - 1$; j++) { 36 if (male_talent[j] < male_talent[j + 1]) {</pre> 37 int temp = male_talent[j]; male_talent[j] = male_talent[j + 1]; 38 male_talent[j + 1] = temp; 39 40 41 42 43 // Printing the combined result 44 for (int i = 0; i < female_count; i++) {</pre> 45 printf("%d ", female_talent[i]); 46 47 for (int i = 0; i < male_count; i++) {</pre> 48 printf("%d ", male_talent[i]); 49 50 51 52 return 0; Input | Expected Got **✓** 5 7 3 2 15 6 7 3 2 15 6 0 3 1 6 0 2 0 7 1 15 **/** 6 39 37 26 13 7 1 39 37 26 13 7 1 0 1 0 26 0 39 0 37 0 7 0 13 12 31 29 18 14 12 10 9 8 5 3 2 1 31 29 18 14 12 10 9 1 12 1 14 1 18 1 1 1 2 1 3 1 5 1 8 1 9

1 10 0 29 0 31 12 0 12 1 12 0 12 1 12 0 12 0 12 1 12 0 12 1 12 1 12 0 12 1 12 Passed all tests! < Shyam Lal, a wealthy landlord from the state of Rajasthan, being an old fellow and tired of doing hard work, decided to sell all his farmland and to live rest of his life with that money. No other farmer is rich enough to buy all his land so he decided to partition the land into rectangular plots of different sizes with different cost per unit area. So, he sold these plots to the farmers but made a mistake. Being illiterate, he made partitions that could be overlapping. When the farmers came to know about it, they ran to him for compensation of extra money they paid to him. So, he decided to return all the money to the farmers of that land which was overlapping with other farmer's land to settle down the conflict. All the portion of conflicted land will be taken back by the landlord. To decide the total compensation, he has to calculate the total amount of money to return back to farmers with the same cost they had purchased from him. Suppose, Shyam Lal has a total land area of 1000 x 1000 equal square blocks where each block is equivalent to a unit square area which can be represented on the co-ordinate axis. Now find the total amount of money, he has to return to the farmers. Help Shyam Lal to accomplish this task. **Input Format:** The first line of the input contains an integer **N**, denoting the total number of land pieces he had distributed. Next N line contains the 5 space separated integers (X1, Y1), (X2, Y2) to represent a rectangular piece of land, and cost per unit area **C**.

(X1, Y1) and (X2, Y2) are the locations of first and last square block on the

Print the total amount he has to return to farmers to solve the conflict.

diagonal of the rectangular region.

Output Format:

Constraints:

 $1 \le N \le 100$

 $1 \le C \le 1000$

SAMPLE INPUT

 $1 \le X1 \le X2 \le 1000$

 $1 \le Y1 \le Y2 \le 1000$

14461 43662 22543 SAMPLE OUTPUT 35 Explanation

A [(1,4), (4, 6)] B[(4, 3), (6, 6)] C [(2, 2), (5, 4] A ∩ B [(4, 4), (4, 6)] B ∩ C [(4, 3), (5, 4)] A ∩ C [(2, 4), (4, 4)] 3 A ∩ B ∩ C [(4, 4), (4, 4)] Simple Illustration of Distribution of Land For given sample input (see given graph for reference), compensation money for different farmers is as follows: Farmer with land area A: $C_1 = 5 * 1 = 5$ Farmer with land area B: $C_2 = 6 * 2 = 12$ Farmer with land area C: $C_3 = 6 * 3 = 18$ Total Compensation Money = $C_1 + C_2 + C_3 = 5 + 12 + 18 = 35$

Answer: (penalty regime: 0 %) 1 #include<stdio.h> int main() 2 3 ▼ { 4 int i, j, n, x1, x2, y1, y2, t = 0; long long total = 0; int $arr[1001][1001] = \{0\};$ 6 7 8 scanf("%d", &n); while(n--) 9 10 scanf("%d %d %d %d %d", &x1, &y1, &x2, &y2, &t); 11 for(i = x1; i <= x2; i++) 12 13 for(j = y1; j <= y2; j++)</pre> 14 15 if(arr[i][j] == 0) 16 arr[i][j] += t; 17 else if(arr[i][j] > 0) 18 arr[i][j] = -1 * (arr[i][j] + t);19 20 else if(arr[i][j] < 0)</pre> arr[i][j] -=t; 21 22 23 24 25 for(i = 1; i < 1001; i++) 26 27 28 for(j = 1; j < 1001; j++) 29 if(arr[i][j] < 0)</pre> 30 total += arr[i][j]; 31 32 33 34 printf("%lld\n", (-1) * total); 35 36 return 0; 37 } **Expected Got** Input 35 35 **/** 1 4 4 6 1 4 3 6 6 2 2 2 5 4 3 **/ /** 48 12 49 27 8 10500 10500 88 34 99 76 44 82 65 94 100 81 58 16 65 66 7

Question **3** Correct Marked out of 1.00 ▼ Flag question

Passed all tests! < Finish review