

Script-Controlled ACL – Restrict Record Access Based on Field Value

7. Project Demonstration

7.1 Demonstration Objective

Demonstrate that the application allows authorized users to access records and blocks users whose attributes do not satisfy the field-based ACL rule.

7.2 Demo Steps

- Open the application login page.
- Log in as User A from Department A.
- Open the record list and show records belonging to Department A.
- Try to access a record belonging to Department B and show that access is denied.
- Log in as an administrator and demonstrate broader access.
- Update a permitted record and show the successful operation.
- Try an unauthorized update or delete and show that the ACL blocks it.

7.3 Sample Demonstration Data

User A: Department = HR. Record 101: Department = HR → Access Allowed. Record 102: Department = Finance → Access Denied. Admin User: Role = ADMIN → Access Allowed according to the administrator rule.

7.4 Expected Result

The system must make the access decision before exposing or modifying the protected record. Allowed requests proceed normally, while denied requests are blocked.

7.5 Presentation Points

- Explain why field-based access is needed.
- Show the ACL condition.
- Show one allowed request.
- Show one denied request.
- Explain how server-side validation prevents simple client-side bypass.

7.6 Final Outcome

The demonstration confirms that Script-Controlled ACL can restrict record access dynamically based on field values and user attributes.