Creating and Managing Tables

EX_NO:1 **DATE:**

1.Create the DEPT table based on the DEPARTMENT following the table instance chart below. Confirm that the table is created.

Column name	ID	NAME
Key Type		
Nulls/Unique		
FK table		
FK column		
Data Type	Number	Varchar2
Length	7	25

QUERY:

Create table deptartment(id number(7),name varchar2(25));

OUTPUT:

2.Create the EMP table based on the following instance chart. Confirm that the table is created.

Column name	ID	LAST_NAME	FIRST_NAME	DEPT_ID
Key Type				
Nulls/Unique				
FK table				
FK column				
Data Type	Number	Varchar2	Varchar2	Number
Length	7	25	25	7

QUERY:
Create table EMI(id number(7),Last_Name varchar2(25),First_Name varchar2(25),Dept_id number(7));

OUTPUT:

3.Modify the EMP table to allow for longer employee last names. Confirm the modification.(Hint: Increase the size to 50)

QUERY:
Alter table EMI modify(Last_Name varchar2(25));

OUTPUT:

4.Create the EMPLOYEES2 table based on the structure of EMPLOYEES table. Include Only the Employee_id, First_name, Last_name, Salary and Dept_id coloumns. Name the columns Id, First_name, Last_name, salary and Dept_id respectively.

QUERY:

Create table E2(id number(7),First_name varchar2(25),Last_name varchar2(25),Salary int,Dept_id number(7));

OUTPUT:

5.Drop the EMP table.

QUERY:

Drop table emp;

OUTPUT:

6.Rename the EMPLOYEES2 table as EMP.

QUERY:

Rename employees2 to emp;

OUTPUT:

7.Add a comment on DEPT and EMP tables. Confirm the modification by describing the table.

QUERY:

comment on table dept is 'Department info';
comment on table emp is Employee info';

OUTPUT:

8.Drop the First_name column from the EMP table and confirm it.

QUERY:

Alter table emp drop column First_name;

OUTPUT:

Evaluation Procedure	Marks awarded
Query(5)	
Execution (5)	
Viva(5)	
Total (15)	
Faculty Signature	

RESULT:

MANIPULATING DATA

EX_NO:2 **DATE:**

1.Create MY_EMPLOYEE table with the following structure

NAME	NULL?	TYPE
ID	Not null	Number(4)
Last_name		Varchar(25)
First_name		Varchar(25)
Userid		Varchar(25)
Salary		Number(9,2)

QUERY:

Create table MY_EMPLOYEE(ID number(4),last_name varchar(25),first_name varchar(25),userid varchar(25),salary number(9,2);

OUTPUT:

2.Add the first and second rows data to MY_EMPLOYEE table from the following sample data.

ID	Last_name	First_name	Userid	salary
1	Patel	Ralph	rpatel	895
2	Dancs	Betty	bdancs	860
3	Biri	Ben	bbiri	1100
4	Newman	Chad	Cnewman	750
5	Ropebur	Audrey	aropebur	1550

QUERY:
Insert into MY_EMPLOYEE VALUES(4,’Newman’,’chad’,’cnewman’,750);

OUTPUT:

3.Display the table with values.

QUERY:

Select * from MY_EMPLOYEE;
OUTPUT:

4.Populate the next two rows of data from the sample data. Concatenate the first letter of the first_name with the first seven characters of the last_name to produce Userid.

QUERY:

Insert into MY_EMPLOYEE VALUES(2,’Dancs’,’Betty’,’bdancs,860);

OUTPUT:

5.Make the data additions permanent.

QUERY:
Select * from MY_EMPLOYEE;

OUTPUT:

ID	LAST_NAME	FIRST_NAME	USER_ID	SALARY
1	Patle	Ralph	raptel	895
2	Dancs	betty	bdancs	860
3	BIRI	BEN	BBIRI	1100
4	NEWMAN	CHAD	CNEWMAN	750

6.Change the last name of employee 3 to Drexler.

QUERY:

UPDATE MY_EMPLOYEE SET last_name =’Drexler’ where ID=3;

OUTPUT:

7.Change the salary to 1000 for all the employees with a salary less than 900.

QUERY:

UPDATE MY_EMPLOYEE SET Salary=1000 where Salary<900;

OUTPUT:

8.Delete Betty dancs from MY _EMPLOYEE table.

QUERY:

Delete from MY_EMPLOYEE where first_name='Betty';

OUTPUT:

9.Empty the fourth row of the emp table.

QUERY:
Delete from MY_EMPLOYEE where ID=4;

OUTPUT:

Evaluation Procedure	Marks awarded
Query(5)	
Execution (5)	
Viva(5)	
Total (15)	
Faculty Signature	

RESULT:

INCLUDING CONSTRAINTS

EX_NO:3 **DATE:**

1.Add a table-level PRIMARY KEY constraint to the EMP table on the ID column.The constraint should be named at creation. Name the constraint my_emp_id_pk.

QUERY:

Create table Employee1(Emp_Id number(6),last_name varchar(25) not null,email varchar(25),primary key(EMP_ID);

OUTPUT:

2.Create a PRIMAY KEY constraint to the DEPT table using the ID colum. The constraint should be named at creation. Name the constraint my_dept_id_pk.

QUERY:
Create table Dept(My_dept_id_pk int,Dept_name varchar(20),Manager_name varchar(25),Location_id varchar(25),Primary key(My_dept_id_pk));

OUTPUT:

3.Add a column DEPT_ID to the EMP table. Add a foreign key reference on the EMP table that ensures that the employee is not assigned to nonexistent deparment. Name the constraint my_emp_dept_id_fk.

QUERY:

Alter table emp add constraint my_emp_dept_id_fk foreign key(dept_id) references emp(id):

OUTPUT:

4.Modify the EMP table. Add a COMMISSION column of NUMBER data type, precision 2, scale 2. Add a constraint to the commission column that ensures that a commission value is greater than zero.

QUERY:
Alter table EMP2 add Commission number (2,2)
Constraint Commission where (Commission>0);
OUTPUT:

Evaluation Procedure	Marks awarded
Query(5)	
Execution (5)	
Viva(5)	
Total (15)	
Faculty Signature	

RESULT:

Writing Basic SQL SELECT Statements

EX_NO:4 **DATE:**

1.The following statement executes successfully.

Identify the Errors

SELECT employee_id, last_name
sal*12 ANNUAL SALARY
FROM employees;

QUERY:

SELECT EMPLOYEE_ID,Last_name ,Salary*12 as Annual salary
From employee;

2.Show the structure of departments the table. Select all the data from it.

QUERY:
Desc Department;

OUTPUT:

3.Create a query to display the last name, job code, hire date, and employee number for each employee, with employee number appearing first.

QUERY:
Select Number,Last_name,job_id,Hire_Date,Emp_ID from Employee;

OUTPUT:

4.Provide an alias STARTDATE for the hire date.

QUERY:

Select hire_date as Start_Date from employee;

OUTPUT:

5.Create a query to display unique job codes from the employee table:

QUERY:

Select Unique JOB CODES from employee;

OUTPUT:

6.Display the last name concatenated with the job ID , separated by a comma and space, and name the column EMPLOYEE and TITLE.

QUERY:
Select Last_name || ‘,’ || JOB_ID as Title from employee;

OUTPUT:

7.Create a query to display all the data from the employees table. Separate each column by a comma. Name the column THE_OUTPUT.

QUERY:
Select Employee_ID ||’,’|| Last_name || ‘,’ || Job_Id || ‘,’ || Email || ’,’ || Salary ||’,’ || Hire_Date As “The Output” From Employee;

OUTPUT:

Evaluation Procedure	Marks awarded
Query(5)	
Execution (5)	
Viva(5)	
Total (15)	
Faculty Signature	

RESULT:

RESTRICTING AND SORTING DATA

EX_NO:5 **DATE:**

1.Create a query to display the last name and salary of employees earning more than 12000.

QUERY:

Select last_name,salary from empo21 where salary>12000;

OUTPUT:

2. Create a query to display the employee last name and department number for employee number 176.

QUERY:

select last_name,department_number from empo21 where emp_id=176;

OUTPUT:

3. Create a query to display the last name and salary of employees whose salary is not in the range of 5000 and 12000. (hints: not between)

QUERY:

select last_name,salary from empo21 where salary not between 5000 and 12000;

OUTPUT:

APEX App Builder SQL Workshop Team Development Gallery

SQL Commands

```
select last_name ,salary from empo21 where salary not between 5000 and 12000;
```

LAST_NAME	SALARY
appu	100000
joe	200
priya	100000
dhruv	20000

4 rows returned in 0.01 seconds

4. Display the employee last name, job ID, and start date of employees hired between February 20,1998 and May 1,1998.order the query in ascending order by start date.(hints: between)

QUERY:

Select last_name,job_id,hire_date from empo21 where hire_date between '02/20/1998' and '05/01/1998' order by hire_date asc;

OUTPUT:

APEX App Builder SQL Workshop Team Development Gallery

SQL Commands

```
select last_name,job_id,Hire_Date from empo21 where Hire_Date between '02/20/1998' and '05/01/1998' order by  Hire_date asc;
```

LAST_NAME	JOB_ID	HIRE_DATE
appu	1234	02/21/1998
dhruv	9101	03/07/1998
joe	8978	04/22/1998

3 rows returned in 0.01 seconds

5. Display the last name and department number of all employees in departments 20 and 50 in alphabetical order by name.(hints: in, orderby)

QUERY:

select last_name, department_number from empo21 where department in (20,50) order by last_name asc;

OUTPUT:

6. Display the last name and salary of all employees who earn between 5000 and 12000 and are in departments 20 and 50 in alphabetical order by name. Label the columns EMPLOYEE, MONTHLY SALARY respectively.(hints: between, in)

QUERY:

Select last_name as"EMPLOYEE",salary as "MONTHLY_SALARY" from empo21 where salary between 5000 and 12000 and department in(20,50) order by Name_emp asc;

OUTPUT:

APEX App Builder SQL Workshop Team Development Gallery

SQL Commands

```
Select last_name as"EMPLOYEE",salary as "MONTHLY_SALARY" from empo21
where salary  between 5000 and 12000 and
department in(20,50)
order by last_name asc;
```

EMPLOYEE	MONTHLY_SALARY
dhruv	11000
priya	5000

2 rows returned in 0.01 seconds

7. Display the last name and hire date of every employee who was hired in 1994.(hints: like) **QUERY:**

SELECT last_name, hire_date FROM empo21 WHERE hire_datevlike '%94';

OUTPUT:

APEX App Builder SQL Workshop Team Development Gallery

SQL Commands

```
SELECT last_name, hire_date
FROM empo21
WHERE hire_date like '%94';
```

LAST_NAME	HIRE_DATE
appu	02/21/1994
joe	04/22/1994

2 rows returned in 0.01 seconds

8. Display the last name and job title of all employees who do not have a manager.(hints: is null)

QUERY:

SELECT last_name, job_id FROM empo21 WHERE manager_id IS NULL;

OUTPUT:

APEX App Builder SQL Workshop Team Development Gallery

SQL Commands

```
SELECT last_name, job_id
FROM empo21
WHERE manager_id IS NULL;
```

LAST_NAME	JOB_ID
joe	8978
dhruv	9101

2 rows returned in 0.01 seconds

9. Display the last name, salary, and commission for all employees who earn commissions. Sort data in descending order of salary and commissions.(hints: is not nul,orderby)

QUERY:

SELECT last_name, salary, commission_pct FROM empo21 WHERE commission_pct IS NOT NULL ORDER BY salary DESC, commission_pct DESC; **OUTPUT:**

APEX App Builder SQL Workshop Team Development Gallery

SQL Commands

```
SELECT last_name, salary, commission_pct
FROM empo21
WHERE commission_pct IS NOT NULL
ORDER BY salary DESC, commission_pct DESC;
```

LAST_NAME	SALARY	COMMISSION_PCT
priya	5000	33
appu	1212	11
joe	200	22

3 rows returned in 0.01 seconds

10. Display the last name of all employees where the third letter of the name is ***a***.(hints:like)

QUERY:

SELECT last_name, hire_date FROM empo21 WHERE hire_datevlike '%94';

OUTPUT:

APEX App Builder SQL Workshop Team Development Gallery

SQL Commands

```
SELECT last_name
FROM empo21
WHERE last_name LIKE '__a%';
```

LAST_NAME
prayae
dhauvae

2 rows returned in 0.01 seconds

11. Display the last name of all employees who have an a and an ***e*** in their last name.(hints: like)

QUERY:

SELECT last_name FROM empo21 WHERE last_name LIKE '%a%' AND last_name LIKE '%e%';

OUTPUT:

APEX App Builder SQL Workshop Team Development Gallery

SQL Commands

0

```
SELECT last_name
FROM empo21
WHERE last_name LIKE '%a%'
AND last_name LIKE '%e%';
```

LAST_NAME
priyae
dhruvae

2 rows returned in 0.00 seconds

12. Display the last name and job and salary for all employees whose job is sales representative or stock clerk and whose salary is not equal to 2500 ,3500 or 7000.(hints:in,not in)

QUERY:

select last_name,job_id,salary from empo21 where job_id in ('sales representative','stock clerk') and salary not in(2500,3500,7000);

OUTPUT:

13. Display the last name, salary, and commission for all employees whose commission amount is 20%.(hints:use predicate logic)

QUERY:

select last_name,salary,commission_pct from employees where commission_pct=0.2;

OUTPUT:

Evaluation Procedure	Marks awarded
Query(5)	
Execution (5)	
Viva(5)	
Total (15)	
Faculty Signature	

RESULT:

SINGLE ROW FUNCTIONS

EX_NO:6 **DATE:**

1. Write a query to display the current date. Label the column Date.

QUERY:

select sysdate from dual;

OUTPUT:

APEX App Builder SQL Workshop Team Development Gallery Search Abisheak Ananat... abisheak08

SQL Commands Schema WKSP_ABISHEAK08

Language SQL Rows 10 Clear Command Find Tables Save Run

```
1 select sysdate from dual;
```

Results Explain Describe Saved SQL History

SYSDATE
03/12/2024

1 rows returned in 0.02 seconds Download

220701040@rajalakshmi.edu.in bhanu23 en Copyright © 1999, 2023, Oracle and/or its affiliates. Oracle APEX 23.2.4

2.The HR department needs a report to display the employee number, last name, salary, and increased by 15.5% (expressed as a whole number) for each employee. Label the column New Salary.

QUERY:

OUTPUT:

APEX App Builder SQL Workshop Team Development Gallery Search Abisheak Ananat... abisheak08

SQL Commands Schema WKSP_ABISHEAK08

Language SQL Rows 10 Clear Command Find Tables Save Run

```
1 select emp_id,last_name,salary,salary+(15.5/100*salary) "new_salary"from empo21;
```

Results Explain Describe Saved SQL History

EMP_ID	LAST_NAME	SALARY	new_salary
12	appu	1212	1399.86
4	joe	200	231
1	prayae	5000	5775
3	dhauvae	11000	12705

4 rows returned in 0.03 seconds Download

220701040@rajalakshmi.edu.in bhanu23 en Copyright © 1999, 2023, Oracle and/or its affiliates. Oracle APEX 23.2.4

3.Modify your query lab_03_02.sql to add a column that subtracts the old salary from the new salary. Label the column Increase.

QUERY:

select employee_id,last_name,salary,salary+(15.5/100*salary) "new_salary",new_salary-salary as "Increase" from empo21;

OUTPUT:

EMP_ID	LAST_NAME	SALARY	new_salary	Increase
12	appu	1212	1399.86	187.86
4	joe	200	231	31
1	prayae	5000	5775	775
3	dhauvae	11000	12705	1705

1. Write a query that displays the last name (with the first letter uppercase and all other letters lowercase) and the length of the last name for all empo21 whose name starts with the letters J, A, or M. Give each column an appropriate label. Sort the results by the empo21' last names.

QUERY:

select initcap(last_name),length(last_name) as "Length_of_last_name" from empo21 where last_name like 'J%' or last_name like 'A%' or last_name like 'M%' order by last_name asc;

OUTPUT:

INITCAP(LAST_NAME)	Length_of_last_name
Joe	3

2. Rewrite the query so that the user is prompted to enter a letter that starts the last name. For example, if the user enters H when prompted for a letter, then the output should show all empo21 whose last name starts with the letter H.

QUERY:

select initcap(last_name),length(last_name) as "Length_of_last_name" from empo21 where last_name like 'J%' or last_name like 'A%' or last_name like 'M%' order by last_name ;

OUTPUT:

3. The HR department wants to find the length of employment for each employee. For each employee, display the last name and calculate the number of months between today and the date on which the employee was hired. Label the column MONTHS_WORKED. Order your results by the number of months employed. Round the number of months up to the closest whole number.

QUERY:

select last_name,round((sysdate-hire_date)/30,0) as "MONTHS_WORKED" from empo21 order by round((sysdate-hire_date)/30,0) asc;

OUTPUT:

4. Create a report that produces the following for each employee:
<employee last name> earns<salary>monthly but wants <3 times salary>.Label the column Dream Salaries.

QUERY:

select last_name||' earns '||salary||' monthly but wants '||salary*3 as "DREAM_SALARIES" from empo21;

OUTPUT:

5. Create a query to display the last name and salary for all empo21. Format the salary to be 15 characters long, left-padded with the $ symbol. Label the column SALARY.

QUERY:

select last_name,lpad (salary,15,'$') as "SALARY" from empo21;

OUTPUT:

6. Display each employee's last name, hire date, and salary review date, which is the first Monday after six months of service. Label the column REVIEW. Format the dates to appear in the format similar to "Monday, the Thirty-First of July, 2000."

QUERY:

SELECT last_name,hire_date,TO_CHAR(NEXT_DAY(ADD_MONTHS(hire_date, 6), 'MONDAY'),'FMDay, "the "FMDD "of "FMMonth, YYYY') AS REVIEW FROM empo21;

OUTPUT:

7. Display the last name, hire date, and day of the week on which the employee started. Label the column DAY. Order the results by the day of the week, starting with Monday.

QUERY:

SELECT last_name,hire_date,TO_CHAR(hire_date,'Day') as Day from empo21 order by TO_CHAR(hire_date,'Day');

OUTPUT:

APEX App Builder SQL Workshop Team Development Gallery Search Abisheak Ananat... abisheak08

SQL Commands Schema WKSP_ABISHEAK08

Language SQL Rows 10 Clear Command Find Tables Save Run

```
SELECT last_name,hire_date,TO_CHAR(hire_date,'Day') as Day from empo21 order by
TO_CHAR(hire_date,'Day');
```

Results Explain Describe Saved SQL History

LAST_NAME	HIRE_DATE	DAY
Joe	04/22/1994	Friday
prayae	02/02/1998	Monday
appu	02/21/1994	Monday
Harsun	05/07/1998	Saturday

4 rows returned in 0.00 seconds Download

220701040@rajalakshmi.edu.in bhanu23 en

Copyright © 1999, 2023, Oracle and/or its affiliates.

Oracle APEX 23.2.4

Evaluation Procedure	Marks awarded
Query(5)	
Execution (5)	
Viva(5)	
Total (15)	
Faculty Signature	

RESULT:

DISPLAYING DATA FROM MULTIPLE TABLES

EX_NO:7 **DATE:**

1.Write a query to display the last name, department number, and department name for all employees.

QUERY:

Select e.last_name,e.department_number,d.dept_id from empo21 e,dept23 d where e.department_number=d.dept_id;

OUTPUT:

2.Create a unique listing of all jobs that are in department 80. Include the location of the department in the output.

QUERY:

select distinct job_id,loc_id from empo21 e,dept23 d where e.department_number=d.dept_id and e.department_number=80;

OUTPUT:

3.Write a query to display the employee last name, department name, location ID, and city of all employees who earn a commission

QUERY:

Select e.last_name,e.department_number,d.dept_name,d.loc_id,l.city from empo21 e,dept23 d,location l where e.department_number=d.dept_id and d.loc_id=l.location_id and e.commission_pct is not null;

OUTPUT:

4. Display the employee last name and department name for all employees who have an a(lowercase) in their last names.

QUERY:

Select empo21.last_name,dept23.dept_name from empo21,dept23where empo21.department_number=dept23.dept_id and last_name like '%a%';

OUTPUT:

5. Write a query to display the last name, job, department number, and department name for all employees who work in Toronto.

QUERY:

Select e.last_name,e.department_number,e.job_id,d.dept_name from empo21 e join dept d on(e.department_number=d.dept_id) join location on (d.location_id=location.location_id)__ where lower(location.city)='toronto';

OUTPUT:

6.Display the employee last name and employee number along with their manager's last name and manager number. Label the columns Employee, Emp#, Manager, and Mgr#, Respectively

QUERY:

Select w.last_name "Employee",w.emp_id "emp#",m.last_name 'manager",m.emp_id "Mgr#" from empo21 m on (w.manager_id=m.emp_id);

OUTPUT:

7. Modify lab4_6.sql to display all employees including King, who has no manager. Order the results by the employee number.

QUERY:

Select w.last_name “Employee”,w.emp_id “emp#”,m.last_name ‘manager”,m.emp_id “Mgr#” from empo21 w left outer join empo21 m on (w.manager_id=m.emp_id);

OUTPUT:

8.Create a query that displays employee last names, department numbers, and all the employees who work in the same department as a given employee. Give each column an appropriate label

QUERY:

select e.department_number dept23,e.last_name colleague from empo21 e join empo21 c on (e.department_number=c.department_number) where e.emp_id <> c.emp_id order by e.department_number,e.last_name,c.last_name;

OUTPUT:

```
select distinct job_id,loc_id from empo21 e,dept23 d where e.department_number=d.dept_id and e.department_number=80;
```

JOB_ID	LOC_ID
8978	49

1 rows returned in 0.03 seconds

9.Show the structure of the JOB_GRADES table. Create a query that displays the name, job, department name, salary, and grade for all employees

QUERY:

SELECT e.last_name, e. job_id, d.dept_name,e.salary, j• grade_level
FROM emp18 e JOIN dept18 d
ON (e.dept_id = d. dept_id)
JOIN job_grade j
ON (e.salary BETWEEN j. lowest_ sal AND j.highest_sal);

OUTPUT:

```
SELECT e.last_name, e.job_id, d.dept_name,e.salary, j.grade_level
FROM empo21 e JOIN dept23 d
ON (e.dept_id = d.dept_id)
JOIN job_grade j
ON (e.salary BETWEEN j.lowest_sal AND j.highest_sal);
```

no data found

10.Create a query to display the name and hire date of any employee hired after employee Davies.

QUERY:

SELECT e. last_name, e. hire_date FROM emp18 e, emp18 davies
WHERE davies.last name = 'Davies'
AND davies.hire_date ‹ e.hire_date;

OUTPUT:

11.Display the names and hire dates for all employees who were hired before their managers, along with their manager's names and hire dates. Label the columns Employee, Emp Hired, Manager, and Mgr Hired, respectively.

QUERY:

SELECT e. last_name AS Employee, e.hire_date AS Emp_Hired,
e. manager_name AS Manager, m.hire_date AS Mgr_Hired
FROM emp18 e
JOIN emp18|m ON e-manager _name = m. last_name
WHERE e.hire_date ‹ m.hire_date;

OUTPUT:

Evaluation Procedure	Marks awarded
Query(5)	
Execution (5)	
Viva(5)	
Total (15)	
Faculty Signature	

RESULT

AGGREGATING DATA USING GROUP FUNCTIONS

EX_NO : 8 **DATE:**

1.Group functions work across many rows to produce one result per group.
True/False

TRUE

2.Group functions include nulls in calculations.
True/False

FALSE

3.The WHERE clause restricts rows prior to inclusion in a group calculation.
True/False

FALSE

4.Find the highest, lowest, sum, and average salary of all employees. Label the columns Maximum, Minimum, Sum, and Average, respectively. Round your results to the nearest whole number

QUERY:

select Round(Max (salary),0)"Maximum", Round (Min (salary),0) "Minimum",

round(sum(salary),0)"sum", round (avg(salary),0) "Average" from EMPB;

OUTPUT:

5.Modify the above query to display the minimum, maximum, sum, and average salary for each job type.

QUERY:

select job_id ,Round(MAX(salary),0) "MAXIMUM",Round (Min(salary),0)"Minimum",Round

(SUM(Salary),0)"sum" ,Round (AVg (salary),0)"average" from EMPB group by job_id;

OUTPUT:

APEX App Builder SQL Workshop Team Development Gallery Search Abisheak Ananat... abisheak08

SQL Commands Schema WKSP_ABISHEAK08

Language SQL Rows 10 Clear Command Find Tables Save Run

```
select job_id ,Round(MAX(salary),0) "MAXIMUM",Round (Min(salary),0)"Minimum",Round (SUM(Salary),0)"sum" ,Round (AVg (salary),0)"average" from EMPB group by job_id;
```

Results Explain Describe Saved SQL History

JOB_ID	MAXIMUM	Minimum	sum	average
44	70000	70000	70000	70000
65	90000	90000	90000	90000
46	60000	60000	60000	60000
47	80000	80000	80000	80000

4 rows returned in 0.01 seconds Download

220701040@rajalakshmi.edu.in bhanu23 en Copyright © 1999, 2023, Oracle and/or its affiliates. Oracle APEX 23.2.4

6.Write a query to display the number of people with the same job. Generalize the query so that the user in the HR department is prompted for a job title.

QUERY:

select job_id, count(*) from EMPB group by job_id ;

select job_id, count(*) from EMPB where job_id='47' group by job_id ;

OUTPUT:

APEX App Builder SQL Workshop Team Development Gallery Search Abisheak Ananat... abisheak08

SQL Commands Schema WKSP_ABISHEAK08

Language SQL Rows 10 Clear Command Find Tables Save Run

```
select job_id, count(*) from EMPB where job_id='47' group by job_id ;
```

Results Explain Describe Saved SQL History

JOB_ID	COUNT(*)
47	1

1 rows returned in 0.01 seconds Download

220701040@rajalakshmi.edu.in bhanu23 en Copyright © 1999, 2023, Oracle and/or its affiliates. Oracle APEX 23.2.4

7.Determine the number of managers without listing them. Label the column Number of Managers. Hint: Use the MANAGER_ID column to determine the number of managers.

QUERY:

select count(distinct manager_id)"Number of managers" from empb;

OUTPUT:

8.Find the difference between the highest and lowest salaries. Label the column DIFFERENCE

QUERY:

select max(salary)-min(salary) difference from empb;

OUTPUT:

9.Create a report to display the manager number and the salary of the lowest-paid employee for that manager. Exclude anyone whose manager is not known. Exclude any groups where the minimum salary is $6,000 or less. Sort the output in descending order of salary.

QUERY:

select manager_id ,MIN(salary) from empb where manager_id is not null group by manager_id having min(salary) >6000 order by min(salary) desc;

OUTPUT:

10.Create a query to display the total number of employees and, of that total, the number of employees hired in 1995, 1996, 1997, and 1998. Create appropriate column headings

QUERY:

selectcount(*)total,sum(decode(to_char(hire_date,'YYYY'),1995,1,0))"1995",sum(decode(to_char(hire_date,'YYYY'),1996,1,0))"1996",sum(decode(to_char(hire_date,'YYYY'),1997,1,0))"1997",sum(decode(to_char(hire_date,'YYYY'),1998,1,0)) "1998" from empb;

OUTPUT:

```
SELECT count(*) total ,sum(decode (to_char(hire_date,'YYYY'),1995,1,0))"1995",
sum(decode(to_char(hire_date ,'YYYY'),1996,1,0))"1996",sum(decode(to_char(hire_date,'YYYY'),1997,1,0))"1997",sum(decode(to_char(hire_date,'YYYY'),1998,1,0)) "1998" from empB;
```

TOTAL	1995	1996	1997	1998
4	1	0	1	0

1 rows returned in 0.01 seconds

11.Create a matrix query to display the job, the salary for that job based on department number, and the total salary for that job, for departments 20, 50, 80, and 90, giving each column an appropriate heading

QUERY:

select job_id "job", sum(decode(dept_id,20,salary))"Dept20",sum (decode(dept_id ,50, salary)) "dept50",sum (decode(dept_id ,80, salary)) "dept80",sum (decode(dept_id ,90, salary)) "dept90",sum(salary) "TOTAl" from empb group by job_id

OUTPUT:

```
select job_id "job", sum(decode(dept_id,20,salary))"Dept20",sum (decode(dept_id ,50, salary)) "dept50",
sum (decode(dept_id ,80, salary)) "dept80",sum (decode(dept_id ,90, salary)) "dept90",sum(salary) "TOTAl" from empb group by job_id
```

job	Dept20	dept50	dept80	dept90	TOTAl
44	-	-	-	-	60000
65	-	-	-	-	90000
46	-	-	-	-	80000
47	-	-	70000	-	70000

4 rows returned in 0.01 seconds

12. Write a query to display each department‘s name, location, number of employees, and the average salary for all the employees in that department. Label the column name-Location, Number of people, and salary respectively. Round the average salary to two decimal places.

QUERY:

select d.dept_name as "dept_name",d.loc as "department location", count(*) "Number of people",round(avg(salary),2) "salary" from dept111 d inner join empb e on(d.dpet_id =e.dept_id) group by d.dept_name ,d.loc;

OUTPUT:

APEX App Builder SQL Workshop Team Development Gallery Search Abisheak Ananat... abisheak08

SQL Commands Schema WKSP_ABISHEAK08

Language SQL Rows 10 Clear Command Find Tables Save Run

```
select d.dept_name as "dept_name",d.loc as "department location",
count(*) "Number of people",round(avg(salary),2) "salary" from dept1 d inner join empb e on(d.dept_id =e.dept_id ) group by d.dept_name ,d.loc;
```

Results Explain Describe Saved SQL History

dept_name	department location	Number of people	salary
CS	CHENNAI	1	70000
IT	MUMBAI	1	90000
IT	TORANTO	1	80000
CS	BANGLORE	1	60000

4 rows returned in 0.07 seconds Download

220701040@rajalakshmi.edu.in bhanu25 en Copyright © 1999, 2025, Oracle and/or its affiliates. Oracle APEX 25.2.4

Evaluation Procedure	Marks awarded
Query(5)	
Execution (5)	
Viva(5)	
Total (15)	

Faculty Signature	

RESULT:

SUB QUERIES

EX_NO:9 **DATE:**

1.)The HR department needs a query that prompts the user for an employee last name. The query then displays the last name and hire date of any employee in the same department as the employee whose name they supply (excluding that employee). For example, if the user enters Zlotkey, find all employees who work with Zlotkey (excluding Zlotkey).

QUERY:

select last_name,hire_date from employees where department_id=(select department_id from employees where last_name='Janu') and last_name not in('Janu');

OUTPUT:

2.) Create a report that displays the employee number, last name, and salary of all employees who earn more than the average salary. Sort the results in order of ascending salary.

QUERY:

select employee_id,last_name,salary from employees where salary>(select avg(salary) from employees) order by salary;

OUTPUT:

APEX App Builder SQL Workshop Team Development Gallery Search Abisheak Ananat... abisheak08

SQL Commands Schema WKSP_ABISHEAK08

Language SQL Rows 10 Clear Command Find Tables Save Run

```
1 select emp_id,last_name,salary from empo21 where salary>(select avg(salary) from empo21) order by salary;
2
3
```

Results Explain Describe Saved SQL History

EMP_ID	LAST_NAME	SALARY
2	Janu	60000
5	Brown	80000

2 rows returned in 0.01 seconds Download

220701040@rajalakshmi.edu.in bhanu23 en Copyright © 1999, 2023, Oracle and/or its affiliates. Oracle APEX 23.2.4

3.) Write a query that displays the employee number and last name of all employees who work in a department with any employee whose last name contains a u.

QUERY:

select employee_id,last_name from employees where department_id=(select department_id from employees where last_name like'%u%');

OUTPUT:

APEX App Builder SQL Workshop Team Development Gallery Search Abisheak Ananat... abisheak08

SQL Commands Schema WKSP_ABISHEAK08

Language SQL Rows 10 Clear Command Find Tables Save Run

```
1 select employee_id,last_name from employees where department_id=(select department_id from employees where last_name like'%u%' );
```

Results Explain Describe Saved SQL History

EMPLOYEE_ID	LAST_NAME
2	Janu
4	Jones
3	Williams

3 rows returned in 0.03 seconds Download

220701040@rajalakshmi.edu.in bhanu23 en Copyright © 1999, 2023, Oracle and/or its affiliates. Oracle APEX 23.2.4

4.) The HR department needs a report that displays the last name, department number, and job ID of all employees whose department location ID is 1700.

QUERY:

select last_name,department_id,job_id from employees where department_id=(select dept_id from departments where location_id=1700);

OUTPUT:

APEX App Builder SQL Workshop Team Development Gallery

SQL Commands

```
select last_name,dept_id,job_id from empo21 where dept_id=(select dept_id from location where location_id=1700);
```

LAST_NAME	DEPT_ID	JOB_ID
Janu	80	102
davies	20	101
Jones	80	104
Brown	5	105
Williams	80	103

5 rows returned in 0.06 seconds

5.)Create a report for HR that displays the last name and salary of every employee who reports to King.

QUERY:

select last_name,salary from employees where manager_id=(select manager_id from employees where manager_name='King');

OUTPUT:

APEX App Builder SQL Workshop Team Development Gallery

SQL Commands

```
select last_name,salary from empo21 where manager_id in(select manager_id from empo21 where manager_name='King');
```

LAST_NAME	SALARY
davies	50000
Williams	20000
Jones	48000

3 rows returned in 0.01 seconds

6.) Create a report for HR that displays the department number, last name, and job ID for every employee in the Executive department.

QUERY:

select department_id,last_name,job_id from employees where department_id in (select dept_id from departments where dept_name='Executive');

OUTPUT:

APEX App Builder SQL Workshop Team Development Gallery

SQL Commands

Schema WKSP_ABISHEAK08

Language SQL Rows 10 Clear Command Find Tables Save Run

```
select department_id,last_name,job_id from employees where department_id in (select dept_id from departments where dept_name='Executive');
```

Results Explain Describe Saved SQL History

DEPARTMENT_ID	LAST_NAME	JOB_ID
80	Janu	ac_account
80	Jones	ac_account
80	Williams	hr_rep

3 rows returned in 0.01 seconds Download

7.) Modify the query 3 to display the employee number, last name, and salary of all employees who earn more than the average salary and who work in a department with any employee whose last name contains a u.

QUERY:

select employee_id,last_name,salary from employees where salary>(select avg(salary) from employees where last_name like '%u%');

OUTPUT:

APEX App Builder SQL Workshop Team Development Gallery

SQL Commands

Schema WKSP_ABISHEAK08

Language SQL Rows 10 Clear Command Find Tables Save Run

```
select employee_id,last_name,salary from employees where salary>(select avg(salary) from employees where last_name like '%u%');
```

Results Explain Describe Saved SQL History

EMPLOYEE_ID	LAST_NAME	SALARY
5	Brown	80000

1 rows returned in 0.01 seconds Download

Evaluation Procedure	Marks awarded
Query(5)	
Execution (5)	
Viva(5)	
Total (15)	
Faculty Signature	

RESULT:

USING THE SET OPERATORS

EX_NO:10 **DATE:**

1.)The HR department needs a list of department IDs for departments that do not contain the job ID ST_CLERK. Use set operators to create this report.

QUERY:

select department_id from employees minus select department_id from employees where job_id='st_clerk';

OUTPUT:

2.)The HR department needs a list of countries that have no departments located in them. Display the country ID and the name of the countries. Use set operators to create this report.

QUERY:

select country_id,state_province from location minus select country_id,state_province from location,departments where location.location_id=departments.location_id;

OUTPUT:

3.) Produce a list of jobs for departments 10, 50, and 20, in that order. Display job ID and department ID using set operators.

QUERY:

select job_id,department_id from employees where department_id=10 union
select job_id,department_id from employees where department_id=50 union
select job_id,department_id from employees where department_id=20;

OUTPUT:

4.) Create a report that lists the employee IDs and job IDs of those employees who currently have a job title that is the same as their job title when they were initially hired by the company (that is, they changed jobs but have now gone back to doing their original job).

QUERY:

select job_id,employee_id from employees intersect select e.job_id,e.employee_id from employees e,job_history j where e.job_id=j.old_job_id;

OUTPUT:

5.)The HR department needs a report with the following specifications: - Last name and department ID of all the employees from the EMPLOYEES table, regardless of whether or not they belong to a department. - Department ID and department name of all the departments from the DEPARTMENTS table, regardless of whether or not they have employees working in them Write a compound query to accomplish this.

QUERY:

select first_name||' '||last_name as "Name",department_id from employees union all select dept_name,dept_id from departments;

OUTPUT:

APEX App Builder SQL Workshop Team Development Gallery Search Abisheak Ananat... abisheak08

SQL Commands Schema WKSP_ABISHEAK08

Language SQL Rows 10 Clear Command Find Tables Save Run

```
1  select last_name as "Name",department_id from employees union all select dept_name,dept_id from departments;
```

Results Explain Describe Saved SQL History

Name	DEPARTMENT_ID
Janu	80
davies	20
Jones	80
Brown	50
Williams	80
Executive	80
IT	23
CS	46
IT	80

9 rows returned in 0.01 seconds Download

220701040@rajalakshmi.edu.in bhanu23 en

Copyright © 1999, 2023, Oracle and/or its affiliates.

Oracle APEX 23.2.4

Evaluation Procedure	Marks awarded
Query(5)	
Execution (5)	
Viva(5)	
Total (15)	
Faculty Signature	

RESULT:

CREATING VIEWS

EX_NO:11 **DATE:**

1.)Create a view called EMPLOYEE_VU based on the employee numbers, employee names and department numbers from the EMPLOYEES table. Change the heading for the employee name to EMPLOYEE.

QUERY:

CREATE OR REPLACE VIEW employees_vu AS SELECT employee_id, last_name employee, department_id FROM employees;

OUTPUT:

2.) Display the contents of the EMPLOYEES_VU view.

QUERY:

select * from employees_vu;

OUTPUT:

3.)Select the view name and text from the USER_VIEWS data dictionary views

QUERY:

SELECT view_name, text FROM user_views;

OUTPUT:

4.)Using your EMPLOYEES_VU view, enter a query to display all employees names and department

QUERY:

SELECT employee, department_id FROM employees_vu;

OUTPUT:

5.)Create a view named DEPT50 that contains the employee number, employee last names and department numbers for all employees in department 50.Label the view columns EMPNO, EMPLOYEE and DEPTNO. Do not allow an employee to be reassigned to another department through the view.

QUERY:

CREATE VIEW dept50 AS SELECT employee_id empno, last_name employee, department_id deptno FROM employees WHERE department_id = 50 WITH CHECK OPTION CONSTRAINT emp_dept_50;

OUTPUT:

6.)Display the structure and contents of the DEPT50 view.

QUERY:

Describe dept50;

OUTPUT:

APEX App Builder SQL Workshop Team Development Gallery Search Abisheak Ananat... abisheak08

SQL Commands Schema WKSP_ABISHEAK08

SQL Commands Schema WKSP_BHANU23

Language SQL Rows 10 Clear Command Find Tables Save Run

```
1 Describe dept50
```

Results Explain Describe Saved SQL History

Object Type VIEW Object DEPT50

Table	Column	Data Type	Length	Precision	Scale	Primary Key	Nullable	Default	Comment
DEPT50	EMPNO	NUMBER	22	-	0	-	-	-	-
	EMPLOYEE	VARCHAR2	20	-	-	-	✓	-	-
	DEPTNO	NUMBER	22	-	0	-	✓	-	-

7.) Attempt to reassign Matos to department 80

QUERY:

UPDATE dept50 SET deptno=80 WHERE employee='Matos';

OUTPUT:

APEX App Builder SQL Workshop Team Development Gallery Search Abisheak Ananat... abisheak08

SQL Commands Schema WKSP_ABISHEAK08

Language SQL Rows 10 Clear Command Find Tables Save Run

```
1 UPDATE dept50
2 SET deptno=80
3 WHERE employee='Matos';
4
5
```

Results Explain Describe Saved SQL History

0 row(s) updated.

0.05 seconds

8.)

Create a view called SALARY_VU based on the employee last names, department names, salaries, and salary grades for all employees. Use the Employees, DEPARTMENTS and JOB_GRADE tables. Label the column Employee, Department, salary, and Grade respectively.

QUERY:

create or replace view salary_vu as select e.last_name "Employee",d.dept_name Department, e.salary "Salary",j.grade_level "Grades" from employees e,departments d,job_grade j where e.department_id=d.dept_id and e.salary between j.lowest_sal and j.highest_sal;

OUTPUT:

Evaluation Procedure	Marks awarded
Query(5)	
Execution (5)	
Viva(5)	

Total (15)	
Faculty Signature	

RESULT:

EXERCISE 12
PRACTICE QUESTIONS

Intro to Constraints; NOT NULL and UNIQUE Constraints

Global Fast Foods has been very successful this past year and has opened several new stores. They need to add a table to their database to store information about each of their store's locations. The owners want to make sure that all entries have an identification number, date opened, address, and city and that no other entry in the table can have the same email address. Based on this information, answer the following questions about the global_locations table. Use the table for your answers.

Global Fast Foods global_locations Table						
NAME	**TYPE**	**LENGTH**	**PRECISION**	**SCALE**	**NULLABLE**	**DEFAULT**
Id						
name						
date_opened						
address						
city						
zip/postal code						
phone						
email						
manager_id						
Emergency contact						

1. What is a "constraint" as it relates to data integrity?

   Database can be as reliable as the data in it, and database rules are implemented as Constraint to maintain data integrity.

2. What are the limitations of constraints that may be applied at the column level and at the table level?

   - Constraints referring to more than one column are defined at Table Level
   - NOT NULL constraint must be defined at column level as per ANSI/ISO SQL standard.

3. Why is it important to give meaningful names to constraints?

   - If a constraint is violated in a SQL statement execution, it is easy to identify the cause with user-named constraints.
   - It is easy to alter names/drop constraint.

4. Based on the information provided by the owners, choose a datatype for each column. Indicate the length, precision, and scale for each NUMBER datatype.

Global Fast Foods global_locations Table						
NAME	TYPE	DataType	LENGTH	PRECISION	SCALE	NULLABLE
id	pk	NUMBER	6	0		No
name		VARCHAR2	50			
date_opened		DATE				No
address		VARCHAR2	50			No
city		VARCHAR2	30			No
zip_postal_code		VARCHAR2	12			
phone		VARCHAR2	20			
email	uk	VARCHAR2	75			
manager_id		NUMBER	6	0		
emergency_contact		VARCHAR2	20			

5. Use "(nullable)" to indicate those columns that can have null values.

Global Fast Foods global_locations Table						
NAME	TYPE	DataType	LENGTH	PRECISION	SCALE	NULLABLE
id	pk	NUMBER	6	0		**No**
name		VARCHAR2	50			**Yes**
date_opened		DATE				No
address		VARCHAR2	50			**No**
city		VARCHAR2	30			**No**
zip_postal_code		VARCHAR2	12			**Yes**
phone		VARCHAR2	20			**Yes**
email	uk	VARCHAR2	75			**Yes**
manager_id		NUMBER	6	0		**Yes**
emergency_contact		VARCHAR2	20			**Yes**

6. Write the CREATE TABLE statement for the Global Fast Foods locations table to define the constraints at the column level.

```
CREATE TABLE  f_global_locations
( id NUMBER(6,0) CONSTRAINT f_gln_id_pk PRIMARY KEY ,
name VARCHAR2(50),
date_opened DATE CONSTRAINT f_gln_dt_opened_nn NOT NULL ENABLE,
address VARCHAR2(50) CONSTRAINT f_gln_add_nn NOT NULL ENABLE,
city VARCHAR2(30)  CONSTRAINT f_gln_city_nn NOT NULL ENABLE,
zip_postal_code VARCHAR2(12),
phone VARCHAR2(20),
email VARCHAR2(75) CONSTRAINT f_gln_email_uk UNIQUE,
manager_id NUMBER(6,0),
emergency_contact VARCHAR2(20)
);
```

7. Execute the CREATE TABLE statement in Oracle Application Express.

Table Created.

8. Execute a DESCRIBE command to view the Table Summary information.

DESCRIBE f_global_locations;

9. Rewrite the CREATE TABLE statement for the Global Fast Foods locations table to define the UNIQUE constraints at the table level. Do not execute this statement.

NAME	TYPE	LENGTH	PRECISION	SCALE	NULLABLE	DEFAULT
id	number	4				
loc_name	varchar2	20			X	
	date					
address	varchar2	30				
city	varchar2	20				
zip_postal	varchar2	20			X	
phone	varchar2	15			X	
email	varchar2	80			X	
manager_id	number	4			X	
contact	varchar2	40			X	

```
CREATE TABLE  f_global_locations
( id NUMBER(6,0) CONSTRAINT f_gln_id_pk PRIMARY KEY ,
name VARCHAR2(50),
date_opened DATE CONSTRAINT f_gln_dt_opened_nn NOT NULL ENABLE,
address VARCHAR2(50) CONSTRAINT f_gln_add_nn NOT NULL ENABLE,
city VARCHAR2(30)  CONSTRAINT f_gln_city_nn NOT NULL ENABLE,
zip_postal_code VARCHAR2(12),
phone VARCHAR2(20),
email VARCHAR2(75) ,
manager_id NUMBER(6,0),
emergency_contact VARCHAR2(20),
 CONSTRAINT f_gln_email_uk UNIQUE(email)
);
```

PRIMARY KEY, FOREIGN KEY, and CHECK Constraints

1. What is the purpose of a

- PRIMARY KEY
- FOREIGN KEY
- CHECK CONSTRAINT

a. PRIMARY KEY

Uniquely identify each row in table.

b. FOREIGN KEY

Referential integrity constraint links back parent table's primary/unique key to child table's column.

c. CHECK CONSTRAINT

Explicitly define condition to be met by each row's fields. This condition must be returned as true or unknown.

2. Using the column information for the animals table below, name constraints where applicable at the table level, otherwise name them at the column level. Define the primary key (animal_id). The license_tag_number must be unique. The admit_date and vaccination_date columns cannot contain null values.

animal_id NUMBER(6) - **PRIMARY KEY**
name VARCHAR2(25)
license_tag_number NUMBER(10) - **UNIQUE**
admit_date DATE -**NOT NULL**
adoption_id NUMBER(5),
vaccination_date DATE -**NOT NULL**

3. Create the animals table. Write the syntax you will use to create the table.

```
CREATE TABLE  animals
( animal_id  NUMBER(6,0) CONSTRAINT anl_anl_id_pk PRIMARY KEY ,
name VARCHAR2(25),
license_tag_number NUMBER(10,0) CONSTRAINT anl_l_tag_num_uk UNIQUE,
admit_date  DATE CONSTRAINT anl_adt_dat_nn NOT NULL ENABLE,
adoption_id   NUMBER(5,0),
vaccination_date  DATE CONSTRAINT anl_vcc_dat_nn NOT NULL ENABLE
);
```

4. Enter one row into the table. Execute a SELECT * statement to verify your input. Refer to the graphic below for input.

ANIMAL_ID	NAME	LICENSE_TAG_NUMBER	ADMIT_DATE	ADOPTION_ID	VACCINATION_DATE
101	Spot	35540	10-Oct-2004	205	12-Oct-2004

```
INSERT INTO animals (animal_id, name, license_tag_number, admit_date, adoption_id, vaccination_date)
VALUES( 101, 'Spot', 35540, TO_DATE('10-Oct-2004', 'DD-Mon-YYYY'), 205, TO_DATE('12-Oct-2004', 'DD-Mon-YYYY'));
```

```
SELECT * FROM animals;
```

5. Write the syntax to create a foreign key (adoption_id) in the animals table that has a corresponding primary-key reference in the adoptions table. Show both the column-level and table-level syntax. Note that because you have not actually created an adoptions table, no adoption_id primary key exists, so the foreign key cannot be added to the animals table.

COLUMN LEVEL STATEMENT:

```
ALTER TABLE animals
MODIFY ( adoption_id   NUMBER(5,0) CONSTRAINT anl_adopt_id_fk  REFERENCES adoptions(id)
ENABLE );
```

TABLE LEVEL STATEMENT:

```
ALTER TABLE  animals ADD CONSTRAINT anl_adopt_id_fk  FOREIGN KEY (adoption_id)
REFERENCES  adoptions(id) ENABLE;
```

6. What is the effect of setting the foreign key in the ANIMAL table as:

a. ON DELETE CASCADE

```
ALTER TABLE  animals
ADD CONSTRAINT anl_adopt_id_fk  FOREIGN KEY (adoption_id)
REFERENCES  adoptions(id) ON DELETE CASCADE  ENABLE ;
```

b. ON DELETE SET NULL

```
ALTER TABLE  animals
ADD CONSTRAINT anl_adopt_id_fk  FOREIGN KEY (adoption_id)
REFERENCES  adoptions(id) ON DELETE SET NULL  ENABLE ;
```

7. What are the restrictions on defining a CHECK constraint?

- I cannot specify check constraint for a view however in this case I could use WITH CHECK OPTION clause
- I am restricted to columns from self table and fields in self row.
- I cannot use subqueries and scalar subquery expressions.

Evaluation Procedure	Marks awarded
Query(5)	
Execution (5)	
Viva(5)	
Total (15)	
Faculty Signature	

PRACTICE PROBLEM
Managing Constraints

Using Oracle Application Express, click the SQL Workshop tab in the menu bar. Click the Object Browser and verify that you have a table named copy_d_clients and a table named copy_d_events. If you don't have these tables in your schema, create them before completing the exercises below. Here is how the original tables are related. The d_clients table has a primary key client_number. This has a primary-key constraint and it is referenced in the foreign-key constraint on the d_events table.

NOTE: The practice exercises use the d_clients and d_events tables in the DJs on Demand database. Students will work with copies of these two tables named copy_d_clients and copy_d_events. Make sure they have new copies of the tables (without changes made from previous exercises). Remember, tables copied using a subquery do not have the integrity constraints as established in the original tables. When using the SELECT statement to view the constraint name, the tablenames must be all capital letters.

1. What are four functions that an ALTER statement can perform on constraints?

- ADD
- DROP
- ENABLE
- DISABLE

2. Since the tables are copies of the original tables, the integrity rules are not passed onto the new tables; only the column datatype definitions remain. You will need to add a PRIMARY KEY constraint to the copy_d_clients table. Name the primary key copy_d_clients_pk . What is the syntax you used to create the PRIMARY KEY constraint to the copy_d_clients.table?

```
ALTER TABLE copy_d_clients
ADD  CONSTRAINT copy_d_clt_client_number_pk PRIMARY KEY (client_number);
```

3. Create a FOREIGN KEY constraint in the copy_d_events table. Name the foreign key copy_d_events_fk. This key references the copy_d_clients table client_number column. What is the syntax you used to create the FOREIGN KEY constraint in the copy_d_events table?

```
ALTER TABLE  copy_d_events
ADD CONSTRAINT copy_d_eve_client_number_fk FOREIGN KEY (client_number) REFERENCES
copy_d_clients (client_number) ENABLE;
```

4. Use a SELECT statement to verify the constraint names for each of the tables. Note that the tablenames must be capitalized.

```
SELECT constraint_name, constraint_type, table_name
FROM user_constraints
WHERE table_name =  UPPER('copy_d_events') ;
```

a. The constraint name for the primary key in the copy_d_clients table is_____.

COPY_D_CLT_CLIENT_NUMBER_PK

5. Drop the PRIMARY KEY constraint on the copy_d_clients table. Explain your results.

```
ALTER TABLE copy_d_clients
DROP CONSTRAINT COPY_D_CLT_CLIENT_NUMBER_PK CASCADE  ;
```

6. Add the following event to the copy_d_events table. Explain your results.

ID	NAME	EVENT_DATE	DESCRIPTION	COST	VENUE_ID	PACKAGE_CODE	THEME_CODE	CLIENT_NUMBER
140	Cline Bas Mitzvah	15-Jul-2004	Church and Private Home formal	4500	105	87	77	7125

```
INSERT INTO
copy_d_events(client_number,id,name,event_date,description,cost,venue_id,package_code,theme_code)
VALUES(7125,140,'Cline Bas Mitzvah',TO_DATE('15-Jul-2004','dd-Mon-yyyy'),'Church and Private Home
formal',4500,105,87,77);
```

RESULT: ORA-02291: integrity constraint (HKUMAR.COPY_D_EVE_CLIENT_NUMBER_FK) violated - parent key not found

7. Create an ALTER TABLE query to disable the primary key in the copy_d_clients table. Then add the values from #6 to the copy_d_events table. Explain your results.

```
ALTER TABLE copy_d_clients
DISABLE CONSTRAINT COPY_D_CLT_CLIENT_NUMBER_PK CASCADE;
```

8. Repeat question 6: Insert the new values in the copy_d_events table. Explain your results.

```
INSERT INTO
copy_d_events(client_number,id,name,event_date,description,cost,venue_id,package_code,theme_code)
VALUES(7125,140,'Cline Bas Mitzvah',TO_DATE('15-Jul-2004','dd-Mon-yyyy'),'Church and Private
Home formal',4500,105,87,77);
```

1 row(s) inserted.

9. Enable the primary-key constraint in the copy_d_clients table. Explain your results.

```
ALTER TABLE copy_d_clients
ENABLE CONSTRAINT COPY_D_CLT_CLIENT_NUMBER_PK ;
```

10. If you wanted to enable the foreign-key column and reestablish the referential integrity between these two tables, what must be done?

```
DELETE FROM copy_d_events WHERE
client_number  NOT IN ( SELECT client_number FROM copy_d_clients);
```

1 row(s) deleted.

```
ALTER TABLE copy_d_events
ENABLE CONSTRAINT COPY_D_EVE_CLIENT_NUMBER_FK;
```

Table altered.

11. Why might you want to disable and then re-enable a constraint?

Generally to make bulk operations fast, where my input data is diligently sanitized and I am sure, it is safe to save some time in this clumsy process.

12. Query the data dictionary for some of the constraints that you have created. How does the data dictionary identify each constraint type?

Queries are same as in point 2,3, 4 above.

- C - Check constraint
  Sub-case - if I see SEARCH_CONDITION something like "FIRST_NAME" IS NOT NULL , its a NOT NULL constraint.
- P - Primary key
- R - Referential integrity (fk)
- U - Unique key

Evaluation Procedure	Marks awarded
Query(5)	
Execution (5)	
Viva(5)	
Total (15)	
Faculty Signature	

EXERCISE 13

Creating Views

1. What are three uses for a view from a DBA's perspective?

- **Restrict access and display selective columns**
- **Reduce complexity of queries from other internal systems. So, providing a way to view same data in a different manner.**
- **Let the app code rely on views and allow the internal implementation of tables to be modified later.**

2. Create a simple view called view_d_songs that contains the ID, title and artist from the DJs on Demand table for each "New Age" type code. In the subquery, use the alias "Song Title" for the title column.

```
CREATE VIEW view_d_songs AS
SELECT d_songs.id, d_songs.title "Song Title", d_songs.artist
from d_songs INNER JOIN d_types ON d_songs.type_code = d_types.code
where d_types.description = 'New Age';
```

3. SELECT * FROM view_d_songs. What was returned?

Results | Explain | Describe | Saved SQL | History

ID	Song Title	ARTIST
47	Hurrah for Today	The Jubilant Trio
49	Lets Celebrate	The Celebrants

2 rows returned in 0.00 seconds Download

4. REPLACE view_d_songs. Add type_code to the column list. Use aliases for all columns.
Or use alias after the CREATE statement as shown.

```
CREATE OR REPLACE VIEW view_d_songs AS
SELECT d_songs.id, d_songs.title "Song Title", d_songs.artist, d_songs.type_code
from d_songs INNER JOIN d_types ON d_songs.type_code = d_types.code
where d_types.description = 'New Age';
```

5. Jason Tsang, the disk jockey for DJs on Demand, needs a list of the past events and those planned for the coming months so he can make arrangements for each event's equipment setup. As the company manager, you do not want him to have access to the price that clients paid for their events. Create a view for Jason to use that displays the name of the event, the event date, and the theme description. Use aliases for each column name.

```
CREATE OR REPLACE VIEW view_d_events_pkgs AS
SELECT evt.name "Name of Event", TO_CHAR(evt.event_date, 'dd-Month-yyyy') "Event date",
thm.description "Theme description"
FROM d_events evt INNER JOIN d_themes thm ON evt.theme_code = thm.code
WHERE evt.event_date <= ADD_MONTHS(SYSDATE,1);
```

6. It is company policy that only upper-level management be allowed access to individual employee salaries. The department managers, however, need to know the minimum, maximum, and average salaries, grouped by department. Use the Oracle database to prepare a view that displays the needed information for department managers.

```
CREATE OR REPLACE VIEW view_min_max_avg_dpt_salary ("Department Id", "Department Name",
"Max Salary", "Min Salary", "Average Salary") AS
SELECT dpt.department_id, dpt.department_name, MAX(NVL(emp.salary,0)),
MIN(NVL(emp.salary,0)), ROUND(AVG(NVL(emp.salary,0)),2)
FROM departments dpt LEFT OUTER JOIN employees emp ON dpt.department_id =
emp.department_id
GROUP BY (dpt.department_id, dpt.department_name);
```

DML Operations and Views

Use the DESCRIBE statement to verify that you have tables named copy_d_songs, copy_d_events, copy_d_cds, and copy_d_clients in your schema. If you don't, write a query to create a copy of each.

1. Query the data dictionary USER_UPDATABLE_COLUMNS to make sure the columns in the base tables will allow UPDATE, INSERT, or DELETE. All table names in the data dictionary are stored in uppercase.

```
SELECT owner, table_name, column_name, updatable,insertable, deletable
FROM user_updatable_columns WHERE LOWER(table_name) = 'copy_d_songs';

SELECT owner, table_name, column_name, updatable,insertable, deletable
FROM user_updatable_columns WHERE LOWER(table_name) = 'copy_d_events';

SELECT owner, table_name, column_name, updatable,insertable, deletable
FROM user_updatable_columns WHERE LOWER(table_name) = 'copy_d_cds';
```

2. Use the CREATE or REPLACE option to create a view of *all* the columns in the copy_d_songs table called view_copy_d_songs.

```
CREATE OR REPLACE VIEW view_copy_d_songs AS
SELECT *
FROM copy_d_songs;

SELECT * FROM view_copy_d_songs;
```

3. Use view_copy_d_songs to INSERT the following data into the underlying copy_d_songs table. Execute a SELECT * from copy_d_songs to verify your DML command. See the graphic.

ID	TITLE	DURATION	ARTIST	TYPE_CODE
88	Mello Jello	2	The What	4

```
INSERT INTO view_copy_d_songs(id,title,duration,artist,type_code)
VALUES(88,'Mello Jello','2 min','The What',4);
```

4. Create a view based on the DJs on Demand COPY_D_CDS table. Name the view read_copy_d_cds. Select all columns to be included in the view. Add a WHERE clause to restrict the year to 2000. Add the WITH READ ONLY option.

```
CREATE OR REPLACE VIEW read_copy_d_cds AS
SELECT *
FROM copy_d_cds
WHERE year = '2000'
WITH READ ONLY ;

SELECT * FROM read_copy_d_cds;
```

5. Using the read_copy_d_cds view, execute a DELETE FROM read_copy_d_cds WHERE cd_number = 90;

ORA-42399: cannot perform a DML operation on a read-only view

6. Use REPLACE to modify read_copy_d_cds. Replace the READ ONLY option with WITH CHECK

OPTION CONSTRAINT ck_read_copy_d_cds. Execute a SELECT * statement to verify that the view exists.

```
CREATE OR REPLACE VIEW read_copy_d_cds AS
SELECT *
FROM copy_d_cds
WHERE year = '2000'
WITH CHECK OPTION CONSTRAINT ck_read_copy_d_cds;
```

7. Use the read_copy_d_cds view to delete any CD of year 2000 from the underlying copy_d_cds.

```
DELETE FROM read_copy_d_cds
WHERE year = '2000';
```

8. Use the read_copy_d_cds view to delete cd_number 90 from the underlying copy_d_cds table.

```
DELETE FROM read_copy_d_cds
WHERE cd_number = 90;
```

9. Use the read_copy_d_cds view to delete year 2001 records.

```
DELETE FROM read_copy_d_cds
WHERE year = '2001';
```

10. Execute a SELECT * statement for the base table copy_d_cds. What rows were deleted?

Only the one in problem 7 above, not the one in 8 and 9

11. What are the restrictions on modifying data through a view?

DELETE.INSERT,MODIFY restricted if it contains:

Group functions
GROUP BY CLAUSE
DISTINCT
pseudocolumn ROWNUM Keyword

12. What is Moore's Law? Do you consider that it will continue to apply indefinitely? Support your opinion with research from the internet.

It roughly predicted that computing power nearly doubles every year. But Moore also said in 2005 that as per nature of exponential functions, this trend may not continue forever.

13. What is the "singularity" in terms of computing?

Singularity is the hypothesis that the invention of artificial superintelligence will abruptly trigger runaway technological growth, resulting in unfathomable changes to human civilization

Managing Views

1. Create a view from the copy_d_songs table called view_copy_d_songs that includes only the title and artist. Execute a SELECT * statement to verify that the view exists.

```
CREATE OR REPLACE VIEW view_copy_d_songs AS
SELECT title, artist
FROM copy_d_songs;

SELECT * FROM view_copy_d_songs;
```

2. Issue a DROP view_copy_d_songs. Execute a SELECT * statement to verify that the view has been deleted.

```
DROP VIEW view_copy_d_songs;
SELECT * FROM view_copy_d_songs;

ORA-00942: table or view does not exist
```

3. Create a query that selects the last name and salary from the Oracle database. Rank the salaries from highest to lowest for the top three employees.

```
SELECT * FROM
(SELECT last_name, salary FROM employees ORDER BY salary  DESC)
WHERE ROWNUM <= 3;
```

4. Construct an inline view from the Oracle database that lists the last name, salary, department ID, and maximum salary for each department. Hint: One query will need to calculate maximum salary by department ID.

```
SELECT empm.last_name, empm.salary, dptmx.department_id
FROM
(SELECT dpt.department_id, MAX(NVL(emp.salary,0)) max_dpt_sal
FROM departments dpt LEFT OUTER JOIN employees emp ON dpt.department_id =
emp.department_id
GROUP BY dpt.department_id) dptmx LEFT OUTER JOIN employees empm ON
dptmx.department_id = empm.department_id
WHERE NVL(empm.salary,0) = dptmx.max_dpt_sal;
```

5. Create a query that will return the staff members of Global Fast Foods ranked by salary from lowest to highest.

```
SELECT ROWNUM,last_name, salary
FROM
(SELECT * FROM f_staffs ORDER BY SALARY);
```

Indexes and Synonyms

1. What is an index and what is it used for?

Definition: These are schema objects which make retrieval of rows from table faster.

Purpose: An index provides direct and fast access to row in table. They provide indexed path to locate data quickly, so hereby reduce necessity of heavy disk input/output operations.

2. What is a ROWID, and how is it used?

Indexes use ROWID's (base 64 string representation of the row address containing block identifier, row location in the block and the database file identifier) which is the fastest way to access any particular row.

3. When will an index be created automatically?

Primary key/unique key use already existing unique index but if index is not present already, it is created while applying unique/primary key constraint.

4. Create a nonunique index (foreign key) for the DJs on Demand column (cd_number) in the D_TRACK_LISTINGS table. Use the Oracle Application Express SQL Workshop Data Browser to confirm that the index was created.

```
CREATE INDEX d_tlg_cd_number_fk_i
 on d_track_listings (cd_number);
```

5. Use the join statement to display the indexes and uniqueness that exist in the data dictionary for the DJs on Demand D_SONGS table.

```
SELECT ucm.index_name, ucm.column_name, ucm.column_position, uix.uniqueness
FROM user_indexes uix INNER JOIN user_ind_columns ucm ON uix.index_name = ucm.index_name
WHERE ucm.table_name = 'D_SONGS';
```

6. Use a SELECT statement to display the index_name, table_name, and uniqueness from the data dictionary USER_INDEXES for the DJs on Demand D_EVENTS table.

```
SELECT index_name, table_name,uniqueness FROM user_indexes where table_name =
'D_EVENTS';
```

7. Write a query to create a synonym called dj_tracks for the DJs on Demand d_track_listings table.

```
CREATE SYNONYM dj_tracks FOR d_track_listings;
```

8. Create a function-based index for the last_name column in DJs on Demand D_PARTNERS table that makes it possible not to have to capitalize the table name for searches. Write a SELECT statement that would use this index.

```
CREATE INDEX d_ptr_last_name_idx
ON d_partners(LOWER(last_name));
```

9. Create a synonym for the D_TRACK_LISTINGS table. Confirm that it has been created by querying the data dictionary.

```
CREATE SYNONYM dj_tracks2 FOR d_track_listings;


SELECT * FROM user_synonyms WHERE table_NAME = UPPER('d_track_listings');
```

10. Drop the synonym that you created in question

```
DROP SYNONYM dj_tracks2;
```

Evaluation Procedure	Marks awarded
Query(5)	
Execution (5)	
Viva(5)	
Total (15)	
Faculty Signature	

RESULT:

OTHER DATABASE OBJECTS

EX_NO:14 **DATE:**

1.)Create a sequence to be used with the primary key column of the DEPT table. The sequence should start at 200 and have a maximum value of 1000. Have your sequence increment by ten numbers. Name the sequence DEPT_ID_SEQ

QUERY:

CREATE SEQUENCE dept_id_seq START WITH 200 INCREMENT BY 10 MAXVALUE 1000;

OUTPUT:

2.)Write a query in a script to display the following information about your sequences: sequence name, maximum value, increment size, and last number

QUERY:

SELECT sequence_name, max_value, increment_by, last_number FROM user_sequences;

OUTPUT:

3.) Write a script to insert two rows into the DEPT table. Name your script lab12_3.sql. Be sure to use the sequence that you created for the ID column. Add two departments named Education and Administration. Confirm your additions. Run the commands in your script.

QUERY:

INSERT INTO dept VALUES (dept_id_seq.nextval, 'Education');

OUTPUT:

4.)Create a nonunique index on the foreign key column (DEPT_ID) in the EMP table.

QUERY:

CREATE INDEX emp_dept_id_idx ON EMPLOYEES (department_id);

OUTPUT:

5.)Display the indexes and uniqueness that exist in the data dictionary for the EMP table.

QUERY:

SELECT index_name,table_name,uniqueness FROM user_indexes WHERE table_name='EMPLOYEES';

OUTPUT:

Evaluation Procedure	Marks awarded
Query(5)	
Execution (5)	
Viva(5)	
Total (15)	
Faculty Signature	

RESULT:

CONTROLLING USER ACCESS

EX_NO:15 **DATE:**

1. What privilege should a user be given to log on to the Oracle Server? Is this a system or an object privilege?

The CREATE SESSION system privilege

2. What privilege should a user be given to create tables?

The CREATE TABLE privilege

3. If you create a table, who can pass along privileges to other users on your table?

You can, or anyone you have given those privileges to by using the WITH GRANT OPTION.

4. You are the DBA. You are creating many users who require the same system privileges. What should you use to make your job easier?

Create a role containing the system privileges and grant the role to the users

5. What command do you use to change your password?

The ALTER USER statement

6. Grant another user access to your DEPARTMENTS table. Have the user grant you query access to his or her DEPARTMENTS table.

Team 2 executes the GRANT statement. GRANT select ON departments TO <user1>;

Team 1 executes the GRANT statement. GRANT select ON departments TO <user2>;

7. Query all the rows in your DEPARTMENTS table.

SELECT * FROM departments;

8. Add a new row to your DEPARTMENTS table. Team 1 should add Education as department number 500. Team 2 should add Human Resources department number 510. Query the other team's table.

Team 1 executes this INSERT statement. INSERT INTO departments(department_id, department_name) VALUES (500, 'Education'); COMMIT;

Team 2 executes this INSERT statement. INSERT INTO departments(department_id, department_name) VALUES (510, 'Administration'); COMMIT;

9. Query the USER_TABLES data dictionary to see information about the tables that you own.

SELECT table_name FROM user_tables;

10. Revoke the SELECT privilege on your table from the other team.

Team 1 revokes the privilege.

```
REVOKE select
ON departments
FROM user2;
```

Team 2 revokes the privilege.

```
REVOKE select
ON departments
FROM user1;
```

11. Remove the row you inserted into the DEPARTMENTS table in step 8 and save the changes.

Team 1 executes this INSERT statement.

```
DELETE FROM departments
WHERE department_id = 500;
COMMIT;
```

Team 2 executes this INSERT statement.

```
DELETE FROM departments
WHERE department_id = 510;
COMMIT;
```

Evaluation Procedure	Marks awarded
Practice Evaluation (5)	
Viva(5)	
Total (10)	
Faculty Signature	

RESULT:

PL/SQL

CONTROL STRUCTURES

EX_NO: **DATE:**

1.) Write a PL/SQL block to calculate the incentive of an employee whose ID is 110.

QUERY:

```
 DECLARE
 incentive  NUMBER(8,2);
BEGIN
 SELECT salary*0.12 INTO incentive
 FROM employees
 WHERE employee_id = 110;
DBMS_OUTPUT.PUT_LINE('Incentive  = ' || TO_CHAR(incentive));
END;
```

OUTPUT:

2.) Write a PL/SQL block to show an invalid case-insensitive reference to a quoted and without quoted user-defined identifier

QUERY:

```
DECLARE
WELCOME varchar2(10) := 'welcome';
BEGIN
DBMS_Output.Put_Line("Welcome");
END;
/
```

```
DECLARE
 WELCOME varchar2(10) := 'welcome';
 BEGIN
 DBMS_Output.Put_Line("Welcome");
 END;
 /
```

OUTPUT:

3.) Write a PL/SQL block to adjust the salary of the employee whose ID 122.

QUERY:

```
DECLARE
 salary_of_emp NUMBER(8,2);
 PROCEDURE approx_salary (
  emp       NUMBER,
  empsal IN OUT NUMBER,
  addless     NUMBER
 ) IS
 BEGIN
  empsal := empsal + addless;
 END;

BEGIN
 SELECT salary INTO salary_of_emp
 FROM employees
 WHERE employee_id = 122;
 DBMS_OUTPUT.PUT_LINE
  ('Before invoking procedure, salary_of_emp: ' || salary_of_emp);
 approx_salary (100, salary_of_emp, 1000);
 DBMS_OUTPUT.PUT_LINE
  ('After invoking procedure, salary_of_emp: ' || salary_of_emp);
END;
/
```

OUTPUT:

4.) Write a PL/SQL block to create a procedure using the "IS [NOT] NULL Operator" and show AND operator returns TRUE if and only if both operands are TRUE.

QUERY:

```
CREATE OR REPLACE PROCEDURE pri_bool(
  boo_name  VARCHAR2,
  boo_val  BOOLEAN
) IS
BEGIN
  IF boo_val IS NULL THEN
    DBMS_OUTPUT.PUT_LINE( boo_name || ' = NULL');
  ELSIF boo_val = TRUE THEN
    DBMS_OUTPUT.PUT_LINE( boo_name || ' = TRUE');
  ELSE
    DBMS_OUTPUT.PUT_LINE( boo_name || ' = FALSE');
  END IF;
END;
/
```

OUTPUT:

5.) Write a PL/SQL block to describe the usage of LIKE operator including wildcard characters and escape character.

QUERY:

```
DECLARE
 PROCEDURE pat_match (
  test_string  VARCHAR2,
  pattern  VARCHAR2
 ) IS
 BEGIN
  IF test_string LIKE pattern THEN
  DBMS_OUTPUT.PUT_LINE ('TRUE');
  ELSE
   DBMS_OUTPUT.PUT_LINE ('FALSE');
  END IF;
 END;
BEGIN
 pat_match('Blweate', 'B%a_e');
pat_match('Blweate',  'B%A_E');
END;
/
```

OUTPUT:

6.) Write a PL/SQL program to arrange the number of two variable in such a way that the small number will store in num_small variable and large number will store in num_large variable

QUERY:

```
DECLARE
num_small NUMBER := 8;
num_large NUMBER := 5;
num_temp NUMBER;
BEGIN

IF num_small > num_large THEN
num_temp := num_small;
num_small := num_large;
num_large := num_temp;
END IF;

DBMS_OUTPUT.PUT_LINE ('num_small = '||num_small);
DBMS_OUTPUT.PUT_LINE ('num_large = '||num_large);
END;
/
```

OUTPUT:

7.) Write a PL/SQL procedure to calculate the incentive on a target achieved and display the message either the record updated or not.

QUERY:

```
DECLARE
 PROCEDURE test1 (
  sal_achieve NUMBER,
  target_qty NUMBER,
  emp_id NUMBER
 )
 IS
  incentive NUMBER := 0;
 updated VARCHAR2(3) := 'No';
 BEGIN
  IF sal_achieve > (target_qty + 200) THEN
   incentive := (sal_achieve - target_qty)/4;
   UPDATE employees
   SET salary = salary + incentive
   WHERE employee_id = emp_id;
   updated := 'Yes';
  END IF;
  DBMS_OUTPUT.PUT_LINE (
   'Table updated? ' || updated || ', ' ||
   'incentive = ' || incentive || '.'
  );
 END test1;
BEGIN
 test1(2300, 2000, 144);
 test1(3600, 3000, 145);
END;
/
```

OUTPUT:

8.) Write a PL/SQL procedure to calculate incentive achieved according to the specific sale limit

QUERY:

```
DECLARE
 PROCEDURE test1 (sal_achieve  NUMBER)
 IS
  incentive  NUMBER := 0;
 BEGIN
  IF sal_achieve > 44000 THEN
   incentive := 1800;
  ELSIF sal_achieve > 32000 THEN
   incentive := 800;
  ELSE
   incentive := 500;
  END IF;
DBMS_OUTPUT.NEW_LINE;
  DBMS_OUTPUT.PUT_LINE (
   'Sale achieved : ' || sal_achieve || ', incentive : ' || incentive || '.'
  );
 END test1;
BEGIN
 test1(45000);
test1(36000);
test1(28000);
END;
/
```

9.) Write a PL/SQL program to count number of employees in department 50 and check whether this department have any vacancies or not. There are 45 vacancies in this department.

QUERY:

```
SET SERVEROUTPUT ON
DECLARE
   tot_emp NUMBER;
         get_dep_id NUMBER;

BEGIN
   get_dep_id := 80;
   SELECT Count(*)
   INTO  tot_emp
   FROM employees e
        join departments d
         ON e.department_id = d.department_id
   WHERE  e.department_id = get_dep_id;
   dbms_output.Put_line ('The employees are in the department '||get_dep_id||' is: '
                    ||To_char(tot_emp));
   IF tot_emp >= 45 THEN
    dbms_output.Put_line ('There are no vacancies in the department '||get_dep_id);
   ELSE
    dbms_output.Put_line ('There are '||to_char(45-tot_emp)||' vacancies in department '||
get_dep_id );
   END IF;
END;
/
```

OUTPUT:

10.) Write a PL/SQL program to count number of employees in a specific department and check whether this department have any vacancies or not. If any vacancies, how many vacancies are in that department.

QUERY:

```
DECLARE
   tot_emp NUMBER;
         get_dep_id NUMBER;

BEGIN
   get_dep_id := 80;
   SELECT Count(*)
   INTO  tot_emp
   FROM employees e
        join departments d
          ON e.department_id = d.dept_id
   WHERE  e.department_id = get_dep_id;

   dbms_output.Put_line ('The employees are in the department '||get_dep_id||' is: '
                    ||To_char(tot_emp));

   IF tot_emp >= 45 THEN
    dbms_output.Put_line ('There are no vacancies in the department '||get_dep_id);
   ELSE
    dbms_output.Put_line ('There are '||to_char(45-tot_emp)||' vacancies in department '||
get_dep_id );
   END IF;
END;
/
```

OUTPUT:

==

11.) Write a PL/SQL program to display the employee IDs, names, job titles, hire dates, and salaries of all employees

QUERY:

```
DECLARE
v_employee_id employees.employee_id%TYPE;
v_full_name employees.first_name%TYPE;
v_job_id employees.job_id%TYPE;
v_hire_date employees.hire_date%TYPE;
v_salary employees.salary%TYPE;
CURSOR c_employees IS
   SELECT employee_id, first_name || ' ' || last_name AS full_name, job_id, hire_date, salary
   FROM employees;
BEGIN
  DBMS_OUTPUT.PUT_LINE('Employee ID | Full Name | Job Title | Hire Date | Salary');
  DBMS_OUTPUT.PUT_LINE('----------------------------------------------------------------');
  OPEN c_employees;
  FETCH c_employees INTO v_employee_id, v_full_name, v_job_id, v_hire_date, v_salary;
  WHILE c_employees%FOUND LOOP
   DBMS_OUTPUT.PUT_LINE(v_employee_id || '      | ' || v_full_name || ' | ' || v_job_id || ' | ' ||
v_hire_date || ' | ' || v_salary);
   FETCH c_employees INTO v_employee_id, v_full_name, v_job_id, v_hire_date, v_salary;
  END LOOP;
  CLOSE c_employees;
END;
/
```

OUTPUT:

12.) Write a PL/SQL program to display the employee IDs, names, and department names of all employees.

QUERY:

```
DECLARE
  CURSOR emp_cursor IS
    SELECT e.employee_id, e.first_name, m.first_name AS manager_name
    FROM employees e
    LEFT JOIN employees m ON e.manager_id = m.employee_id;
emp_record emp_cursor%ROWTYPE;
BEGIN
  OPEN emp_cursor;
  FETCH emp_cursor INTO emp_record;
  WHILE emp_cursor%FOUND LOOP
    DBMS_OUTPUT.PUT_LINE('Employee ID: ' || emp_record.employee_id);
    DBMS_OUTPUT.PUT_LINE('Employee Name: ' || emp_record.first_name);
    DBMS_OUTPUT.PUT_LINE('Manager Name: ' || emp_record.manager_name);
    DBMS_OUTPUT.PUT_LINE(' ---------------------- ');
    FETCH emp_cursor INTO emp_record;
  END LOOP;
  CLOSE emp_cursor;
END;
/
```

OUTPUT:

13.) Write a PL/SQL program to display the job IDs, titles, and minimum salaries of all jobs

QUERY:

```
DECLARE
  CURSOR job_cursor IS
    SELECT e.job_id, j.lowest_sal
    FROM job_grade j,employees e;
job_record job_cursor%ROWTYPE;
BEGIN
  OPEN job_cursor;
  FETCH job_cursor INTO job_record;
  WHILE job_cursor%FOUND LOOP
    DBMS_OUTPUT.PUT_LINE('Job ID: ' || job_record.job_id);
    DBMS_OUTPUT.PUT_LINE('Minimum Salary: ' || job_record.lowest_sal);
    DBMS_OUTPUT.PUT_LINE(' ---------------------- ');
    FETCH job_cursor INTO job_record;
  END LOOP;
  CLOSE job_cursor;
END;
/
```

OUTPUT:

14.) Write a PL/SQL program to display the employee IDs, names, and job history start dates of all employees.

QUERY:

```
DECLARE
   CURSOR employees_cur IS
    SELECT employee_id,last_name, job_id,start_date
    FROM  employees NATURAL join job_history;
   emp_start_date DATE;
BEGIN
   dbms_output.Put_line(Rpad('Employee ID', 15)||Rpad('Last Name', 25)|| Rpad('Job Id', 35)
||'Start Date');
dbms_output.Put_line('----------------------------------------------------------------------------------------');
FOR emp_sal_rec IN employees_cur LOOP
   -- find out most recent end_date in job_history
   SELECT Max(end_date) + 1
   INTO emp_start_date
   FROM  job_history
   WHERE  employee_id = emp_sal_rec.employee_id;
   IF emp_start_date IS NULL THEN
    emp_start_date := emp_sal_rec.start_date;
   END IF;
   dbms_output.Put_line(Rpad(emp_sal_rec.employee_id, 15)
                  ||Rpad(emp_sal_rec.last_name, 25)
                  || Rpad(emp_sal_rec.job_id, 35)
                  || To_char(emp_start_date, 'dd-mon-yyyy'));
END LOOP;
END;
/
```

OUTPUT:

15.) Write a PL/SQL program to display the employee IDs, names, and job history end dates of all employees.

QUERY:

```
DECLARE
```

```
v_employee_id employees.employee_id%TYPE;
v_first_name employees.last_name%TYPE;
v_end_date job_history.end_date%TYPE;
  CURSOR c_employees IS
    SELECT e.employee_id, e.first_name, jh.end_date
    FROM employees e
    JOIN job_history jh ON e.employee_id = jh.employee_id;
BEGIN
  OPEN c_employees;
  FETCH c_employees INTO v_employee_id, v_first_name, v_end_date;
  WHILE c_employees%FOUND LOOP
    DBMS_OUTPUT.PUT_LINE('Employee ID: ' || v_employee_id);
    DBMS_OUTPUT.PUT_LINE('Employee Name: ' || v_first_name);
    DBMS_OUTPUT.PUT_LINE('End Date: ' || v_end_date);
    DBMS_OUTPUT.PUT_LINE(' ------------------- ');
    FETCH c_employees INTO v_employee_id, v_first_name, v_end_date;
  END LOOP;
  CLOSE c_employees;
END;
```

OUTPUT:

Evaluation Procedure	Marks awarded
Query(5)	
Execution (5)	
Viva(5)	
Total (15)	
Faculty Signature	

RESULT:

PROCEDURES AND FUNCTIONS

EX_NO: 17 **DATE:**

1.)Factorial of a number using function.

QUERY:

```
DECLARE
   fac NUMBER := 1;
   n NUMBER := :1;
BEGIN
   WHILE n > 0 LOOP
      fac := n * fac;
      n := n - 1;
   END LOOP;
   DBMS_OUTPUT.PUT_LINE(fac);
END;
```

OUTPUT:

2.) Write a PL/SQL program using Procedures IN,INOUT,OUT parameters to retrieve the corresponding book information in library.

QUERY:

```
CREATE OR REPLACE PROCEDURE get_book_info (
   p_book_id IN NUMBER,
   p_title IN OUT VARCHAR2,
   p_author OUT VARCHAR2,
   p_year_published OUT NUMBER
)
AS
BEGIN
   SELECT title, author, year_published INTO p_title, p_author, p_year_published
   FROM books
   WHERE book_id = p_book_id;

   p_title := p_title || ' - Retrieved';
EXCEPTION
   WHEN NO_DATA_FOUND THEN
      p_title := NULL;
      p_author := NULL;
      p_year_published := NULL;
END;


DECLARE
   v_book_id NUMBER := 1;
   v_title VARCHAR2(100);
   v_author VARCHAR2(100);
   v_year_published NUMBER;
BEGIN
   v_title := 'Initial Title';
```

```
    get_book_info(p_book_id => v_book_id, p_title => v_title, p_author => v_author,
p_year_published => v_year_published);

    DBMS_OUTPUT.PUT_LINE('Title: ' || v_title);
    DBMS_OUTPUT.PUT_LINE('Author: ' || v_author);
    DBMS_OUTPUT.PUT_LINE('Year Published: ' || v_year_published);
END;
```

OUTPUT:

Query(5)	
Execution (5)	
Viva(5)	
Total (15)	
Faculty Signature	

RESULT:

TRIGGER

EX_NO: 18 **DATE:**

1.)Write a code in PL/SQL to develop a trigger that enforces referential integrity by preventing the deletion of a parent record if child records exist

QUERY:

```
CREATE OR REPLACE TRIGGER prevent_parent_deletion
BEFORE DELETE ON parent_table
FOR EACH ROW
DECLARE
   child_exists EXCEPTION;
   PRAGMA EXCEPTION_INIT(child_exists, -20001);
   v_child_count NUMBER;
BEGIN
   SELECT COUNT(*) INTO v_child_count FROM child_table WHERE parent_id =
:OLD.parent_id;
   IF v_child_count > 0 THEN
      RAISE child_exists;
   END IF;
EXCEPTION
   WHEN child_exists THEN
      RAISE_APPLICATION_ERROR(-20001, 'Cannot delete parent record while child records
exist.');
END;
```

OUTPUT:

2.) Write a code in PL/SQL to create a trigger that checks for duplicate values in a specific column and raises an exception if found

QUERY:

```
CREATE OR REPLACE TRIGGER check_duplicates
BEFORE INSERT OR UPDATE ON unique_values_table
FOR EACH ROW
DECLARE
   duplicate_found EXCEPTION;
   PRAGMA EXCEPTION_INIT(duplicate_found, -20002);
   v_count NUMBER;
BEGIN
   SELECT COUNT(*) INTO v_count FROM unique_values_table
   WHERE unique_col = :NEW.unique_col AND id != :NEW.id;
   IF v_count > 0 THEN
      RAISE duplicate_found;
   END IF;
EXCEPTION
   WHEN duplicate_found THEN
      RAISE_APPLICATION_ERROR(-20002, 'Duplicate value found in unique_col.');
END;
```

OUTPUT:

3.) Write a code in PL/SQL to create a trigger that restricts the insertion of new rows if the total of a column's values exceeds a certain threshold

QUERY:

```
CREATE OR REPLACE TRIGGER check_threshold
BEFORE INSERT OR UPDATE ON threshold_table
FOR EACH ROW
DECLARE
   threshold_exceeded EXCEPTION;
   PRAGMA EXCEPTION_INIT(threshold_exceeded, -20003);
   v_sum NUMBER;
   v_threshold NUMBER := 10000; -- Set your threshold here
BEGIN
   SELECT SUM(value_col) INTO v_sum FROM threshold_table;
   v_sum := v_sum + :NEW.value_col;
   IF v_sum > v_threshold THEN
      RAISE threshold_exceeded;
   END IF;
```

```
EXCEPTION
   WHEN threshold_exceeded THEN
      RAISE_APPLICATION_ERROR(-20003, 'Threshold exceeded for value_col.');
END;
```

OUTPUT:

4.) Write a code in PL/SQL to design a trigger that captures changes made to specific columns and logs them in an audit table.

QUERY:

```
CREATE OR REPLACE TRIGGER log_changes
```

```
AFTER UPDATE ON main_table
FOR EACH ROW
BEGIN
   INSERT INTO audit_table (audit_id, changed_id, old_col1, new_col1, old_col2, new_col2, change_time)
   VALUES (audit_seq.NEXTVAL, :OLD.id, :OLD.col1, :NEW.col1, :OLD.col2, :NEW.col2, SYSTIMESTAMP);
END;
```

OUTPUT:

5.) Write a code in PL/SQL to implement a trigger that records user activity (inserts, updates, deletes) in an audit log for a given set of tables.

QUERY:

```
CREATE OR REPLACE TRIGGER log_user_activity
AFTER INSERT OR UPDATE OR DELETE ON activity_table
FOR EACH ROW
BEGIN
   IF INSERTING THEN
      INSERT INTO user_activity_log (log_id, action, table_name, record_id, change_time)
      VALUES (activity_log_seq.NEXTVAL, 'INSERT', 'activity_table', :NEW.id, SYSTIMESTAMP);
   ELSIF UPDATING THEN
      INSERT INTO user_activity_log (log_id, action, table_name, record_id, change_time)
      VALUES (activity_log_seq.NEXTVAL, 'UPDATE', 'activity_table', :NEW.id,
SYSTIMESTAMP);
   ELSIF DELETING THEN
      INSERT INTO user_activity_log (log_id, action, table_name, record_id, change_time)
      VALUES (activity_log_seq.NEXTVAL, 'DELETE', 'activity_table', :OLD.id, SYSTIMESTAMP);
   END IF;
END;
```

OUTPUT:

6.) Write a code in PL/SQL to implement a trigger that automatically calculates and updates a running total column for a table whenever new rows are inserted

QUERY:

```
CREATE OR REPLACE TRIGGER update_running_total
BEFORE INSERT ON running_total_table
FOR EACH ROW
DECLARE
   v_total NUMBER;
BEGIN
   SELECT NVL(SUM(amount), 0) INTO v_total FROM running_total_table;
   :NEW.running_total := v_total + :NEW.amount;
```

END;

OUTPUT:

APEX
App Builder
SQL Workshop
Team Development
Gallery
Search
Abisheak Ananat...
abisheak08
Language
SQL
Rows
10
Clear Command
Find Tables
Save
Run
CREATE OR REPLACE TRIGGER update_running_total
BEFORE INSERT ON running_total_table
FOR EACH ROW
DECLARE
v_total NUMBER;
BEGIN
SELECT NVL(SUM(amount), 0) INTO v_total FROM running_total_table;
:NEW.running_total := v_total + :NEW.amount;
END;
/
Results
Explain
Describe
Saved SQL
History
Trigger created.
0.04 seconds
220701049@rajalakshmi.edu.in
chandar
en
Copyright © 1999, 2023, Oracle and/or its affiliates.
Oracle APEX 23.2.4

7.) Write a code in PL/SQL to create a trigger that validates the availability of items before allowing an order to be placed, considering stock levels and pending orders

QUERY:

```
CREATE OR REPLACE TRIGGER validate_order
BEFORE INSERT ON orders
FOR EACH ROW
DECLARE
   v_stock NUMBER;
   insufficient_stock EXCEPTION;
   PRAGMA EXCEPTION_INIT(insufficient_stock, -20004);
BEGIN
   SELECT stock_quantity INTO v_stock FROM items WHERE item_id = :NEW.item_id;
   IF v_stock < :NEW.order_quantity THEN
      RAISE insufficient_stock;
   END IF;
   UPDATE items SET stock_quantity = stock_quantity - :NEW.order_quantity WHERE item_id
= :NEW.item_id;
EXCEPTION
   WHEN insufficient_stock THEN
      RAISE_APPLICATION_ERROR(-20004, 'Insufficient stock for the item.');
END;
```

OUTPUT:

Evaluation Procedure	Marks awarded
Query(5)	
Execution (5)	
Viva(5)	
Total (15)	
Faculty Signature	

RESULT:

MONGO DB

EX_NO: 19 **DATE:**

1.) Write a MongoDB query to find the restaurant Id, name, borough and cuisine for those restaurants which prepared dish except 'American' and 'Chinees' or restaurant's name begins with letter 'Wil'.

QUERY:

db.restaurants.find({ $or: [{ name: /^Wil/ }, { cuisine: { $nin: ['American', 'Chinese'] } }] , { restaurant_id: 1, name: 1, borough: 1, cuisine: 1 });

OUTPUT:

2.) Write a MongoDB query to find the restaurant Id, name, and grades for those restaurants which achieved a grade of "A" and scored 11 on an ISODate "2014-08- 11T00:00:00Z" among many of survey dates.

QUERY:

db.restaurants.find({ grades: { $elemMatch: { grade: "A",score: 11, date: ISODate("2014-08-11T00:00:00Z")} }},{ restaurant_id: 1,name: 1,grades: 1 });

OUTPUT:

3.) Write a MongoDB query to find the restaurant Id, name and grades for those restaurants where the 2nd element of grades array contains a grade of "A" and score 9 on an ISODate "2014-08-11T00:00:00Z".

QUERY:

db.restaurants.find({"grades.1.grade": "A", "grades.1.score": 9, "grades.1.date": ISODate("2014-08-1T00:00:00Z") },{ restaurant_id: 1, name: 1, grades: 1 });

OUTPUT:

4.) Write a MongoDB query to find the restaurant Id, name, address and geographical location for those restaurants where 2nd element of coord array contains a value which is more than 42 and upto 52

QUERY:

db.restaurants.find({$and : [{"address.coord.1": {$gt : 42}},{"address.coord.1": {$lte : 52}}]}, {_id:0, restaurant_id:1, name:1, address:1})

OUTPUT:

5.) Write a MongoDB query to arrange the name of the restaurants in ascending order along with all the columns.

QUERY:

db.restaurants.find({}, { _id: 0 }).sort({ name: 1 });

OUTPUT:

6.) Write a MongoDB query to arrange the name of the restaurants in descending along with all the columns.

QUERY:

db.restaurants.find({}, { _id: 0 }).sort({ name: -1 })

OUTPUT:

7.) Write a MongoDB query to arranged the name of the cuisine in ascending order and for that same cuisine borough should be in descending order.

QUERY:

db.restaurants.find({}, { _id: 0 }).sort({ cuisine: 1, borough: -1 })

OUTPUT:

8.) Write a MongoDB query to know whether all the addresses contains the street or not.

QUERY:

db.restaurants.find({ "address.street": { $exists: true, $ne: "" } })

OUTPUT:

9.) Write a MongoDB query which will select all documents in the restaurants collection where the coord field value is Double.

QUERY:

db.restaurants.find({ "address.coord": { $elemMatch: { $type: "double" } } })

OUTPUT:

10. Write a MongoDB query which will select the restaurant Id, name and grades for those restaurants which returns 0 as a remainder after dividing the score by 7.

QUERY:

db.restaurants.find({ "grades.score": { $mod: [7, 0] } }, { restaurant_id: 1, name: 1, grades: 1 });

OUTPUT:

11. Write a MongoDB query to find the restaurant name, borough, longitude and attitude and cuisine for those restaurants which contains 'mon' as three letters somewhere in its name.

QUERY:

db.restaurants.find({ name: /mon/i }, { name: 1, borough: 1, "address.coord": 1, cuisine: 1 })

OUTPUT:

12. Write a MongoDB query to find the restaurant name, borough, longitude and latitude and cuisine for those restaurants which contain 'Mad' as first three letters of its name.

QUERY:

db.restaurants.find({ name: /^Mad/i }, { name: 1, borough: 1, "address.coord": 1, cuisine: 1 })

OUTPUT:

13. Write a MongoDB query to find the restaurants that have at least one grade with a score of less than 5.

QUERY:

db.restaurants.find({ "grades": { $elemMatch: { "score": { $lt: 5 } } } })

OUTPUT:

14. Write a MongoDB query to find the restaurants that have at least one grade with a score of less than 5 and that are located in the borough of Manhattan.

QUERY:

db.restaurants.find({ "grades": { $elemMatch: { "score": { $lt: 5 } } }, "borough": "Manhattan" })

OUTPUT:

15.Write a MongoDB query to find the restaurants that have at least one grade with a score of less than 5 and that are located in the borough of Manhattan or Brooklyn.

QUERY:

db.restaurants.find({ "grades": { $elemMatch: { "score": { $lt: 5 } } }, $or: [{ "borough": "Manhattan" }, { "borough": "Brooklyn" }] })

OUTPUT:

16. Write a MongoDB query to find the restaurants that have at least one grade with a score of less than 5 and that are located in the borough of Manhattan or Brooklyn, and their cuisine is not American.

QUERY:

db.restaurants.find({ "grades": { $elemMatch: { "score": { $lt: 5 } } }, $or: [{ "borough": "Manhattan" }, { "borough": "Brooklyn" }], "cuisine": { $ne: "American" } })

OUTPUT:

17. Write a MongoDB query to find the restaurants that have at least one grade with a score of less than 5 and that are located in the borough of Manhattan or Brooklyn, and their cuisine is not American or Chinese.

QUERY:

db.restaurants.find({ "grades": { $elemMatch: { "score": { $lt: 5 } } }, $or: [{ "borough": "Manhattan" }, { "borough": "Brooklyn" }], "cuisine": { $nin: ["American", "Chinese"] } })

OUTPUT:

18. Write a MongoDB query to find the restaurants that have a grade with a score of 2 and a grade with a score of 6.

QUERY:

db.restaurants.find({ $and: [{ "grades.grade": "A", "grades.score": 2 }, { "grades.grade": "A", "grades.score": 6 }] })

OUTPUT:

19. Write a MongoDB query to find the restaurants that have a grade with a score of 2 and a grade with a score of 6 and are located in the borough of Manhattan.

QUERY:

db.restaurants.find({ $and: [{ "grades.grade": "A", "grades.score": 2 }, { "grades.grade": "A", "grades.score": 6 }], "borough": "Manhattan" })

OUTPUT:

20. Write a MongoDB query to find the restaurants that have a grade with a score of 2 and a grade with a score of 6 and are located in the borough of Manhattan or Brooklyn.

QUERY:

db.restaurants.find({ $and: [{ "grades.grade": "A", "grades.score": 2 }, { "grades.grade": "A", "grades.score": 6 }], $or: [{ "borough": "Manhattan" }, { "borough": "Brooklyn" }] })

OUTPUT:

21. Write a MongoDB query to find the restaurants that have a grade with a score of 2 and a grade with a score of 6 and are located in the borough of Manhattan or Brooklyn, and their cuisine is not American.

QUERY:

db.restaurants.find({ $and: [{ "grades.grade": "A", "grades.score": 2 }, { "grades.grade": "A", "grades.score": 6 }], $or: [{ "borough": "Manhattan" }, { "borough": "Brooklyn" }], "cuisine": { $ne: "American" } })

OUTPUT:

22. Write a MongoDB query to find the restaurants that have a grade with a score of 2 and a grade with a score of 6 and are located in the borough of Manhattan or Brooklyn, and their cuisine is not American or Chinese.

QUERY:

db.restaurants.find({ $and: [{ "grades.grade": "A", "grades.score": 2 }, { "grades.grade": "A", "grades.score": 6 }], $or: [{ "borough": "Manhattan" }, { "borough": "Brooklyn" }], "cuisine": { $nin: ["American", "Chinese"] } })

OUTPUT:

23. Write a MongoDB query to find the restaurants that have a grade with a score of 2 or a grade with a score of 6.

QUERY:

db.restaurants.find({ $or: [{ "grades.score": 2 }, { "grades.score": 6 }] })

OUTPUT:

Evaluation Procedure	Marks awarded
Query(5)	
Execution (5)	
Viva(5)	
Total (15)	
Faculty Signature	

RESULT:

MONGO DB

EX_NO: 20 **DATE:**

1.)Find all movies with full information from the 'movies' collection that released in the year 1893.

QUERY:

db.movies.find({ year: 1893 })

OUTPUT:

2.)Find all movies with full information from the 'movies' collection that have a runtime greater than 120 minutes.

QUERY:

db.movies.find({ runtime: { $gt: 120 } })

OUTPUT:

3.)Find all movies with full information from the 'movies' collection that have "Short" genre.

QUERY:

db.movies.find({ genres: 'Short' })

OUTPUT:

4.)Retrieve all movies from the 'movies' collection that were directed by "William K.L. Dickson" and include complete information for each movie.

QUERY:

db.movies.find({ directors: 'William K.L. Dickson' })

OUTPUT:

5.)Retrieve all movies from the 'movies' collection that were released in the USA and include complete information for each movie.

QUERY:

db.movies.find({ countries: 'USA' })

OUTPUT:

6.)Retrieve all movies from the 'movies' collection that have complete information and are rated as "UNRATED".

QUERY:

db.movies.find({ rated: 'UNRATED' })

OUTPUT:

7.)Retrieve all movies from the 'movies' collection that have complete information and have received more than 1000 votes on IMDb.

QUERY:

db.movies.find({ 'imdb.votes': { $gt: 1000 } })

OUTPUT:

8.)Retrieve all movies from the 'movies' collection that have complete information and have an IMDb rating higher than 7.

QUERY:

db.movies.find({ 'imdb.rating': { $gt: 7 } })

OUTPUT:

9.)Retrieve all movies from the 'movies' collection that have complete information and have a viewer rating higher than 4 on Tomatoes.

QUERY:

db.movies.find({ 'tomatoes.viewer.rating': { $gt: 4 } })

OUTPUT:

10.)Retrieve all movies from the 'movies' collection that have received an award.

QUERY:

db.movies.find({ 'awards.wins': { $gt: 0 } })

OUTPUT:

11.)Find all movies with title, languages, released, directors, writers, awards, year, genres, runtime, cast, countries from the 'movies' collection in MongoDB that have at least one nomination.

QUERY:

db.movies.find({ 'awards.nominations': { $gt: 0 } }, { title: 1, languages: 1, released: 1, directors: 1, writers: 1, awards: 1, year: 1, genres: 1, runtime: 1, cast: 1, countries: 1 })

OUTPUT:

12.)Find all movies with title, languages, released, directors, writers, awards, year, genres, runtime, cast, countries from the 'movies' collection in MongoDB with cast including "Charles Kayser".

QUERY:

db.movies.find({ cast: 'Charles Kayser' }, { title: 1, languages: 1, released: 1, directors: 1, writers: 1, awards: 1, year: 1, genres: 1, runtime: 1, cast: 1, countries: 1 })

OUTPUT:

13.)Retrieve all movies with title, languages, released, directors, writers, countries from the 'movies' collection in MongoDB that released on May 9, 1893.

QUERY:

db.movies.find({ released: ISODate("1893-05-09T00:00:00.000Z") }, { title: 1, languages: 1, released: 1, directors: 1, writers: 1, countries: 1 })

OUTPUT:

14.)Retrieve all movies with title, languages, released, directors, writers, countries from the 'movies' collection in MongoDB that have a word "scene" in the title.

QUERY:

db.movies.find({ title: /scene/i }, { title: 1, languages: 1, released: 1, directors: 1, writers: 1, countries: 1 })

OUTPUT:

Evaluation Procedure	Marks awarded
Query(5)	
Execution (5)	
Viva(5)	
Total (15)	
Faculty Signature	

RESULT: