Measurement: Sensors 32 (2024) 101053

Contents lists available at ScienceDirect

Measurement: Sensors

journal homepage: www.sciencedirect.com/journal/measurement-sensors

Improved healthcare monitoring of coronary heart disease patients in time-series fashion using deep learning model

Shambhu Bhardwaj [a,*], Vipul Vekariya [b], Baldev Singh [c], Sri Vinay [d], Alli Arul [e], Maria Daya Roopa [f]

[a] Department of Computing Sciences& Information Technology, Teerthanker Mahaveer University, Moradabad, Uttar Pradesh, India
[b] Department of Computer Science and Engineering, Parul University, Vadodara, Gujarat, India
[c] Department of Computer Science & Engineering, Vivekananda Global University, Jaipur, India
[d] School of Computer Science Engineering and IS, Presidency University, Bengaluru, India
[e] Department of MCA, Presidency College, Bengaluru, India
[f] Department of Statistics, Christ University, Bangalore, India

ARTICLE INFO

Keywords:
Decision support
Coronary heart disease
Time series forecasting
Machine learning

ABSTRACT

In this paper, an Improved Healthcare monitoring of Coronary Heart Diseaseframework is developed for patients in time-series fashion using DL (deep learning) model. The model uses DL called Convolutional Neural Network (CNN)via radial basis function integrated with artificial neural network to classify the time-series data from the electrodes. When choosing the algorithm that will be used to determine the forecast, the level of accuracy that is provided by an algorithm is one of the factors that is taken into consideration. The classification is carried out in a time-series fashion and the results of which are monitored in timely fashion. A ML (machine learning) model is designed using Python simulation, and time series data is validated using the suggested model. Data of a reputed medical university was used for testing encompassing 335 records with 36 clinical features. The accuracies, precisions, recalls, and f-measures of the suggested model's performances were assessed. This approach is used to determine whether the strategy that has been presented is the one that will prove to be the successful in the long run.

1. Introduction

The information that is stored in electronic health records (EHRs), includes chronological details but also a plethora of clinical data. Every single encounter that takes place between a medical practitioner and a patient is recorded and given a time stamp. The structure, breadth, and quantity of information that is contained in EHRs, in addition to the nature of the samples, make it extremely difficult to work with the data presented here due to the nature of the aforementioned factors [1]. The EHR-based predictive modelling that has been carried out up until this point has relied on general characteristics. On the other hand, these methods do not take into consideration the temporal connections that may exist between the various features [2].

One way that can be utilised to evaluate whether an individual will develop a disease in the future is to look at the pathophysiologic changes that have already taken place in the body of the individual. These changes have already taken place. to improve the accuracy of predictive models, it may be beneficial to locate temporal event sequences that can be utilised to differentiate disease cases from controls. These patterns of occurrence can be implemented in several different ways, depending on the context [3].

The determination of a patient prognosis is likely to be one of the most challenging tasks that you, as a practitioner, are required to do. Medical professionals need to be able to recognise a rapid deterioration in a patient condition based on clinical and objective criteria to reduce the likelihood of unfavourable outcomes occurring [4]. They must then be able to adjust their treatment strategies in accordance with this recognition. This analysis could stand to profit from the application of an algorithm that is able to include enormous amounts of data in a manner that is not only more time- and labour-effective but also generates more precise forecasts [5].

Researchers are now able to gain access to EHRs for the purpose of

* Corresponding author.
E-mail addresses: shambhu.bharadwaj@gmail.com (S. Bhardwaj), vipul.vekariya18435@paruluniversity.ac.in (V. Vekariya), baldev_singh@vgu.ac.in (B. Singh), alli-college@presidency.edu.in (A. Arul), maria.roopa@res.christuniversity.in (M.D. Roopa).

https://doi.org/10.1016/j.measen.2024.101053
Received 14 March 2023; Received in revised form 9 October 2023; Accepted 14 February 2024
Available online 15 February 2024
2665-9174/© 2024 The Authors. Published by Elsevier Ltd. This is an open access article under the CC BY-NC-ND license (http://creativecommons.org/licenses/by-nc-nd/4.0/).

research using ML since there has been recent recognition of the potential that is inherent in vast amounts of raw data. Even though they have some flaws, electronic health records, often known as EHRs, are becoming an increasingly important source of information [6]. EHRs contain all the digital clinical data that is created at the level of a single patient in healthcare institutions, which is the reason why this is the case. It is feasible to get vast quantities of data; records can be ordered chronologically; and the data covers all aspects of the therapy that the hospital gives to its patients [7].

The development of research into the use of ML for forecasting likelihood of illnesses has been hampered by several challenges. Extremely large datasets, which are required is notoriously difficult to obtain, particularly in the field of medicine, where protecting the confidentiality of patients is of the utmost importance. This makes it particularly challenging to obtain the extremely large datasets for the algorithms. This meant that there were fewer shared standards by which competing models could be rated, and it also made it more difficult to track the success of the methodology as a whole [8].

Clinicians are required to make decisions on their own and to provide logical justifications for such decisions in accordance with the standards that have been established by their profession. On the other hand, they are not newcomers to the realm of black-box algorithms [9]. At this time, clinical decisions are made based on data, despite the fact that doctors have only a surface-level grasp of the origins of such data.

It is possible that the introduction of regulatory procedures that guarantee dependability is to fault for the broad acceptance of this technology. These procedures have contributed to an increase in the amount of trust that may be placed in such information. The same can be stated about how essential it is to carry out research on the interpretability of ML, which is a topic that is becoming increasingly important. Even if the level of precision of the model were increased, it is highly doubtful that the medical community would accept the inherent lack of openness and accountability in the model [10].

Despite the inherent limitation of the black-box problem, which is the inability to find explanations that are helpful insights into the behavior of the model and help in establishing trust, which is essential for the deployment of the model. This is because the black-box problem prevents one from finding to be highly complex. According to this concept, the objectives of interpretability approaches should be to uncover any bias in the training data, any unfairness in the algorithmsany failures in generalization, and any other information that can be exploited to fine-tune the model [11].

The deep neural network (DNN) model is composed of a huge number of computer blocks that are connected to one another and stacked in layers. Each computer block learns weights to generate a unique processing of the supplied data. Along with the research and development of designs that improve interpretability, use of recurrent neural networks (RNN) for predictions has increased substantially. These networks are popularity based on EHRs.

Attention models provide the impression that they are a successful strategy for handling the problem because of the way in which they concentrate the consideration of an algorithm on the most significant components of a data stream. In addition to enhancing performance, it has been discovered that attention processes can also provide factors that can be used for clinical interpretation [12–14].

In this work Coronary Heart Disease is predicated on DL with the intention of elevating the level of medical surveillance that is provided to patients who are afflicted with coronary heart disease. In this model, time series data obtained from electrodes are classified using DL techniques namely CNN. The degree of accuracy produced by the algorithm in question will be taken into consideration to choose which algorithm will be used to generate the forecast. A technique known as time series allows us to classify the data into categories and track how they change over time.

2. Related works

The widespread devastation that can be caused by an epidemic or pandemic [15], many disease prediction models are developed for diseases. These models can be found in the following sentences: Infectious diseases were taken into consideration when developing these models. One of the most important reasons why these dangers need to be predicted is because medical institutions sometimes react slowly when confronted with the possibility of infectious disease risks [16].

Using nonmedical datasets such as Google Trends [17] or Twitter [18], several authors have attempted to estimate the course of infectious illness trends in real time. The advancement of ML approaches over the course of the past decade has made it possible to create increasingly accurate forecast models [19].

In earlier forecasting evaluations, other types of regression analysis, such as Poisson distribution [20], were utilised. The generalized linear models served as the foundation for these forms. Bayesian networks and Generalized Linear Model (GLM) [21] are two alternatives that are employed substantially more frequently than SARIMA. This was done by comparing the linear models to DNN and LSTM models. This realization came about after only a little period of reflection and consideration.

When either the SARIMA or the NARNN were utilised independently, the performance of hybrid models ARIMA-NARNN did not outperform either of that model individual performance. Most of the research that was conducted and published on time-series forecasting featured at least one methodological flaw [22]. There is a possibility that one or more of the following factors contributed to the outcome: DL techniques were not utilised, the datasets that were used were insufficient, or the computational software that was used was incapable of simultaneously managing a greater number of models. There is a possibility that one or more of the following factors contributed to the outcome. In addition, it probable that medical professionals all over the world lack the knowledge and skills necessary to make the most use of ML solutions [23].

In time series forecasting, other sophisticated ML algorithms can also be employed successfully. to put these cutting-edge algorithms to action, you must first establish a realistic time window within which to perform candidate feature analysis. The next step is to create informative characteristics based on actual, up-to-date instances of both the target and the covariate [24].

To make a prediction model more accurate, it is often necessary to make changes to the target data itself, rather than simply adding additional features. These adjustments are essential regardless of whether the target is thought of as being stationary, periodic, or progressive in character (e.g., exponential). All three of these transformations are examples of types of differences. All these are illustrative instances of various categories of distinctions [25].

When such data preparation is carried out, it sets the way for the application of innovative ML methods such as XGBoost and LightGBM. These methods, on the other hand, offer researchers with an additional set of hurdles and layers of decisions, such as optimizing the model hyperparameters, implementing the model code, and effectively training and verifying the models using historical data. AutoTS, is a method that empirically tests and evaluates dozens or hundreds of permutations of data pre-processing and the model that has the lowest amount of model error when it is applied to out-of-sample data. The goal of this technique is to find the model that can best predict future outcomes based on data that was collected in the past [26].

Kim and Kang used a neural network [27] proposed a mechanism for diagnosing cardiac problems. Feature sensitivity analysis was utilised to find the key characteristics. High sensitivity traits are more significant than low sensitivity features. Correlated features are discovered by comparing the change in trait sensitivity with the change in trait value, which is done after choosing unrelated features. If a change in the value of one characteristic also causes a greater than average change in the sensitivity of the other trait, the two traits are linked.

In [28], a diagnostic CAD dataset taken from two general hospitals in

Kano State, Nigeria, was used to create an ML-based CAD prediction model. The data collection is used to develop prediction models, which are then assessed for accuracy using ML methods such as Support Vector Machine, K Nearest Neighbour, Random Tree, Naive Bayes, gradient Boosting, and Logistic Regression. Receiver operating curves, accuracy, specificity, and sensitivity are related to (ROC) performance assessments. The ML model based on Random Forest is discovered to be the best model in terms of accuracy (92.04%), the ML model based on Naive Bayes is discovered to be the best model in terms of specificity (92.40%), and the best model in terms of sensitivity was found to be the machine-based support vector model (ML model) (92.40%). The random forest-based ML model was discovered to be the best model for ROC with 92.20%, and it also had the best model with 87.34%. The decision tree is made using the random forest machine learning technique, which is thought to be the best model in terms of accuracy and ROC and may be utilised to design a diagnostic expert system for Nigerian patients with coronary artery disease.

The primary goal of this work is to offer a model for predicting the development of heart disease. This study also sought to identify the best classification method to assess patients' risk for heart disease. Three classification algorithms, Nave Bayes, Decision Trees, and Random Forests, are utilised at various levels of assessment in this work's comparative investigation and analysis. Even though these ML algorithms are often employed, accurately predicting cardiac disease is a crucial challenge. However, DL offers a number of benefits over conventional ML techniques, such as feature learning, handling large and complex data, improving performance, handling non-linear relationships, processing both structured and unstructured data, predictive modelling, missing data management, and sequential data management. Deep algorithms are therefore assessed using a variety of metrics and assessment techniques. Consequently, a better strategy may be developed by academics and medical professionals.

The data collection is used to develop prediction models, which are then assessed for accuracy using ML methods such as Support Vector Machine, K Nearest Neighbour, Random Tree, Naive Bayes, gradient Boosting, and Logistic Regression. Receiver operating curves, accuracy, specificity, and sensitivity are all related. (ROC) performance assessment method.

3. Proposed method

Only matrices that encode single-channel or multi-channel time series data can be accepted as input, which, is the same as the input data type that can be accepted by the Keras API. Each real-valued multi-channel time series sequence carries a label that is assigned to correspond to a certain category. It is essential to ensure that the length of each of the sequences included in the dataset is the same. The data to be input will be segmented into a training set, a test set, and a validation set.

The user is required to make use of a sliding window and assign a representative label to each time frame if the initial time series has many labels connected with each time window. This is the case when the initial time series has numerous labels associated with each time window. DNN does not contain any functions for this stage because the decisions that need to be taken for window size selection and other preprocessing methods are quite dependent on the application.

3.1. Feature extraction

When both sets of vectors are evaluated, the results obtained from using the medical thought vectors that we had built as input were noticeably superior to those obtained from testing the one-hot vectors. By utilising the Skip-gram natural language processing embedding technique, it would be able to generate vector representations of ICD-10, CPT, and procedure codes which allowed a thorough examination of data. Vector is being done with the intention of revealing the fundamental connections that exist between the various sets of codes. This development is being done with the intention of shedding light on the fundamental connections that exist between the various sets of codes.

To generate medical concept vectors, the log probability is maximized at each stage by iteratively sliding a window of a given size across a collection of codes. This allowed us to construct the concept vectors in the most efficient manner possible. The study generates the concept vectors in the time- and labor-effective way feasible. The study produces the concept vectors in the most efficient and effective manner possible, saving both time and effort.

$$max\frac{1}{T}\sum_{T-1}\sum -w \le j \le wj \ne 0\log_p\left(c_{t+j}\middle|c_t\right) \tag{1}$$

where

$$p\left(c_{t+j}\middle|c_t\right) = exp\left(v\left(c_{t+j}\right)T_v(c_t)\right)\sum_{N_e-1}exp(v(c)T_v(c_t)) \tag{2}$$

where.

T - patient visits,
w-window size,
c_t-position code, and
v (c_t) - vector representation.

The skip-gram technique, when applied to concepts that are sufficiently near in time, tries to maximise the inner product of the distinctive vector representation of each concept. This is done to find the optimal solution. When the method is applied to different concepts, this is the result. The default values of window sizes (in bytes) and vector representations of hyperparameters were values between 50 and 1000. These values can be changed at any time.

The usage of a window with a size of five made it possible to expand the dimensionality of the medical idea vectors. The encounter, the drug order, the treatment order, and the problem list were the key sources of data that we drew upon during our investigation and analysis. This was done to better understand the uses of Skip-gram in the medical field.

We provide RNN as a progressive time-series model to considerably enhance the accuracy of forecasting the degree to which the patient eight coronary arteries will be blocked. This was done to improve the patient overall prognosis (Fig. 1).

The very last part of the model is altered in such a manner that it makes use of a combined progressive time-series network framework. A technique known as incremental learning will be employed to cause the network to automatically update itself; in the process of doing so, a forgetting factor will be applied to adapt the proportion of new observations to older observations.

During the process of gradually improving the feature set, this will be carried out. In contrast to progressive neural networks, which are just one form of network, incrementally linked progressive time-series networks are a completely different kind of network. The most common variety of network is referred to as a progressive neural network. The operation of the complete model is depicted for us in Fig. 1, which offers a graphical representation of the idea.

Each of these layers oversees a particular facet of the model that it includes and is accountable for that aspect. Processing of the real-valued vector that was produced from the text is the responsibility of the feature processing layer, which is the layer below it in the hierarchy.

When all the processing is done, a vector will have been produced; this vector will then be appended to the vector that was used as an input by the layer below it. This will happen when all the processing is complete. Following the completion of all the processing, this step will be carried out. It is vital to minimise the importance of preliminary data as much as is humanly possible while creating progressive time-series networks that are integrated in phases.



Fig. 1. Architecture of the proposed model.

If you are attempting to maintain track of a moving target, the most recent set of statistics that it has provided will give you with more information than the averages that it has produced in the past will. This is because the most recent set of figures represents the most current state of the target. This is since the most recent set of numbers represents the goal in its most current state. This is because the most current set of statistics represents the most recent incidence of the target, which is why this is the case.

The network will place a greater emphasis on the results of the patient most recent blood test than it will on the results of the patient previous blood tests when it comes to making predictions regarding the degree to which coronary artery blockage exists within the body of the patient. This is because the most recent results from a blood test provide the most up-to-date information.

To facilitate the network capacity for incremental learning and subsequent self-updating, an element of forgetting will be incorporated into the incremental feature base update. The network will be able to change the proportion of fresh data to old observations because of this. This is done to ensure that the most recent data is reflected in future predictions and that the weight of historical data is kept to a minimum.

The findings of a patient various blood biochemical tests are entered into a neural network in the form of data vector values. This helps the network comprehend patient's condition better. The most recent conclusion is given the most weight, and the weights for successive discoveries drop in a linear fashion as the examination interval grows.

The most recent assumption is given the most weight because it was the most recent one. The most consideration is paid to the most recent decision reached. The objective function of the model is going to be a binary cross-entropy function, and when the model is being trained, the value of this function is going to be minimized to achieve the best possible results. Adjustments that need to be made to the weight of the model hidden layer can be made by applying the following equation:

The study is interested in determining how successfully the proposed system can make recommendations, a great place to start is by comparing a variety of different approaches to the measurement of similarity. This is an excellent in determining how successful the proposed system can make recommendations.

$$\delta_i = \begin{cases} \left(y_i^{(n)} - \widehat{Y}_i^{(n)}\right)\left(1 - tanh^2(net_i)\right) & i \in 0 \\ \left(\sum_{je^l} \delta_j w_{ij}\right)\left(1 - tanh^2(net_i)\right) & i \in h \end{cases} \tag{3}$$

$$w_i = w_i - \eta \frac{\partial E}{\partial w_i} \tag{4}$$

If we assume that A and B are two sets (or vectors) of keywords that need to be compared (respectively for previous and upcoming events attended), then it provides the specifics of similarity measures for the planned work for a certain number (n) of datapoints contained within the sets. This is because assumes that A and B are two sets (or vectors) of keywords that need to be compared. This is reached as a direct consequence of the assumption, which states that A and B are two distinct sets (or vectors) of keywords that need to be compared.

3.2. Jaccard distance

This distance is referred to as the Jaccard distance, and its calculation involves dividing components that are unique into groups by the total counts of components that are shared by both sets of samples. To determine the Jaccard distance (J), please make use of the equation that has been supplied for your convenience below.

$$J(A, B) = \frac{|A \cap B|}{|A \cup B|} \tag{5}$$

3.3. Euclidean distance

Calculate sums of squared differences between the elements of the two arrays or vectors that you are comparing, and then take the square root of that number. First, you should calculate the sum of the squared differences that exist between the members of the arrays or vectors that you are comparing. The result gives the Euclidean distance between the two pieces of data that you supplied before. The following equation can be used to determine the Euclidean distance (E) between two points in space:

$$\mathrm{E} = |\mathrm{A} - \mathrm{B}| = \sqrt{\sum_{\mathrm{i}-1}^{\mathrm{n}} (\mathrm{a_i} - \mathrm{b_i})^2} \tag{6}$$

3.4. Cosine similarity

Cosine similarity is a useful technique for assessing degrees of similarity between two vectors or arrays as it concentrates on directions of

vectors in place of their magnitudes. This enables calculating the cosine similarity between two vectors or arrays a practical procedure. The level of resemblance between two vectors or arrays may be assessed using cosine similarity. Because this utility is compatible with the TF-IDF format, it can be utilised with it. Use the following equation to determine the cosine distance (cos(θ)) between two points:

$$cos(\theta) = J(A,B) = \frac{A.B}{\|A\| \times \|B\|} = \frac{\sum_{i-1}^{n} A_i B_i}{\sqrt{\sum_{i-1}^{n} A_i^2} \sqrt{\sum_{i-1}^{n} B_i^2}} \tag{7}$$

Even though there are other systems that use a methodology that is analogous to the one that was described, none of them digitally automate the process by making use of artificial intelligence (AI). Even though the suggested way achieves the same results as the other systems, this is the situation that has arisen. The fact that a student participates in co-curricular or extra-curricular activities, which make a significant contribution to the abilities indicated by graduate qualities, is also not taken into consideration by the methodologies that are currently in use. There is an urgent need for a more accurate measurement of competency, which may be attained through the strategic implementation of a system that offers projections and suggestions. This can be done.

3.5. Time series forecasting (TSF)

A method must be sensitive enough to pick up on any temporal dependencies that may be present in the signals for it to be capable of accurately determining the current level of wear that a tool has. Using data from sensors is required to accurately determine the current level. Alterations in the temporal structures of the sensor signals are something that may be expected as the instrument continues to degrade. It is vitally necessary for a tool that is used for categorization to be able to recognise these alterations and put them in the correct group for regular wear.

Sequence-based methods and feature-based methods are the two basic types of processes that are commonly utilised when it comes to the classification of time series. Both methods can be broken down into subtypes. It has been demonstrated on numerous occasions that the sequence-based strategy referred to as TSF, performs significantly better than its nearest neighbours in either category of problem.

When paired with the capacity to travel through time without being affected by it, this becomes a particularly true statement. One of the drawbacks of utilising this strategy is the length of time that is required to carry out the necessary computations, which can be rather time-consuming. As the size of the training set grows, there is a linear increase in the total amount of time necessary for calculation, and there is also an increase in the total amount of time required for prediction.

DL is a technology that can automatically extract crucial information while maintaining a consistent forecast time. This is achieved using neural networks and it is responsible for making this accomplishment conceivable. CNNs have demonstrated that they are able to navigate through enormous data sets. Although these are normally utilised for visual activities, speech recognition, and the processing of language, there has been a recent emphasis placed on employing them for the purpose of categorising time series.

The visual cortex of the human brain served as the conceptual framework for the development of DLs, which was the primary drive behind the invention of DLs. This was the fundamental impetus behind the invention of DLs. Because of the limited size of their local receptive fields, neurons in the visual cortex are only able to respond to stimuli that occur in a certain portion of the complete field of view.

When these receptive fields combine, they could produce an image that is continuous across the entirety of the visual field. This is because the image is generated by receptive fields. This takes place whenever the two meet. Certain neurons can respond to more complex patterns, which are further combinations of simpler patterns, since their receptive fields are greater than those of other neurons, giving them an advantage over other neurons in this regard.

Research has shown that neurons in the visual cortex of the brain only respond to stimuli that are brought into focus in a very specific region of the complete field of view. When all these distinct receptive fields work together, they have the potential to generate an image that is continuous over the entirety of the observer field of vision. It is feasible for certain neurons to respond to more complex patterns that are further combinations of patterns that are simpler because the receptive fields of these neurons are greater than those of other neurons.

Topologies for artificial neural networks have been established as a direct consequence of the processes that are basic to the brain. These architectures can recognise complicated patterns as a result of the fact that the decisions that they make are reliant on the outputs of neurons that are located at lower levels within the network. This is why the ML field has developed over time. Both the convolution layer and the pooling layer are regarded as the most crucial elements of CNN.

Each neuron that makes up a convolution layer is coupled to at least one additional neuron that resides in the layer underneath it. to create these connections between the neurons in the two levels, the receptive fields of the neurons in both layers are utilised. In the first layer of convolution, for example, each neuron is only connected to the pixels that lie inside its receptive field rather than to all the pixels in the input image. This contrasts with the second layer of convolution, which connects each neuron to all the pixels in the input image. This is because every neuron possesses its own one-of-a-kind receptive field.

In the second convolution layer, each neuron is connected to all the pixels in the input image. This is the case because in this layer the neurons are convolutional. In contrast to the first convolution layer, in which only a subset of the pixels is connected, this layer has all its pixels connected. Following this step, neurons of first layers contained inside narrow rectangles are connected to neurons of convolution layers in all possible ways.

The process of convolution is carried out in layers, with the first layer overseeing locating lower-level qualities and successive layers overseeing integrating higher-level characteristics. to perform an adequate job of processing the many kinds of features, it is necessary for each neuron in each convolution layer to employ a unique set of weights, which are also referred to as filters. It is feasible that one filter may be able to recognise vertical lines while another filter will be able to recognise horizontal lines. Likewise, it is also possible that both filters will recognise diagonal lines. There is the possibility of either of these two outcomes.

During the process of convolution, a feature map is built by constructing comparisons between different elements of the filter and different sections of the picture. These comparisons make up the building blocks of the feature map. On this map, the areas of the picture that are most like the filter characteristics are highlighted. To take into consideration the vast number of different observable properties of the visual system, each convolutional neuron would need to incorporate several weights or filters into its design. If a CNN is provided with a training set, it can find out which filters are the most useful in resolving a particular classification difficulty and learn how to employ those filters. This allows the CNN to improve its classification accuracy.

The training method for the current force classification will determine the filters that make it possible to differentiate features at the flute level in the very first instance, regardless of the position of those features within the image. These filters will be determined by the current force classification. While determining which filters will be utilised throughout the process, this step will be carried out as part of that process. We will have to employ ever-more-complicated convolutions to determine the state of the instrument while also considering all its flutes.

The pooling layer is just another necessary part of the CNN that is accountable for a vital function. The output of the preceding layer convolution is brought into this layer, where it is then scaled down. As a direct consequence of this, the model dimensionality, as well as its

processing complexity and sensitivity at the local level, are all reduced. Convolutions, which can include a rectified linear unit (ReLU) step to expedite training, and pooling layers, which reduce picture size at deeper layers, are often stacked in the design of a convolutional neural network. This process of CNN architecture is shown in (Fig. 2).

Pooling layers also reduce the amount of information in an image. These two layers are responsible for lowering the size of photos when they are stacked deeper. Both layers have been designed with the goal of reducing the quantity of data that is necessary to portray an image. After this stage, a multilayer neural network will be coupled to the output of the very last stage of convolution and pooling to finish the classification.

4. Results and discussions

Data from Shimla Medical College was gathered for testing purposes. Age, gender, smoking, hypertension, diabetes mellitus, dyslipidemia, symptoms, random blood sugar, total cholesterol, low density lipoprotein, high density lipoprotein, triglycerides, systolic blood pressure, and diastolic blood pressure are among the 36 clinical patient attributes represented in the data, which contains 335 records of patients. Height, weight, BMI, BMI type, waist circumference, visceral obesity, ankle-brachial index, exercise duration, metabolic level equivalent, pressure product, recovery period, tube, ischemia score, CAD, extent, CAD score, and CAD score quartile are all factors that need to be considered.

Tensorflow CIFAR-10 framework, which was designed specifically for DL, has been utilised. When it comes to the classification of three-channel images, this CNN architecture, which is already available for usage in commercial applications, has been shown to have a high level of accuracy. In this architectural design, the two convolution layers, the ReLU layer, and the pooling layer are all piled one on top of the other and the pooling is the final layer. 64 filters are utilised in each iteration of the convolution process.

The proposed model for score prediction is put through its paces using the present dataset, which includes several DL training, testing, and validation procedures. These algorithms are graded in order from best to worst based on their performance when measured against a range of metrics. When taking into consideration the following parameters:

N represents the number of data points, Y represents the score value, $\bar{y}$ average represents the score value, and $\hat{y}$ projected value represents the score The following is a short list of some examples of performance indicators:

4.1. R^2

R squared, also known as R2, is a metric that statisticians use to quantify how much of the volatility of a dependent variable can be accounted for by an independent variable or variables in a regression model. This is done by comparing the amount of variance in the dependent variable to the variance in the independent variable or variables. Regression models typically include this metric in their analysis. The value of R^2 can be calculated by using the formula presented as below.

$$R^2 = 1 - \frac{\sum (y_i - \hat{y})^2}{\sum (y_i - \hat{y})^2} \tag{8}$$

4.2. MAE

The mean absolute error is a measurement that can be used to determine the error gap that exists between two observations that both represent the same criterion. The mean absolute error is a measurement that can be used to determine the error gap that exists between two observations that both represent the same criterion.

$$MAE = \frac{1}{N} \sum_{i-1}^{N} |y_i - \hat{y}| \tag{9}$$

4.3. MSE

MSE is a measurement that considers the average squared deviation and compares the actual value to the expected value.

$$MSE = \frac{1}{N} \sum_{i-1}^{N} (y_i - \hat{y})^2 \tag{10}$$

4.4. MAPE

The mean absolute percentage error, also known as MAPE for short, is a statistical measure of the prediction made by a forecasting technique that functions in a manner that is comparable to that of a model accuracy. The MAPE and accuracy can both be calculated:

$$MAPE = \frac{100}{N} \sum_{i=1}^{N} \frac{|\hat{y}_i - y_i|}{y_i} \tag{11}$$

$$Accuracy = 100 - MAPE \tag{12}$$

By using above equations and calculated Accuracy which is shown in (Fig. 3), Precision in (Fig. 4), Recall in (Fig. 5), and F-Measure in (Fig. 6).

Table 1 provides a comparative analysis of the proposed TS-CNN and the various existing approaches using several parameters like accuracy, precision, recall and F-measure.

Since, models of DL can be interpreted at any point, we constructed a multivariate time series-based DL architecture for the prediction of adverse events by making use of data from EHR systems for the purpose of this research.

We were able to use the same method for EHRs using the same proposed model and acquire activation maps at predictor levels. Their cohort was nearly twice as large as the one we are analyzing here, and they included 17 variables for a period of 48 h rather than only 10. It is plausible that factors such as these are to blame for the observable



Fig. 2. CNN architecture.



Fig. 3. Accuracy.



Fig. 4. Precision.



Fig. 5. Recall.

variation in performance.

Even though this was not the primary goal of the study, it is interesting to note that by utilising a penalized regression model, we were able to achieve results that were very close to those obtained by utilising



Fig. 6. F-measure.

the proposed model, thereby confirming earlier results in analogous contexts. Although this was not the primary objective of the study, it is interesting to note that by doing so, we were able to achieve results that were very close to those obtained.

While this was not the primary objective of the study, it is interesting to note that by doing so, we were able to achieve these results. However, it is essential to highlight that while we do incorporate many predictors in our analysis, only a subset of them is time-varying, which may reduce proposed model ability to identify distant relationships. It is important to note that while we do incorporate many predictors in our analysis, it is important to highlight that while this is the case.

The constraints imposed by our working environment; it is not possible to make a comparison that is conclusive between the models' levels of performance. These constraints include limited counts of observations, a limited number of time-varying covariates, and an absence of out-of-sample data for the purpose of external validation. Because of these considerations, it is impossible for us to make a fair evaluation of how well the different models work. Unfortunately, the aims of model interpretability are outside the scope of our research on activations retrieved from the attention mechanism.

To be more specific, the model is unable to discern between positive and negative correlations that occur between predictors and results. On the other hand, there is a lot of work put into the field of research on interpretability, and new methods and tools are continually being generated in this sector of the industry.

5. Conclusions

In this paper, an improved health care monitoring system based on DL with the intention of improving the medical surveillance of patients is proposed. The model includes a time series modelling, where the that is generated by the electrodes can be categorised properly. The time series data are validated by utilising the model that was proposed, the creation of which was carried out with the assistance of a Python simulation. The classification is accomplished using a time-series approach, and the outcomes are observed in real time as they take place. Accuracy is one of the factors that are used in the process of selecting a particular algorithm as the method that will be utilised in the process of making the prediction. This method is utilised to ascertain whether the strategy that has been presented is the one that will prove to be the most fruitful over the course of time. For the Future Scope more DL approach will be used for best analysis of the heart diseases and for earlier prediction of diseases so that the rate of the death cases can be minimized by the awareness about the diseases.

Table 1
Comparison of various parameter analyses.

Metrics	GLM	ARIMA	SARIMA	DNN-LSTM	NARNN	RNN	Auto TS	Proposed TS-CNN
Accuracy	82	84	82	86	92	96	94	97
Precision	87	88	84	88	96	97	96	98
Recall	85	92	88	90	87	98	97	99
F-measure	85	90	84	86	88	98	96	99

Funding statement

For such a research, the author(s) did not receive any specific funding.

Declaration of competing interest

The authors declare that they have no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.

Data availability

No data was used for the research described in the article.

References

[1] N. Gautam, S.N. Ghanta, J. Mueller, M. Mansour, Z. Chen, C. Puente, S.J. Al Aref, Artificial intelligence, wearables and remote monitoring for heart failure: current and future applications, Diagnostics 12 (12) (2022) 2964.
[2] V. Sapra, L. Sapra, A. Bhardwaj, S. Bharany, A. Saxena, F.K. Karim, S. Ghorashi, A. W. Mohamed, Integrated approach using deep neural network and CBR for detecting severity of coronary artery disease, Alexandria Eng. J. 68 (2023) 709–720.
[3] M. Alsharqi, W.J. Woodward, J.A. Mumith, D.C. Markham, R. Upton, P. Leeson, Artificial intelligence and echocardiography, Echo Res. Pract. 5 (2018) R115–R125.
[4] H.R. Chua, K. Zheng, A. Vathsala, K.Y. Ngiam, H.K. Yap, L. Lu, B.C. Ooi, Health care analytics with time-invariant and time-variant feature importance to predict hospital-acquired acute kidney injury: observational longitudinal study, J. Med. Internet Res. 23 (12) (2021) e30805.
[5] H. Su, L. Yao, D. Hou, M. Sun, J. Hou, J. Ying, R. Hou, Cloud computing management architecture for digital health remote patient monitoring, in: 2021 IEEE International Conference on Smart Computing (SMARTCOMP), IEEE, 2021, August, pp. 209–214.
[6] S.J. Khiabani, A. Batani, E. Khanmohammadi, A hybrid decision support system for heart failure diagnosis using neural networks and statistical process control, Healthcare Analytics 2 (2022) 100110.
[7] A.T. Garmendia, I. Gkouzionis, C. Triantafyllidis, V. Dimakopoulos, S. Liliopoulos, M. Chadeau-Hyam, Towards Personalised Early Prediction of Intra-operative Hypotension Following Anesthesia Using Deep Learning and Phenotypic Heterogeneity, medRxiv, 2023, p. 2023, 01.
[8] F. Di Martino, F. Delmastro, Explainable AI for clinical and remote health applications: a survey on tabular and time series data, Artif. Intell. Rev. (2022) 1–55.
[9] D. Castiñeira, K.R. Schlosser, A. Geva, A.R. Rahmani, G. Fiore, B.K. Walsh, M. Santillana, Adding continuous vital sign information to static clinical data improves the prediction of length of stay after intubation: a data-driven machine learning approach, Respir. Care 65 (9) (2020) 1367–1377.
[10] W. Hsu, J. Warren, P. Riddle, Multivariate sequential analytics for cardiovascular disease event prediction, Methods Inf. Med. 61 (S 02) (2022) e149–e171.
[11] D. Zhang, Y. Li, C.A. Kalbaugh, L. Shi, J. Divers, S. Islam, B.H. Annex, Machine learning approach to predict in-hospital mortality in patients admitted for peripheral artery disease in the United States, J. Am. Heart Assoc. 11 (20) (2022) e026987.
[12] D. Romero, R. Jané, Detecting obstructive apnea episodes using dynamic bayesian networks and ECG-based time-series, in: 2022 44th Annual International Conference of the IEEE Engineering in Medicine & Biology Society (EMBC), IEEE, 2022, July, pp. 3273–3276.
[13] H.C. Thorsen-Meyer, A.B. Nielsen, A.P. Nielsen, B.S. Kaas-Hansen, P. Toft, J. Schierbeck, A. Perner, Dynamic and explainable machine learning prediction of mortality in patients in the intensive care unit: a retrospective study of high-frequency data in electronic patient records, The Lancet Digital Health 2 (4) (2020) e179–e191.
[14] S. Tipirneni, C.K. Reddy, Self-supervised transformer for sparse and irregularly sampled multivariate clinical time-series, ACM Trans. Knowl. Discov. Data 16 (6) (2022) 1–17.
[15] A. Kline, H. Wang, Y. Li, S. Dennis, M. Hutch, Z. Xu, Y. Luo, Multimodal machine learning in precision health: a scoping review, npj Digital Medicine 5 (1) (2022) 171.
[16] D. Ben-Israel, W.B. Jacobs, S. Casha, S. Lang, W.H.A. Ryu, M. de Lotbiniere-Bassett, D.W. Cadotte, The impact of machine learning on patient care: a systematic review, Artif. Intell. Med. 103 (2020) 101785.
[17] C. Cong, Y. Kato, H.D. Vasconcellos, M.R. Ostovaneh, J.A. Lima, B. Ambale-Venkatesh, Deep learning-based end-to-end automated stenosis classification and localization on catheter coronary angiography, medRxiv (2021) 2021, 03.
[18] S. Shekhar, D. Eswaran, B. Hooi, J. Elmer, C. Faloutsos, L. Akoglu, Benefit-aware early prediction of health outcomes on multivariate eeg time series, J. Biomed. Inf. (2023) 104296.
[19] I. Vagliano, N.C. Chesnaye, J.H. Leopold, K.J. Jager, A. Abu-Hanna, M.C. Schut, Machine learning models for predicting acute kidney injury: a systematic review and critical appraisal, Clinical Kidney Journal 15 (12) (2022) 2266–2280.
[20] B. Lim, S. Zohren, Time-series forecasting with deep learning: a survey, Philosophical Transactions of the Royal Society A 379 (2194) (2021) 20200209.
[21] R.P. Masini, M.C. Medeiros, E.F. Mendes, Machine learning advances for time series forecasting, J. Econ. Surv. 37 (1) (2023) 76–111.
[22] N. Feroze, Forecasting the patterns of COVID-19 and causal impacts of lockdown in top five affected countries using Bayesian Structural Time Series Models, Chaos, Solit. Fractals 140 (2020) 110196.
[23] N. Wu, B. Green, X. Ben, S. O'Banion, Deep Transformer Models for Time Series Forecasting: the Influenza Prevalence Case, 2020 *arXiv preprint arXiv:2001.08317*.
[24] H. Hewamalage, C. Bergmeir, K. Bandara, Recurrent neural networks for time series forecasting: current status and future directions, Int. J. Forecast. 37 (1) (2021) 388–427.
[25] I.E. Livieris, E. Pintelas, P. Pintelas, A CNN–LSTM model for gold price time-series forecasting, Neural Comput. Appl. 32 (2020) 17351–17360.
[26] Y. Xing, C. Lv, D. Cao, Personalized vehicle trajectory prediction based on joint time-series modeling for connected vehicles, IEEE Trans. Veh. Technol. 69 (2) (2019) 1341–1352.
[27] J.K. Kim, S. Kang, Neural network-based coronary heart disease risk prediction using feature correlation analysis, Journal of Healthcare Engineering 2017 (2017) 13, https://doi.org/10.1155/2017/2780501.2780501.
[28] L.J. Muhammad, I. Al-Shourbaji, A.A. Haruna, I.A. Mohammed, A. Ahmad, M. B. Jibrin, Machine learning predictive models for coronary artery disease, SN Computer Science 2 (5) (2021) 350.