```
import pandas as pd
data = pd.read_csv("/Users/Downloads/claimants (1).csv")
```

```
data.head()
```

	CASENUM	ATTORNEY	CLMSEX	CLMINSUR	SEATBELT	CLMAGE	LOSS
0	5	0	0.0	1.0	0.0	50.0	34.940
1	3	1	1.0	0.0	0.0	18.0	0.891
2	66	1	0.0	1.0	0.0	5.0	0.330
3	70	0	0.0	1.0	1.0	31.0	0.037
4	96	1	0.0	1.0	0.0	30.0	0.038

```
data.tail()
```

	CASENUM	ATTORNEY	CLMSEX	CLMINSUR	SEATBELT	CLMAGE	LOSS
1335	34100	1	0.0	1.0	0.0	NaN	0.576
1336	34110	0	1.0	1.0	0.0	46.0	3.705
1337	34113	1	1.0	1.0	0.0	39.0	0.099
1338	34145	0	1.0	0.0	0.0	8.0	3.177
1339	34153	1	1.0	1.0	0.0	30.0	0.688

```
data.describe()
```

	CASENUM	ATTORNEY	CLMSEX	CLMINSUR	SEATBELT	CLMAGE	LOSS
count	1340.000000	1340.000000	1328.000000	1299.000000	1292.000000	1151.000000	1340.000000
mean	11202.001493	0.488806	0.558735	0.907621	0.017028	28.414422	3.806307
std	9512.750796	0.500061	0.496725	0.289671	0.129425	20.304451	10.636903
min	0.000000	0.000000	0.000000	0.000000	0.000000	0.000000	0.000000
25%	4177.000000	0.000000	0.000000	1.000000	0.000000	9.000000	0.400000
50%	8756.500000	0.000000	1.000000	1.000000	0.000000	30.000000	1.069500
75%	15702.500000	1.000000	1.000000	1.000000	0.000000	43.000000	3.781500
max	34153.000000	1.000000	1.000000	1.000000	1.000000	95.000000	173.604000

```
data.info()
```

Explore our developer-friendly HTML to PDF API Printed using PDFCrowd HTML to PDF

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 1340 entries, 0 to 1339
Data columns (total 7 columns):
 #   Column    Non-Null Count  Dtype
---  ------    --------------  -----
 0   CASENUM   1340 non-null   int64
 1   ATTORNEY  1340 non-null   int64
 2   CLMSEX    1328 non-null   float64
 3   CLMINSUR  1299 non-null   float64
 4   SEATBELT  1292 non-null   float64
 5   CLMAGE    1151 non-null   float64
 6   LOSS      1340 non-null   float64
dtypes: float64(5), int64(2)
memory usage: 73.4 KB
```

In [19]:

```
data.shape
```

Out[19]:

```
(1340, 7)
```

In [20]:

```
data.nunique()
```

Out[20]:

```
CASENUM     1283
ATTORNEY       2
CLMSEX         2
CLMINSUR       2
SEATBELT       2
CLMAGE        68
LOSS         916
dtype: int64
```

In [21]:

```
data = data.dropna()
```

In [22]:

```
x = data[['CASENUM','LOSS','CLMSEX','CLMINSUR','SEATBELT','CLMAGE']]
y = data['ATTORNEY']
print(x.head())
print(y.head())
```

```
   CASENUM    LOSS  CLMSEX  CLMINSUR  SEATBELT  CLMAGE
0        5  34.940     0.0       1.0       0.0    50.0
1        3   0.891     1.0       0.0       0.0    18.0
2       66   0.330     0.0       1.0       0.0     5.0
3       70   0.037     0.0       1.0       1.0    31.0
4       96   0.038     0.0       1.0       0.0    30.0
0    0
1    1
2    1
3    0
4    1
Name: ATTORNEY, dtype: int64
```

In [23]:

```
from sklearn.model_selection import train_test_split
x_train, x_test, y_train, y_test = train_test_split(x,y,test_size = 0.2, random_state =
```

In [24]:

Explore our developer-friendly HTML to PDF API Printed using PDFCrowd HTML to PDF

```
from sklearn.linear_model import LogisticRegression
from sklearn.metrics import accuracy_score
from sklearn.preprocessing import StandardScaler


scaler = StandardScaler()
x_train = scaler.fit_transform(x_train)
x_test = scaler.transform(x_test)

model = LogisticRegression(max_iter=1000)
model.fit(x_train, y_train)

y_pred = model.predict(x_test)
```

In [25]:

```
print("Accuracy:", accuracy_score(y_test, y_pred))
```

```
Accuracy: 0.6727272727272727
```

In [ ]:

Explore our developer-friendly HTML to PDF API Printed using PDFCrowd HTML to PDF