## Chapter 7

# System of Particles and Rotational Motion

### **Solutions**

#### **SECTION - A**

#### **Objective Type Questions**

#### (Centre of Mass)

1. Three point masses  $m_1$ ,  $m_2$  and  $m_3$  are placed at the corners of a thin massless rectangular sheet (1.2 m × 1.0 m) as shown. Centre of mass will be located at the point



$$x_{\rm cm} = \frac{m_1 x_1 + m_2 x_2 + m_3 x_3}{m_1 + m_2 + m_3}$$


$$y_{\rm cm} = \frac{m_1 y_1 + m_2 y_2 + m_3 y_3}{m_1 + m_2 + m_3}$$

$$x_{cm} = \frac{(1.6)(0) + (2.4)(0) + 2(1.2)}{1.6 + 2.4 + 2} = 0.4 \text{ m}$$

$$y_{cm} = \frac{(1.6)(0) + (2.4)1 + 2(0)}{1.6 + 2.4 + 2} = 0.4 \text{ m}$$

So, 
$$(x_{cm}, y_{cm}) = (0.4, 0.4) \text{ m}$$

Figure shows a composite system of two uniform rods of lengths as indicated. Then the coordinates of the 2. centre of mass of the system of rods are



- (1)  $\left(\frac{L}{2}, \frac{2L}{3}\right)$
- (2)  $\left(\frac{L}{4}, \frac{2L}{3}\right)$
- (3)  $\left(\frac{L}{6}, \frac{2L}{3}\right)$  (4)  $\left(\frac{L}{6}, \frac{L}{3}\right)$

Sol. Answer (3)

Centre of mass of the uniform rod will lie at its centre

$$x_{\rm cm} = \frac{m_1 x_1 + m_2 x_2}{m_1 + m_2}$$

$$x_{cm} = \frac{m(\frac{L}{2}) + 2m(0)}{3m}, \quad y_{cm} = \frac{2m(L) + m(0)}{3m}$$

$$x_{\rm cm} = \frac{L}{6}$$
 ,  $y_{\rm cm} = \frac{2L}{3}$ 

A circular plate of diameter 'a' is kept in contact with a square plate of side a as shown. The density of the 3. material and the thickness are same everywhere. The centre of mass of composite system will be



- (1) Inside the circular plate
- (3) At the point of contact

(2) Inside the square plate (4) Outside the system

Sol. Answer (2)


$$x_{cm} = \frac{A_1 x_1 + A_2 x_2}{A_1 + A_2}$$
 [ taking origin at contact point ]

$$= \frac{\frac{\pi a^2}{4} \left(\frac{-a}{2}\right) + a^2 \left(\frac{a}{2}\right)}{\frac{\pi a^2}{4} + a^2} = \frac{a^3 \left(1 - \frac{\pi}{4}\right)}{2a^2 \left(a + \frac{\pi}{4}\right)}$$

$$=\frac{a\left(1-\frac{\pi}{4}\right)}{2\left(1+\frac{\pi}{4}\right)}>0$$

 $\Rightarrow x_{cm}$  is inside the square plate

From a uniform square plate, one-fourth part is removed as shown. The centre of mass of remaining part will lie on




(1) OC

(2) OA

- (3) OB
- (4) OD

Sol. Answer (2)

Centre of mass will lie on the line of symmetry



OA is the line of symmetry of the remaining part

A man of mass m is suspended in air by holding the rope of a balloon of mass M. As the man climbs up the rope, the balloon M5.



- (1) Moves upward
- (3) Remains stationary

- (2) Moves downward
- (4) Cannot say

Sol. Answer (2)

Net external force is zero, and centre of mass of the system is initially at rest. So position of centre of mass will not change. So to have  $x_{cm}$  = constant the balloon will move downwards.

- A man of mass m starts moving on a plank of mass M with constant velocity v with respect to plank. If the 6. plank lies on a smooth horizontal surface, then velocity of plank with respect to ground is

#### (Motion of Centre of Mass)

- Two particles A and B initially at rest move towards each other under a mutual force of attraction. At the instant when velocity of A is v and that of B is 2v, the velocity of centre of mass of the system
  - (1) v

(2) 2v

(3) 3v

(4) Zero

Sol. Answer (4)

If 
$$F_{\text{ext}} = 0$$

 $v_{\rm cm}$  is at rest initially so  $v_{\rm cm}$  = 0

as 
$$F_{\text{ext}} = 0$$

$$\Rightarrow a_{cm} = 0$$

- 8. A shell following a parabolic path explodes somewhere in its flight. The centre of mass of fragments will move
  - (1) Vertical direction
- (2) Any direction
- (3) Horizontal direction (4) Same parabolic path

Sol. Answer (4)

The path of centre of mass will not change due to internal forces

- roftelina serios spri. Id. 9. A ball of mass m is thrown upward and another ball of same mass is thrown downward so as to move freely under gravity. The acceleration of centre of mass is
  - (1) g

(3) 2g

Sol. Answer (1)

$$a_{cm} = \frac{m(-g) + m(-g)}{m + m} \Rightarrow a_{cm} = -g$$

#### (Torque and Angular Momentum)

- 10. An angular impulse of 20 Nms is applied to a hollow cylinder of mass 2 kg and radius 20 cm. The change in its angular speed is

- (4) 2500 rad/s

Sol. Answer (3)

(1) 25 rad/s (2) 2.5 rad/s (3) 250 rad/s

Answer (3)
$$20 = 2\left(\frac{1}{2}\right)(2)\left(\frac{20}{100}\right)^2\Delta\omega \quad \begin{bmatrix} \text{Angular impulse} \\ = \text{Change in angular momentum} \end{bmatrix}$$

$$\Delta\omega = \frac{500}{2} = 250 \text{ rad/s}$$

- A hollow sphere of mass 1 kg and radius 10 cm is free to rotate about its diameter. If a force of 30 N is applied tangentially to it, its angular acceleration is (in rad/s<sup>2</sup>)
  - (1) 5000

(2) 450

(3) 50


(4) 5

Sol. Answer (2)

Use  $\tau = I\alpha$ 

$$30\left(\frac{10}{100}\right) = \frac{2}{3}(1)\left(\frac{10}{100}\right)^2 \alpha \implies \alpha = 450 \text{ rad/s}^2$$

12. Two equal and opposite forces are applied tangentially to a uniform disc of mass M and radius R as shown in the figure. If the disc is pivoted at its centre and free to rotate in its plane, the angular acceleration of the disc is



- (4) Zero

Sol. Answer (3)

$$2FR = \frac{1}{2}MR^2\alpha$$

$$\alpha = \frac{4F}{MR}$$

- 13. A wheel having moment of inertia 4 kg m<sup>2</sup> about its symmetrical axis, rotates at rate of 240 rpm about it. The torque which can stop the rotation of the wheel in one minute is
  - (1)  $\frac{5\pi}{7}$ Nm
- (2)  $\frac{8\pi}{15}$ Nm

Sol. Answer (2)

$$w = w_0 - \alpha t$$

$$\alpha = \frac{w_0}{t} = \frac{2\pi(240)}{60 \times 60}$$

$$\alpha = \frac{8\pi}{60} \, \text{rad/s}^2$$

$$\tau = I\alpha$$

$$=4\frac{8\pi}{60}=\frac{8\pi}{15}\,\text{Nm}$$

- 14. A force  $\vec{F} = (2\hat{i} + 3\hat{j} 5\hat{k})$  N acts at a point  $\vec{r_1} = (2\hat{i} + 4\hat{j} + 7\hat{k})$  m. The torque of the force about the point  $\vec{r}_2 = (\hat{i} + 2\hat{j} + 3\hat{k}) m$  is

- (1)  $(17\hat{i} + 5\hat{k} 3\hat{i})$  Nm (2)  $(2\hat{i} + 4\hat{i} 6\hat{k})$  Nm (3)  $(12\hat{i} 5\hat{i} + 7\hat{k})$  Nm (4)  $(13\hat{i} 22\hat{i} \hat{k})$  Nm


$$\vec{r} = \vec{r_1} - \vec{r_2} = (2i + 4j + 7k) - (i + 2j + 3k)$$

$$=\hat{i}+2\hat{j}+4\hat{k}$$

$$\vec{F} = 2\hat{i} + 3\hat{j} - 5\hat{k}$$

$$\tau = \vec{r} \times \vec{F} = \begin{vmatrix} i & j & k \\ 1 & 2 & 4 \\ 2 & 3 & -5 \end{vmatrix} = -22\hat{i} + 13\hat{j} - \hat{k}$$


15. A particle of mass *m* is moving with constant velocity *v* parallel to the *x*-axis as shown in the figure. Its angular momentum about origin O is



- (1) *mvb*
- (3)  $mv\sqrt{a^2+b^2}$

- (2) *mva*
- (4) mv(a+b)

Sol. Answer (1)



$$|L| = mbv$$


- 16. A particle of mass 5 kg is moving with a uniform speed  $3\sqrt{2}$  in XOY plane along the line Y = X + 4. The magnitude of its angular momentum about the origin is
  - (1) 40 units
- (2) 60 units
- (3) Zero
- (4)  $40\sqrt{2}$  units

Sol. Answer (2)


$$L = mvr$$

$$= (5) \left(3\sqrt{2}\right) \left(2\sqrt{2}\right)$$

= 60 units



17. A particle *P* is moving along a straight line as shown in the figure. During the motion of the particle from *A* to *B* the angular momentum of the particle about *O* 



(1) Increases

(2) Decreases

(3) Remains constant


(4) First increases and then decreases

$$L = mvr$$

$$r_{\perp}$$
 is constant so  $L = \text{constant}$ 

#### (Equililbrium of a Rigid Body)

18. For equilibrium of the system, value of mass m should be



(1) 9 kg

(2) 15 kg

(3) 21 kg

(4) 1 kg

Sol. Answer (2)

Net torque = 0 for equilibrium

$$12I = m\left(\frac{I}{2}\right) + 3\left(\frac{3I}{2}\right)$$

$$12/-4.5I = \frac{mI}{2}$$

$$7.5I = \frac{mI}{2}$$

$$m = 15 \text{ kg}$$

#### (Moment of Inertia)

- 19. The moment of inertia of a body depends on
  - (1) The mass of the body
  - (3) The axis of rotation of the body

Sol. Answer (4)

$$I = mr^2$$

20. The moment of inertia of a thin uniform circular disc about one of its diameter is *I*. Its moment of inertia about an axis tangent to it and perpendicular to its plane is



(2) 21

(3)  $\frac{1}{2}$ 

All of these


(4) 6/


(2) The distribution of the mass in the body

Sol. Answer (4)

$$I = \frac{MR^2}{4}$$

Using parallel axis theorem





Now perpendicular axis theorem

$$I' = I'' + I$$

$$=\frac{MR^2}{4}+MR^2+\frac{MR^2}{4}$$

$$=\frac{3}{2}MR^2$$

$$=\frac{3}{2}.(4I)=6I$$

- 21. The two spheres, one of which is hollow and other solid, have identical masses and moment of inertia about their respective diameters. The ratio of their radii is given by
  - (1) 5:7

(2) 3:5

- (3)  $\sqrt{3}:\sqrt{5}$
- (4) 3:7

Sol. Answer (3)

$$\frac{2}{3}mr_1^2 = \frac{2}{5}mr_2^2$$

$$\frac{r_1}{r_2} = \sqrt{\frac{3}{5}}$$


- 22. A circular disc is to be made by using iron and aluminium so that it possesses maximum moment of inertia about geometrical axis. It is possible with
  - (1) Aluminium at interior and iron surrounding it
  - (2) Iron at interior surrounded by aluminium
  - (3) Using iron and aluminium layers in alternate order
  - (4) Sheet of iron is used at both external surfaces and aluminium as interior layer

Sol. Answer (1)

Iron is much denser than Aluminium. To have the maximum moment of inertia, material having higher density should be placed farther from the rotational axis.

(Theorems of Perpendicular Axes and parallel Axes)

23. Three solid spheres each of mass *P* and radius *Q* are arranged as shown in fig. The moment of inertia of the arrangement about *YY'* axis



(1) 
$$\frac{7}{5}PQ^2$$

(2) 
$$\frac{14}{5}PQ^2$$

(3) 
$$\frac{16}{5}PQ^2$$

(4) 
$$\frac{5}{14}PQ^2$$

$$I = \left(\frac{2}{5}mR^2\right) + \left(\frac{2}{5}mR^2 + mR^2\right) + \left(\frac{2}{5}mR^2 + mR^2\right) = \frac{16}{5}mR^2$$

- Four spheres of diameter 2a and mass M are placed with their centres on the four corners of a square of side b. Then moment of inertia of the system about an axis about one of the sides of the square is
  - (1)  $Ma^2 + 2Mb^2$

(3)  $Ma^2 + 4Mh^2$ 

(4)  $\frac{8}{5}$   $Ma^2 + 2Mb^2$ 

Sol. Answer (4)

$$I = 4\left(\frac{2}{5}Ma^2\right) + 2Mb^2$$

$$= \frac{8}{5}Ma^2 + 2Mb^2$$

25. Three rods each of mass m and length L are joined to form an equilateral triangle as shown in the figure. What is the moment of inertia about an axis passing through the centre of mass of the system and perpendicular to the plane?



- (1)  $2 mL^2$
- $(2) \quad \frac{mL^2}{2}$

Sol. Answer (2)


Using parallel axis theorem for one rod Nedical III

$$I = \frac{mI^2}{12} + m\left(\frac{I}{2\sqrt{3}}\right)^2$$

For all three rods

$$l' = 3l = 3ml^2 \left[ \frac{1}{12} + \frac{1}{12} \right] = \frac{ml^2}{2}$$


The moment of inertia of a thin square plate ABCD of uniform thickness about an axis passing through the centre O and perpendicular to the plane of the plate is I. Which of the following is false?



- (1)  $I = I_1 + I_2$
- (2)  $I = I_1 + I_3$
- (3)  $I = I_4 + I_2$

Using perpendicular axis theorem,  $I \neq I_1 + I_2 + I_3 + I_4$ 

27. A thin wire of length  $\ell$  and mass m is bent in the form of a semicircle as shown. Its moment of inertia about an axis joining its free ends will be



(1)  $m\ell^2$ 

(2) Zero

- $(3) \quad \frac{m\ell^2}{\pi^2}$
- $(4) \quad \frac{m\ell^2}{2\pi^2}$

Sol. Answer (4)

$$\ell = \pi R$$

$$\Rightarrow R = \frac{\ell}{\pi}$$

$$I = \frac{mr^2}{2}$$

$$I = \frac{1}{2}m\left(\frac{\ell}{\pi}\right)^2$$

$$\Rightarrow I = \frac{m\ell^2}{2\pi^2}$$

28. Four thin uniform rods each of length *L* and mass *m* are joined to form a square. The moment of inertia of square about an axis along its one diagonal is



(2) 
$$\frac{2}{3}mL$$




(4) 
$$\frac{4 \text{ mL}^2}{3}$$

$$I = 4 \left( \frac{mL^2 \sin^2 45^\circ}{3} \right)$$



$$=\frac{2}{3}mL^2$$



- 29. Two point masses m and 3m are placed at distance r. The moment of inertia of the system about an axis passing through the centre of mass of system and perpendicular to the line joining the point masses is
  - (1)  $\frac{3}{5}mr^2$
- (2)  $\frac{3}{4}mr^2$
- (3)  $\frac{3}{2}mr^2$
- (4)  $\frac{6}{7}mr^2$

187

Sol. Answer (2)

$$I = m \left(\frac{3r}{4}\right)^2 + 3m \left(\frac{r}{4}\right)^2$$

$$0 \longrightarrow 0 \longrightarrow 0$$

$$0 \longrightarrow 3 \xrightarrow{r} 0 \longrightarrow 0$$

$$0 \longrightarrow 3 \xrightarrow{r} 0 \longrightarrow 0$$

$$=\frac{3}{4}mr^2$$

#### (Kinematics of Rotational Motion about a Fixed Axis)

- 30. A wheel starts from rest and attains an angular velocity of 20 radian/s after being uniformly accelerated for 10 s. The total angle in radian through which it has turned in 10 second is
  - (1)  $20 \pi$

(2)  $40 \pi$ 

- (3) 100
- (4)  $100 \pi$

Sol. Answer (3)

$$\omega_f = \omega_I + \alpha t$$

$$20 = 0 + \alpha(10)$$

$$\alpha = 2 \text{ rad/s}^2$$

Now,  $\theta = \omega_i t + \frac{1}{2} \alpha t^2$ 

$$\theta = \frac{1}{2}(2)(100)$$

= 100 radian

#### (Dynamics of Rotational Motion about a Fixed Axis)


- 31. A meter stick is held vertically with one end on the floor and is allowed to fall. The speed of the other end when it hits the floor assuming that the end at the floor does not slip is  $(g = 9.8 \text{ m/s}^2)$ 
  - (1) 3.2 m/s
- (2) 5.4 m/s
- (3) 7.6 m/s
- (4) 9.2 m/s

Sol. Answer (2)

$$\frac{mgl}{2} = \frac{1}{2} \frac{ml^2}{3} \omega^2$$

$$\omega^2 = \frac{3g}{\ell} \Rightarrow \omega = \sqrt{\frac{3g}{\ell}} = \sqrt{30}$$

32. A quarter disc of radius R and mass m is rotating about the axis OO' (perpendicular to the plane of the disc) as shown. Rotational kinetic energy of the quarter disc is



- $(1) \quad \frac{1}{2} mR^2 \omega^2$
- $(2) \quad \frac{1}{4} mR^2 \omega^2$
- (3)  $\frac{1}{8}mR^2\omega^2$
- $(4) \quad \frac{1}{16} mR^2 \omega^2$


$$k = \frac{1}{2}I\omega^2$$

$$=\frac{1}{2}\left(\frac{mr^2}{2}\right)\omega^2$$

$$k = \frac{1}{4}mr^2\omega^2$$

- 33. A metre stick is pivoted about its centre. A piece of wax of mass 20 g travelling horizontally and perpendicular to it at 5 m/s strikes and adheres to one end of the stick so that the stick starts to rotate in a horizontal circle. Given the moment of inertia of the stick and wax about the pivot is 0.02 kg m<sup>2</sup>, the initial angular velocity of the stick is
  - (1) 1.58 rad/s
- (2) 2.24 rad/s
- (3) 2.50 rad/s
- (4) 5.00 rad/s

Sol. Answer (3)



$$L = I\alpha$$

$$\frac{20}{1000} \times 5 \times \frac{l}{2} = 0.02 \,\omega \implies \omega = 2.5 \text{ rad/s}$$

- $L = I\omega$   $\frac{20}{1000} \times 5 \times \frac{I}{2} = 0.02 \,\omega \implies \omega = 2.5 \text{ rad/s}$ 34. A circular disc of mass 2 kg and radius 10 cm rolls without slipping with a speed 2 m/s. The total kinetic energy of disc is energy of disc is
  - (1) 10 J

(2) 6 J

- (4) 4 J

Sol. Answer (2)


$$k = \frac{1}{2}mv^{2} + \frac{1}{2}I\omega^{2}$$

$$= \frac{1}{2}mv^{2} + \frac{1}{2}\frac{mI^{2}}{2} \cdot \frac{v^{2}}{I^{2}}$$

$$= \frac{3}{4}(2)(2)^{2}$$

$$= 6 \text{ J}$$


35. In case of pure rolling, what will be the velocity of point A of the ring of radius R?



(1)  $V_{cm}$ 

- (2)  $\sqrt{2} v_{cm}$
- (3)  $\frac{V_{\rm cm}}{2}$
- (4)  $2v_{cm}$

$$v_{net} = \sqrt{v_{cm}^2 + v_{cm}^2}$$
$$= v_{cm}\sqrt{2}$$



36. A thin circular ring of mass M and radius r is rotating about its axis with a constant angular velocity  $\omega$ . Two objects, each of mass m are attached gently to the opposite ends of a diameter of the ring. The ring now rotates with an angular velocity

(1) 
$$\frac{\omega M}{m+M}$$

$$(2) \frac{\omega(M-2m)}{M+2m}$$

(3) 
$$\frac{\omega M}{M+2m}$$

(4) 
$$\omega \left( \frac{M+2m}{M} \right)$$

Sol. Answer (3)

$$I_1\omega_1 = I_2\omega_2$$

$$Mr^2\omega = (M + 2m) r^2\omega'$$

$$\omega' = \frac{M\omega}{M + 2m}$$

37. A horizontal disc rotating freely about a vertical axis through its centre makes 90 revolutions per minute. A small piece of wax of mass m falls vertically on the disc and sticks to it at a distance r from the axis. If the number of revolutions per minute reduce to 60, then the moment of inertia of the disc is

(2) 
$$\frac{3}{2}mr^2$$

Sol. Answer (3)

$$w_1 = \frac{2\pi 90}{60} = 3\pi \text{ rps}$$

$$w_2 = \frac{2\pi 60}{60} = 2\pi \text{ rps}$$

Using angular momentum conservation

$$I(1.5) = (I + mr^2) (1)$$

$$\frac{1}{2} = mr^2$$

$$I = 2mr^2$$

If two discs of moment of inertia  $I_1$  and  $I_2$  rotating about collinear axis passing through their centres of mass and perpendicular to their plane with angular speeds  $\omega_1$  and  $\omega_2$  respectively in opposite directions are made to rotate combinedly along same axis, then the magnitude of angular velocity of the system is

$$(1) \quad \frac{I_1 \omega_1 + I_2 \omega_2}{I_1 + I_2}$$

(2) 
$$\frac{I_1\omega_1 - I_2\omega_2}{I_1 + I_2}$$
 (3)  $\frac{I_1\omega_1 + I_2\omega_2}{\omega_1 + \omega_2}$  (4)  $\frac{I_1\omega_1 - I_2\omega_2}{\omega_1 - \omega_2}$ 

$$(3) \quad \frac{I_1\omega_1 + I_2\omega_2}{\omega_4 + \omega_2}$$

$$(4) \quad \frac{I_1 \omega_1 - I_2 \omega_2}{\omega_1 - \omega_2}$$

Using angular momentum conservation,  $I_1\omega_1 + I_2\omega_2 = (I_1 + I_2)\omega$ 

$$\omega = \frac{I_1 \omega_1 + I_2 \omega_2}{I_1 + I_2}$$

#### (Angular Momentum in Case of Rotation about a Fixed Axis)

- 39. The angular momentum of a particle performing uniform circular motion is L. If the kinetic energy of partical is doubled and frequency is halved, then angular momentum becomes
  - (1)  $\frac{L}{2}$

(2) 2L

(3)  $\frac{L}{4}$ 

(4) 4L

Sol. Answer (4)

$$L = I\omega$$

$$K = \frac{1}{2}I\omega^2$$

$$2K = \frac{1}{2}I'\left(\frac{\omega}{2}\right)^2$$

$$\frac{1}{2} = \frac{I}{I'}(4)$$

$$I' = 8I$$

$$L' = \left(8I\right)\left(\frac{\omega}{2}\right) = 4I\omega$$

$$\Rightarrow L' = 4 L$$

- Fhat 40. If torque acting upon a system is zero, the quantity that remains constant is
  - (1) Force
- (2) Linear momentum
- (3) Angular momentum (4) Angular velocity

Sol. Answer (3)

41. A constant torque acting on a uniform circular wheel changes its angular momentum from  $A_0$  to  $4A_0$  in 4 seconds. The magnitude of this torque is

(1) 
$$\frac{3A_0}{4}$$


(2)  $A_0$ 

- (3)  $4A_0$
- $(4) 12A_0$

$$\tau = \frac{\Delta L}{\Delta t}$$

$$\tau = \frac{4A_0 - A_0}{4} = \frac{3A_0}{4}$$

42. A uniform rod of mass *m* and length *l* is suspended by two strings at its ends as shown. When one of the strings is cut, the rod starts falling with an initial angular acceleration



(1)  $\frac{g}{I}$ 

(2)  $\frac{g}{2l}$ 

- $(3) \quad \frac{3g}{2I}$
- (4)  $\frac{3g}{4I}$

Sol. Answer (3)

$$\tau = I\alpha$$

$$\frac{mgl}{2} = \frac{mI^2}{3}\alpha$$

$$\alpha = \frac{3g}{2I} \quad \text{and } a = \alpha r$$

$$= \frac{I}{2} \cdot \frac{3g}{2I} = \frac{3g}{4}$$


- 43. Two like parallel forces 20 N and 30 N act at the ends A and B of a rod 1.5 m long. The resultant of the forces will act at the point
  - (1) 90 cm from A
- (2) 75 cm from B
- (3) 20 cm from B
- 4) 85 cm from A

Sol. Answer (1)

Net torque should be same for the new point

$$20(0.75) + 30(0.75) = 50(x)$$

Solve for x




#### (Rolling Motion)

- 44. A solid sphere, a spherical shell, a ring and a disc of same radius and mass are allowed to roll down an inclined plane without slipping. The one which reaches the bottom first is
  - (1) Solid sphere
- (2) Spherical shell
- (3) Rina
- (4) Disc

Sol. Answer (1)

Body of smaller  $\frac{K^2}{R^2}$  will take less time so solid sphere will reach the ground first.

45. A disc of mass *m* and radius *r* is free to rotate about its centre as shown in the figure. A string is wrapped over its rim and a block of mass *m* is attached to the free end of the string. The system is released from rest. The speed of the block as it descends through a height *h*, is



- (1)  $\sqrt{2gh}$
- (2)  $\sqrt{\frac{2}{3}gh}$

- $(3) \quad 2\sqrt{\frac{gh}{3}}$
- $(4) \quad \frac{1}{2}\sqrt{3gh}$

Using mechanical energy conservation

$$mgh = \frac{1}{2}mv^2 + \frac{1}{2}\left(\frac{1}{2}\right)mr^2 \cdot \frac{v^2}{r^2}$$

$$mgh = \frac{3}{4}mv^2$$

$$v^2 = \frac{4gh}{3}$$

$$v = \sqrt{\frac{4gh}{3}}$$

- 46. When a body is rolling without slipping on a rough horizontal surface, the work done by friction is
  - (1) Always zero

(2) May be zero

(3) Always positive

(4) Always negative

Sol. Answer (1)

- Redications of Aakash Educational Sanicas South (4) 37 47. A solid spherical ball is rolling without slipping down an inclined plane. The fraction of its total energy associated with rotation is
  - (1)  $\frac{2}{5}$

$$K_R = \frac{1}{2} \left( \frac{2}{5} m r^2 \right) \frac{v^2}{r^2}$$

$$K_R = \frac{1}{5}mv^2$$

$$K_{Tr} = \frac{1}{2}mv^2$$

$$K_{Total} = \frac{1}{5}mv^2 + \frac{1}{2}mv^2$$

$$=\frac{7}{10}mv^2$$

$$\frac{K_R}{K_{Total}} = \frac{\frac{1}{5}mv^2}{\frac{7}{10}mv^2} = \frac{2}{7}$$

- 48. A solid cylinder of mass M and radius R rolls down an inclined plane of height h without slipping. The speed of its centre of mass when it reaches the bottom is
  - (1)  $\sqrt{2gh}$
- (2)  $\sqrt{\frac{4}{3}gh}$
- (3)  $\sqrt{\frac{3}{4}gh}$
- (4)  $\sqrt{\frac{4g}{h}}$

$$Mgh = \frac{1}{2}mv^2 + \frac{1}{2}I\omega^2$$

$$=\frac{1}{2}mv^2+\frac{1}{2}\frac{ml^2}{2}\cdot\frac{v^2}{l^2}$$

Solving,

$$v = \sqrt{\frac{4gh}{3}}$$

- 49. An inclined plane makes an angle of 30° with the horizontal. A solid sphere rolling down this inclined plane from rest without slipping has a linear acceleration equal to
  - (1)  $\frac{g}{3}$

(3)  $\frac{5g}{7}$ 

Sol. Answer (4)

$$\tau = I\alpha$$

$$\alpha = \frac{\tau}{I} = \frac{mgr \sin \theta}{\frac{2}{5}mr^2 + mr^2}$$

$$a = \alpha r = \frac{mgr^2 \sin \theta}{\frac{2}{5}mr^2 + mr^2}$$

$$a = \frac{5g\sin 30^{\circ}}{7} = \frac{5g}{14}$$

- Redical III. It the foliation of Sanicas Part. Ital.

  The for a 50. What is the minimum coefficient of friction for a solid sphere to roll without slipping on an inclined plane of inclination  $\theta$ ?
  - (1)  $\frac{2}{7} \tan \theta$

(2)  $\frac{1}{3}g \tan \theta$ 

(3)  $\frac{1}{2} \tan \theta$ 

(4)  $\frac{2}{5} \tan \theta$ 

$$\mu = \frac{I \tan \theta}{I + mr^2} = \frac{\frac{2}{5} mr^2 \tan \theta}{\frac{2}{5} mr^2 + mr^2} = \frac{2 \tan \theta}{7}$$

- 51. An object slides down a smooth incline and reaches the bottom with velocity v. If same mass is in the form of a ring and it rolls down an inclined plane of same height and angle of inclination, then its velocity at the bottom of inclined plane will be
  - (1) v

- (3) 2 v
- (4)  $\sqrt{2} v$

$$v = \sqrt{2gh}$$

$$mgh = \frac{1}{2}mv^2 + \frac{1}{2}mr^2\frac{v^2}{r^2}$$

$$v' = \sqrt{gh}$$

$$v' = \frac{v}{\sqrt{2}}$$

- 52. A swimmer while jumping into river from a height easily forms a loop in air if
  - (1) He pulls his arms and legs in

(2) He spreads his arms and legs

(3) He keeps himself straight

(4) None of these

Sol. Answer (1)

Using angular momentum conservation, by pulling his arms and legs in, moment of inertia will decrease hence ω will increase.

#### **SECTION - B**

## Objective Type Questions

(Centre of Mass)

The linear mass density( $\lambda$ ) of a rod of length L kept along x-axis varies as  $\lambda = \alpha + \beta x$ ; where  $\alpha$  and  $\beta$  are positive constants. The centre of mass of the rod is at

(1) 
$$\frac{(2\beta + 3\alpha L)L}{2(2\beta + \alpha L)}$$

(2) 
$$\frac{(3\alpha + 2\beta L)L}{3(2\alpha + \beta L)}$$

$$(3) \quad \frac{(3\beta + 2\alpha L)L}{3(2\beta + \alpha L)}$$

$$\frac{(2\beta + 3\alpha L)L}{2(2\beta + \alpha L)} \qquad (2) \quad \frac{(3\alpha + 2\beta L)L}{3(2\alpha + \beta L)} \qquad (3) \quad \frac{(3\beta + 2\alpha L)L}{3(2\beta + \alpha L)} \qquad (4) \quad \frac{(3\beta + 2\alpha L)L}{3\beta + 2\alpha}$$

$$\lambda = \alpha + \beta x$$

$$dm = (\alpha + \beta x)dx$$


$$x_{cm} = \frac{\int_{L}^{L} x(\alpha + \beta x) dx}{\int_{0}^{L} (\alpha + \beta x) dx} = \frac{\alpha \int_{0}^{L} x dx + \beta \int_{0}^{L} x^{2} dx}{\alpha \int_{0}^{L} dx + \beta \int_{0}^{L} x dx}$$

$$x_{cm} = \frac{\alpha L^2}{\frac{2}{2} + \frac{\beta L^3}{3}}$$
$$\alpha L + \frac{\beta L^2}{2}$$

- 2. A man of mass 60 kg is standing on a boat of mass 140 kg, which is at rest in still water. The man is initially at 20 m from the shore. He starts walking on the boat for 4 s with constant speed 1.5 m/s towards the shore. The final distance of the man from the shore is
  - (1) 15.8 m
- (2) 4.2 m

- (3) 12.6 m
- (4) 14.1 m

Distance travelled by the man on boat in 4 second =  $(1.5) \times 4$ 



140x = 60 (6 - x)

$$140x = 360 - 60x$$

$$x = 1.8 \text{ m}$$

So final distance of the man from the shore will be 20 - (6 - 1.8) = 15.8 m

- A bomb of mass m is projected from the ground with speed v at angle  $\theta$  with the horizontal. At the maximum height from the ground it explodes into two fragments of equal mass. If one fragment comes to rest immediately after explosion, then the horizontal range of centre of mass is

Sol. Answer (4)

Path of the centre of mass will not change due to internal forces

$$R_{cm} = \frac{v^2 \sin 2\theta}{g}$$

- FOLINGE PARTIES

  f negilibrings Parties

  inc. Two blocks of masses 5 kg and 2 kg are connected by a spring of negilible mass and placed on a frictionless 4. horizontal surface. An impulse gives a velocity of 7 m/s to the heavier block in the direction of the lighter block. The velocity of the centre of mass is
  - (1) 30 m/s
- (2) 20 m/s
- (4) 5 m/s

Sol. Answer (4)

(1) 30 m/s (2) 20 m/s

Answer (4)
$$v_{cm} = \frac{m_1 v_1 + m_2 v_2}{m_1 + m_2} = \frac{5(7) + 2(0)}{7} = 5 \text{ m/s}$$


que and Angular Momentum)

(Torque and Angular Momentum)

- A particle starts from the point (0, 8) metre and moves with uniform velocity of  $\vec{v} = 3\hat{i}$  m/s. What is the angular momentum of the particle after 5 s about origin (mass of particle is 1 kg)?
  - (1)  $-12\hat{k} \text{ kg m}^2/\text{s}$
- (2)  $-24\hat{k} \text{ kg m}^2/\text{s}$
- (3)  $-32\hat{k}$  kg m<sup>2</sup>/s (4)  $-36\hat{k}$  kg m<sup>2</sup>/s

$$L = mvr_{\perp}$$
  
= (1)(3)(8)

$$= 24(-\hat{k}) \, \text{kgm}^2/\text{s}$$



- A ball of mass 1 kg is projected with a velocity of  $20\sqrt{2}$  m/s from the origin of an xy co-ordinate axis system 6. at an angle 45° with x-axis (horizontal). The angular momentum [In SI units] of the ball about the point of projection after 2 s of projection is [take  $g = 10 \text{ m/s}^2$ ] (y-axis is taken as vertical)
  - (1)  $-400 \hat{k}$
- (2)  $200 \hat{i}$

- (3) 300  $\hat{i}$
- (4)  $-350 \hat{i}$

Time of flight 
$$T = \frac{2u\sin\theta}{g} = \frac{2(20\sqrt{2})\frac{1}{\sqrt{2}}}{10} = 4$$
 second

⇒ After 2 second particle will be at maximum height of the projectile

$$r_{\perp} = H_{\text{max}} = \frac{u^2 \sin^2 \theta}{2g} = 20 \text{ m}$$


So 
$$L = (1)(20)(20) = 400(-\hat{k})$$

(Moment of Inertia)

- $(1-\frac{4}{\pi^2})$   $mr^2\left(1+\frac{4}{\pi^2}\right)$   $s dia^2$ 7. The moment of inertia of a uniform semicircular wire of mass m and radius r, about an axis passing through its centre of mass and perpendicular to its plane is
  - (1)  $\frac{mr^2}{2}$
- (2)  $mr^2$

Sol. Answer (3)

$$mr^2 = I_{cm} + m \left(\frac{2r}{\pi}\right)^2$$



$$I_{cm} = mr^2 \left[ 1 - \frac{4}{\pi^2} \right]$$


- Moment of inertia of a uniform circular disc about its diameter is I. Its moment of inertia about an axis parallel to 8. its plane and passing through a point on its rim will be
  - (1) 31

(2) 41

(3) 51

(4) 61

$$I = \frac{1}{4}mr^2$$



$$I' = \frac{1}{4}mr^2 + mr^2$$

$$I' = \frac{5}{4}mr^2$$

$$I' = 5I$$

(1)  $\frac{1}{3}$ 

(2)  $\frac{2}{3}$ 

(3)  $\frac{3}{1}$ 

(4)  $\frac{3}{2}$ 

Sol. Answer (3)

$$I = \frac{1}{2}V\rho r^2$$

$$I = \frac{1}{2}\pi r^2 t \rho r^2$$

$$I = \frac{\pi r^4 t \rho}{2}$$

$$\pi r_1^2 t \rho_1 = \pi r_2^2 t \rho_2$$

$$r_1^4 \rho_1^2 = r_2^4 \rho_2^2$$

$$\frac{r_1^4}{r_2^4} = \frac{\rho_2^2}{\rho_1^2}$$

So, 
$$\frac{I_1}{I_2} = \frac{\pi r_1^4 t \rho_1}{\pi r_2^4 t \rho_2} = \frac{\rho_2^2}{\rho_1^2} \cdot \frac{\rho_1}{\rho_2} = \frac{\rho_2}{\rho_1} = 3$$

10. A thin wire of length *I* and mass *m* is bent in the form of a semicircle. The moment of inertia about an axis perpendicular to its plane and passing through the end of the wire is

- (1)  $\frac{ml^2}{2}$
- (2) 2*ml*<sup>2</sup>

- $(3) \frac{ml^2}{\pi^2}$
- $(4) \quad \frac{2ml^2}{\pi^2}$

Sol. Answer (4)


$$\ell = \pi r$$

$$r=\frac{I}{\pi}$$

$$I=2m\left(\frac{I}{\pi}\right)^2$$

$$=\frac{2ml^2}{\pi^2}$$

11. Four rings each of mass *M* and radius *R* are arranged as shown in the figure. The moment of inertia of the system about the axis *yy'* is



- (1)  $2MR^2$
- (2) 3MR<sup>2</sup>

- (3) 4MR<sup>2</sup>
- (4) 5MR<sup>2</sup>

For upper and lower rings, 
$$I_1 = \frac{MR^2}{2}$$


For middle rings, using parallel axis theorem

$$I_2 = \frac{MR^2}{2} + MR^2$$

$$=\frac{3}{2}MR^2$$

$$I = 2I_1 + 2I_2 = MR^2 + 3MR^2 = 4MR^2$$

12. Three particles each of mass m are placed at the corners of equilateral triangle of side I



Which of the following is /are correct?

- (1) Moment of inertia about axis '1' is  $\frac{5}{4}ml^2$
- (2) Moment of inertia about axis '2' is  $\frac{3}{4}ml^2$
- (3) Moment of inertia about an axis passing through one corner and perpendicular to the plane is  $2m^p$

#### Sol. Answer (4)

$$I_1 = mI^2 + m\left(\frac{I}{2}\right)^2$$
  $I_2 = m\left(\frac{I\sqrt{3}}{2}\right)^2$ 

(3) Moment of inertia about an axis passing through one corner.


(4) All of these


Answer (4)
$$I_1 = mI^2 + m\left(\frac{I}{2}\right)^2 \qquad I_2 = m\left(\frac{I\sqrt{3}}{2}\right)^2$$


$$I_1 = \frac{5mI^2}{4}, \quad I_2 = \frac{3mI^2}{4}, \quad I_3 = mI^2 + mI^2$$


 $= 2ml^2$ 

13. A square plate has a moment of inertia  $l_0$  about an axis lying in its plane, passing through its centre and making an angle  $\theta$  with one of the sides. Which graph represents the variation of I with  $\theta$ ?










Using perpendicular axis theorem




$$I = 2I'$$

$$I' = \frac{I}{2} = \text{Constant}$$



From a uniform disc of radius R and mass 9 M, a small disc of radius  $\frac{R}{3}$  is removed as shown. What is the moment of inertia of remaining disc about an axis passing through the centre of disc and perpendicular to its plane?



(1) 
$$\frac{32}{9}MR^2$$

(2) 
$$10 MR^2$$

(3) 
$$\frac{40}{9}MR^2$$

$$(4) 4 MR^2$$

Sol. Answer (4)

$$I_1 = \frac{1}{2}(9M)(R^2) = \frac{9MR^2}{2}$$

$$I_2 = \frac{1}{2}M\left(\frac{R}{3}\right)^2 + M\left(\frac{2R}{3}\right)^2$$

$$= \frac{MR^2}{18} + \frac{4MR^2}{9} = \frac{9MR^2}{18} = \frac{MR^2}{2}$$

$$I = I_1 - I_2 = 4MR^2$$

15. Two rods of equal lengths(I) and equal mass M are kept along x and y axis respectively such that their centre of mass lie at origin. The moment of inertia about an line y = x, is

(1) 
$$\frac{ml^2}{3}$$


$$(2) \frac{ml^2}{4}$$

(3) 
$$\frac{ml^2}{12}$$

(4) 
$$\frac{ml^2}{6}$$

$$I_{\text{Total}} = 2 \left( \frac{mI^2}{12} \sin^2 45^\circ \right)$$

$$\frac{2ml^2}{12} \cdot \frac{1}{2} = \frac{ml^2}{12}$$



- 16. Two rings of same mass and radius *R* are placed with their planes perpendicular to each other and centres at a common point. The radius of gyration of the system about an axis passing through the centre and perpendicular to the plane of one ring is
  - (1) 2R


 $(2) \quad \frac{R}{\sqrt{2}}$ 

- (3)  $\sqrt{\frac{3}{2}}R$
- $(4) \quad \frac{\sqrt{3}R}{2}$

Sol. Answer (4)

$$I_{AB} = mr^2 + \frac{mr^2}{2}$$





$$\frac{3mr^2}{2} = 2mk^2$$

$$k = \frac{\sqrt{3}}{2}R$$

- 17. A thin uniform wire of mass *m* and length *l* is bent into a circle. The moment of inertia of the wire about an axis passing through its one end and perpendicular to the plane of the circle is
  - $(1) \quad \frac{2mL^2}{\pi^2}$
- $(2) \quad \frac{mL^2}{\pi^2}$

- $(3) \quad \frac{mL^2}{2\pi^2}$
- $(4) \quad \frac{mL^2}{3\pi^2}$

Sol. Answer (3)

$$2\pi r = L$$

$$r=\frac{L}{2\pi}$$
,  $I=2mr^2=2m\left(\frac{L}{2\pi}\right)^2$ 

- 18. The angular velocity of a body changes from  $\omega_1$  to  $\omega_2$  without applying a torque but by changing the moment of inertia about its axis of rotation. The ratio of its corresponding radii of gyration is
  - (1)  $\omega_1 : \omega_2$

(2)  $\sqrt{\omega_1}:\sqrt{\omega_2}$ 

(3)  $\omega_2$ :  $\omega_1$ 

(4)  $\sqrt{\omega_2}$ :  $\sqrt{\omega_1}$ 

Sol. Answer (4)

Using angular momentum conservation,  $I_1\omega_1 = I_2\omega_2$ 

$$\frac{I_1}{I_2} = \frac{\omega_2}{\omega_1}$$

$$\frac{mk_1^2}{mk_2^2} = \frac{\omega_2}{\omega_1}$$

$$\frac{k_1}{k_2} = \sqrt{\frac{\omega_2}{\omega_1}}$$

#### (Dynamics of Rotational Motion about a Fixed Axis)

- 19. A hot solid sphere is rotating about a diameter at an angular velocity  $\omega_0$ . If it cools so that its radius reduces to  $\frac{\cdot}{n}$ of its original value, its angular velocity becomes
  - (1)  $\eta \omega_0$

- (4)  $\eta^2 \omega_0$

Sol. Answer (4)

Angular momentum will be conserved

$$\frac{2}{5}mr^2\omega_0 = \frac{2}{5}m\left(\frac{r}{\eta}\right)^2\omega'$$

$$\omega' = \eta^2 \omega_0$$

- 20. A thin rod of mass m and length I is suspended from one of its ends. It is set into oscillation about a horizontal axis. Its angular speed is ω while passing through its mean position. How high will its centre of mass rise from its lowest position?

Sol. Answer (4)

 $\frac{1}{2} \frac{ml^2}{3} . \omega^2 = mgh$  (Energy conservation)

$$h = \frac{I^2 \omega^2}{6g}$$

- (4)  $\frac{\omega^2 l^2}{6g}$ 21. A solid body rotates about a fixed axis such that its angular velocity depends on  $\theta$  as  $\omega = k\theta^{-1}$  where k is a positive constants. At t = 0,  $\theta = 0$ , then time dependence of  $\theta$  is given as
  - (1)  $\theta = kt$
- (3)  $\theta = \sqrt{kt}$
- (4)  $\theta = \sqrt{2kt}$

$$\omega = \frac{k}{\Omega}$$


$$\frac{d\theta}{dt} = \frac{k}{\theta}$$

$$\int \theta d\theta = k \int dt$$

$$\frac{\theta^2}{2} = kt$$

$$\theta = \sqrt{2kt}$$

22. A uniform disc of mass m and radius R is pivoted at point P and is free to rotate in vertical plane. The centre C of disc is initially in horizontal position with P as shown in figure. If it is released from this position, then its angular acceleration when the line PC is inclined to the horizontal at an angle  $\theta$  is



$$(1) \quad \frac{2g\cos\theta}{3R}$$

(2) 
$$\frac{g \sin \theta}{2R}$$

(3) 
$$\frac{2g\sin\theta}{R}$$


$$(4) \quad \frac{2g\sin\theta}{3R}$$

Sol. Answer (1)

$$\tau = I\alpha$$

$$mg(R\cos\theta) = \frac{3}{2}mr^2\alpha$$

$$\alpha = \frac{2g\cos\theta}{3r}$$



(Angular Momentum in Case of Rotation about a Fixed Axis)

- 23. A particle undergoes uniform circular motion. About which point in the plane of the circle, will the angular momentum of the particle remain conserved?
  - (1) Centre of the circle

(2) On the circumference of the circle

(3) Inside the circle other than centre

(4) Outside the circle

Sol. Answer (1)

External torque about centre will always be zero hence angular momentum of the particle will remain conserved.

- 24. When a planet moves around sun, then its
  - (1) Angular velocity is constant
  - (3) Linear velocity is constant

- (2) Areal velocity is constant
- (4) Linear momentum is conserved

Sol. Answer (2)

#### (Rolling Motion)

25. A force F is applied at the centre of a disc of mass M. The minimum value of coefficient of friction of the surface for rolling is



(2) 
$$\frac{F}{3Mq}$$

$$(3) \frac{2F}{5Ma}$$

$$(4) \quad \frac{2F}{7Mc}$$

Sol. Answer (2)

$$F - f = Ma$$







Using (1) and (2),

$$F = \frac{3}{2}Ma \Rightarrow a = \frac{2F}{3M}$$

$$f=\frac{1}{2}M\cdot\frac{2F}{3M}$$

$$f = \frac{F}{3} = \mu Mg$$

$$\Rightarrow \mu = \frac{F}{3Ma}$$

- 26. When a rolling body enters onto a smooth horizontal surface, it will
  - (1) Continue rolling

(2) Starts slipping

(3) Come to rest

(4) Slipping as well as rolling

#### Sol. Answer (1)

Smooth surface won't be able to change *w* or *v* of the body. So to conserve its angular momentum it will continue to roll on the smooth surface.

- 27. A hollow sphere of mass m and radius R is rolling downward on a rough inclined plane of inclination  $\theta$ . If the coefficient of friction between the hollow sphere and incline is  $\mu$ , then
  - (1) Friction opposes its translation

- (2) Friction supports rotation motion
- (3) On decreasing  $\theta$ , frictional force decreases
- (4) All of these

Sol. Answer (4)

- 28. A heavy solid sphere is thrown on a horizontal rough surface with initial velocity *u* without rolling. What will be its speed, when it starts pure rolling motion?
  - (1)  $\frac{3u}{5}$

(2)  $\frac{2u}{5}$ 

(3)  $\frac{5u}{7}$ 

 $(4) \quad \frac{2u}{7}$ 

Sol. Answer (3)

Using angular momentum conservation,  $mur = mvr + \frac{2}{5}mr^2\left(\frac{v}{r}\right)$ 

$$u=7\frac{v}{5}$$

$$v=\frac{5u}{7}$$

- 29. A cylinder rolls down two different inclined planes of the same height but of different inclinations
  - (1) In both cases the speed and time of descent will be different
  - (2) In both cases the speed and time of descent will be same
  - (3) The speed will be different but time of descent will be same
  - (4) The time of descent will be different but speed will be same

- 30. A disc of mass 3 kg rolls down an inclined plane of height 5 m. The translational kinetic energy of the disc on reaching the bottom of the inclined plane is
  - (1) 50 J

(2) 100 J

- (3) 150 J
- (4) 175 J

Sol. Answer (2)


Using mechanical energy conservation,  $mgh = \frac{1}{2}mv^2 + \frac{1}{2}I\omega^2$ 

$$3(5)(10) = \frac{1}{2}mv^2 + \frac{1}{2}ml^2\left(\frac{v^2}{l^2}\right)$$

$$150 = \frac{3}{4}mv^2 \Rightarrow mv^2 = 200$$

$$\frac{1}{2}mv^2 = 100 \text{ J} = \text{K.E.}_{\text{Translation}}$$

31. A rod of length *L* leans against a smooth vertical wall while its other end is on a smooth floor. The end that leans against the wall moves uniformly vertically downward. Select the correct alternative



- (1) The speed of lower end increases at a constant rate
- (2) The speed of the lower end decreases but never becomes zero
- (3) The speed of the lower end gets smaller and smaller and vanishes when the upper end touches the ground
- (4) The speed of the lower end remain constant till upper end touches the ground

Sol. Answer (3)

Using constraint motion relation

$$v'\cos\theta = v\sin\theta$$

 $v' = v \tan \theta$ 

ation  $\theta$ 


As  $\theta$  keeps on decreasing,  $\tan \theta$  will also decrease and at last  $\theta$  will become zero and v' = 0

#### **SECTION - C**

#### **Previous Years Questions**

- 1. A rope is wound around a hollow cylinder of mass 3 kg and radius 40 cm. What is the angular acceleration of the cylinder if the rope is pulled with a force of 30 N?

  [NEET-2017]
  - (1) 25 m/s<sup>2</sup>
- (2) 0.25 rad/s<sup>2</sup>
- (3) 25 rad/s<sup>2</sup>
- (4) 5 m/s<sup>2</sup>



$$\tau = I \alpha$$

$$F \times R = MR^2\alpha$$

$$30 \times 0.4 = 3 \times (0.4)^2 \alpha$$

$$12 = 3 \times 0.16 \alpha$$

$$400 = 16 \alpha \Rightarrow \alpha = 25 \text{ rad/s}^2$$

- Which of the following statements are correct? 2.
  - (a) Centre of mass of a body always coincides with the centre of gravity of the body.
  - (b) Centre of mass of a body is the point at which the total gravitational torque on the body is zero
  - (c) A couple on a body produce both translational and rotational motion in a body.
  - (d) Mechanical advantage greater than one means that small effort can be used to lift a large load.

[NEET-2017]

Sol. Answer (1)

Centre of mass may or may not coincide with centre of gravity.

.e and race to fa [NE]  $\frac{1}{8}(\omega_1-\omega_2)^2$  The results of the re 3. Two discs of same moment of inertia rotating about their regular axis passing through centre and perpendicular to the plane of disc with angular velocities  $\omega_1$  and  $\omega_2$ . They are brought into contact face to face coinciding the axis of rotation. The expression for loss of energy during this process is [NEET-2017]

(1) 
$$\frac{1}{2}I(\omega_1 + \omega_2)^2$$
 (2)  $\frac{1}{4}I(\omega_1 - \omega_2)$ 

(2) 
$$\frac{1}{4}I(\omega_1 - \omega_2)^2$$

(3) 
$$I(\omega_1 - \omega_2)^2$$

(4) 
$$\frac{1}{8}(\omega_1 - \omega_2)^2$$

Sol. Answer (2)

$$\Delta KE = \frac{1}{2} \frac{I_1 I_2}{I_1 + I_2} (\omega_1 - \omega_2)^2$$
$$= \frac{1}{2} \frac{I^2}{(2I)} (\omega_1 - \omega_2)^2$$
$$= \frac{1}{4} I(\omega_1 - \omega_2)^2$$

Two rotating bodies A and B of masses m and 2m with moments of inertia  $I_A$  and  $I_B$  ( $I_B > I_A$ ) have equal kinetic energy of rotation. If  $L_A$  and  $L_B$  be their angular momenta respectively, then [NEET (Phase-2) 2016]

(1) 
$$L_A = \frac{L_B}{2}$$

(2) 
$$L_A = 2L_B$$

$$(3) \ L_B > L_A$$

$$(4) \ L_A > L_B$$

$$E = \frac{L^2}{2I}$$

$$\Rightarrow E_A = E_B$$

$$\Rightarrow \frac{L_A^2}{2I_A} = \frac{L_B^2}{2I_B}$$

$$I_B > I_A$$

$$\Rightarrow L_B > L_A$$

5. A solid sphere of mass m and radius R is rotating about its diameter. A solid cylinder of the same mass and same radius is also rotating about its geometrical axis with an angular speed twice that of the sphere. The ratio of their kinetic energies of rotation ( $E_{\rm sphere}$  /  $E_{\rm cylinder}$ ) will be

[NEET (Phase-2) 2016]

(1) 2:3

(2) 1:5

(3) 1:4

(4) 3:1

Sol. Answer (2)

$$\frac{E_{\text{sphere}}}{E_{\text{cylinder}}} = \frac{\frac{1}{2} \left(\frac{2}{5} m R^2\right) \omega^2}{\frac{1}{2} \left(\frac{1}{2} m R^2\right) (2\omega)^2} = \frac{1}{5}$$


A light rod of length l has two masses  $m_1$  and  $m_2$  attached to its two ends. The moment of inertia of the system about an axis perpendicular to the rod and passing through the centre of mass is

[NEET (Phase-2) 2016]


(1)  $\frac{m_1 m_2}{m_1 + m_2} l^2$ 

(3)  $(m_1 + m_2)l^2$ 

Sol. Answer (1)



(~~+~~) 
$$\sqrt{m_1m_2}i$$




$$I = m_1 x_1^2 + m_2 x_2^2 = \frac{m_1 m_2}{m_1 + m_2} l^2$$

The Louisian a Service Spyr. Ltd.) From a disc of radius R and mass M, a circular hole of diameter R, whose rim passes through the centre is cut. What is the moment of inertia of the remaining part of the disc about a perpendicular axis, passing through the centre? [NEET-2016]



(2) 
$$\frac{15MR^2}{32}$$

(3) 
$$\frac{13MR^2}{32}$$



$$I = I_{\text{remain}} + I_{(R/2)}$$

$$\Rightarrow$$
  $I_{\text{remain}} = I - I_{(R/2)}$ 

$$= \frac{MR^{2}}{2} - \left[ \frac{\frac{M}{4}(R/2)^{2}}{2} + \frac{M}{4} \left( \frac{R}{2} \right)^{2} \right]$$

$$= \frac{MR^{2}}{2} - \left[ \frac{MR^{2}}{32} + \frac{MR^{2}}{16} \right]$$

$$= \frac{MR^{2}}{2} - \left[ \frac{MR^{2} + 2MR^{2}}{32} \right]$$

$$= \frac{MR^{2}}{2} - \frac{3MR^{2}}{32} = \frac{16MR^{2} - 3MR^{2}}{32} = \frac{13MR^{2}}{32}$$

- 8. A disk and a sphere of same radius but different masses roll off on two inclined planes of the same altitude and length. Which one of the two objects gets to the bottom of the plane first? [NEET-2016]
  - (1) Depends on their masses

(2) Disk

(3) Sphere

(4) Both reach at the same time

Sol. Answer (3)

$$a_{\rm sphere} > a_{\rm disc}$$

Acceleration (a) =  $\frac{g \sin \theta}{1 + K^2/r^2}$ , independent of mass and radius.

- 9. An automobile moves on a road with a speed of 54 km h<sup>-1</sup>. The radius of its wheels is 0.45 m and the moment of inertia of the wheel about its axis of rotation is 3 kg m<sup>2</sup>. If the vehicle is brought to rest in 15 s, the magnitude of average torque transmitted by its brakes to the wheel is

  [Re-AIPMT-2015]
  - (1)  $2.86 \text{ kg m}^2\text{s}^{-2}$

(2) 6.66 kg m<sup>2</sup>s<sup>-2</sup>

(3)  $8.58 \text{ kg m}^2\text{s}^{-2}$ 


(4) 10.86 kg m<sup>2</sup>s<sup>-2</sup>

Sol. Answer (2)

$$\tau = I\alpha = I\frac{a}{r} = I\frac{V}{tr} = \frac{3 \times 54 \times \frac{5}{18}}{15 \times 0.45}$$

 $\tau$  = 6.66 kg m<sup>2</sup>s<sup>-2</sup>

10. Point masses  $m_1$  and  $m_2$  are placed at the opposite ends of a rigid rod of length L, and negligible mass. The rod is to be set rotating about an axis perpendicular to it. The position of point P on this rod through which the axis should pass so that the work required to set the rod rotating with angular velocity  $\omega_0$  is minimum, is given by [Re-AIPMT-2015]



(1) 
$$x = \frac{m_2 L}{m_1 + m_2}$$

(2) 
$$x = \frac{m_1 L}{m_1 + m_2}$$

(3) 
$$x = \frac{m_1}{m_2}L$$

(4) 
$$x = \frac{m_2}{m_1} L$$

Minimum work ⇒ Minimum rotational kinetic energy

- ⇒ Maximum angular momentum ⇒ Minimum moment of inertia
- So, its rotation should be about CM

$$x = \frac{m_2 L}{m_1 + m_2}$$

- 11. A force  $\vec{F} = \alpha \hat{i} + 3\hat{j} + 6\hat{k}$  is acting at a point  $\vec{r} = 2\hat{i} 6\hat{j} 12\hat{k}$ . The value of  $\alpha$  for which angular momentum about origin is conserved is [Re-AIPMT-2015]
  - (1) 1

(2) -1

(3) 2

(4) Zero

#### Sol. Answer (2)

Angular momentum conserved  $\Rightarrow \tau = 0$ 

$$\Rightarrow \vec{r} \times \vec{F} = 0$$

$$\Rightarrow \frac{F_x}{X} = \frac{F_y}{V} = \frac{F_z}{Z}$$

$$\Rightarrow \frac{\alpha}{2} = \frac{3}{-6} = \frac{6}{-12}$$

$$\Rightarrow \alpha = -1$$

12. A rod of weight *W* is supported by two parallel knife edges *A* and *B* and is in equilibrium in a horizontal position. The knives are at a distance *d* from each other. The centre of mass of the rod is at distance *x* from *A*. The normal reaction on *A* is

(1) 
$$\frac{W(d-x)}{d}$$


(2) 
$$\frac{Wx}{d}$$



$$(4) \quad \frac{W(d-x)}{x}$$

Sol. Answer (1)

13. A mass m moves in a circle on a smooth horizontal plane with velocity  $v_0$  at a radius  $R_0$ . The mass is attached to a string which passes through a smooth hole in the plane as shown.



The tension in the string is increased gradually and finally m moves in a circle of radius  $\frac{R_0}{2}$ . The final value of the kinetic energy is **[AIPMT-2015]** 


(1)  $\frac{1}{2} m v_0^2$ 

(2)  $mv_0^2$ 

(3)  $\frac{1}{4} m v_0^2$ 

(4)  $2mv_0^2$ 

14. Three identical spherical shells, each of mass *m* and radius *r* are placed as shown in figure. Consider an axis *XX'* which is touching to two shells and passing through diameter to third shell. Moment of inertia of the system consisting of these three spherical shells about *XX'* axis is **[AIPMT-2015]** 



- (1) 4*mr*<sup>2</sup>
- (2)  $\frac{11}{5} mr^2$
- (3)  $3mr^2$
- (4)  $\frac{16}{5}mr^2$

Sol. Answer (1)

- 15. Two spherical bodies of mass *M* and 5*M* and radii *R* and 2*R* are released in free space with initial separation between their centres equal to 12 *R*. If they attract each other due to gravitational force only, then the distance covered by the smaller body before collision is **[AIPMT-2015]** 
  - (1) 1.5R
  - (3) 4.5R

- (2) 2.5R
- (4) 7.5R

Sol. Answer (4)

- 16. A solid cylinder of mass 50 kg and radius 0.5 m is free to rotate about the horizontal axis. A massless string is wound round the cylinder with one end attached to it and other hanging freely. Tension in the string required to produce an angular acceleration of 2 rev/s<sup>2</sup> is [AIPMT-2014]
  - (1) 25 N
  - (3) 78.5 N

(2) 50 N

Sol. Answer (4)

Use  $\tau = I\alpha$ 

T.R. = 
$$\frac{mR^2}{2} \cdot \alpha$$

- 17. The ratio of the accelerations for a solid sphere (mass m and radius R) rolling down an incline of angle  $\theta$  without slipping and slipping down the incline without rolling is **[AIPMT-2014]** 
  - (1) 5:7
  - (2) 2:3
  - (3) 2:5
  - (4) 7:5
- Sol. Answer (1)

$$\frac{a_1}{a_2} = \frac{\frac{g\sin\theta}{\left(\frac{2}{5} + 1\right)}}{g\sin\theta} = 5 : 7$$

[AIPMT (Prelims)-2012]

- A small object of uniform density rolls up a curved surface with an initial velocity v. It reaches upto a maximum height of  $\frac{3v^2}{4a}$  with respect to the initial position. The object is: [NEET-2013]
  - (1) Solid sphere
  - (2) Hollow sphere
  - (3) Disc
  - (4) Ring

Sol. Answer (3)


$$U_i + k_i = U_f + k_f$$

$$0 + \left(\frac{1}{2}mv^2 + \frac{1}{2}I\left(\frac{v}{r}\right)^2\right) = mg\left(\frac{3v^2}{4g}\right) + 0$$

Solving this, we get

$$I = \frac{Mr^2}{2} \Rightarrow \text{body is disc}$$


19. A rod PQ of mass M and length L is hinged at end P. The rod is kept horizontal by a massless string tied to point Q as shown in figure. When string is cut, the initial angular acceleration of the rod is: [NEET-2013]



(1)  $\frac{g}{I}$ 

Sol. Answer (4)

. Answer (4)  $ABC \text{ is an equilateral triangle with O as its centre } \vec{F_1}, \vec{F_2} \text{ and } \vec{F_3} \text{ . represent three forces acting along the sides}$ AB, BC and AC respectively. If the total torque about O is zero then the magnitude of  $\vec{F}_3$  is




(1)  $\frac{F_1 + F_2}{2}$ 

(2)  $2(F_1 + F_2)$ 

(3)  $F_1 + F_2$ 

(4)  $F_1 - F_2$ 



$$F_1 r + F_2 r = F_3 r \Rightarrow F_3 = F_1 + F_2$$

21. When a mass is rotating in a plane about a fixed point, its angular momentum is directed along

[AIPMT (Prelims)-2012]

- (1) The radius
- (2) The tangent to the orbit
- (3) A line perpendicular to the plane of rotation
- (4) The line making an angle of 45° to the plane of rotation

Sol. Answer (3)

- 22. Two persons of masses 55 kg and 65 kg respectively, are at the opposite ends of a boat. The length of the boat is 3.0 m and weighs 100 kg. The 55 kg man walks up to the 65 kg man and sits with him. If the boat is in still water the center of mass of the system shifts by

  [AIPMT (Prelims)-2012]
  - (1) Zero

(2) 0.75 m

(3) 3.0 m

(4) 2.3 m

Sol. Answer (1)

Net external force on the man and boat is zero and centre of mass is initially at rest. So centre of mass will not move.

- 23. A circular platform is mounted on a frictionless vertical axle. Its radius R = 2 m and its moment of inertia about the axle is 200 kg m<sup>2</sup>. It is initially at rest. A 50 kg man stands on the edge of the platform and begins to walk along the edge at the speed of 1 ms<sup>-1</sup> relative to the ground. Time taken by the man to complete one revolution is [AIPMT (Mains)-2012]
  - (1) πs

(2)  $\frac{3\pi}{2}$ s

(3)  $2\pi s$ 

(4)  $\frac{\pi}{2}$ s

$$0 = (50)(1)(2)-200 \omega$$

$$\omega = \frac{1}{2} \text{ rad/s}$$

$$v_{rel} = 1 + 2\left(\frac{1}{2}\right) = 2$$

$$T = \frac{(2\pi)(2)}{2} = 2\pi \text{ s}$$

24. The moment of inertia of uniform circular disc is maximum about an axis perpendicular to the disc and passing through [AIPMT (Mains)-2012]



(1) B

(2) C

(3) D

(4) A

Sol. Answer (1)

$$I_{new} = I_{cm} + md^2$$
 (parallel axis theorem)

 $I_{cm}$  is same for all points but d is maximum for B

- 25. Three masses are placed on the x-axis: 300 g at origin, 500 g at x = 40 cm and 400 g at x = 70 cm. The distance of the centre of mass from the origin is


  [AIPMT (Mains)-2012]
  - (1) 40 cm


(2) 45 cm

(3) 50 cm

(4) 30 cm

Sol. Answer (1)







26. A mass m moving horizontally (along the x-axis) with velocity v collides and sticks to a mass of 3m moving vertically upward (along the y-axis) with velocity 2v. The final velocity of the combination is

[AIPMT (Mains)-2012]

- (1)  $\frac{2}{3}v\hat{i} + \frac{1}{3}v\hat{j}$
- (2)  $\frac{3}{2}v\hat{i} + \frac{1}{4}v$
- (3)  $\frac{1}{4}v\hat{i} + \frac{3}{2}v\hat{j}$
- (4)  $\frac{1}{3}v\hat{i} + \frac{2}{3}v\hat{j}$

Sol. Answer (3)

- 27. The moment of inertia of a thin uniform rod of mass M and length L about an axis passing through its midpoint and perpendicular to its length is  $I_0$ . Its moment of inertia about an axis passing through one of its ends and perpendicular to its length is

  [AIPMT (Prelims)-2011]
  - (1)  $I_0 + ML^2$

(2)  $I_0 + \frac{ML^2}{2}$ 

(3)  $I_0 + \frac{ML^2}{4}$ 

(4)  $I_0 + 2ML^2$ 

$$I_0 = \frac{ML^2}{12}$$

$$I = I_0 + M \left(\frac{L}{2}\right)^2 = I_0 + \frac{ML^2}{4}$$

- 28. The instantaneous angular position of a point on a rotating wheel is given by the equation,  $\theta(t) = 2t^3 - 6t^2$ . The torque on the wheel becomes zero at [AIPMT (Prelims)-2011]
  - (1) t = 2 s
- (2) t = 1 s
- (3) t = 0.5 s
- (4) t = 0.25 s

Sol. Answer (2)


$$\theta = 2t^3 - 6t^2$$

$$\omega = \frac{d\theta}{dt} = 6t^2 - 12t$$

$$\alpha = \frac{d\omega}{dt} = 12t - 12$$

$$\alpha = 0 \Rightarrow 12t - 12 = 0 \Rightarrow t = 1$$

29. A small mass attached to a string rotates on a frictionless table top as shown. If the tension in the string is increased by pulling the string causing the radius of the circular motion to decrease by a factor of 2, the kinetic energy of the mass will [AIPMT (Mains)-2011]



- (1) Increase by a factor of 4
- (3) Remain constant

- (2) Decrease by a factor of 2
- (4) Increase by a factor of 2

Sol. Answer (1)

Use angular momentum conservation,  $m_1v_1r_1 = m_2v_2r_2$ 

A circular disk of moment of inertia  $I_t$  is rotating in a horizontal plane, about its symmetry axis, with a constant angular speed  $\omega_i$ . Another disk of moment of inertia  $I_b$  is dropped coaxially onto the rotating disk. Initially the second disk has zero angular speed. Eventually both the disks rotate with a constant angular speed  $\omega_e$ . The energy lost by the initially rotating disc to friction is: [AIPMT (Prelims)-2010]



(2) 
$$\frac{1}{2} \frac{I_t^2}{(I_t + I_b)} \omega_1^2$$

$$\omega_1^2 \qquad (3) \frac{I_b - I_t}{(I_t + I_b)} \omega_1^2$$

(4) 
$$\frac{1}{2} \frac{I_b - I_t}{(I_t + I_b)} \omega_1^2$$

Sol. Answer (4)

31. Two particles which are initially at rest, move towards each other under the action of their internal attraction. If their speeds are v and 2v at any instant, then the speed of centre of mass of the system will be:

[AIPMT (Prelims)-2010]

(1) 2v

(2) Zero

(3) 1.5v

Sol. Answer (2)

$$\vec{F}_{ext} = 0 \implies \vec{a}_{cm} = 0$$
  
 $\Rightarrow (v_{cm})_i = (v_{cm})_i = 0$ 

- 32. A ball moving with velocity 2 m/s collides head on with another stationary ball of double the mass. If the coefficient of restitution is 0.5 then their velocities (in m/s) after collision will be [AIPMT (Prelims)-2010]
  - (1) 0, 2

(2) 0, 1

(3) 1, 1

(4) 1, 0.5

Sol. Answer (2)

- 33. A man of 50 kg mass is standing in a gravity free space at a height of 10 m above the floor. He throws a stone of 0.5 kg mass downwards with a speed 2 m/s. When the stone reaches the floor, the distance of the man above the floor will be [AIPMT (Prelims)-2010]
  - (1) 20 m
- (2) 9.9 m

- (3) 10.1 m
- (4) 10 m

Sol. Answer (3)

- 34. From a circular disc of radius R and mass 9M, a small disc of mass M and radius  $\frac{R}{3}$  is removed concentrically. The moment of inertia of the remaining disc about an axis perpendicular to the plane of the disc and passing through its centre is **[AIPMT (Mains)-2010]** 
  - (1)  $\frac{40}{9}MR^2$
- (2)  $MR^2$

- (3)  $4MR^2$
- (4)  $\frac{4}{9}MR^2$

Sol. Answer (1)

$$I_1 = \frac{1}{2} (9M) R^2 = \frac{9MR^2}{2}$$

$$I_2 = \frac{1}{2}M\left(\frac{R}{3}\right)^2 = \frac{MR^2}{18}$$

$$I = I_1 - I_2 = \frac{9MR^2}{2} - \frac{MR^2}{18} = \frac{40MR^2}{9}$$

- 35. A solid cylinder and a hollow cylinder, both of the same mass and same external diameter are released from the same height at the same time on a inclined plane. Both roll down without slipping. Which one will reach the bottom first?

  [AIPMT (Mains)-2010]
  - (1) Both together only when angle of inclination of plane is 45°
  - (2) Both together
  - (3) Hollow cylinder
  - (4) Solid cylinder

Sol. Answer (4)

$$a = r\alpha = \frac{r\tau}{I}$$
  $(\because \tau = I\alpha)$ 

So 
$$a = \frac{mgr^2 \sin \theta}{I + mr^2}$$

If I is less, a is more, t is less

- 36. (a) Centre of gravity (C.G.) of a body is the point at which the weight of the body acts
  - (b) Centre of mass coincides with the centre of gravity if the earth is assumed to have infinitely large radius
  - (c) To evalute the gravitational field intensity due to any body at an external point, the entire mass of the body can be considered to be concentrated at its C.G.
  - (d) The radius of gyration of any body rotating about an axis is the length of the perpendicular dropped from the C.G. of the body to the axis

Which one of the following pairs of statements is correct?

[AIPMT (Mains)-2010]

- (1) (d) and (a)
- (2) (a) and (b)
- (3) (b) and (c)
- (4) (c) and (d)

Sol. Answer (2)

37. A thin circular ring of mass M and radius r is rotating about its axis with constant angular velocity  $\omega$ . Two objects each of mass m are attached gently to the opposite ends of a diameter of the ring. The ring now rotates with angular velocity given by [AIPMT (Mains)-2010]

$$(1) \quad \frac{\left(M+2m\right)\omega}{2m}$$

(2) 
$$\frac{2M\omega}{M+2m}$$

$$(3) \quad \frac{\left(M+2m\right)\omega}{M}$$

(4) 
$$\frac{M\omega}{M+2m}$$

Sol. Answer (4)

38. A thin circular ring of mass M and radius R is rotating in a horizontal plane about an axis vertical to its plane with a constant angular velocity  $\omega$ . If two objects each of mass m be attached gently to the opposite ends of a diameter of the ring, the ring will then rotate with an angular velocity:

[AIPMT (Prelims)-2009]

$$(1) \quad \frac{\omega M}{M+2m}$$

(2) 
$$\frac{\omega(M+2m)}{M}$$

(3) 
$$\frac{\omega M}{M+m}$$

$$(4) \quad \frac{\omega(M-2m)}{M+2m}$$

Sol. Answer (1)

Using angular momentum conservation

$$(Mr^2\omega) = (M + 2m)r^2\omega'$$

$$\omega' = \frac{M}{M + 2m}\omega$$

39. An explosion blows a rock into three parts. Two parts go off at right angles to each other. These two are, 1 kg first part moving with a velocity of 12 ms<sup>-1</sup> and 2 kg second part moving with a velocity of 8 ms<sup>-1</sup>. If the third part files off with a velocity of 4 ms<sup>-1</sup>, its mass would be **[AIPMT (Prelims)-2009]** 

Sol. Answer (4)

40. If  $\vec{F}$  is the force acting on a particle having position vector  $\vec{r}$  and  $\vec{\tau}$  be the torque of this force about the origin, then:

(1) 
$$\vec{r} \cdot \vec{\tau} > 0$$
 and  $\vec{F} \cdot \vec{\tau} < 0$ 

(2) 
$$\vec{r} \cdot \vec{\tau} = 0$$
 and  $\vec{F} \cdot \vec{\tau} = 0$ 

(3) 
$$\vec{r} \cdot \vec{\tau} = 0$$
 and  $\vec{F} \cdot \vec{\tau} \neq 0$ 

(4) 
$$\vec{r} \cdot \vec{\tau} \neq 0$$
 and  $\vec{F} \cdot \vec{\tau} = 0$ 

Sol. Answer (2)

 $\vec{\tau}$  will be perpendicular to  $\vec{F}$  and  $\vec{r}$  as  $\vec{\tau} = \vec{r} \times \vec{F}$ 

41. Four identical thin rods each of mass M and length  $\ell$ , form a square frame. Moment of inertia of this frame about an axis through the centre of the square and perpendicular to its plane is: **[AIPMT (Prelims)-2009]** 

$$(1) \quad \frac{2}{3} M\ell^2$$

(2) 
$$\frac{13}{3}M\ell^2$$

$$(3) \quad \frac{1}{3} M\ell^2$$

$$(4) \quad \frac{4}{3} M\ell^2$$

Sol. Answer (4)

$$I = I_{cm} + Md^2$$

$$I_{Total} = 4I = 4\left[\frac{MI^2}{12} + M\left(\frac{I}{2}\right)^2\right] = \frac{4MI^2}{3}$$

- 42. Two bodies of mass 1 kg and 3 kg have position vectors  $\hat{i} + 2\hat{j} + \hat{k}$  and  $-3\hat{i} 2\hat{j} + \hat{k}$ , respectively. The centre of mass of this system has a position vector: [AIPMT (Prelims)-2009]
  - (1)  $-2\hat{i} \hat{i} + \hat{k}$
- (2)  $2\hat{i} \hat{i} 2\hat{k}$
- (3)  $-\hat{i} + \hat{j} + \hat{k}$  (4)  $-2\hat{i} + 2\hat{k}$

Sol. Answer (1)

$$\vec{r}_{cm} = \frac{m_1 \vec{r}_1 + m_2 \vec{r}_2}{m_1 + m_2} = \frac{\left(i + 2j + k\right) + \left(-9i - 6j + 3k\right)}{4} = \frac{-8\hat{i} - 4\hat{j} + 4\hat{k}}{4} \implies \vec{r}_{cm} = -2\hat{i} - \hat{j} + \hat{k}$$

- The ratio of the radii of gyration of a circular disc to that of a circular ring, each of same mass and radius, around their respective axes is
  - (1)  $\sqrt{2}$  :  $\sqrt{3}$
- (2)  $\sqrt{3} : \sqrt{2}$

Sol. Answer (3)


$$\frac{M_1 K_1^2}{M_2 K_2^2} = \frac{\frac{M_1 r^2}{2}}{M_2 r^2}$$

Given  $M_1 = M_2$ 

$$\frac{K_1}{K_2} = \frac{1}{\sqrt{2}}$$

- 44. A thin rod of length L and mass M is bent at its midpoint into two halves so that the angle between them is 90°. The moment of inertia of the bent rod about an axis passing through the bending point and perpendicular to the plane defined by the two halves of the rod is [AIPMT (Prelims)-2008]

Sol. Answer (3)



$$I = 2I = \frac{2\frac{M}{2}\left(\frac{L}{2}\right)^2}{3} = \frac{ML^2}{12}$$

- 45. A wheel has angular acceleration of 3 rad/sec<sup>2</sup> and an initial angular speed of 2 rad/sec. In a time of 2 sec it has rotated through an angle (in radian) of **[AIPMT (Prelims)-2007]** 
  - (1) 4

(2) 6


(3) 10

(4) 12

Sol. Answer (3)

46. A particle of mass m moves in the XY plane with a velocity V along the straight line AB. If the angular momentum of the particle with respect to origin O is  $L_A$  when it is at A and  $L_B$  when it is at B, then

[AIPMT (Prelims)-2007]



- (1)  $L_A < L_B$
- (2)  $L_A > L_B$
- (3)  $L_A = L_B$
- (4) The relationship between  $L_A$  and  $L_B$  depends upon the slope of the line AB

Sol. Answer (3)

Perpendicular distance from O of line AB will be constant. Hence angular momentum will be constant.

47. A uniform rod AB of length I, and mass m is free to rotate about point A. The rod is released from rest in the horizontal position. Given that the moment of inertia of the rod about A is  $\frac{ml^2}{3}$ , the initial angular acceleration of the rod will be [AIPMT (Prelims)-2007]



 $(1) \quad \frac{3g}{2I}$ 

 $(2) \quad \frac{2g}{3I}$ 

- (3)  $mg\frac{1}{2}$
- (4)  $\frac{3}{2}g^{i}$

Sol. Answer (1)


- 48. The moment of inertia of a uniform circular disc of radius *R* and mass *M* about an axis touching the disc at its diameter and normal to the disc is : [AIPMT (Prelims)-2006]
  - (1) MR<sup>2</sup>

- (2)  $\frac{2}{5}MR^2$
- (3)  $\frac{3}{2}MR^2$
- (4)  $\frac{1}{2}MR^2$

Sol. Answer (3)

49. A uniform rod of length l and mass m is free to rotate in a vertical plane about A. The rod initially in horizontal position is released. The initial angular acceleration of the rod is (Moment of inertia of rod about A is  $\frac{ml^2}{3}$ )

[AIPMT (Prelims)-2006]



(1)  $\frac{39}{21}$ 

 $(2) \quad \frac{2I}{3g}$ 

- $(3) \quad \frac{3g}{2l^2}$
- (4)  $mg\frac{1}{2}$

Sol. Answer (1)

$$\tau = I\alpha$$

$$\frac{mgl}{2} = \frac{ml^2}{3}\alpha$$

$$\alpha = \frac{3g}{2I}$$

- 50. A drum of radius R and mass M, rolls down without slipping along an inclined plane of angle θ. The frictional force [AIPMT (Prelims)-2005]
  - (1) Converts translational energy to rotational energy
- (2) Dissipates energy as heat

(3) Decreases the rotational motion

(4) Decreases the rotational and translational motion

Sol. Answer (1)

- 51. Two bodies have their moments of inertia *I* and 2*I* respectively about their axis of rotation. If their kinetic energies of rotation are equal, their angular momenta will be in the ratio [AIPMT (Prelims)-2005]
  - (1) 1:2
- (2)  $\sqrt{2}$ : 1
- (3) 2:1
- (4) 1:  $\sqrt{2}$

Sol. Answer (4)

$$\frac{L_1}{L_2} = \frac{\sqrt{2IK}}{\sqrt{2(2I)K}} = \frac{1}{\sqrt{2}}$$

52. The moment of inertia of a uniform circular disc of radius *R* and mass *M* about an axis passing from the edge of the disc and normal to the disc is **[AIPMT (Prelims)-2005]** 



(2)  $MR^2$ 





Sol. Answer (4)

$$I = I_{cm} + MR^2$$

$$=\frac{MR^2}{2}+MR^2$$

$$=\frac{3}{2}MR^2$$

- Hedicare di
- 53. A solid cylinder of mass 3 kg is rolling on a horizontal surface with velocity 4 ms<sup>-1</sup>. It collides with a horizontal spring of force constant 200 Nm<sup>-1</sup>. The maximum compression produced in the spring will be

[AIPMT (Prelims)-2012]

(1) 0.7 m

(2) 0.2 m

(3) 0.5 m

(4) 0.6 m

Sol. Answer (4)

Use energy conservation

$$U_i + K_i = U_f + K_f$$

$$0 + \frac{1}{2}mv^2 + \frac{1}{2}I\omega^2 = \frac{1}{2}kx^2 + 0$$

54 The centre of mass of a solid cone along the line from the center of the base to the vertex is at


(1) One-fourth of the height

(2) One-third of the height

(3) One-fifth of the height

(4) None of these

Sol. Answer (1)



One fourth of the height

55. The centre of mass of a system of particles does not depend on

- (1) Position of the particles
  - (2) Relative distances between the particles
  - (3) Masses of the particles
  - (4) Forces acting on the particles

Sol. Answer (4)

$$x_{cm} = \frac{m_1 x_1 + m_2 x_2}{m_1 + m_2}$$

So  $x_{cm}$  or  $y_{cm}$  does not depend upon force acting on the particles.

56. Consider a system of two particles having masses  $m_1$  and  $m_2$ . If the particle of mass  $m_1$  is pushed towards  $m_2$  through a distance d, by what distance should be particle of mass  $m_2$  be moved so as to keep the centre of mass of the system of particles at the original position?

(1) 
$$\frac{m_1}{m_1 + m_2}d$$


(2) 
$$\frac{m_1}{m_2}d$$

(4) 
$$\frac{m_2}{m_1}$$
 a

Sol. Answer (2)

$$m_1 d = m_2 x$$

$$x = \frac{m_1 d}{m_2}$$



- (1) Line joining centres of any two balls
- (2) Centre of one of the balls

(3) Horizontal surface

(4) Point of intersection of the medians

Sol. Answer (4)



Centre of mass will lie on the centroid of this triangle i.e., point of intersection of the medians.

58. A rod of length 3 m has its mass per unit length directly proportional to distance *x* from one of its ends then its centre of gravity from that end will be at

(1) 1.5 m

(2) 2 m

(3) 2.5 m

(4) 3.0 m

Sol. Answer (2)

$$dm = kxdx$$

$$\{ as \lambda = kx \}$$

$$x_{cm} = \frac{\int x dm}{\int dm} = \frac{\int_{0}^{3} x \ kx dx}{\int_{0}^{3} kx dx} = \frac{\left[\frac{kx^{3}}{3}\right]_{0}^{3}}{\left[\frac{kx^{2}}{2}\right]_{0}^{3}} = \frac{2}{3}(3) = 2 \text{ m}$$

- 59. The ratio of radii of gyration of a circular ring and a circular disc, of the same mass and radius, about an axis passing through their centres and perpendicular to their planes are
  - (1)  $\sqrt{2}:1$
- (2) 1:  $\sqrt{2}$

- (3) 3:2
- (4) 2:1


Sol. Answer (1)

$$\frac{M_1 K_1^2}{M_2 K_2^2} = \frac{I_1}{I_2} = \frac{M_1 r^2}{\left(\frac{M_1 r^2}{2}\right)}$$

$$M_1 = M_2$$
 (given)

So 
$$\frac{K_1}{K_2} = \sqrt{2}$$

60. The ABC is a triangular plate of uniform thickness. The sides are in the ratio shown in the figure.  $I_{AB}$ ,  $I_{BC}$  and  $I_{CA}$  are the moments of inertia of the plate about AB, BC and CA respectively. Which one of the following relations is correct?



$$(1) I_{AB} + I_{BC} = I_{CA}$$

$$(4) I_{BC} > I_{AB}$$

Sol. Answer (4)

$$I_{AB} = m(3)^2$$


$$I_{BC} = m(4)^2$$

$$I_{CA} = mr^2$$

r < 4

$$\Rightarrow I_{BC} > I_{AB}$$

61. Three particles, each of mass m gram, are situated at the vertices of an equilateral triangle ABC of side I cm (as shown in the figure). The moment of inertia of the system about a line AX perpendicular to AB and in the plane of ABC, in  $gcm^2$  units will be



- (1)  $\frac{3}{4}ml^2$
- (2)  $2ml^2$

- (3)  $\frac{5}{4}mI^2$
- (4)  $\frac{3}{4}ml^2$


221

Sol. Answer (3)

$$I = I_1 + I_2 + I_3$$

$$= 0 + m \left(\frac{I}{2}\right)^2 + mI^2$$

$$= \frac{5mI^2}{4}$$



- 62. A circular disc is to be made by using iron and aluminium so that it acquires maximum moment of inertia about geometrical axis. It is possible with
  - (1) Aluminium at interior and iron surround to it
  - (2) Iron at interior and aluminium surround to it
  - (3) Using iron and aluminium layers in alternate order
  - (4) Sheet of iron is used at both external surface and aluminium sheet as interna layers

Sol. Answer (1)

As density of iron is higher than Aluminium. So iron should be farther from the rotational axis.

63. The ratio of the radii of gyration of a circular disc about a tangential axis in the plane of the disc and of a circular ring of the same radius about a tangential axis in the plane of the ring is

(3) 
$$\sqrt{5}:\sqrt{6}$$

(4) 
$$1 \cdot \sqrt{2}$$

Sol. Answer (3)

For disc, using parallel axis theorem first and then using perpendicular axis theorem

$$I_{disc} = \frac{5}{4}Mr^2$$

$$I_{ring} = \frac{3}{2}Mr^2$$

$$\frac{I_{disc}}{I_{ring}} = \frac{5(2)}{4(3)} = \frac{5}{6} = \frac{K_1^2}{K_2^2}$$

$$\Rightarrow \frac{K_1}{K_2} = \sqrt{\frac{5}{6}}$$

- 64. The reduced mass of two particles having masses m and 2m is
  - (1) 2*m*

(2) 3m

(3)  $\frac{2m}{3}$ 

 $(4) \frac{m}{2}$ 

Sol. Answer (3)

Reduced mass 
$$\mu = \frac{m_1 m_2}{m_1 + m_2} = \frac{m(2m)}{m + 2m} = \frac{2m}{3}$$

- 65. What is the torque of the force  $\vec{F} = 2\hat{i} 3\hat{j} + 4\hat{k}$  N acting at the point  $\vec{r} = 3\hat{i} + 2\hat{j} + 3\hat{k}$  m about origin?

  - (1)  $-6\hat{i} + 6\hat{j} 12\hat{k}$  (2)  $-17\hat{i} + 6\hat{j} + 13\hat{k}$  (3)  $6\hat{i} 6\hat{j} + 12\hat{k}$  (4)  $17\hat{i} 6\hat{j} 13\hat{k}$

Sol. Answer (4)

$$\tau = \vec{r} \times \vec{F} = \begin{vmatrix} i & j & k \\ 3 & 2 & 3 \\ 2 - 3 & 4 \end{vmatrix}$$

$$\hat{i}(17) - \hat{j}(6) + \hat{k}(-13)$$

$$17\hat{i} - 6\hat{j} - 13\hat{k}$$

- 66. A couple produces
  - (1) Linear and rotational motion

(2) No motion

(3) Purely linear motion

(4) Purely rotational motion

Sol. Answer (4)

- 67. The angular speed of a fly-wheel making 120 revolutions/minute is
  - (1)  $4\pi \text{ rad/s}$
- (2)  $4\pi^2$  rad/s
- (3)  $\pi$  rad/s

Sol. Answer (1)

120 rev/min = 
$$\frac{2\pi(120)}{60}$$
 =  $4\pi$  rad/s

- Two discs are rotating about their axes, normal to the discs and passing through the centres of the discs. Disc  $D_1$  has 2 kg mass and 0.2 m radius and initial angular velocity of 50 rad s<sup>-1</sup>. Disc  $D_2$  has 4kg mass, 0.1 m radius and initial angular velocity of 200 rad s<sup>-1</sup>. The two discs are brought in contact face to face, with their axes of rotation coincident. The final angular velocity (in rad.s-1) of the system is
  - (1) 40

(2) 60

- (4) 120

Sol. Answer (3)

Using angular momentum conservation

$$I_1 \; \omega_1 \, + \, I_2 \; \omega_2 = (I_1 \, + \, I_2) \omega$$

$$\frac{1}{2}(2)(0.2)^2(50) + \frac{1}{2}4(0.1)^2(200)$$

$$= \left[ \frac{1}{2} (2) (0.2)^2 + \frac{1}{2} (4) (0.1)^2 \right] \omega$$

$$6 = \frac{6}{100}\omega$$

 $\omega$  = 100 rad/s

- 69. A wheel having moment of inertia 2 kgm<sup>2</sup> about its vertical axis, rotates at the rate of 60 rpm about this axis. The torque which can stop the wheel's rotation in one minute would be
  - (1)  $\frac{2\pi}{15}$ Nm
- (2)  $\frac{\pi}{12}$ Nm
- (3)  $\frac{\pi}{15}$ Nm
- (4)  $\frac{\pi}{18}$ Nm

Sol. Answer (3)

$$\alpha = \frac{0 - \frac{60 \times 2\pi}{60}}{60} = \frac{-2\pi}{60} \text{ rad/s}^2$$

$$\tau = I\alpha = (2)\left(\frac{\pi}{30}\right) = \frac{\pi}{15} \text{ Nm}$$

- 70. What is the value of linear velocity, if  $\vec{\omega} = 3\hat{i} 4\hat{j} + \hat{k}$  and  $\vec{r} = 5\hat{i} 6\hat{j} + 6\hat{k}$ ?

  - (1)  $4\hat{i} 13\hat{j} + 6\hat{k}$  (2)  $-18\hat{i} 13\hat{j} + 2\hat{k}$  (3)  $6\hat{i} + 2\hat{j} + 3\hat{k}$  (4)  $6\hat{i} 2\hat{j} + 8\hat{k}$

Sol. Answer (2)

$$\vec{v} = \vec{\omega} \times \vec{r}$$

$$= \begin{vmatrix} i & j & k \\ 3 & -4 & 1 \\ 5 & -6 & 6 \end{vmatrix}$$

$$i(-18) - i(13) + k(2)$$

$$=-18i-13\hat{i}+2\hat{k}$$

- 71. If  $|\overrightarrow{A} \times \overrightarrow{B}| = \sqrt{3} \overrightarrow{A} \cdot \overrightarrow{B}$  then the value of  $|\overrightarrow{A} + \overrightarrow{B}|$  is

Sol. Answer (1)

$$|\vec{A}| |\vec{B}| \sin \theta = \sqrt{3} |\vec{A}| |\vec{B}| \cos \theta$$

$$\tan \theta = \sqrt{3}$$

$$\theta = 60^{\circ}$$

$$|\vec{A} + \vec{B}|^2 = |\vec{A}|^2 + |\vec{B}|^2 + 2\vec{A}\vec{B} = (A^2 + B^2 + AB)^{\frac{1}{2}}$$

Sol. Answer (4)

- $|\vec{A} + \vec{B}|^2 = |\vec{A}|^2 + |\vec{B}|^2 + 2\vec{A}\vec{B} = (A^2 + B^2 + AB)^{\frac{1}{2}}$ The angle between the vectors  $\vec{A}$  and  $\vec{B}$  is  $\theta$ , the hard between the vectors  $\vec{A}$  and  $\vec{A}$  will be an and  $\vec{A}$  will be and  $\vec{A}$  will be and  $\vec{A}$  will be an and  $\vec{A}$  will be an analysis of  $\vec{A}$  where  $\vec{A}$  is the angle  $\vec{A}$  and  $\vec{A}$  will be an analysis of  $\vec{A}$  and  $\vec{A}$  will be an a 73. A round disc of moment of inertia  $l_1$  about its axis perpendicular to its plane and passing through its centre is placed over another disc of moment of inertia  $I_2$  rotating with an angular velocity  $\omega$  about the same axis. The final angular velocity of the combination of discs is
  - (1)  $\frac{I_2\omega}{I_1+I_2}$

(2)  $\omega$ 

(4)  $\frac{(I_1 + I_2)\omega}{I_1}$ 

Sol. Answer (1)

Using angular momentum conservation,  $I_1(0) + I_2(\omega) = (I_1 + I_2)\omega'$ 

$$\omega' = \frac{I_2 \omega}{I_1 + I_2}$$

- 74. A disc is rotating with angular speed ω. If a child sits on it, what is conserved?
  - (1) Linear momentum
- (2) Angular momentum
- (3) Kinetic energy
- (4) Potential energy

Sol. Answer (2)

- 75. A solid cylinder is rolling without slipping on a plane having inclination θ and the coefficient of static friction  $\mu_s$ . The relation between  $\theta$  and  $\mu_s$  is
  - (1)  $\tan \theta > 3 \mu_s$
- (2)  $\tan \theta \le 3 \mu_s$
- (3)  $\tan \theta < 3 \mu_s^2$  (4) None of these

Sol. Answer (2)

$$\mu_s \ge \frac{\frac{1}{2}mr^2\tan\theta}{\frac{1}{2}mr^2 + mr^2}$$

$$\mu_s \ge \frac{\tan \theta}{3}$$

 $3\mu \geq \tan\theta$ 

- 76. A solid spherical ball rolls on a table. Ratio of its rotational kinetic energy to total kinetic energy is

  (1)  $\frac{1}{2}$  (2)  $\frac{1}{6}$  (3)  $\frac{7}{10}$  (4)  $\frac{2}{7}$

**Sol.** Answer (4)

- 77. A hollow cylinder and a solid cylinder are rolling without slipping down an inclined plane, then which of these (2) Hollow cylinder reaches earlier?
  - (1) Solid cylinder
  - (3) Both simultaneously

- (4) Can't say anything

Sol. Answer (1)

Body of smaller  $\frac{K^2}{R^2}$  will take less time. Solid cylinder has smaller  $\frac{K^2}{R^2}$ 

- 78. A disc is rolling such that the velocity of its centre of mass is  $v_{cm}$ . Which one will be correct?
  - (1) The velocity of highest point is 2  $v_{\rm cm}$  and point of contact is zero
  - (2) The velocity of highest point is  $v_{\rm cm}$  and point of contact is  $v_{\rm cm}$
  - (3) The velocity of highest point is  $2v_{\rm cm}$  and point of contact is  $v_{\rm cm}$
  - (4) The velocity of highest point is  $2v_{cm}$  and point of contact is  $2v_{cm}$

Sol. Answer (1)

- 79. A solid sphere of radius *R* is placed on a smooth horizontal surface. A horizontal force F is applied at height *h* from the lowest point. For the maximum acceleration of centre of mass, which is correct?
  - (1) h = R
  - (2) h = 2R
  - (3) h = 0
  - (4) Centre of mass has same acceleration in each case

Sol. Answer (4)

Acceleration of CM is independent of point of application of force.

- 80. A point *P* is the contact point of a wheel on ground which rolls on ground without slipping. The value of displacement of the point *P* when wheel completes half of rotation (If radius of wheel is 1 m)
  - (1) 2 m

(2)  $\sqrt{\pi^2 + 4}$  m

(3) π m


(4)  $\sqrt{\pi^2 + 2}$  m

Sol. Answer (2)

Use pythagoras theorem

$$r = R\sqrt{\pi^2 + 4}$$

$$=\sqrt{\pi^2+4}$$
 m



Nedical

- 81. A solid cylinder of mass *M* and radius *R* rolls without slipping down an inclined plane of length *L* and height *h*. What is the speed of its centre of mass when the cylinder reaches its bottom?
  - (1)  $\sqrt{2gh}$
  - (3)  $\sqrt{\frac{4}{3}}gh$

(2)  $\sqrt{\frac{3}{4}gh}$ 

Sol. Answer (3)

Using mechanical energy conservation

$$Mgh = \frac{1}{2}mv^2 + \frac{1}{2}\left(\frac{1}{2}MR^2\right)\frac{v^2}{R^2}$$

$$Mgh = \frac{3}{4}Mv^2$$

$$v = \sqrt{\frac{4gh}{3}}$$

- 82. A drum of radius R and mass M, rolls down without slipping along an inclined plane of angle  $\theta$ . The frictional force
  - (1) Dissipates energy as heat
  - (2) Decreases the rotational motion
  - (3) Decreases the rotational and translational motion
  - (4) Converts translational energy to rotational energy

Sol. Answer (4)

- 83. A ball rolls without slipping. The radius of gyration of the ball about an axis passing through its centre of mass is K. If radius of the ball be R, then the fraction of total energy associated with its rotational energy will be
  - (1)  $\frac{K^2 + R^2}{R^2}$  (2)  $\frac{K^2}{R^2}$

- (3)  $\frac{K^2}{K^2 + R^2}$  (4)  $\frac{R^2}{K^2 + R^2}$

Sol. Answer (3)

$$K_{Rot} = \frac{1}{2}MK^2 \frac{v^2}{R^2}$$

$$K_{Total} = \frac{1}{2}MK^2 \frac{v^2}{R^2} + \frac{1}{2}Mv^2$$

$$\frac{K_{Rot}}{K_{Total}} = \frac{\frac{K^2}{R^2}}{1 + \frac{K^2}{R^2}} = \frac{K^2}{K^2 + R^2}$$

- The moment of inertia of a disc of mass M and radius R about an axis, which is tangential to the circumference of the disc and parallel to its diameter is
  - (1)  $\frac{5}{4}MR^2$
- (2)  $\frac{2}{3}MR^2$

Sol. Answer (1)

$$I = \frac{MR^2}{4} + MR^2$$





## **SECTION - D**

## **Assertion - Reason Type Questions**

- A: Centre of mass of a system may or may not lie inside the system.
  - R: The position of centre of mass depends on distribution of mass within the system.

Sol. Answer (1)

- A: The position of centre of mass relative to body is independent of the choice of coordinate system.
  - R: Centre of mass does not shift its position in the absence of an external force.

Sol. Answer (3)

- A: A bomb at rest explodes. The centre of mass of fragments moves along parabolic path.
  - R: Under the effect of gravity only the path followed by centre of mass is always parabolic.

Sol. Answer (4)

- A: If an object is taken to the centre of earth, then its centre of gravity cannot be defined.
  - R: At the centre of earth acceleration due to gravity is zero.

Sol. Answer (1)

A: It is very difficult to open or close a door if force is applied near the hinge.

R: The moment of applied force is minimum near the hinge.

Sol. Answer (1)

6. A: The moment of force is maximum for a point if force applied on it and its position vector w.r.t. the point of rotation are perpendicular.

R: The magnitude of torque is independent of the direction of application of force.

Sol. Answer (3)

7. A: If angular momentum of an object is constant about a point, then net torque on it about that point is zero.

R: Torque is equal to the rate of change of angular momentum.

Sol. Answer (1)

8. A: Two rings of equal mass and radius made of different materials, will have same moment of inertia.

R: Moment of inertia depends on mass as well as distribution of mass in the object.

Sol. Answer (1)

9. A: In pure rolling motion all the points of a rigid body have same linear velocity.

R: Rolling motion is not possible on smooth surface.

Sol. Answer (4)

10. A: For an object in rolling motion rotational kinetic energy is always equal to translational kinetic energy.

R: For an object in rolling motion magnitude of linear speed and angular speed are equal.

Sol. Answer (4)

11. A: The work done by friction force on an object during pure rolling motion is zero.

R: In pure rolling motion, there is relative motion at the point of contact.

Sol. Answer (3)

12. A: When a rigid body rotates about any fixed axis, then all the particles of it move in circles of different radii but with same angular velocity.

R: In rigid body relative position of particles are fixed.

Sol. Answer (1)

13. A: A rigid body can't be in a pure rolling on a rough inclined plane without giving any external force.

R: Since there is no torque providing force acting on the body in the above case, the body can't come in a rolling condition.

Sol. Answer (4)

14. A: When a ring moves in pure rolling condition on ground, it has 50% translational and 50% rotational energy.

R: 
$$\frac{KE_{trans}}{KE_{rot}} = \frac{\frac{1}{2}MV^2}{\frac{1}{2}I\omega^2} = \frac{\frac{1}{2}MV^2}{\frac{1}{2}(MR^2)\frac{V^2}{R^2}} = 1:1.$$

Sol. Answer (1)

15. A: For a body to be in rotational equilibrium the net torque acting on the body about any point is zero.

R: For net torque to be zero, net force should also be zero.

**Sol.** Answer (3)