Fitxa de Producte i Control Qualitat

Codi Document	FP10935	Data Document	23/11/2015
Versió Document	v001	Contacte	E. Pallarés

Nom:	Power button	Ref. Disseny:	BCN3DSigma-M01C01.0P11Z
Ref. Interna	10935		
Mètode Emmag.	Gaveta		
Traçabilitat	No		
Proveïdor	RS	Ref. Proveïdor	741-0912 (Marquardt 1881.1103)



Descripció del producte: Interruptors de la sèrie 1881 de Marquardt. Valor nominal del contacte: 250 VAC a 12 A. Diàmetre màxim: 23 mm.

QUALITAT					
Percentatge d'unitats a revisar: 10%					
Acció	Eines/útils	Rang admissible	Acció si no es compleix		
Mesurar el diàmetre	Peu de rei	23 +/- 1,5 mm	Rebuig		
Inspecció visual	-	Cap llengüeta aixafada, sense cops	Retraball - Posar pestanya recte amb alicates		

Document de referència

DP01 - Definició Procés Magatzem

Document Associat

RI01 - Registre Indicències Magatzem



<u>"</u> EN 60335 cap. 30 conform 15 A 250 V AC 1 1/2 HP Actuator color / printing Contact distance in mm Connection description 12 (4) A 250 V AC 1E4 15 A 125 V AC 3/4 HP 8 (8) A 250 V AC 5E4 Connection type Contact material **Miscellaneous** Stock version Actuator **ON/OFF** switch (SPST) 1881.1103 Ū 4.8 ≥3 IP 40 Ag Ū 1881.1104 IP 40 lacktriangle4.8 ≥3 1881.1105 IP 40 4.8 ≥3 Ū 1881.1106 4.8 ≥3 Ag IP 40 lacktriangleŪ 1881.1108 4.8 ≥3 Ag IP 51 with swtiching system cover Normally open contact (SPNO) opening connection 1b closed Ū 1881.1209 4.8 IP 51 ≥ 3 Ag with swtiching system cover DIN 46 244-A4.8-0.8 Quick-connect terminal 4.8 Basic type 1881 X = Wall thickness Ø 0.75 ... 1.25 20.3 1.25 ... 2 20.8 21.1