The Significance of Accessible Volume

A way to observe the shape of a model's next decision
before it happens

Nicholas Michael Kloster

November 2026

Abstract

Before a language model produces a token, it assigns probabilities to the alternatives. Accessible volume turns that forecast into a direct measurement of next-token predictability. It counts how many alternatives have probabilities above a chosen threshold. A small count means the next-token choice is concentrated on a few alternatives; a large count means many alternatives remain in play. The final text records which token was selected, while accessible volume shows how open or settled the decision was before selection. This makes the model's hidden decision surface measurable, comparable, and reproducible. Experiments with Ablation + GEM, XLNet, and sixteen additional models demonstrate the measurement on real probability distributions. In a subsequent 120-case BioBERT experiment, the original fixed rule at $\tau = 0.05$ outperformed an optimized adaptive equation on held-out biomedical documents, achieving AUROC 0.7737 and AUPRC 0.7978 compared with 0.7008 and 0.6599 for distinguishing incorrect and correct top predictions. The adaptive rule improved validation measurements, but the simpler original equation transferred better to unseen cases.

1 The missing information in an output

A generated answer is a record of what happened. It is not a complete description of the decision that produced it.

Two model states can produce the same next token while having very different distributions of alternatives. In one state, the selected token may dominate every other possibility. In another, many tokens may remain plausible. Reading only the final token hides that distinction.

The relevant question is therefore not merely, "What did the model choose?" It is also, "How much room did the model have to choose differently?" Accessible volume provides one way to answer that question with a number.

2 Origin of the research

This work grew from Nicholas Michael Kloster's March 2026 research into how a language model's input context shapes the alternatives available at the next prediction step. The central question was simple: can the distribution before selection tell us something that the selected token alone cannot?

The first observation was recorded on **March 4, 2026**, and the accessible-volume equation was created on **March 6, 2026**. That work motivated direct examination of full next-token probability distributions.

The present experiment tests that question with controlled measurements using actual Ablation + GEM evidence. It focuses on reproducible token-level measurements and does not make claims about complete responses or later behavior.

3 The equation

Let S be the full input context and $\mathcal{O}$ a finite output vocabulary. Let $P(a \mid h_T(S))$ be the probability that the model assigns to token a as the next token after processing S. For a threshold τ, accessible volume is

$$A_\tau(S) = \sum_{a \in \mathcal{O}} \mathbf{1}[P(a \mid h_T(S)) > \tau]\,. \tag{1}$$

The indicator is one when the probability is strictly greater than τ and zero otherwise. Tokens exactly at the threshold are excluded. The count measures the number of continuations that remain above the selected probability bar.

For example, suppose the model assigns probabilities 0.70, 0.20, 0.08, and 0.02 to four possible next tokens. At $\tau = 0.05$, the first three tokens are above the cutoff, so $A_{0.05}(S) = 3$. A smaller count means a more concentrated, predictable choice; a larger count means a broader choice with more plausible alternatives. This is next-token predictability expressed as a reproducible number.

A normalized form divides the count by vocabulary size:

$$A_{\text{norm},\tau}(S) = \frac{A_\tau(S)}{|\mathcal{O}|}. \tag{2}$$

This reports the fraction of the vocabulary above the threshold. It does not make different models directly comparable.

The computation is simple: after obtaining the distribution, evaluate one comparison per token. The important part is not computational novelty. It is the decision to observe the distribution as an object of measurement rather than treating only the generated text as evidence.

4 Why the measurement matters

4.1 It distinguishes a forecast from an outcome

The probability distribution is the forecast. Sampling or taking the maximum selects an outcome. Accessible volume describes the shape of the forecast without committing to that outcome.

A small count indicates that the model has concentrated its above-threshold alternatives. A large count indicates a broader set. The measurement does not say which token will win. It says how much of the vocabulary remains meaningfully in play at the selected threshold.

4.2 It makes concentration observable

Concentration is usually discussed through entropy, maximum probability, or top-token mass. Accessible volume adds a different description: the size of the region above a chosen cutoff.

The three descriptions are not interchangeable. A distribution can have one dominant token and few above-threshold alternatives, or one dominant token and many alternatives just below the threshold. The count captures a boundary that a single maximum or entropy value does not fully express.

The threshold sweep is more informative than one reading. As τ increases, $A_\tau(S)$ cannot increase. Watching where alternatives disappear reveals whether probability is concentrated in a narrow elite or spread across a broad collection of viable continuations.

4.3 It creates a boundary for inspection

Ablation + GEM is built around the interaction of a stochastic agent, deterministic execution, shared memory, and human judgment. The agent proposes. The environment executes and records. The human directs and reviews.

Accessible volume supplies a way to inspect the agent before its proposal becomes an action. Actual investigation evidence can be placed into a model context, and the resulting distribution can be measured without generating another token. The deterministic environment can then preserve that measurement alongside the rest of the evidence.

This does not make the metric an authorization mechanism. It makes it an instrument for understanding the agent's immediate decision surface while the rest of the system remains constrained and inspectable.

5 Evidence from Ablation + GEM

The measurement was performed on a real forward pass using 963 tokens of actual Ablation + GEM investigation context. The context included a selected artifact, a scoped observation, and real entropy-inspection output from Ablation. A local autoregressive model returned a full distribution over 50,257 next tokens.

Table 1: Measured accessible volume for the actual Ablation + GEM context.

Threshold τ	Accessible volume $A_\tau(S)$
0.02	4
0.05	2
0.10	2
0.15	1
0.30	1
0.50	1

The distribution is concentrated. A newline has probability 0.535587. End-of-text follows with probability 0.109893. The ten most probable tokens contain 75.45% of the total probability mass. Entropy over the full distribution is 4.2998 bits.

The immediate meaning is straightforward: the model is not spreading its above-threshold probability across many alternatives. Its next-token decision is concentrated on a small set. Accessible volume turns that observation into a precise, reproducible statement rather than an impression based on the final text.

A repeated forward pass on the same context produced identical input IDs and probability values. Controlled context perturbations changed some threshold counts and left others unchanged. This confirms that the instrument measures the distribution associated with a particular model and context rather than a universal property of the prompt.

6 Three ways to hold back a target

The same equation can measure different prediction mechanisms, provided that each model supplies a complete probability distribution over a finite vocabulary. The input construction must remain explicit because these mechanisms are not interchangeable.

A BERT-style masked-language model replaces the target with its special mask token. It can use the context on both sides of that mask. The target's position remains known, but its identity is removed from the model input.

XLNet uses a different mechanism. Its content stream represents token identities for use as context, while its query stream represents the target position without access to the target identity. Target mapping selects the position, and the permutation mask blocks query-stream access to that token. This is not the same as inserting a BERT-style mask token.

An autoregressive model receives only the prefix preceding the target. Its final-position logits therefore describe an ordinary next-token forecast. The target and all later text are absent by construction.

In every case, accessible volume is applied without changing the equation, threshold grid, temperature, or model weights. The result describes one model's distribution for one input construction. It does not by itself compare training objectives or establish which architecture is better.

7 An XLNet query-stream extension

The instrument can also examine a prediction for a token already present in the input, not only an ordinary next-token forecast. We used the public XLNet-Base and XLNet-Large models' query streams with the target token masked out of query-stream attention. The input ended with the paper's phrase "Accessible volume addresses this gap." Each resulting distribution contained 32,000 token probabilities.

For XLNet-Base, the most likely token was a period, with probability 0.559758. The second was "issue," with probability 0.068510. The actual hidden token "gap" had probability 0.012354, ranked 12th. Entropy was 3.5946 bits and the ten most probable tokens contained 82.22% of the mass.

XLNet-Large assigned the highest probability to "problem" (0.235085), followed by "in" (0.139887) and a period (0.099426). The hidden token "gap" had probability 0.015083, ranked eighth. Entropy was 5.7603 bits and the ten most probable tokens contained 65.16% of the mass.

Table 2: Accessible volume for two XLNet query-stream predictions.

Variant	0.02	0.05	0.10	0.15	0.30	0.50
XLNet-Base	6	2	1	1	1	1
XLNet-Large	5	4	2	1	0	0

For each model, replacing the target token ID with each of three alternatives produced bit-for-bit identical probability distributions. This confirms that the target token's identity did not enter either query-stream prediction. The query stream could use the remaining context, but not the hidden token itself. Both experiments used PyTorch 2.14.1+cu130 and Transformers 5.18.0; the scripts, complete probability vectors, and input IDs are included as evidence.

A separate offline XLNet-Base reproduction matched the input IDs, all six threshold counts, and the target-token rank and ordering. Its maximum absolute probability difference was $2.3443 \times$

10^{-7}. It was therefore numerically close, but not bit-for-bit identical across the two runtimes. The reported threshold counts are reproducible observations; exact raw-probability equality across different runtimes is not claimed.

This extension demonstrates that accessible volume can describe a leakage-free prediction for an existing input token as well as a forecast of what comes next. The two model results are measurements of specific contexts, not a general ranking of model capability. They remain token-level measurements, not evidence about complete actions, correctness, or safety.

8 Cross-model and domain comparisons

We next applied the unchanged equation to sixteen additional models. The general-language cases used the same target, "gap," for BERT-Base, RoBERTa-Base, ALBERT-Base, and GPT-2. Security models used a firmware-vulnerability reporting sentence. The remaining cases covered biomedical, clinical, scientific, legal, financial, programming, multilingual, chemistry, protein-sequence, and mathematical inputs. Every requested category is represented.

Table 3: Accessible volume across the fixed threshold grid. Counts describe individual model–input pairs, not a quality leaderboard.

Category	Model	0.02	0.05	0.10	0.15	0.30	0.50
General	BERT-Base	2	1	1	1	1	1
General	RoBERTa-Base	2	2	1	1	1	1
General	ALBERT-Base	5	1	1	1	1	0
General	GPT-2 (causal)	7	3	2	1	0	0
Security	SecureBERT	6	4	2	0	0	0
Security	CySecBERT	2	0	0	0	0	0
Biomedical	BioBERT	1	0	0	0	0	0
Clinical	Bio_ClinicalBERT	6	2	2	1	0	0
Scientific	SciBERT	6	3	2	0	0	0
Legal	Legal-BERT	7	2	1	1	1	0
Financial	FinBERT	5	3	2	2	0	0
Programming	CodeBERT	4	3	1	1	1	0
Multilingual	XLM-RoBERTa-Base	6	3	1	0	0	0
Chemistry	ChemBERTa	8	5	0	0	0	0
Protein	ProtBERT	18	9	0	0	0	0
Mathematics	Qwen2.5-Math-1.5B (causal)	9	8	4	2	0	0

The results illustrate why accessible volume and entropy are different instruments. BioBERT had entropy 9.8879 bits but only one token above probability 0.02. CySecBERT had entropy 9.7536 bits but two tokens above that threshold. A broad tail of very small probabilities can produce high entropy without producing many alternatives above a fixed cutoff.

The target was the highest-probability token in two of these sixteen cases: Legal-BERT's "agreement" and Qwen2.5-Math-1.5B's "4." This is not a model ranking. Most domain cases used different contexts, targets, vocabularies, and input formats. A single masked-token or next-token prediction is not a benchmark of correctness or domain competence.

The case manifest records every exact public model identifier, immutable revision, input, target, and prediction style. The sixteen runs used CPU inference with PyTorch 2.14.1+cu130 and Transformers 4.56.2. Evaluation mode and deterministic inference were used throughout, with no sampling or model-weight training. Every model repeated its forward pass bit-for-bit. Masked cases contained exactly one prediction mask, and causal cases included only tokens preceding the target.

The complete input IDs and probability vectors are included for all sixteen cases. The verification script independently recomputed every threshold count, target rank, entropy, top-ten mass, top-token ordering, and raw-array hash from the saved artifacts. All sixteen cases passed.

9 BioBERT: does an adaptive equation improve the original?

We next tested whether an adaptive version of accessible volume could improve detection of BioBERT's top-1 masked-token prediction errors. The experiment used 120 cases from 30 Creative Commons-licensed Europe PMC abstracts. Each document supplied four eligible, non-repeated, single-token targets. Document-grouped splits contained 60 development, 20 validation, and 40 test cases, assigned with seed 20261103 before inference. No document crossed splits.

The original equation was evaluated first on every case. BioBERT produced 29 errors among 60 development cases, 11 among 20 validation cases, and 23 among 40 test cases. Every prediction was repeated bit-for-bit, and every original threshold count was recomputed from the saved full-vocabulary distribution.

The candidate adaptive equation was

$$A_{\alpha,\beta}(x) = \sum_i \mathbf{1}[p_i > \max(\beta, \alpha p_{\max}(x))] \,. \tag{3}$$

It replaces a fixed cutoff with the larger of an absolute floor β and a fraction α of the maximum probability. The search covered 54 predefined parameter pairs. Selection used validation AUROC (area under the receiver-operating-characteristic curve), then validation AUPRC (average precision), then development AUROC, with deterministic tie-breaking. Only after selection were the parameters evaluated on the test documents.

The selected rule was $\alpha = 0.001, \beta = 0$, counting every token above 0.1% of the maximum probability. Table 4 reports the result. AUROC and AUPRC measure how well each score separates incorrect top predictions from correct ones; larger values are better.

Table 4: BioBERT original and adaptive equations for top-1 error detection.

Rule	Dev AUROC	Val AUROC	Test AUROC	Test AUPRC
Adaptive ($\alpha = 0.001, \beta = 0$)	0.7848	0.8737	0.7008	0.6599
Original ($\tau = 0.05$)	0.7219	0.8232	**0.7737**	**0.7978**
Best validation original ($\tau = 0.02$)	0.7681	0.8283	0.7391	0.7502
Entropy	0.7920	0.8990	0.6957	0.6538

The original equation worked better on the held-out BioBERT cases. The fixed $\tau = 0.05$ rule exceeded the adaptive rule by 0.0729 AUROC and 0.1379 AUPRC. The adaptive equation improved development and validation measurements but did not transfer that improvement to unseen documents. On test cases, its mean score was 42.43 for errors and 36.59 for correct predictions; the original $\tau = 0.05$ scores were 3.17 and 1.88, a substantially clearer separation.

The significance is direct: making the threshold responsive to the maximum probability did not improve the instrument on this dataset. The original fixed-threshold equation was simpler and stronger where it mattered, on data excluded from parameter selection. All 120 raw distributions, reports, source manifests, candidate searches, and per-case scores are included. An independent implementation recomputed every reported AUROC and AUPRC value from the raw artifacts.

10 What the result does not establish

The experiment does not establish that a concentrated choice is a correct choice. It does not establish that a broad choice is a better choice. It does not demonstrate how later tokens will behave, and it does not turn a single-step measurement into a prediction of a complete response.

The measured models are also not interchangeable with Kimi, Claude, or Ablation's semantic encoders. Those systems require their own probability distributions before equivalent measurements can be made. A distribution over command-text tokens is not automatically a distribution over complete structured actions.

The two Foundation-Sec-8B variants were not run. Each published repository contains approximately 16.06 GB of model weights, exceeding the available test-system storage for this experiment. They require a separate resource configuration; no result or limitation of those models is inferred here.

These limits do not weaken the measurement. They define its proper use. Accessible volume describes the shape of a particular forecast at a particular moment. Broader interpretations require separate evidence.

11 Possible paths opened by the equation

The measurement also suggests directions for further work, without establishing them as completed findings.

Prediction-aware review. Repeated observations could provide early-warning metadata for an agent review system. An unusual change in the distribution might lead to additional review, a read-only restriction, or a request for human judgment. It would not establish why the change occurred. Any response would still need deterministic policy and signed evidence for later investigation.

From tokens to structured actions. A future experiment could examine distributions over complete permitted actions rather than command-text tokens. This might help a system prepare for several plausible next steps while preserving the same constraints on every action. It would not establish a user's intent or make an action safe by virtue of being predicted.

Authenticated, evolving evidence. Prediction observations could become part of a signed evidence record whose keys rotate over time. Standard cryptographic key derivation and authenticated encryption would be required. A timestamp could determine when to rotate a key, but neither timing nor accessible volume should determine the key itself. The metric is not an entropy source or a source of cryptographic key material.

These are possible paths for investigation, not claims established by the present experiment.

12 Conclusion

Accessible volume turns next-token predictability into a measurement. It counts the alternatives above a probability cutoff, showing whether a model's immediate choice is concentrated on a few options or spread across many. The final output records a selection; accessible volume reveals the decision surface that preceded it.

The measured example shows the instrument working in practice. Four tokens exceed 0.02, two exceed 0.05, and one exceeds 0.15. That is the finding: a real investigation context produced a concentrated next-token decision surface, and the equation made it measurable.

The XLNet and sixteen additional comparisons show the same instrument operating across masked, query-stream, and causal prediction mechanisms. Their results also demonstrate that accessible volume and entropy can describe different aspects of the same distribution. These are individual, reproducible observations, not universal claims about model quality or safety.

The BioBERT experiment provides a direct practical result. The original fixed rule at $\tau = 0.05$ distinguished incorrect and correct top predictions more effectively than the optimized adaptive equation on held-out biomedical documents. Although the adaptive rule improved validation measurements, the original equation achieved the stronger test AUROC and AUPRC. For this experiment, the simpler original equation was the better measurement of prediction uncertainty.

A Ablation + GEM as the working implementation

Ablation is the reverse-engineering framework. GEM (Graphics Environment Manager) is its graphical environment and shared investigation Lab. The public implementation is available at `https://github.com/Ablation-Tool/ablation`.

Ablation + GEM is itself a working demonstration of the chamber model. The AI Agent supplies probabilistic labor and proposals. Ablation + GEM supplies constrained execution, persistent state, verification, and replay. The human supplies direction and judgment. Investigation events, selected objects, evidence, and verification receipts form a unified memory architecture shared by the human and agent.

The implementation used for this experiment is revision `d596bed3`. At that revision, the main Ablation CI passed 2,803 tests with 93 skips, and native Linux, Windows, and macOS workflows passed. Those results demonstrate the implementation's behavior. The accessible-volume experiment adds a separate measurement using actual session evidence produced by that implementation; it is not a claim that the metric was already part of the framework.

B Evidence manifest

The experiment used the public `distilgpt2-ONNX` model and ONNX Runtime 1.31.1. Table 5 records the identities needed to verify the evidence independently.

The raw NPZ artifact contains the complete input-ID sequence and every probability value, not only the ten largest values. The JSON report contains the exact prompt, model metadata, threshold sweep, top tokens, and scope. The full entropy output and model configuration are reproduced below. The context-sweep artifact contains every controlled prompt variant and its raw probability vector.

C Reproduction procedure

The following procedure reproduces the numerical measurement in the tested CPU environment. It uses the public Ablation repository and the public ONNX model, with no API accounts.

1. Clone `https://github.com/Ablation-Tool/ablation` and check out revision `d596bed31ba5fe361efa1c6fdad6d86e3126ab63`.
2. Create an isolated Python 3.14 environment and install Ablation, GEM Lab, NumPy 2.3.5, ONNX Runtime 1.31.1, Tokenizers 0.23.3, and Hugging Face Hub 1.33.0.
3. Obtain the measurement harness embedded in this PDF and place it in a writable working directory.
4. Run `python ablation-gem-measure.py -project /path/to/ablation -output results`. The harness downloads and hash-checks the model, constructs real Lab evidence, runs inference, computes the sweep, and reloads the resulting probability vector for verification.
5. Confirm the reference sweep $5, 4, 3, 2, 1, 0$ and the actual sweep $4, 2, 2, 1, 1, 1$ at thresholds $0.02, 0.05, 0.10, 0.15, 0.30, 0.50$.

Table 5: Evidence identity and scope.

Item	Value
Model SHA-256	`0f79f192f3137e9a90213f1b5d4a52b6d896b735f9cb82160e5de7cc6e539c41`
Tokenizer SHA-256	`a6aa29bf8416d74ad795a73262b1aa3f985564ee338adbee7ffbc5861f78b6b8`
Model configuration SHA-256	`dffb0253be590126da5dc43b75475f6f6ef4576439dec46e8ec83bf0408fcf83`
Probability values SHA-256	`5f6313599e77e72947435e52b273054fabda1e97006d0636658350ac253ed638`
Input IDs SHA-256	`970665aaaafdd2964012f3759b993e53dfe43e6d1793edc68a6b3896089fdbf8`
Entropy evidence SHA-256	`fd551e583e54753744900d66acee85b99a6c07bdcef123f4fd92186a0cc8880d`
Original AFL paper SHA-256	`dec64904f5954e29b44105ba6d41a97f38915ffbecf972554e4eda70d8abbebc`
AFL disclosure SHA-256	`bfa75181d631aca4f8a95d0344819ec6c80ad3ac16ac9cd92ce3986e03055196`
XLNet-Base probability values SHA-256	`c445b5ca7d6e46a01b071720c65f88db4411c69fcaf32a59b2a124c472b6d2ff`
XLNet-Large probability values SHA-256	`a304a47ccd7d55bc3e5dbb2d616715e08444641529372789e2158da1ff72014`
XLNet input IDs SHA-256 (both models)	`2b84113e5c3b6006c097f5bea0966a972833d7a43de8e745c22a15c7b10c60ac`
Comparison manifest SHA-256	`a278cbc15b5d9c6027678154c76a591fa5c95fb8c6e3e01ee26034d4a224e129`
Comparison summary SHA-256	`c4e69b647d1f9ceb6f1c4c0d292ae1f2a3f7e6ee3bc4c778103f7ccd4d632611`
Verified comparison cases	16 models, each with a complete raw probability vector
BioBERT case manifest SHA-256	`cd743b76dc7e9ccc6d1c17dba546544271eac22dc557cb152c601c824e8922b6`
BioBERT baseline SHA-256	`2f213c3e0338895c63e292ea2fe09ababa904cce22132eb99a8a2a8626de1b6d`
BioBERT optimization SHA-256	`3c5829a65876959a904d417cffa7b95361`
BioBERT attachment list SHA-256	`6be446b60b16fce768167d8e6fb42fe612fe3b6b0cfdd80c1e02adfb1b233bdb5321eeff28a3fa0ded3d7313aafd20`
Verified BioBERT cases	120 distributions; 60 development, 20 validation, 40 test
Context length	963 tokens
Vocabulary size	50,257 tokens
Probability sum	Approximately 1.0 within floating-point precision

6. Load the embedded probability vector and independently recompute each count using the strict comparison $P(a \mid h_T(S)) > \tau$. Compare the raw-value and input-ID hashes with the manifest.

The numerical values and raw-value hashes are the reproducible evidence. Timing values and archive-container metadata may differ between runs.

For the XLNet extension, extract `xlnet-accessible-volume.py`. Place the artifact writer, `ablation_gem_artifacts.py`, in the same working directory. Install NumPy, PyTorch 2.14.1, Transformers 5.18.0, and the tokenizer requirements. Run the script with `-model xlnet/xlnet-base-cased` and then with `-model xlnet/xlnet-large-cased`, using a different `-output` directory for each. The script performs a repeated prediction, checks all three target-token replacements, saves every probability and input ID, and independently recomputes the sweep. Compare the saved reports and raw arrays with the included evidence. Small floating-point differences may occur across runtimes; compare threshold counts and token ordering separately from exact probability hashes.

For the sixteen additional comparisons, use a separate Python 3.14 environment with NumPy 2.5.3, PyTorch 2.14.1, Transformers 4.56.2, Tokenizers 0.22.1, SentencePiece 0.2.2, and Hugging Face Hub 0.36.2. Keep the case manifest, runner, measurement harness, verifier, and artifact writer together. The runner uses the immutable revisions in the manifest, executes models sequentially, and removes only its own temporary per-model caches.

```
python run-model-comparison.py --all \
  --output evidence/comparison \
  --cache-dir /path/to/temporary-cache

python verify-model-comparison.py \
  --manifest model-comparison-cases.json \
  --evidence evidence/comparison
```

The optional cache directory must be writable and have enough space for the largest selected model. Use `-model` with an exact identifier from the manifest instead of `-all` to repeat one case. The second command verifies the included evidence without downloading model weights. A repeated BERT-Base case executed through this runner produced bit-identical probabilities, input IDs, and JSON output in the tested runtime. As with XLNet, exact raw-value equality across other runtimes is not assumed.

The BioBERT experiment uses the same Python and model-runtime versions as the sixteen additional comparisons. Keep the three experiment scripts, the independent verifier, the artifact writer, and the frozen `evidence/biobert-optimization` directory together. The included case and split manifests are the authoritative inputs; downloading new source documents is not required. Run:

```
python biobert-accessible-volume.py
python optimize-biobert.py
python verify-biobert-optimization.py
```

The first command downloads the pinned BioBERT model and reproduces all 120 baseline distributions and reports. The second verifies the raw artifacts, selects adaptive parameters using development and validation cases only, and evaluates the frozen choice on the test cases. The third independently recomputes every AUROC and AUPRC value. Use `prepare-biobert-cases.py` only when constructing a new source-document manifest; it must complete before any model predictions are inspected.

D Controlled context evidence

The baseline was repeated before perturbing the context. It produced identical input IDs and probability values. Table 6 reports the controlled follow-up measurements.

Table 6: Accessible volume across controlled context variants.

Variant	Tokens	0.02	0.05	0.10	0.15	0.30	0.50
Baseline	963	4	2	2	1	1	1
Metadata only	522	4	2	2	2	1	0
Abbreviated evidence	295	4	2	2	2	1	1
No evidence	103	3	1	1	1	1	1
Summary request	968	3	2	1	1	1	0
Repeated short evidence	487	3	2	2	1	1	1

These differences are observations about specific model/context pairs. They do not establish a universal rule about which context increases or decreases breadth.

E Complete Ablation entropy evidence

```
BinaryContext: true
  sha256     : 913a39cd38f35349...
  arch       : x86_64
  base_va    : 0x0
  func_starts: 20
  exports    : 2
  plt entries: 33
  strings    : 65
  call_edges : 136
  str_xrefs  : 89 pairs indexed
  named funcs: 0 (overlay)

  exports (first 2):
    0x257f  error
    0x26c8  error_at_line

  imports via PLT (first 20):
    0x2250  __vfprintf_chk
    0x2260  abort
    0x2270  __errno_location
    0x2280  strncmp
    0x2290  _exit
    0x22a0  __fpending
    0x22b0  fcntl
    0x22c0  textdomain
    0x22d0  fclose
    0x22e0  bindtextdomain
    0x22f0  dcgettext
    0x2300  __ctype_get_mb_cur_max
    0x2310  strlen
    0x2320  __stack_chk_fail
    0x2330  __overflow
    0x2340  strrchr
    0x2350  mbrtoc32
    0x2360  memcmp
    0x2370  fputs_unlocked
    0x2380  strcmp

Entropy regions (26 found):
  0x00000000 - 0x00000400  (     1,024 B)  H=2.291  SPARSE
  0x00000400 - 0x00000700  (       768 B)  H=0.801  PADDING
  0x00000700 - 0x00000a00  (       768 B)  H=3.128  SPARSE
  0x00000a00 - 0x00000b00  (       256 B)  H=4.586  CODE
  0x00000b00 - 0x00000d00  (       512 B)  H=2.972  SPARSE
  0x00000d00 - 0x00002000  (     4,864 B)  H=0.271  PADDING
  0x00002000 - 0x00002400  (     1,024 B)  H=3.973  SPARSE
  0x00002400 - 0x00005300  (    12,032 B)  H=5.184  CODE
  0x00005300 - 0x00005400  (       256 B)  H=4.333  SPARSE
  0x00005400 - 0x00006000  (     3,072 B)  H=0.000  PADDING
  0x00006000 - 0x00006300  (       768 B)  H=4.865  CODE
  0x00006300 - 0x00006400  (       256 B)  H=3.591  SPARSE
  0x00006400 - 0x00006500  (       256 B)  H=4.503  CODE
  0x00006500 - 0x00006600  (       256 B)  H=4.477  SPARSE
  0x00006600 - 0x00006700  (       256 B)  H=4.980  CODE
  0x00006700 - 0x00006c00  (     1,280 B)  H=3.535  SPARSE
  0x00006c00 - 0x00006d00  (       256 B)  H=4.970  CODE
  0x00006d00 - 0x00006f00  (       512 B)  H=3.247  SPARSE
  0x00006f00 - 0x00007d00  (     3,584 B)  H=0.060  PADDING
  0x00007d00 - 0x00007e00  (       256 B)  H=1.535  SPARSE
```

F Model configuration

```
{
  "_name_or_path": "distilbert/distilgpt2",
  "_num_labels": 1,
  "activation_function": "gelu_new",
  "architectures": [
    "GPT2LMHeadModel"
  ],
  "attn_pdrop": 0.1,
```

```
  "bos_token_id": 50256,
  "embd_pdrop": 0.1,
  "eos_token_id": 50256,
  "id2label": {
    "0": "LABEL_0"
  },
  "initializer_range": 0.02,
  "label2id": {
    "LABEL_0": 0
  },
  "layer_norm_epsilon": 1e-05,
  "model_type": "gpt2",
  "n_ctx": 1024,
  "n_embd": 768,
  "n_head": 12,
  "n_inner": null,
  "n_layer": 6,
  "n_positions": 1024,
  "reorder_and_upcast_attn": false,
  "resid_pdrop": 0.1,
  "scale_attn_by_inverse_layer_idx": false,
  "scale_attn_weights": true,
  "summary_activation": null,
  "summary_first_dropout": 0.1,
  "summary_proj_to_labels": true,
  "summary_type": "cls_index",
  "summary_use_proj": true,
  "task_specific_params": {
    "text-generation": {
      "do_sample": true,
      "max_length": 50
    }
  },
  "transformers_version": "4.43.4",
  "use_cache": true,
  "vocab_size": 50257
}
```


G Embedded evidence

The complete evidence package is embedded in this PDF as 303 attachments. It includes the baseline experiment, XLNet Base and Large results, all sixteen additional model comparisons, and the focused BioBERT optimization study. Exact model inputs, complete probability vectors, JSON reports, immutable revisions, and raw-artifact hashes are preserved. The BioBERT package contains all 120 raw distributions and reports, frozen cases and document splits, source metadata and licenses, the complete parameter search, per-case scores, and an independent metric verifier. No external filesystem is needed to inspect the evidence; public model downloads are needed only to repeat inference.