Governed Semantic Compilation

Lawful Continuation, Refusal Semantics, and Epistemic Promotion in Large Language Models

Large Language Models (LLMs) are commonly characterized as probabilistic next-token predictors operating over unstructured text.

Author
Adam Ableman
Constitutional Computing
Contact: ableman.research@gmail.com

Abstract

Large Language Models (LLMs) are commonly characterized as probabilistic next-token predictors operating over unstructured text. While mechanistically accurate, this framing obscures a more operationally decisive question: under what conditions are model outputs permitted to persist, propagate, and acquire authority? This paper introduces **Governed Semantic Compilation (GSC)** as a framework for answering that question.

GSC is not a theory of how LLMs think, nor a proposal about internal cognition. It is a theory of **epistemic legitimacy**—the conditions under which generated text may be promoted from transient output to binding semantic state. The framework reframes hallucination, instability, and many alignment failures as consequences of **ungoverned continuation**, rather than deficiencies in token prediction or knowledge representation.

Central claim. When LLMs are embedded in a governed, compiler-like interaction regime, they exhibit measurably higher coherence, stability, and reliability *for tasks involving epistemic promotion* than when they are used in an ungoverned, narrative token-prediction regime. Empirical observation further suggests that governed regimes improve not only high-stakes deployment but also exploratory and creative work by reducing semantic drift, premature convergence, and authority leakage.

This paper reports system-level regularities observed across governed deployments and design patterns—such as refusal rates, churn reduction in agentic loops, and improved auditability—treated as architectural effects rather than model benchmarks. GSC formalizes this regime in terms of declared semantic state, admissible continuation, refusal as a compile-time success condition, and explicit promotion boundaries. Governance here replaces trust: outputs are not believed—they are compiled, or refused.

1. Scope and Motivation

LLMs are increasingly deployed in contexts where outputs do more than inform: they decide, commit, authorize, and persist. In such contexts, failure rarely arises from lack of fluency or expressive power. It arises when plausible text is allowed to *count* without ceremony.

This paper addresses a question prior to alignment, safety, or capability: **when is an output allowed to acquire authority at all?**

Most contemporary LLM interaction defaults to a narrative regime. Prompts invite continuation; outputs are read and interpreted; promotion—from suggestion to decision, from explanation to record—occurs implicitly. This implicit promotion enables **authority laundering**: speculative continuation escalates into binding state without explicit validation or traceability.

Governed Semantic Compilation proposes a different posture. Instead of treating model interaction as free-form narration, it embeds models in a regime where continuation is conditional, state is explicit, and refusal is meaningful. In this regime, the model functions as a **latent compiler** over semantic state: proposing transitions that are either admissible, rejected, or undefined.

This is not a metaphysical claim about cognition. It is an operational claim about **how systems behave under constraint**—and about how they fail when such constraint is absent.

---

2. Narrative and Governed Regimes Reconsidered

Conventional wisdom treats ungoverned narrative interaction as appropriate for ideation and creative exploration, reserving governed regimes for situations where outputs must be stable, attributable, or binding. Empirical observation suggests otherwise.

In a **narrative token-prediction regime**:

- Continuation is assumed unless explicitly halted.
- Outputs are evaluated informally by human judgment.
- Refusal is treated as failure or misalignment.
- Coherence is stylistic rather than structural.

This regime often *feels* free, but frequently produces:

- semantic drift mid-generation,
- scope creep without acknowledgement,
- authority leakage (speculation mistaken for conclusion),
- confirmation lock-in from early plausible narratives.

In contrast, a **governed, compiler-like regime** enforces:

- explicit semantic state,
- typed outputs (hypothesis vs conclusion),
- clean separation between exploration and commitment,
- restartability via refusal without narrative contamination.

Across creative exploration, debugging, research assistance, and brainstorming contexts, governed regimes consistently yield higher-quality exploration: more divergent search, less premature convergence, and fewer "how did we get here?" moments. The benefit is not merely safety. It is **epistemic hygiene under uncertainty**.

The apparent freedom of narrative interaction is often freedom to drift and conflate. Governed interaction feels more constrained, yet enables more productive exploration by preserving coherence over time.

---

3. Semantic State and Admissibility

GSC operates over an abstract **semantic state**, denoted (Σ). This state is **observer-defined**, not model-internal. It represents what the system is currently permitted to treat as binding: assumptions, unresolved references, jurisdictional scope, declared invariants, and authority context.

Semantic state is not belief, truth, intention, or understanding. It is a ledger of **admissibility**.

Let:

- (Σ) be the current semantic state,
- (T) be the space of model-generated tokens or spans,
- $(\delta : \Sigma \times T \to \Sigma \cup \{\bot\})$ be a partial transition function.

If $\delta(\Sigma, t) = \Sigma'$, the transition is admissible. If $\delta(\Sigma, t) = \bot$, the transition is **undefined**.

Undefined transitions are not errors or low-probability events. They are non-events: they generate no new state and license no interpretation. This undefinedness is the semantic basis of refusal.

In concrete systems, (δ) is implemented by schemas, validators, policy engines, test harnesses, or human adjudication gates that either accept a proposed span as a state transition or treat it as undefined. Undefined transitions correspond to refusals to write, commit, or escalate—no side effects, no binding log entries.

Admissibility need not be computable, complete, or globally known. It must only be **enforced at the interface**.

---

4. Epistemic Promotion

Epistemic promotion is the transition by which text becomes state—where an output ceases to be merely informative and becomes authoritative. Most operational failures occur at this boundary.

In ungoverned systems:

- A speculative explanation becomes a root cause.
- A suggestion becomes policy.
- A summary becomes a legal or medical finding.

Promotion occurs implicitly, often retroactively, and without receipts.

GSC requires promotion to be explicit and typed. An output may be:

- exploratory (non-binding),
- proposed (pending validation),
- committed (state-changing),
- or refused (undefined).

Failure vignette. A model generates a plausible explanation for a production outage. Logged without constraint, it becomes the official root cause. Mitigations build upon it. The outage recurs. Under GSC, the explanation would have been refused promotion absent admissible evidence. The failure was not incorrect text, but ungoverned promotion.

---

5. Refusal as Compile-Time Success

Refusal is central to GSC. A refusal indicates that no admissible continuation exists under current constraints. It is a **successful compilation outcome**, preserving integrity by preventing illegitimate state change.

Two refusal modes must be distinguished:

1. **Transition refusal:** $\delta(\Sigma, t) = \bot$ under current constraints.
2. **Constraint refusal:** the admissibility rules themselves are in doubt and must be revised before continuation may proceed.

The latter signals the need for explicit constraint revision rather than further narration. This distinction mirrors governed epistemic systems in which remainder is separated from revision.

Refusal is costly but honest. Overconstraint can suppress discovery; poorly designed admissibility rules can encode bias. GSC therefore treats refusal as a disciplined trade: bounded correctness over speculative completeness.

---

6. Negative Certainty

GSC elevates **negative certainty**: knowledge of where continuation must stop.

Negative certainty does not assert truth; it bounds authority. It ensures that escalation, reuse, and persistence cannot proceed silently. It trades breadth for integrity and requires that learning occur through **explicit constraint revision**, not silent drift.

In high-stakes or chaotic environments, negative certainty is often the only stable epistemic signal available.

---

7. Canonical Example: Taming Thrash in Agentic Coding Loops

Ungoverned agentic coding systems commonly exhibit **thrash**: repeated speculative edits, regressions, and narrative explanations promoted prematurely as facts. Each loop compounds uncertainty, increasing churn rather than convergence.

In an ungoverned loop:

- The agent proposes a diff.
- The diff is applied.
- A speculative explanation is narrated as justification.
- Failure triggers another speculative diff, now conditioned on an unearned narrative.

Under GSC, the loop is restructured:

- Proposed diffs are **previews**, not commits.
- Tests, schemas, and policy checks implement (δ).
- Only validated diffs are promoted to state.
- Failed checks produce refusals, enabling clean backtracking without narrative contamination.

Observed effects include sharp reduction in retry loops, collapse of explanation thrash into typed receipts, and stabilization of long-running agentic workflows. The improvement arises not from better reasoning, but from **withdrawing illegitimate continuation**.

---

8. What GSC Is Not

Several boundaries are essential:

- GSC does not claim LLMs are deterministic.
- It does not require static typing or decidability.
- It does not assume access to model-internal state.

- It does not reduce LLM behavior to formal semantics.

What GSC shares with compilation is narrower:

- partial functions,
- admissibility constraints,
- undefined transitions,
- termination semantics.

Compilation here refers to **lawful continuation**, not executable code.

---

9. Governance, Power, and Audit

Semantic state (Σ) is observer-defined. This relocates power—it does not remove it. Under GSC, authority moves from interpretation to constraint definition.

No framework can eliminate power. GSC ensures only that power cannot operate silently. Governance becomes auditable, contestable, and revisable because it is explicit.

GSC does not guarantee just governance. It guarantees **visible governance**.

---

10. Failure Modes of GSC

GSC can fail:

- **Overconstraint:** chronic refusals on resolvable tasks.
- **Governance capture:** admissibility rules encoding institutional interests.
- **Strategic refusal:** "cannot answer" used as shield against accountability.
- **Boundary leakage:** ungoverned subsystems contaminating governed state.

These are not contradictions. They are reminders that **governance must itself be governed**. GSC does not promise good outcomes; it promises that bad ones cannot accumulate quietly.

---

11. Design Sketch: Preview -> Validate -> Commit

A minimal GSC workflow:

1. The model generates a **preview** artifact (non-binding).
2. External validators (tests, schemas, policy, or human gates) run.
3. If all pass, a **promotion receipt** is attached.
4. The artifact is **committed** into (Σ).
5. If checks fail or are incomplete, the transition is undefined -> **refusal**.

This pattern converts narrative output into governed state transitions and generalizes across domains.

---

12. Conclusion

Governed Semantic Compilation reframes LLM behavior not as a question of intelligence or trust, but of permission. Outputs do not fail because they are wrong; they fail because they are allowed to count when they should not.

GSC does not promise truth. It promises that falsehood cannot acquire authority without leaving a trace.

As language models increasingly participate in legal, civic, medical, and autonomous systems, the question of when output is allowed to count will become unavoidable. Governance is not an overlay; it is the condition under which language becomes lawfully actionable at all.

A system that cannot refuse honestly cannot compile truthfully.

Corpus-Wide Reference Positioning

This paper argues that large Language Models (LLMs) are commonly characterized as probabilistic next-token predictors operating over unstructured text. Its nearest external comparison fields are semantic, formal, token. The sources in [E1], [E2], [E3], [E4], [E5], [E6], [E7] are cited as predecessor literature, adjacent standards, or counterpressure - not as evidence that they caused the Ableman framework or that they validate its novel claims. The comparison isolates where established work already supplies provenance, formal assurance, institutional constraint, empirical method, or engineering practice, and where this paper adds a distinct claim about admissibility, authority, semantic custody, or governed realization.

Within the Ableman corpus, the highest-priority current cross-links are [A1], [A2], [A3], [A4], [A5], [A6], [A7]. These are links among separately custodied works, not silent identity mergers. Their role is to expose mutual dependencies, terminology collisions, and places where a reader should traverse the corpus before treating this paper as self-sufficient.

Reference-pass counterevidence and limit search

The pass applied the following pressure tests: Formal vocabularies and graph links make commitments explicit but cannot by themselves establish correct identity, shared interpretation, or lossless translation between contexts. Formal assurance remains relative to the encoded model, trusted base, and refinement chain; proof does not remove specification error or unmodeled environmental behavior. Statistical compression can improve efficiency while destroying distinctions needed for interpretation; semantic labels can conversely overstate stability that

usage does not support. These limits are not generic disclaimers: they identify the assumptions that a later empirical, formal, or implementation review must try to break.

Reference-pass influence and novelty boundary

No newly added external source is asserted to be a documented authorial influence unless the predecessor source already said so. `Predecessor` means earlier relevant work;

`adjacent` means a useful comparison; `standard` means an interoperability or assurance baseline; and `counterevidence` marks work that narrows or pressures a claim. Novelty therefore remains a reviewable, claim-level question rather than an inference from a low similarity score or an absent citation.

References

External scholarship, standards, and prior art

[**E1**] Richard Cyganiak, David Wood, and Markus Lanthaler, eds. *RDF 1.1 Concepts and Abstract Syntax*. W3C Recommendation, 25 February 2014. https://www.w3.org/TR/rdf11-concepts/ **Relationship:** Adjacent graph data model and identity baseline.

[**E2**] Alistair Miles and Sean Bechhofer, eds. *SKOS Simple Knowledge Organization System Reference*. W3C Recommendation, 18 August 2009. https://www.w3.org/TR/skos-reference **Relationship:** Adjacent standard for concepts, labels, schemes, notes, and semantic mappings.

[**E3**] W3C OWL Working Group. *OWL 2 Web Ontology Language Document Overview*, Second Edition. W3C Recommendation, 11 December 2012. https://www.w3.org/TR/owl2-overview/ **Relationship:** Adjacent formal ontology standard used to compare declared semantics and inference commitments.

[**E4**] Mark D. Wilkinson et al. "The FAIR Guiding Principles for Scientific Data Management and Stewardship." *Scientific Data* 3, 2016, 160018. DOI: 10.1038/sdata.2016.18. https://doi.org/10.1038/sdata.2016.18 **Relationship:** Predecessor stewardship principles for findability, accessibility, interoperability, and reuse.

[**E5**] Peter Gardenfors. *Conceptual Spaces: The Geometry of Thought*. MIT Press, 2000. mitpress.mit.edu source **Relationship:** Predecessor geometric treatment of concepts; cited as comparison, not as validation of the paper's manifold terminology.

[**E6**] George C. Necula. "Proof-Carrying Code." *POPL '97*, 1997, pp. 106-119. DOI: 10.1145/263699.263712. https://doi.org/10.1145/263699.263712 **Relationship:** Predecessor for binding machine-checkable evidence to executable artifacts; the present paper may demand broader semantic or constitutional obligations.

[**E7**] Xavier Leroy. "Formal Verification of a Realistic Compiler." *Communications of the ACM* 52(7), 2009, pp. 107-115. DOI: 10.1145/1538788.1538814. https://doi.org/10.1145/1538788.1538814 **Relationship:** Predecessor verified-compilation result used to distinguish proven translation preservation from broader governance claims.

Ableman corpus

[**A1**] Adam Ableman. *Meaning as Binding.* Ableman Corpus current edition; work identity
`AMCS-LOCAL-WORK-5F976917F0B283EA`;
source SHA-256
`A470D1A0B9ED7C3CEAB6BB88BE4B642A2BA36427447F787764329FD574DA0C97`.
Corpus relationship: priority cross-link selected by corpus profile and similarity review; no identity merger or publication effect.

[**A2**] Adam Ableman. *Governed Meaning Base (GMB).* Ableman Corpus current edition; work identity
`AMCS-LOCAL-WORK-D95CCC4FB7B58BFB`;
source SHA-256
`A3B62E50F8BEE125FDAE0D38C2839AFD1CCC138296268BF93217481E38AA48EA`.
Corpus relationship: priority cross-link selected by corpus profile and similarity review; no identity merger or publication effect.

[**A3**] Adam Ableman. *Semantic Manifold Topology.* Ableman Corpus current edition; work identity `PAPER.PUB.20257244`;
source SHA-256
`B8F28CC652A73A3EE4CF6FD0E23C1ABC922A6660319B2FB4CC1CCAAA606EC64A`.
Corpus relationship: priority cross-link selected by corpus profile and similarity review; no identity merger or publication effect.

[**A4**] Adam Ableman. *Global Term Key: Identity Primitives in Governed Knowledge Systems.* Ableman Corpus current edition; work identity
`AMCS-LOCAL-WORK-358AC09F5A13587E`;
source SHA-256
`AFB29CFCB4B58A78B79709AD453CEE9088CCB2AE40F30A70260F1B54F5160579`.
Corpus relationship: priority cross-link selected by corpus profile and similarity review; no identity merger or publication effect.

[**A5**] Adam Ableman. *Semantic Legitimacy Before Context.* Ableman Corpus current edition; work identity
`AMCS-LOCAL-WORK-091E34BA93992CE4`;
source SHA-256
`DEB7626CE1AB54F4B541347DCC3C4E14DC4F682230ACCCE1A93D1D536A50C44C`.
Corpus relationship: priority cross-link selected by corpus profile and similarity review; no identity merger or publication effect.

[**A6**] Adam Ableman. *MCIR: A Canonical Intermediate Representation for*

Governed Transformation. Ableman Corpus current edition; work identity `PAPER.PUB.21095303`;
source SHA-256
`EA129ECBA95F7B07CAA7B33A54F91F52913C94A14DA227EB9A06CFD083E4E5BF`.
Corpus relationship: priority cross-link selected by corpus profile and similarity review; no identity merger or publication effect.

[**A7**] Adam Ableman. *Hybrid Semantic Compiler Architectures.* Ableman Corpus current edition; work identity `PAPER.PUB.21228038`;
source SHA-256
`EBCD6DDDA9B547639AEBED79FB68069473CF1248E41C527B48C9624BBE2C0496`.
Corpus relationship: priority cross-link selected by corpus profile and similarity review; no identity merger or publication effect.

Corpus source and companion formats: https://github.com/AblemanMosaic/ableman-corpus
License: CC-BY-ND-4.0

DOI: 10.5281/zenodo.18453681