Governed Meaning Base (GMB)

From Constitutional Crystallization to a Governed Semantic Substrate

A meaning base becomes authoritative only through bounded admission, evidence, and revisable standing.

Author
Adam Ableman
Constitutional Computing
Contact: ableman.research@gmail.com

Abstract

This paper specifies the Governed Meaning Base (GMB), a candidate governed substrate for storing, querying, relating, and revising semantic artifacts without collapsing exact source custody, logical work identity, concept identity, evidence, authority, and standing. GMB is proposed as the entry-oriented peer of document-oriented constitutional codices: codices preserve coherent specifications, while a meaning base supports incremental semantic operations over typed entries.

The substrate separates exact state, admissibility, and meaning. Each admitted entry binds a semantic payload to type, scope, posture, provenance, dependencies, evidence, lineage, and standing. Proposed mutations pass through a typed decision surface that may allow, refuse, or defer. Receipt existence does not prove truth or correct effect; it records a bounded decision, observation, verification, promotion, or revision. Queries that support consequential downstream action are bound to the exact corpus state and projection policy used.

GMB is also positioned within the wider research architecture. Hyperpedia is a curated human- and agent-facing projection from a meaning base; crystalline context capsules are bounded agent projections; and the Crystal Network is a distribution and federation layer through which separately governed meaning bases may exchange signed, scoped claims without surrendering local admission. These are profiles and consumers of a common semantic substrate, not automatic identity mergers.

The paper proposes, rather than grants, the relation between GMB, the earlier Constitutional Crystallization Framework (CCF), the Ableman Format Specification (AFS), Constitutional Encyclopedia and Dictionary profiles, MCIR, governed semantic compilation, receipts, and cryptographic phase. It defines the core objects, invariants, realization funnel, failure modes, and evidence obligations needed to evaluate the proposal. Canonical, author, publication, identity, and implementation standing remain separate decisions.

1. The Two Instantiations of AFS

1.1 Document-Type and Database-Type

AFS specifies *what* governance discipline applies to constitutional artifacts. It does not specify *how* those artifacts are stored, accessed, or composed. Two architecturally distinct instantiations have emerged in practice, each addressing a different operational mode:

Constitutional Codex (CX) – the document-type instantiation. A CX artifact is a textual specification organized into the AFS layer structure (CX-S, CX-CM, CX-IC, CX-IR, optionally CX-A and CX-RM). Codices are authored, versioned, and read as documents; they are the primary medium for specifying systems, applications, or domains. The Constitutional Codex working paper is the current corpus reference candidate for the document type; publication and canonical standing are separate.

Governed Meaning Base (GMB) – the database-type instantiation. A GMB artifact is a corpus of typed semantic entries stored in a queryable substrate, with governance enforced at every mutation boundary. GMBs are the medium for ongoing semantic content–knowledge bases, lexical dictionaries, evidence corpora–where the unit of operation is the entry rather than the document.

The two instantiations are peers, not levels of a hierarchy. A working AFS deployment typically uses both: Codices specify the systems; GMBs hold the operational semantic content the systems reason over. The same AFS governance discipline applies to both, instantiated in different operational forms.

1.2 Why Both Are Needed

Some semantic content has document character: it is authored as a coherent whole, versioned as a unit, read end-to-end. A specification of the Universal Governance Kernel is a Codex because it is composed once, refined as a whole, and consumed by readers (human or agentic) as a unified artifact. The unit of governance is the document.

Other semantic content has database character: it accretes incrementally, is queried by partial match or by structural relationship, evolves entry by entry rather than document by document. A knowledge corpus describing thousands of concepts, or a lexicon of disambiguated semantic primitives across a domain, is a GMB because the unit of governance is the entry and the operations are insert, update, refuse, query–not author and version.

Forcing all semantic content into one instantiation produces friction. A 10,000-entry dictionary expressed as a Codex is unreadable as a document. A small system specification expressed as a database loses the document-level coherence that gives Codices their force. The two instantiations exist because semantic

content has two operational modes, and AFS supports both under shared governance.

1.3 Shared Governance Across Instantiations

Both instantiations inherit the same AFS invariants:

- **Receipted transitions.** Every mutation produces a receipt. In CX, receipts are layer-amendment records; in GMB, receipts are entry-mutation records.
- **Authority declaration.** Every mutation declares its authority source. In CX, this is the Governor authorization for an S-amendment or IC selection; in GMB, this is the agent or process authorized to insert, update, or refuse an entry.
- **Refusal as first-class outcome.** Both instantiations treat refusal as a successful governance outcome, not an error. A CX phase may refuse to advance; a GMB mutation may refuse to admit a new entry.
- **Content-addressed identity.** Both rely on canonical hashing of normalized content for stable identity that survives reformatting, rewording, or storage migration.
- **Lineage preservation.** Both maintain a chain of prior states that allows reconstruction of how the current state was reached.

The shared governance is not coincidental. GMB and CX are alternative operational realizations of the same constitutional discipline; the instantiation choice is a question of operational mode, not a question of how strict the governance is.

---

2. Lineage: From CCF to GMB

The framework concept that governs GMB has prior history under a different name. Earlier work introduced the *Constitutional Crystallization Framework (CCF)* as a structured method for transforming high-entropy conceptual material–prose, narrative, exploratory discourse–into stabilized semantic artifacts admissible under explicit governance. The framework defined a three-stage gradient (Pre-Crystallization Material -> Crystallization Program -> Crystallization Kernel), a posture taxonomy for claim typing, a dependency-mapping discipline, and admissibility-gated promotion criteria.

As the work matured, two architectural distinctions clarified the framework's scope:

The framework concept is not its operational substrate. CCF described both the *idea* of crystallization (meaning must cool before it lawfully binds) and the *substrate* on which crystallization occurs (a governed database with content-addressed identity, lineage chains, and admissibility gating). These are different things. The idea is properly a position about how meaning acquires authority. The substrate is properly a database architecture.

The substrate is one of two AFS instantiations, not a standalone framework. The crystallization substrate fits naturally as the database-type instantiation of AFS, peer to the Codex document-type instantiation. Treating it as a standalone framework obscured this peering and made cross-references between Codex methodology and crystallization methodology harder to express coherently.

The author-confirmed name lineage is **Constitutional Crystallization Framework (CCF) -> Constitutional/Crystallized Meaning Base (CMB) -> Governed Meaning Base (GMB)**. GMB is the current name. CCF and CMB remain historical aliases for exact titles, citations, source custody, and explanations whose developmental phase matters. The conceptual content of CCF is preserved and distributed:

- The *crystallization concept* (phase transition by which meaning acquires binding authority) belongs to the Constitutional Semantic Crystallization paper [Ableman, forthcoming, consolidated].
- The *cross-domain pattern* (how systems in many fields develop intermediate stabilization layers) belongs to the same consolidated crystallization paper, drawing on prior Crystallization Gradient material.
- The *operational substrate* (governed database with lineage, admissibility, refusal semantics, query operations) is what this paper defines as GMB.
- The *authoring methodology* (extraction spine, posture tagging, promotion gates) is absorbed into AFS authoring practice as CX:AES methodology, applied during Codex construction and during GMB entry admission alike.

Earlier published work that referenced CCF stands as historical record. Current work uses GMB; CCF and GMB remain available for exact historical citation and phase-specific explanation. Where ambiguity might arise–particularly in synthesis papers like Constitutional Binding Theory that enumerate AFS substrates–both terms appear in transitional periods, with CCF marked as the predecessor name.

This lineage clarification matters for cross-referencing. A reader landing on a 2026-published paper that says "constitutional substrates such as CCF" should be able to find GMB and recognize the connection. This paper is a candidate bridge whose lineage claim remains subject to author adjudication.

---

3. The GMB Substrate

3.1 Substrate Overview

A GMB is a governed corpus database. The unit of content is an **entry**: a typed, content-addressed, authority-bound, lineage-tracked semantic artifact. A GMB exposes a small governed operation set: insert, query, refuse, amend, withdraw. Each operation is an admissibility event, not a database transaction. Each event produces a receipt.

The substrate has five architectural components:

1. **Entry store.** Holds the corpus content. Each entry is keyed by a content hash of its canonical form and carries typed metadata fields (authority, posture, scope, classification, lineage pointers, refusal markers).
2. **Admissibility gate.** Mediates all mutations to the entry store. Insert and amend operations submit a proposed entry; the gate evaluates the proposal against the corpus's declared invariants and either admits, refuses, or escalates.
3. **Lineage chain.** Records the sequence of admitted mutations. Each entry references its prior state (if amended) or its admission receipt (if newly inserted). The chain supports replay: the corpus state at any prior epoch can be reconstructed.
4. **Receipt log.** Records every governance event–admissions, refusals, queries with binding consequence, scope changes. Distinct from the lineage chain in that it records *all* events, not only state-mutating ones.
5. **Query interface.** Supports retrieval over the corpus by entry identity, by structural relationship, by typed metadata field, or by content match. Queries are read operations and do not produce lineage events; high-binding queries (queries whose results will be promoted to claims) may produce receipts depending on the query type.

3.2 Entry Structure

A GMB entry is a structured object. The minimum fields are:

- **Identity** – content hash of the canonical form, providing stable address that survives reformatting.
- **Type** – the entry's class (CE entry, CD entry, custom domain type).
- **Authority** – declaration of the agent, process, or constitutional rule under which this entry was admitted.
- **Posture** – the entry's epistemic posture (OBSERVED, ASSUMED, DERIVED, DECIDED, REQUIRED, FORBIDDEN, REFUSED, DEFERRED), inherited from earlier crystallization vocabulary and expanded as needed.
- **Scope** – the domain or context in which this entry's claims hold.
- **Lineage** – pointer to prior state if this is an amendment; null if this is an admission.
- **Dependencies** – explicit references to other entries this entry depends on, refines, contradicts, or presupposes.
- **Admission receipt** – pointer to the receipt log entry that records this entry's admission event.
- **Refusal markers** – fields recording any refusal events that pertain to this entry (e.g., "this entry was proposed in form X and refused; it was admitted in form Y after revision").

Domain-specific entry types extend this structure with type-specific fields. CE entries carry knowledge-domain content with S/C/I substructure; CD entries carry GTK bindings with their three-part structure (binding identity, alias set, competing binding set).

3.2 Formal Entry and State Model

Let an exact source artifact be a with byte commitment $H_s(a)$. A semantic entry is not a itself but a governed assertion

$$e = (k, \tau, p, s, \pi, d, v, \ell, \epsilon, \sigma),$$

where k is entry identifier, τ is entry type, p is semantic payload, s is scope, π is epistemic posture, d is dependency set, v is valid-time interval, ℓ is lineage, ϵ is evidence and provenance, and σ is current standing. Exact source regions remain linked through custody records rather than being replaced by the normalized payload.

The corpus at epoch n is a state K_n. A proposed operation o is evaluated by

$$D(o, K_n, J_n, A_n) \in \{\text{ALLOW}, \text{REFUSE}, \text{DEFER}\},$$

under jurisdiction J_n and authority state A_n. Only an allowed operation whose declared effect is observed and verified may support a successor state K_{n+1}. Decision, effect, verification, promotion, and revision receipts remain distinct.

Three independent commitments prevent common collapse:

- H_s commits exact or canonicalized state;
- H_c commits admissibility under the governing configuration; and
- H_m commits the semantic regime under which the entry is interpreted.

An optional H_j localizes jurisdiction. Equal H_s does not imply equal standing; equal H_m does not imply equal bytes; a valid H_c does not prove the entry true.

3.3 Entry Identity Is Not Content Equality

The original draft used one content hash as entry identity and suggested that semantically equivalent rewordings would collide. That conflates two different operations. A cryptographic content hash changes when bytes or canonical serialization change. A semantic hash may place different surfaces into a declared equivalence class, but only under an explicit semantic lens whose version, jurisdiction, and collision policy are governed.

GMB therefore preserves at least:

1. exact artifact identity;
2. canonical serialization identity;

3. semantic-equivalence claim;
4. logical entry identity through revision; and
5. standing of each identity relation.

A duplicate canonical payload is not a cryptographic collision. A true digest collision, a duplicate submission, a proposed revision, and a claimed semantic equivalent require different decision paths and different receipts.

3.4 The Admissibility Gate

The admissibility gate is the substrate's enforcement mechanism. When a mutation is proposed, the gate evaluates:

1. **Identity check.** Does the proposal duplicate an existing exact or canonical payload, claim semantic equivalence, revise a logical entry, or present a true digest collision? These cases are classified separately. Duplicate payload does not imply supersession, and a claimed semantic equivalent requires the declared semantic lens and evidence.
2. **Authority check.** Does the proposing agent have authority to admit an entry of this type into this scope? Authority declarations are checked against the corpus's authority registry.
3. **Posture check.** Is the entry's declared posture admissible at this corpus state? A REQUIRED claim against a corpus that already contains a contradicting REQUIRED claim, for example, may be refused.
4. **Dependency check.** Are this entry's declared dependencies present and admitted? An entry depending on entries not yet in the corpus is held pending or refused.
5. **Invariant check.** Does admitting this entry violate any of the corpus's structural invariants? Examples: "every CD entry must have exactly one binding identity"; "no CE entry may declare REQUIRED status without an explicit constitutional root reference."

If all required checks pass, the proposal may receive an allow decision. State advances only after the declared mutation effect is observed, verified, and promoted under the configured protocol. A failed prohibition yields refusal; missing authority or evidence may yield defer. A fault or an observed effect without conforming evidence requires reconciliation rather than being relabeled as a clean non-event.

Refusal is not an error. It is a successful governance outcome. The substrate distinguishes refusal from system fault; a refusal receipt is admissible evidence that the substrate is functioning, while a system fault is a defect.

3.5 Query as Governed Operation

Most database operations conceptualize queries as side-effect-free reads. GMB does not. Some queries–particularly queries whose results will be promoted to claims, used as evidence in admissibility decisions elsewhere, or fed to agentic executors that may bind on the results–have governance consequence. These are **binding queries**.

A binding query produces a receipt. The receipt records the query, the corpus state at query time, and the result. This allows downstream binding decisions to reference the specific corpus state they depended on, rather than the corpus state at some unspecified later time. It also allows replay: a binding query can be re-executed against a historical corpus state to reproduce the result.

Non-binding queries–exploratory searches, browse-mode interactions, ad-hoc inspections–do not produce receipts. The query profile may declare whether a result is binding, but self-declaration is not sufficient at a consequential effect boundary. Capabilities that can publish, execute, promote, or otherwise bind must require an eligible state-bound query receipt or explicitly refuse/defer. Exploratory reads remain unreceipted only while their outputs retain exploratory standing.

---

4. Hosted Content Types

GMB hosts multiple content types in current AFS practice. The two primary hosted types are introduced here; others (custom domain GMBs for specialized corpora) follow the same substrate pattern.

4.1 Constitutional Encyclopedia (CE)

A CE is a GMB-hosted knowledge corpus where each entry describes a concept, phenomenon, system, or domain area. CE entries inherit the GMB substrate's governance and add S/C/I structure to the content body:

- **Specification fragment** – what the entry asserts about its subject's invariants.
- **Configuration fragment** – admissible variation, parameters, contextual modifiers.
- **Implementation fragment** – observed instances, examples, manifestations under specific contexts.

The S/C/I substructure mirrors the AFS layer discipline. A CE entry is, in miniature, a typed semantic artifact with the same layer separation that governs Codices and GMB substrate operations.

CE entries are linked: an entry on "constitutional governance" may link to entries on its constituent concepts (admissibility, refusal, authority, lineage), to entries on

related but distinct concepts (corporate governance, computational governance), and to entries on its applications (specific governance kernel implementations). The link types are typed–depends_on, refines, contradicts, presupposes–and admit graph queries that traverse the conceptual structure.

4.2 Constitutional Dictionary (CD)

A CD is a GMB-hosted lexicon where each entry is a Global Term Key: a disambiguated semantic binding [Ableman, *Global Term Key*, forthcoming] composed of three parts:

- **Binding identity** – which word/concept binding is active in this entry
- **Alias set** – what other words can call this concept
- **Competing binding set** – what other concepts this word can call (polysemy)

CD entries inherit the same S/C/I structure as CE entries. The Specification fragment of a CD entry declares what the binding *must* mean (its invariant lexical structure); the Configuration fragment declares admissible variation in usage; the Implementation fragment provides observed usages.

CDs solve a problem that conventional dictionaries do not address: lexical disambiguation as constitutional anchoring rather than mere classification. The same word in a CD may have multiple entries (one per active binding), explicitly typed, with explicit competing-binding pointers. A reader or agent navigating a CD always has a typed binding to anchor against.

4.3 Custom Domain GMBs

A GMB is not restricted to CE+CD content. Domain-specific corpora–evidence stores, governance precedent libraries, structured observation corpora–follow the same substrate pattern with domain-specific entry types. The substrate guarantees the governance properties; the entry type defines the content shape.

Examples of legitimate custom GMBs in current AFS practice include CONDEX corpora (Constitutional Context Index, indexing evidence from PCM materials), domain-specific governance precedent GMBs, and domain GMBs hosting the operational invariants of specific systems (the GK Domain GMB, for example, holding the 41 invariants of governance kernel systems).

---

5. Governance Properties

GMB inherits five governance properties from the AFS discipline, instantiated in database-substrate form.

5.1 Lineage Preservation

Every state of the corpus is reconstructible from the lineage chain. An entry that has been amended five times has five prior states accessible via lineage pointers; an entry that has been withdrawn carries a withdrawal receipt that names the moment of withdrawal and the authority. The corpus is not a snapshot; it is a chain of admitted mutations whose current state is the result of replaying the chain.

This matters because conventional databases lose the path by which their current state was reached. A row in a relational database has an audit log if the deployment was careful; GMB has lineage as a substrate property, not as an optional add-on.

5.2 Admissibility Gating

No mutation enters the corpus without passing the admissibility gate. There is no "raw write" path. This is operationally significant: it means corpus invariants are guarantees, not aspirations. A GMB whose corpus declares invariant I will not contain entries violating I, because the gate refused them.

This contrasts with conventional database constraint systems, which enforce some invariants (foreign keys, type checks, uniqueness constraints) but not others (semantic invariants requiring declarative reasoning). GMB's invariant check stage is general: any computable predicate over the proposed entry plus the current corpus state can be a corpus invariant.

5.3 Refusal Semantics

A refused mutation produces a refusal receipt. Refusal is a positive outcome of the substrate. Refusal receipts accumulate; they are part of the corpus's history; they support analysis ("what kinds of mutations have been refused, by what authority, in what scope?").

A GMB without refusal capability is not a GMB. Conventional databases that simply reject invalid writes silently–or surface a generic error to the application–lose the receipted refusal artifact and lose the ability to reason about refusal patterns.

5.4 Layered State and Semantic Identity

GMB uses layered commitments rather than one overloaded hash. Exact bytes and canonical serialization support deterministic reconstruction and deduplication. Semantic hashing expresses equivalence only relative to a declared lens and version. Logical entry identity supplies continuity through revision. Publication and work identity remain outside the entry hash.

This permits storage deduplication without semantic overclaim. Repeated exact payloads may share storage while retaining distinct submission or authority

events. Reworded entries may be proposed as semantically equivalent, but the claim is evaluated, scoped, and revisable rather than made true by normalization. A true digest collision is treated as a cryptographic incident, not as an ordinary duplicate.

The relationship to *Semantic Hashing* and *The Three Hash Rule* is direct: meaning equivalence is declared and governed, while state, admissibility, and meaning remain independent commitments.

5.5 Receipt Production Across All Operations

Every operation that has governance consequence produces a receipt. Admissions produce admission receipts; refusals produce refusal receipts; binding queries produce query receipts; amendments produce amendment receipts; withdrawals produce withdrawal receipts. The receipt log is the substrate's behavioral record.

This connects GMB directly to *Receipt-Bound Capabilities* [Ableman 2026]: the capability to mutate the corpus is bound to the obligation to produce a receipt. The specified interface provides no lawful path for a governed operation to acquire standing without the required receipt. A physical effect may nevertheless occur during a substrate fault or partition. Such an orphaned effect is not promoted, but it is not assumed away; it must be detected, recorded, reconciled, and either remediated or incorporated through a separately authorized recovery path.

---

6. Relation to Prior and Adjacent Work

6.1 The Governed Knowledge Loop and Knowledge Reactor

Earlier work introduced the *Governed Knowledge Loop (GKL)* as the lifecycle through which epistemic artifacts evolve, and the *Constitutional Knowledge Reactor (CKR)* as an operational architecture implementing the GKL. GMB is a generalization and consolidation of this prior work:

The GKL is preserved as the *lifecycle* over which GMB entries evolve–observation, crystallization, structural integration, contradiction detection, admissibility evaluation, lawful termination or continuation. Each phase of the GKL corresponds to operations GMB supports.

The CKR is preserved as a *specific class* of GMB instantiation–a GMB optimized for knowledge corpus mutation and structural discovery. Where CKR was framed as an architecture for knowledge systems specifically, GMB is the substrate beneath, applicable to any governed corpus (knowledge, lexical, evidentiary, precedent, custom).

The shift in framing reflects architectural maturation: knowledge reactors are one application of the substrate; the substrate itself is the canonical reference.

6.2 Distinguishing GMB from Conventional Databases

Conventional databases (relational, document, graph, time-series, vector) optimize for storage and retrieval efficiency over typed content. They support consistency models, transaction semantics, and query languages. They do not natively support governance, authority declarations, refusal semantics as first-class outcomes, lineage chains, or content-addressed identity.

Some of these properties can be layered on top of conventional databases through application-level discipline. The GMB position is that they should be substrate-level, not layer-level. A database in which lineage is enforced by application code is one defective deployment away from losing lineage; a database in which lineage is substrate-level cannot lose it without substrate failure.

6.3 Distinguishing GMB from Knowledge Graphs

Knowledge graphs (RDF stores, graph databases, semantic web infrastructure) provide typed entities and relationships with formal semantics. They are closer to GMB in conception than relational databases are. The principal distinctions:

- Knowledge graphs typically lack governance: any agent with write access can assert any triple. GMB enforces admissibility.
- Knowledge graphs typically lack lineage: the current state is what is queryable, with version history as an optional add-on. GMB preserves lineage as substrate.
- Knowledge graphs typically lack refusal semantics: a triple is asserted or it is not. GMB's refusal receipts make the *non-admission* of content visible and analyzable.
- Knowledge graphs use schema-defined types with implicit identity. GMB uses content-addressed identity with explicit, declarative type fields.

The distinction is not knowledge-graph-versus-GMB as competitors; GMB *could be implemented* on a graph-database substrate. The distinction is between knowledge-graph-as-typically-deployed and the governance properties GMB requires regardless of underlying storage technology.

6.4 Relation to MCIR

MCIR (Meta-Compilation Intermediate Representation) is the canonical machine-legible representation of crystallized meaning. MCIR is the *form*; GMB is the *substrate*. A GMB stores entries whose canonical form is MCIR-compatible, but GMB is not itself MCIR. The relationship is analogous to filesystem and file format: a filesystem stores files whose internal format is independent of the filesystem.

In current AFS practice, GMB entries' canonical forms compile to MCIR for machine consumption. Entries authored in higher-level forms (GCNL, structured prose) are admitted to GMB after crystallization to canonical form; the crystallization happens at the gate.

6.5 Relation to Receipt-Bound Capabilities

RBC defines capability tokens whose use is inseparable from receipt production. Every governed GMB operation is, in effect, an RBC invocation: the capability to admit, amend, refuse, or query is bound to the obligation to produce the corresponding receipt. GMB is one of the principal substrates on which RBC operates at scale.

6.6 Relation to Cryptographic Phase

Cryptographic Phase [Ableman 2026] introduces declared semantic epochs as cryptographically enforced coordinates. GMB integrates phase as a substrate property: every entry is admitted within a declared phase; entries from different phases are not silently equivalent even if their canonical forms collide. This prevents semantic replay across governance transitions–a GMB whose admissibility rules changed between phase 1 and phase 2 will not silently treat phase-1 entries as still admissible under phase-2 rules.

6.7 Hyperpedia, Agent Memory, and the Crystal Network

GMB becomes more intelligible when separated from three consumers and deployment profiles:

Hyperpedia is the curated knowledge and meaning interface. It projects selected entries, source regions, definitions, relations, disputes, confidence, and citations into a pedagogical, Wikipedia-like surface. Hyperpedia does not become authoritative by presentation; every claim should resolve to GMB entry state and exact source custody.

Crystalline agent memory is a bounded context profile. A compiler selects task-relevant entries, dependencies, unresolved conflicts, authority limits, and receipts into a context capsule. The capsule is a projection with a declared omission boundary and expiry/revision relation; it is not the whole meaning base and does not grant the agent authority over it.

The Crystal Network or Distributed Knowledge Network is a federation profile. Nodes exchange content commitments, semantic claims, evidence, receipts, and revision notices. Each receiving node retains local jurisdiction and re-evaluates admission; network carriage does not force semantic or authority equivalence.

These relations can be summarized as:

$$\text{GMB state} \xrightarrow{\text{curated projection}} \text{Hyperpedia},$$

$$\text{GMB state} \xrightarrow{\text{bounded compilation}} \text{agent capsule},$$

$$\text{GMB state} \leftrightarrow_{\text{federated claims}} \text{Crystal Network nodes.}$$

The equations express projection relations, not identity. One GMB can support several interfaces and capsules; one network can federate several independently governed meaning bases.

---

7. Implementation Considerations

GMB is a candidate substrate specification, not an implementation. The corpus contains implementation candidates and related governed stores, but this paper does not establish that any deployment satisfies the complete specification. Each implementation claim requires an exact artifact, configuration, test boundary, and verification record.

7.1 Storage Layer

The storage layer holds entry content, metadata, lineage pointers, and receipts. Working implementations have used SQLite for single-node deployments (the UGK Lite reference implementation), with expectation of distributed substrates (key-value stores, graph databases, or content-addressed storage networks) for larger deployments. The substrate-level discipline is independent of the storage technology; correctness is a property of the gate and the lineage chain, not of the underlying store.

7.2 Gate Implementation

The admissibility gate is a software component executing the check sequence (identity, authority, posture, dependency, invariant). Implementations are typically expressed as a series of admissibility predicates evaluated against the proposed entry plus current corpus state. The predicates are specified in the GMB's S layer (the corpus's invariants are part of its specification), with implementation in a host language.

7.3 Receipt Log

The receipt log is append-only and tamper-evident. Working implementations have used hash-chained receipt records, with cryptographic signatures over the chain head producing tamper-detection guarantees. The receipt log is queryable for audit and replay purposes; it is not generally exposed as a primary GMB query interface.

7.4 Query Interface

The query interface supports retrieval by identity, by structural relationship, by metadata field, and by content match. Implementations typically expose this

through a query DSL or programmatic interface. Queries marked as binding additionally produce query receipts logged to the receipt store.

7.5 Scale Considerations

The current corpus contains stores at thousands-to-tens-of-thousands scale and large receipt collections, but the exact mapping from those artifacts to this GMB specification remains to be verified. Correctness obligations are not scale-independent in practice: indexing, concurrency, partial failure, compaction, retention, and verification cost can expose new failure modes. Performance and conformance therefore remain deployment-specific evidence requirements.

7.6 Realization Funnel

- **Stage:** Possibility
  GMB work: A corpus could preserve meaning, evidence, authority, refusal, and revision together.
  Standing in this paper: Motivating possibility.
- **Stage:** Specification
  GMB work: Define entries, commitments, decisions, receipts, lineage, query projections, and standing.
  Standing in this paper: Candidate specification.
- **Stage:** CM1
  GMB work: Enumerate SQL, document, graph, content-addressed, local, distributed, strict, permissive, and hybrid realizations, including unsafe ones.
  Standing in this paper: Partially enumerated.
- **Stage:** CM2
  GMB work: Prefer inspectable, source-bound, reversible, non-bypassable, privacy-preserving, and exit-supporting configurations.
  Standing in this paper: Preference criteria proposed.
- **Stage:** Instance Configuration
  GMB work: Select schema, hashes, semantic lenses, authorities, storage engine, receipt protocol, concurrency rules, retention, threat model, and limits.
  Standing in this paper: Not fixed here.
- **Stage:** Implementation Realization
  GMB work: Build one configured meaning base and its Hyperpedia, capsule, or federation projections.
  Standing in this paper: Candidate artifacts exist; conformance not granted here.
- **Stage:** Evidence
  GMB work: Verify replay, negative cases, orphaned effects, query binding,

scaling, recovery, and cross-node behavior.
Standing in this paper: Required; incomplete.

- **Stage:** Revision
  GMB work: Amend entries, specifications, lenses, and confidence while preserving predecessor state and dependent claims.
  Standing in this paper: Required protocol direction.

This placement prevents a conceptual architecture, a database schema, and a deployed governed meaning base from being treated as the same achievement.

7.7 Principal Failure Modes

The specification must expose or refuse at least: semantic-equivalence overclaim; authority laundering through stored documents; forged or stale receipts; out-of-band writes; incomplete replay; hidden query-state drift; dependency cycles; premature promotion of AI synthesis; privacy leakage through projections; unbounded context compilation; federation without local re-admission; orphaned effects; phase replay; and deletion of source custody after semantic extraction.

Governed Semantic State Substrate

Across the completed P1 corpus, the current **Governed Meaning Base (GMB)** is the **governed semantic state substrate for admitted sources, concepts, relations, claims, evidence, disputes, standing, and revisions**. The exact historical artifact title remains Constitutional/Crystallized Meaning Base (CMB), but current synthesis follows the author-confirmed `CCF -> CMB -> GMB` lineage. GMB is not the whole corpus, the universal GSM, Hyperpedia, a semantic atlas, or an automatic authority over hosted content.

- **Adjacent work:** *The Ableman Format Specification (AFS)*
  Supplies: Format families, profiles, schemas, and scoped conformance contracts.
  GMB boundary: GMB may instantiate an AFS corpus profile; storing a record does not prove profile conformance.

- **Adjacent work:** *Global Term Key: Constitutional Lexical Identity Through Disambiguated Semantic Binding*
  Supplies: Registered names, senses, and disambiguated lexical identity.
  GMB boundary: GTK supports entry resolution; GMB remains the governed state and lifecycle substrate.

- **Adjacent work:** *Governed Semantic Cartography*
  Supplies: Coordinates, projections, traversal, and atlas coherence.
  GMB boundary: GSC renders and navigates views over GMB state; a view is not the base itself.

- **Adjacent work:** *Meaning Crystals*
  Supplies: Portable packages of bounded semantic state.
  GMB boundary: Crystals export or transport slices; they do not replace admission, standing, or revision in the base.
- **Adjacent work:** *Reasoning by Way of Receipts*
  Supplies: Records of reasoning, decisions, alternatives, and revision.
  GMB boundary: Receipts support transition history; they do not make hosted claims true.

A governed entry should expose:

$$E = (identity, type, content, source, provenance, relations, evidence, standing, authority, disputes, nonclaims, revision, visibility)$$

Entry identity, content equality, semantic equivalence, current standing, and publication identity remain separate. Admission means that an exact entry version entered a declared governed state under a stated profile. It does not mean author endorsement, truth, completeness, novelty, or executable authority.

Queries are governed projections. A query result must bind the base snapshot, profile, identity resolver, access policy, projection, evidence and standing cuts, omissions, and timestamp. Absence from one result may mean nonexistence, exclusion, insufficient standing, access restriction, unresolved identity, projection loss, or query failure; those cases cannot be collapsed.

The universal GSM can type `HOSTED_IN_GMB`, `ADMITTED_UNDER_PROFILE`, `HAS_ENTRY_IDENTITY`, `RESOLVED_BY_GTK`, `SUPPORTED_BY_EVIDENCE`, `HAS_STANDING`, `DISPUTED_BY`, `VISIBLE_UNDER`, `PROJECTED_AS_VIEW`, `EXPORTED_AS_CRYSTAL`, `REVISED_FROM_ENTRY`, and `REFUSED_BY_GATE`. GMB stores typed state; it does not become identical to the model that types it.

This integration establishes four editorial commitments: adopt governed semantic state substrate as GMB's official corpus role; adopt the governed-entry schema; treat every query as a bound governed projection; and preserve entry identity/content/equivalence/standing/publication separation across all interfaces.

Structurally, Temporally, and Operationally Bound Semantic State

The fixed-seed comparison with the MCIR DAG theorem, Semantic Field Analysis, Quant Insights for ACG, and Operational ESA distinguishes stored governed state from the projections and decisions made from it:

$$G = (snapshot, entries, reference_profile, temporal_cut, \\ identity_regime, standing_cut, access_policy, \\ projection, consumer, purpose, omissions, expiry, \\ revision)$$

An entry set may satisfy a version-ranked referential closure profile without being semantically complete, true, current, or independently warranted. SFA diagnostics run over an exact projection and remain candidates. Quant evaluation binds availability, admission, decision, effect, and correction times so later knowledge cannot leak into historical claims.

Operational ESA consumes a purpose-bounded orientation projection containing goals, custody, authority, artifacts, observations, conflicts, unknowns, dependencies, failures, actions, and stop conditions. The capsule is not the GMB and must carry freshness, omissions, access constraints, source bindings, and expiry. A receiving agent still accepts or refuses custody separately.

No consumer can promote its view back into governed state without a new admission transition. The universal GSM can type `SNAPSHOTS_GMB_STATE`, `CLOSED_UNDER_REFERENCE_PROFILE`, `ANALYZED_BY_SFA_RUN`, `VALID_AT_TEMPORAL_CUT`, `PROJECTED_AS_OPERATIONAL_ORIENTATION`, `EXPIRES_FOR_CONSUMER`, and `REQUIRES_READMISSION_FOR_MUTATION`.

This randomized review establishes four editorial commitments: adopt the bound-state projection object; retain structural closure as one profile; add temporal admissibility to queries; and treat Operational ESA capsules as expiring consumer projections requiring separate mutation admission.

Durable Semantic State, Not the Corpus or Its Projections

Twenty retained downstream uses materially depend on GMB as a durable governed semantic-state substrate; eighty-nine additional lexical leads merely repeat the current-name ruling, historical CMB label, or generic meaning-base adjacency. The exact source title remains Constitutional/Crystallized Meaning Base (CMB), while the author-confirmed current name is Governed Meaning Base (GMB). This lineage correction does not make GMB identical to the whole corpus, universal GSM, Hyperpedia, semantic atlas, knowledge loop, context capsule, or federation.

$$G^* = (base_id, snapshot, entry_id, entry_type, content, \\ source, authorship, provenance, relations, evidence, \\ counterevidence, standing, authority, disputes, \\ nonclaims, visibility, retention, dependents, revision, \\ successor)$$

Entry identity, byte equality, content equality, semantic equivalence, current standing, author adoption, publication identity, and executable authority remain separate. Admission says only that an exact entry entered a declared governed state under a named profile and authority. Every write, retraction, split, merge, standing change, or deletion requires subject, predecessor, decision, dependents, effect, evidence, and receipt.

Queries, atlases, Hyperpedia pages, agent capsules, skill artifacts, and network exchanges are purpose-bounded projections. Each binds the base snapshot, identity resolver, access and standing cuts, profile, omissions, ordering, consumer, purpose, timestamp, expiry, and remainder. Absence may mean nonexistence, exclusion, access restriction, standing failure, identity conflict, projection loss, or query failure.

The universal GSM can type `HOSTED_IN_GMB`, `ADMITTED_UNDER_GMB_PROFILE`, `HAS_GMB_ENTRY_IDENTITY`, `DISTINGUISHES_AUTHORSHIP`, `DISPUTED_IN_GMB`, `CHANGES_GMB_STANDING`, `PROJECTS_FROM_GMB_SNAPSHOT`, `EXPIRES_GMB_PROJECTION`, `REQUIRES_READMISSION_FOR_MUTATION`, and `SUCCEEDS_GMB_ENTRY`.

This review establishes four editorial commitments: retain the exact CMB title and current GMB identity without architecture duplication; adopt the expanded semantic-state record; govern all mutation and dependent invalidation; and treat every query, atlas, capsule, skill, and federation message as an expiring projection rather than the base.

A Meaning Base Must Not Become an Oracle

Name and architectural role

The selected source belongs to the historical CCF -> CMB -> GMB lineage. In current architecture prose, **Governed Meaning Base (GMB)** is the preferred name. The exact historical title remains part of source and publication custody. The GMB is durable governed semantic state; it is not identical to the whole corpus, the Atlas, a search index, an embedding space, a generated explanation, or a public projection.

Public orientation

The practical question is how a knowledge base can preserve meaning, provenance, disagreement, and revision without becoming a black-box authority. A GMB should let an agent speak *through* recorded sources and standing while making omission, synthesis, uncertainty, and conflict visible.

Adversarial tests

1. **Semantic ossification.** A once-useful entry becomes stale but remains easy to retrieve. Entries require temporal scope, review state, dependents, and successor relations.

2. **Authority laundering.** Repetition, ranking, or machine fluency makes AI synthesis appear authorial. Every projection must retain source, authorship class, standing, and transformation lineage.
3. **False unification.** Disputed identities or incompatible definitions are merged for convenience. The base must preserve branches, conflict, and non-identity until an authorized decision exists.
4. **Provenance without access.** A source pointer exists but is unavailable, private, deleted, or hash-mismatched. The result is a typed custody or accessibility gap, not verified support.
5. **Query leakage.** Search, explanation, or aggregation reveals protected material. Admission authority does not imply disclosure authority; projection needs its own policy and receipt.
6. **Index-as-truth.** Retrieval rank is treated as semantic importance or truth. Ranking is a projection profile with biases, not standing.
7. **Centralization failure.** One base becomes an institutional bottleneck or single point of semantic control. Branching, export, reconstruction, and provider exit are necessary sovereignty properties.

Claim and evidence ceiling

The compact record

$$\begin{aligned} G^* = (&entry, content, source, authorship, provenance,\\ &relations, evidence, counterevidence, standing,\\ &authority, disputes, visibility, retention, dependents,\\ &revision, successor) \end{aligned}$$

is a normative information model, not proof that every field can be populated accurately or economically. Hashes establish byte identity; they do not establish meaning, truth, consent, lawful collection, or completeness. Internal corpus integration shows architectural fit. Claims about retrieval quality, human comprehension, scalability, privacy, institutional legitimacy, or long-term preservation require separate evidence.

8. Conclusion

The Governed Meaning Base (GMB) is proposed as a database-type instantiation within the Ableman Format Specification architecture. It is the operational substrate on which governed semantic corpora are built–knowledge bases, lexical dictionaries, evidence stores, custom domain corpora–under the same constitutional discipline that governs the document-type instantiation (the Constitutional Codex).

GMB is proposed as the operational-substrate successor of earlier framework work referenced in published literature as the Constitutional Crystallization Framework (CCF). The framework's conceptual content–that meaning must

crystallize before it can lawfully bind–is preserved and distributed across newer work; the operational substrate, formerly conflated with the framework concept, is now named GMB.

The substrate's defining properties are receipted transitions, admissibility gating, refusal as a first-class outcome, content-addressed identity, and lineage preservation. These are inherited from the AFS discipline and instantiated in database-substrate form. They distinguish GMB from conventional databases (which lack governance) and from knowledge graphs (which lack admissibility, lineage, and refusal as substrate properties).

GMB hosts current AFS content types–the Constitutional Encyclopedia (CE), the Constitutional Dictionary (CD), and custom domain corpora. Each inherits the substrate properties; each adds type-specific fields and operations. The two primary content types together provide the operational corpus underlying governed knowledge and language work in AFS practice.

The candidate relationship to other AFS components is structurally explicit: GMB is the database peer of CX in the AFS umbrella; both rest on shared MCIR canonical form; both produce receipts via the RBC discipline; both operate within phase-bound semantic regimes per Cryptographic Phase. The corpus is governed, queryable, and reproducible across time–a substrate fit to host knowledge in the era when knowledge increasingly drives action under consequential authority.

Realization Scope and Evidence Boundary

This successor makes the paper's stage boundary explicit. It narrows claims rather than manufacturing missing evidence: a stage named as context is not thereby claimed as implemented, validated, or complete.

- **Possibility Space.** The present paper does not claim a complete possibility space treatment. That stage remains successor work and cannot be inferred from the architecture described here.

Editorial Provenance and Standing

This revision applies the direct author ruling `CCF -> CMB -> GMB`. **Governed Meaning Base (GMB)** is the current name of the evolving architecture. **Constitutional Crystallization Framework (CCF)** and **Constitutional/Crystallized Meaning Base (CMB)** identify earlier stages and remain part of the historical record. Their older labels must not cause later integrations to count three independent current architectures. This terminology ruling does not itself establish conformance, publication, implementation, or canonical standing.

Corpus-Wide Reference Positioning

This paper argues that this paper specifies the Governed Meaning Base (GMB), a candidate governed substrate for storing, querying, relating, and revising semantic artifacts without collapsing exact source custody, logical work identity, concept identity, evidence, authority, and standing. Its nearest external comparison fields are semantic, provenance, observation. The sources in [E1], [E2], [E3], [E4], [E5], [E6], [E7] are cited as predecessor literature, adjacent standards, or counterpressure - not as evidence that they caused the Ableman framework or that they validate its novel claims. The comparison isolates where established work already supplies provenance, formal assurance, institutional constraint, empirical method, or engineering practice, and where this paper adds a distinct claim about admissibility, authority, semantic custody, or governed realization.

Within the Ableman corpus, the highest-priority current cross-links are [A1], [A2], [A3], [A4], [A5], [A6], [A7]. These are links among separately custodied works, not silent identity mergers. Their role is to expose mutual dependencies, terminology collisions, and places where a reader should traverse the corpus before treating this paper as self-sufficient.

Reference-pass counterevidence and limit search

The pass applied the following pressure tests: Formal vocabularies and graph links make commitments explicit but cannot by themselves establish correct identity, shared interpretation, or lossless translation between contexts. A complete provenance graph can faithfully record a false or unauthorized process; provenance is evidence about lineage, not automatic truth or legitimacy. Telemetry can be complete at the instrumented boundary while omitting the causal variable, real-world effect, or authority question that matters. These limits are not generic disclaimers: they identify the assumptions that a later empirical, formal, or implementation review must try to break.

Reference-pass influence and novelty boundary

No newly added external source is asserted to be a documented authorial influence unless the predecessor source already said so. `Predecessor` means earlier relevant work;

`adjacent` means a useful comparison; `standard` means an interoperability or assurance baseline; and `counterevidence` marks work that narrows or pressures a claim. Novelty therefore remains a reviewable, claim-level question rather than an inference from a low similarity score or an absent citation.

References

External scholarship, standards, and prior art

[**E1**] Richard Cyganiak, David Wood, and Markus Lanthaler, eds. *RDF 1.1 Concepts and Abstract Syntax*. W3C Recommendation, 25 February 2014. https://www.w3.org/TR/rdf11-concepts/ **Relationship:** Adjacent graph data model and identity baseline.

[**E2**] Alistair Miles and Sean Bechhofer, eds. *SKOS Simple Knowledge Organization System Reference*. W3C Recommendation, 18 August 2009. https://www.w3.org/TR/skos-reference **Relationship:** Adjacent standard for concepts, labels, schemes, notes, and semantic mappings.

[**E3**] W3C OWL Working Group. *OWL 2 Web Ontology Language Document Overview*, Second Edition. W3C Recommendation, 11 December 2012. https://www.w3.org/TR/owl2-overview/ **Relationship:** Adjacent formal ontology standard used to compare declared semantics and inference commitments.

[**E4**] Mark D. Wilkinson et al. "The FAIR Guiding Principles for Scientific Data Management and Stewardship." *Scientific Data* 3, 2016, 160018. DOI: 10.1038/sdata.2016.18. https://doi.org/10.1038/sdata.2016.18 **Relationship:** Predecessor stewardship principles for findability, accessibility, interoperability, and reuse.

[**E5**] Peter Gardenfors. *Conceptual Spaces: The Geometry of Thought*. MIT Press, 2000. mitpress.mit.edu source **Relationship:** Predecessor geometric treatment of concepts; cited as comparison, not as validation of the paper's manifold terminology.

[**E6**] W3C. *PROV-O: The PROV Ontology*. W3C Recommendation, 30 April 2013. https://www.w3.org/TR/prov-o/ **Relationship:** Adjacent provenance standard; it models entities, activities, and agents, but does not by itself establish the paper's stronger authority or standing claims.

[**E7**] Santiago Torres-Arias et al. "in-toto: Providing Farm-to-Table Guarantees for Bits and Bytes." *28th USENIX Security Symposium*, 2019, pp. 1393-1410. usenix.org source **Relationship:** Predecessor supply-chain lineage system used for comparison; no influence claim is made unless the source head already documents one.

Ableman corpus

[**A1**] Adam Ableman. *Meaning as Binding*. Ableman Corpus current edition; work identity
`AMCS-LOCAL-WORK-5F976917F0B283EA`;
source SHA-256
`A470D1A0B9ED7C3CEAB6BB88BE4B642A2BA36427447F787764329FD574DA0C97`.
Corpus relationship: priority cross-link selected by corpus profile and similarity review; no identity merger or publication effect.

[**A2**] Adam Ableman. *Semantic Manifold Topology.* Ableman Corpus current edition; work identity `PAPER.PUB.20257244`;
source SHA-256
`B8F28CC652A73A3EE4CF6FD0E23C1ABC922A6660319B2FB4CC1CCAAA606EC64A`.
Corpus relationship: priority cross-link selected by corpus profile and similarity review; no identity merger or publication effect.

[**A3**] Adam Ableman. *Global Term Key: Identity Primitives in Governed Knowledge Systems.* Ableman Corpus current edition; work identity
`AMCS-LOCAL-WORK-358AC09F5A13587E`;
source SHA-256
`AFB29CFCB4B58A78B79709AD453CEE9088CCB2AE40F30A70260F1B54F5160579`.
Corpus relationship: priority cross-link selected by corpus profile and similarity review; no identity merger or publication effect.

[**A4**] Adam Ableman. *Semantic Legitimacy Before Context.* Ableman Corpus current edition; work identity
`AMCS-LOCAL-WORK-091E34BA93992CE4`;
source SHA-256
`DEB7626CE1AB54F4B541347DCC3C4E14DC4F682230ACCCE1A93D1D536A50C44C`.
Corpus relationship: priority cross-link selected by corpus profile and similarity review; no identity merger or publication effect.

[**A5**] Adam Ableman. *Reasoning by Way of Receipts.* Ableman Corpus current edition; work identity
`AMCS-LOCAL-WORK-04E427F6F4D94454`;
source SHA-256
`AF86A66CCD6A103DD75208500AE99148911A6453B6DFDF36A954279F21AB8489`.
Corpus relationship: priority cross-link selected by corpus profile and similarity review; no identity merger or publication effect.

[**A6**] Adam Ableman. *The Epistemic Lineage Engine.* Ableman Corpus current edition; work identity
`AMCS-LOCAL-WORK-E0EC3DC7EABF5060`;
source SHA-256
`CDD74D9AFAB6532645E68F7F6C9F0F7A9E472D9B8E717290522566FF8DC01F11`.
Corpus relationship: priority cross-link selected by corpus profile and similarity review; no identity merger or publication effect.

[**A7**] Adam Ableman. *The Three Hash Rule.* Ableman Corpus current edition; work identity `PAPER.PUB.20788617`;
source SHA-256
`F6FA73D083B70711A8C817F7779751D1506FEBA0E356DB9805BB1570663731B5`.
Corpus relationship: priority cross-link selected by corpus profile and similarity review; no identity merger or publication effect.

Editorial source notes retained from predecessor

Adam Ableman *Ableman's Razor: A Typed Grammar for Ontology Exploration, Configuration Collapse, and Implementation Feedback.* Zenodo, 2026. doi:10.5281/zenodo.18113475

Adam Ableman *Cryptographic Phase: Declared Time, Semantic Stability, and Epochal Identity.* Zenodo, 2026. doi:10.5281/zenodo.18503394

Adam Ableman *Receipt-Bound Capabilities: Membrane Tokens for Governed Interaction with Reality.* Zenodo, 2026. doi:10.5281/zenodo.18601631

Adam Ableman *Semantic Hashing: Hashes as Declared Equivalence Classes of Meaning.* Zenodo, 2026. doi:10.5281/zenodo.18500533

Adam Ableman *Meaning as Binding: A Relational Ontology for Constitutional Computational Substrates.* Ableman Corpus edition in the current corpus; DOI and publication identity are recorded separately.

Adam Ableman *The Constitutional Codex: AI-Executable Specification and Phase-Gated Construction for Deterministic System Realization.* Forthcoming.

Adam Ableman *Semantic Crystallization.* Zenodo, 2026. doi:10.5281/zenodo.20310115

Adam Ableman *Global Term Key: Constitutional Lexical Identity Through Disambiguated Semantic Binding.* Forthcoming.

Adam Ableman *Meta-Compilation Intermediate Representation: A Canonical Substrate for Crystallized Meaning.* Forthcoming.

Adam Ableman *Ableman Format Specification (AFS): The Constitutional Specification Ecosystem.* Forthcoming.

Adam Ableman *The Governed Knowledge Loop: A Constitutional Bootstrapping Architecture for Semantic Computing Infrastructure.* Forthcoming.

Adam Ableman *The Constitutional Knowledge Reactor: An Operational Architecture for the Governed Knowledge Loop.* Forthcoming.

Reference-standing note

Items labeled forthcoming or unpublished are local corpus relationships, not publication claims. The DOI-bearing references above were matched to the author-supplied publication baseline. The AFS, CX, CE, CD, GTK, MCIR, GKL, CKR, Hyperpedia, and Crystal Network identity relations remain subject to corpus-wide adjudication; this paper proposes architectural placement but does not merge them.

Corpus source and companion formats: https://github.com/AblemanMosaic/ableman-corpus
License: CC-BY-ND-4.0

DOI: 10.5281/zenodo.23847514