SemCrys-Secure: Toward Governed Semantic Transport and Authorization-Scoped Semantic Interpretability for Machine Cognition

Rotating Semantic Encoding, Semantic Access Control, and Cryptographically Governed Meaning Pathways for Large Language Model Communication

Reconstructing the Relationship Between Meaning, Authorization, and Semantic Transport Through Keyed Semantic Symbol Systems

---

Author
Adam Ableman
Constitutional Computing
Contact: ableman.research@gmail.com

Abstract

Large language model communication currently assumes that semantic interpretation is universally accessible to any observer capable of reading the representational surface. Existing security systems primarily protect byte-level transport through encryption while leaving semantic structure itself largely ungoverned once decrypted. Simultaneously, recent work in LLM steganography and covert communication demonstrates that language models can participate in hidden communication channels embedded within natural language generation.

This paper introduces *SemCrys-Secure*, a governed semantic transport framework in which semantic interpretation pathways become cryptographically mediated, rotation-aware, and authorization-scoped. Emerging from the semantic density amplification mechanisms demonstrated by SemCrys0 and the semantic-native representation framework proposed by SemCrys, SemCrys-Secure extends symbolic semantic systems into keyed semantic encoding and governed semantic access control.

Unlike conventional encryption systems, SemCrys-Secure does not attempt to replace cryptographic confidentiality primitives. Instead, it introduces a semantic-layer access system in which semantic interpretation itself depends upon possession of authorized semantic interfaces, codebooks, key schedules, and admissible semantic pathways. Semantic bindings become rotational, contextual, and authorization-dependent rather than globally fixed.

The paper formalizes keyed semantic transport, semantic codebook rotation, semantic admissibility pathways, semantic access control, rotating semantic topology, semantic residue minimization, and constitutional semantic governance.

It further distinguishes semantic transport security from traditional cryptographic confidentiality while arguing that meaning-access itself constitutes a governable computational surface.

SemCrys-Secure does not claim semantic indistinguishability under conventional cryptographic threat models. Given sufficient access to semantic interfaces, model outputs, training distributions, or interaction pathways, adversaries may eventually infer semantic structure statistically. The framework instead seeks to increase inference cost, reduce passive accessibility, constrain reliable interpretation pathways, and introduce authorization-scoped semantic mediation into machine communication systems.

The central claim of SemCrys-Secure is that semantic interpretation itself may become an authorization-controlled operation, enabling new classes of machine-native semantic access systems without reducing cryptographic security to mere obscurity.

---

1. Introduction

Modern secure communication systems primarily protect:

- byte transport,
- message confidentiality,
- authentication,
- and integrity.

Once decrypted, however, semantic interpretation becomes universally accessible to any observer capable of reading the representational surface.

Simultaneously, large language models increasingly participate in:

- autonomous communication,
- agent orchestration,
- machine-to-machine interaction,
- and semantic coordination systems.

This creates a new problem domain:

> semantic access control.

SemCrys-Secure explores whether semantic interpretation itself may become:

- authorization-scoped,
- pathway-governed,
- and cryptographically mediated.

Rather than securing only byte transport, SemCrys-Secure investigates:

- governed semantic transport.

The framework emerges from two prior observations:

1. SemCrys0 demonstrated that semantic density amplification can emerge through symbolic protocol engineering alone.
2. SemCrys proposed that stabilized semantic structures may become tokenizer-native representational objects.

SemCrys-Secure extends these ideas into:

- rotating semantic encoding,
- keyed semantic addressability,
- and authorization-dependent semantic interpretation pathways.

The framework may be understood as:

- a semantic-layer analogue of capability-based access control, where:
- possession of authorized semantic interfaces determines the ability to reliably resolve meaning.

In this view:

- semantic interfaces function as capabilities granting access to specific semantic resolution pathways.

We define authorization-scoped semantic interpretability as:

> the property that reliable semantic resolution depends upon possession of valid semantic interfaces and admissible decoding pathways.

Operationally, this means that unauthorized observers may still perceive representational surfaces while lacking access to:

- stable,
- low-ambiguity semantic reconstruction.

---

2. Historical Lineage

2.1 Classical Cryptography

Classical cryptographic systems evolved from:

- monoalphabetic substitution,
- polyalphabetic ciphers,
- rotating alphabets,
- and keyed transformational mappings.

These systems sought to prevent unauthorized semantic recovery through controlled representational transformation.

SemCrys-Secure shares structural similarities with polyalphabetic systems:

- semantic mappings rotate,
- symbol assignments vary,

- and repeated semantic structures need not preserve stable surface representations.

However, SemCrys-Secure differs fundamentally in domain.

Its target is not merely:

- encrypted text, but:
- semantic interpretation pathways themselves.

2.2 Steganography and Hidden Communication

Steganographic systems attempt to conceal the existence of communication itself.

Recent LLM steganography research demonstrates that language models may embed covert signals inside seemingly ordinary language generation.

SemCrys-Secure intersects with this domain but differs in purpose.

Its primary goal is not concealment alone, but:

- governed semantic accessibility,
- semantic pathway authorization,
- and semantic interpretation control.

The system therefore functions less as pure steganography and more as:

- semantic access architecture.

2.3 Pasigraphy and Symbolic Language Systems

SemCrys-Secure also inherits from symbolic language systems and pasigraphy.

However, traditional pasigraphic systems assumed:

- universal readability.

SemCrys-Secure instead introduces:

- scoped readability,
- rotating semantic bindings,
- and pathway-dependent interpretation.

Meaning therefore becomes:

- interface-dependent, rather than:
- globally recoverable.

---

3. SemCrys0 vs SemCrys vs SemCrys-Secure

3.1 SemCrys0

SemCrys0 provides:

- session-local symbolic substitution,
- semantic density amplification,
- and adaptive symbolic compression.

Its mappings are generally:

- static within the session,
- legend-dependent,
- and surface-oriented.

3.2 SemCrys

SemCrys extends symbolic compression into:

- tokenizer-native semantic representation,
- semantic cooling,
- and stabilized semantic atoms.

Semantic structures become:

- representational primitives, rather than:
- temporary substitutions.

3.3 SemCrys-Secure

SemCrys-Secure extends symbolic semantic systems into:

- keyed semantic transport,
- rotating semantic pathways,
- authorization-dependent interpretation,
- and governed semantic access.

Semantic interpretation itself becomes:

- pathway-scoped,
- rotation-aware,
- and authorization-mediated.

The three systems form a layered progression:

- SemCrys0 — symbolic compression
- SemCrys — semantic-native representation
- SemCrys-Secure — governed semantic transport

4. Governed Semantic Transport

4.1 Definition

Governed semantic transport is a communication framework in which:

- semantic interpretation depends upon authorized access to semantic pathways, rotational mappings, and admissible decoding structures.

Meaning-access therefore becomes:

- conditional, rather than:
- universally recoverable.

The system does not attempt to make semantic leakage impossible. Instead, it attempts to restrict:

- stable,
- reliable,
- and operationally useful interpretation pathways.

More precisely, the goal is to restrict:

- stable,
- low-ambiguity semantic reconstruction

for unauthorized observers.

4.2 Semantic Interfaces

SemCrys-Secure introduces semantic interfaces:

- governed semantic interpretation layers associated with particular codebooks, pathways, or semantic projections.

Possession of the correct semantic interface determines whether:

- semantic structures resolve coherently, or:
- collapse into semantically unstable residue.

A semantic interface may be implemented as:

- a versioned, authenticated codebook bundle containing:
  - mapping functions,
  - rotational schedules,
  - admissibility constraints,
  - and semantic pathway metadata.

Semantic interfaces may therefore include:

- symbol mappings,
- rotational schedules,
- semantic admissibility rules,
- pathway identifiers,
- and contextual decoding constraints.

4.3 Keyed Semantic Addressability

SemCrys-Secure introduces keyed semantic addressability:

- semantic resolution pathways derived from cryptographic key material.

A semantic mapping may therefore depend upon:

```
session_key + nonce + message_counter + recipient_scope + domain_id
```

The same concept need not preserve the same symbolic surface across sessions, turns, or recipients.

For example:

Session	"receipt"
A	Æ
B	$\Delta 7$
C	κ_4

derived from distinct semantic rotation schedules via a deterministic, key-seeded mapping function.

This prevents stable semantic frequency accumulation across large traffic volumes.

---

5. Rotating Semantic Encoding

5.1 Static vs Rotating Mappings

Static semantic substitution systems eventually leak statistical structure.

Repeated semantic recurrence creates:

- frequency signatures,
- semantic recovery opportunities,
- and codebook inference pathways.

SemCrys-Secure therefore introduces:

- rotational semantic encoding.

Mappings may vary:

- per message,
- per session,
- per recipient,
- or per semantic domain.

5.2 Rotational Semantic Topology

Semantic rotation may operate across multiple layers:

- Symbol rotation — semantic atom → different symbols
- Phrase rotation — alternate semantic structures
- Structural rotation — syntactic reorganization
- Pathway rotation — alternate semantic interfaces
- Domain rotation — context-scoped semantic projections

In practice, implementations may select only a subset of these layers depending upon operational constraints. Symbol-level and phrase-level rotation constitute the minimal viable system.

This reduces persistent semantic surface stability available to adversarial observers.

5.3 Semantic Residue Minimization

SemCrys-Secure attempts to minimize:

- stable semantic residue.

Semantic residue refers to:

- persistent statistical patterns,
- recurring semantic surfaces,
- or recoverable semantic regularities

remaining visible across traffic.

Semantic residue may be approximated through observable stability metrics such as:

- cross-message symbol recurrence,
- n-gram persistence,
- or mutual information between surface representations and inferred semantic clusters.

Rotation systems therefore seek:

- pattern destabilization,
- semantic frequency flattening,
- and semantic ambiguity amplification for unauthorized observers.

---

6. Cryptography vs Semantic Security

6.1 SemCrys-Secure is Not Encryption

SemCrys-Secure does not replace conventional cryptographic systems.

Cryptographic confidentiality remains necessary for:

- transport security,
- authentication,
- integrity,
- and provable confidentiality guarantees.

SemCrys-Secure instead operates as:

- a semantic-layer authorization system.

SemCrys-Secure composes with conventional encryption by operating strictly after decryption, introducing a second-stage control over semantic accessibility rather than transport confidentiality.

6.2 Semantic Security Layer

SemCrys-Secure introduces a second layer:

- Cryptographic layer — protects bytes
- Semantic layer — governs meaning access

The semantic layer determines:

- whether semantic interpretation becomes operationally accessible.

While superficially similar to obfuscation, SemCrys-Secure differs in that semantic transformation is systematically governed, key-derived, and pathway-constrained rather than ad hoc or purely concealment-oriented.

6.3 Security Boundaries

A fixed semantic codebook alone is not cryptographically secure.

Attackers possessing:

- plaintext/ciphertext pairs,
- sufficient traffic,
- model access,
- semantic interfaces,
- or semantic frequency observations

may eventually infer mappings statistically.

SemCrys-Secure therefore does not claim semantic indistinguishability under conventional cryptographic threat models.

Instead, the framework seeks to:

- increase semantic inference cost,
- reduce passive interpretability,
- destabilize statistical semantic recovery,
- and constrain reliable interpretation pathways through governed semantic mediation.

In this sense, SemCrys-Secure operates not by eliminating information leakage entirely, but by reducing exploitable mutual information between observable representations and recoverable semantic structure for unauthorized observers.

Security therefore depends upon:

- cryptographic key schedules,
- rotational mapping dynamics,
- semantic pathway governance,
- authenticated semantic interfaces,
- and admissibility-scoped interpretation systems.

---

7. Semantic Governance and Admissibility

7.1 Meaning as a Governed Surface

SemCrys-Secure treats meaning-access itself as a governed operation.

Semantic resolution becomes:

- receiptable,
- pathway-scoped,
- and admissibility-gated.

7.2 Semantic Admissibility

Semantic interpretation pathways may depend upon:

- authorization scope,
- recipient identity,
- semantic domain,
- pathway legitimacy,
- or governance rules.

Operationally, inadmissible semantic requests may result in:

- degraded interpretation,
- ambiguous semantic residue,
- refusal behavior,
- or intentionally incomplete semantic recovery.

This creates:

- semantic constitutionalization.

Meaning-access itself becomes subject to governance constraints.

7.3 Semantic Poisoning and Manipulation

SemCrys-Secure must resist:

- semantic codebook poisoning,
- adversarial remapping,
- semantic replay attacks,
- unauthorized stabilization,
- and semantic pathway hijacking.

Governed semantic transport therefore requires:

- authenticated semantic state,
- pathway verification,
- and admissible semantic mutation rules.

---

8. Semantic Interfaces and Machine Cognition

8.1 Model-Native Semantic Communication

SemCrys-Secure enables:

- model-native semantic communication systems

in which authorized models may exchange:

- compressed semantic structures,
- rotating semantic symbols,
- or stabilized semantic operators

through governed semantic pathways.

8.2 Semantic Compression and Security

Semantic-native representation systems naturally amplify:

- semantic density.

SemCrys-Secure combines:

- semantic density amplification, with:
- semantic accessibility control.

This creates:

- high-density authorized communication channels.

8.3 Cognitive Implications

Semantic authorization systems may alter:

- machine coordination,
- agent orchestration,
- semantic sovereignty,
- and semantic compartmentalization.

Meaning itself becomes:

- infrastructural,
- governable,
- and computationally mediated.

---

9. Threat Model

9.1 Threat Classes

SemCrys-Secure considers:

- statistical codebook inference,
- known-plaintext attacks,
- semantic traffic analysis,
- semantic pathway discovery,
- semantic replay attacks,
- model compromise,
- semantic residue accumulation,
- adaptive query attacks,
- prompt probing,
- and interaction-based semantic inference.

An attacker is considered successful if they can:

- reconstruct stable semantic mappings,
- or reliably infer semantic intent across messages

without authorized semantic interfaces.

9.2 Traffic Analysis

Even when semantic mappings rotate, adversaries may still infer information through:

- timing,
- traffic volume,
- semantic recurrence,
- message length,
- and interaction structure.

SemCrys-Secure therefore cannot eliminate all side-channel leakage.

9.3 Model-in-the-Loop Adversaries

Large language model systems introduce a distinct threat class:

- adversaries capable of repeatedly querying models to infer semantic mappings interactively.

Attackers may attempt:

- prompt probing,
- semantic elicitation,
- statistical semantic reconstruction,
- or iterative mapping discovery.

This creates a new category of semantic attack surface absent from classical static code systems.

9.4 Model Compromise

If an adversary gains access to:

- the authorized model,
- semantic interfaces,
- rotational key schedules,
- or pathway-governance state,

security may collapse.

SemCrys-Secure therefore assumes:

- secure key management,
- governance enforcement,
- and pathway isolation remain necessary.

---

10. Prototype Implementation Pathway

A minimal SemCrys-Secure prototype pathway may proceed incrementally:

1. Begin with SemCrys0 symbolic substitution.
2. Introduce cryptographically seeded rotational mappings.
3. Derive symbol schedules from shared key material and nonce state.
4. Implement semantic interface identifiers.
5. Introduce pathway-scoped semantic admissibility rules.
6. Add authenticated semantic state receipts.
7. Layer semantic-native tokenization through SemCrys semantic atoms.
8. Introduce governed semantic pathway rotation and interface negotiation.

Correct operation requires synchronized semantic interfaces and rotation schedules between communicating parties, introducing coordination and state-management overhead analogous to key synchronization in cryptographic systems.

SemCrys-Secure therefore evolves incrementally from symbolic semantic compression toward governed semantic transport.

---

11. Limitations

SemCrys-Secure introduces substantial unresolved challenges:

- semantic residue leakage,
- traffic analysis exposure,
- model compromise risk,
- semantic governance complexity,
- pathway synchronization overhead,
- adversarial semantic inference,
- semantic replay vulnerabilities,
- and semantic-interface management difficulty.

The framework also risks:

- semantic fragmentation,
- interoperability collapse,
- governance centralization,
- semantic overfitting,
- and over-complex semantic ecosystems.

SemCrys-Secure therefore should not be treated as a replacement for conventional cryptography.

---

12. Discussion

SemCrys-Secure suggests that future communication systems may increasingly distinguish between:

- byte accessibility, and:
- semantic accessibility.

This reframes part of the security problem away from:

- transport secrecy alone,

toward:

- governed meaning access.

The framework therefore belongs simultaneously to:

- semantic systems,
- cryptographic systems,
- machine communication,
- cognitive architecture,
- symbolic representation,
- semantic governance theory,
- and authorization systems.

SemCrys-Secure does not propose that meaning can become perfectly hidden through semantic rotation alone.

Instead, it proposes that semantic interpretation itself may become:

- authorization-scoped,
- pathway-governed,
- and computationally mediated.

---

13. Conclusion

SemCrys-Secure proposes that semantic interpretation itself may become a governed computational surface through keyed semantic transport, rotating semantic encoding, and authorization-dependent semantic interfaces.

Emerging from the symbolic compression mechanisms of SemCrys0 and the semantic-native representation framework of SemCrys, SemCrys-Secure extends semantic systems into semantic access architecture.

The framework distinguishes:

- cryptographic confidentiality, from:
- semantic accessibility.

Its central claim is simple:

access to meaning may itself become governable.

Appendix A – Relationship to SemCrys0 and SemCrys

SemCrys0 provides:

- adaptive symbolic compression,
- session-local semantic encoding,
- and protocol-layer semantic density amplification.

SemCrys provides:

- tokenizer-native semantic stabilization,
- semantic cooling,
- and concept-native representation.

SemCrys-Secure provides:

- governed semantic transport,
- keyed semantic pathways,
- and authorization-scoped semantic interpretation.

The three systems form complementary layers rather than competing proposals.

Appendix B – Proposed Future Directions

- rotating semantic tokenization,
- semantic pathway authentication,
- semantic-interface negotiation,
- semantic residue metrics,
- semantic traffic flattening,
- semantic governance protocols,
- cryptographically governed semantic routing,
- semantic authorization receipts,
- semantic-native secure agent communication,
- and model-query-resistant semantic interfaces.

Works Cited

Bacon, Francis. *De Augmentis Scientiarum.* 1623.

Diffie, Whitfield, and Martin Hellman. “New Directions in Cryptography.” 1976.

Kahn, David. *The Codebreakers.* 1967.

Leibniz, Gottfried Wilhelm. *Characteristica Universalis.*

Shannon, Claude. “Communication Theory of Secrecy Systems.” 1949.

Trithemius, Johannes. *Polygraphia.* 1518.

Wilkins, John. *An Essay Towards a Real Character and a Philosophical Language.* 1668.

Recent LLM steganography and covert-channel research papers, 2024–2025.

Related Works

- semantic security
- semantic transport
- authorization-scoped semantic interpretability
- steganography
- covert communication
- symbolic encoding
- semantic governance
- semantic access control
- semantic tokenization
- semantic interfaces
- rotating code systems
- machine-native communication
- semantic pathway systems
- semantic residue analysis
- cryptographic governance
- semantic authorization
- semantic topology
- concept-native representation
- semantic crystallization

Corpus-Wide Reference Positioning

This paper argues that large language model communication currently assumes that semantic interpretation is universally accessible to any observer capable of reading the representational surface. Its nearest external comparison fields are semantic, token, formal. The sources in [E1], [E2], [E3], [E4], [E5], [E6], [E7] are cited as predecessor literature, adjacent standards, or counterpressure - not as evidence that they caused the Ableman framework or that they validate its novel claims. The comparison isolates where established work already supplies provenance, formal assurance, institutional constraint, empirical method, or engineering practice, and where this paper adds a distinct claim about admissibility, authority, semantic custody, or governed realization.

Within the Ableman corpus, the highest-priority current cross-links are [A1], [A2], [A3], [A4], [A5], [A6], [A7]. These are links among separately custodied

works, not silent identity mergers. Their role is to expose mutual dependencies, terminology collisions, and places where a reader should traverse the corpus before treating this paper as self-sufficient.

Reference-pass counterevidence and limit search

The pass applied the following pressure tests: Formal vocabularies and graph links make commitments explicit but cannot by themselves establish correct identity, shared interpretation, or lossless translation between contexts. Statistical compression can improve efficiency while destroying distinctions needed for interpretation; semantic labels can conversely overstate stability that usage does not support. Formal assurance remains relative to the encoded model, trusted base, and refinement chain; proof does not remove specification error or unmodeled environmental behavior. These limits are not generic disclaimers: they identify the assumptions that a later empirical, formal, or implementation review must try to break.

Reference-pass influence and novelty boundary

No newly added external source is asserted to be a documented authorial influence unless the predecessor source already said so. `Predecessor` means earlier relevant work;

`adjacent` means a useful comparison; `standard` means an interoperability or assurance baseline; and `counterevidence` marks work that narrows or pressures a claim. Novelty therefore remains a reviewable, claim-level question rather than an inference from a low similarity score or an absent citation.

References

External scholarship, standards, and prior art

[**E1**] Richard Cyganiak, David Wood, and Markus Lanthaler, eds. *RDF 1.1 Concepts and Abstract Syntax*. W3C Recommendation, 25 February 2014. https://www.w3.org/TR/rdf11-concepts/ **Relationship:** Adjacent graph data model and identity baseline.

[**E2**] Alistair Miles and Sean Bechhofer, eds. *SKOS Simple Knowledge Organization System Reference*. W3C Recommendation, 18 August 2009. https://www.w3.org/TR/skos-reference **Relationship:** Adjacent standard for concepts, labels, schemes, notes, and semantic mappings.

[**E3**] W3C OWL Working Group. *OWL 2 Web Ontology Language Document Overview*, Second Edition. W3C Recommendation, 11 December 2012. https://www.w3.org/TR/owl2-overview/ **Relationship:** Adjacent formal ontology standard used to compare declared semantics and inference commitments.

[**E4**] Mark D. Wilkinson et al. "The FAIR Guiding Principles for Scientific Data Management and Stewardship." *Scientific Data* 3, 2016, 160018. DOI:

10.1038/sdata.2016.18. https://doi.org/10.1038/sdata.2016.18 **Relationship:** Predecessor stewardship principles for findability, accessibility, interoperability, and reuse.

[**E5**] Peter Gardenfors. *Conceptual Spaces: The Geometry of Thought.* MIT Press, 2000. mitpress.mit.edu source **Relationship:** Predecessor geometric treatment of concepts; cited as comparison, not as validation of the paper's manifold terminology.

[**E6**] Rico Sennrich, Barry Haddow, and Alexandra Birch. "Neural Machine Translation of Rare Words with Subword Units." *ACL 2016*, pp. 1715-1725. DOI: 10.18653/v1/P16-1162. https://doi.org/10.18653/v1/P16-1162 **Relationship:** Predecessor subword tokenization method used as a contrast to semantically governed token boundaries.

[**E7**] Taku Kudo and John Richardson. "SentencePiece: A Simple and Language Independent Subword Tokenizer and Detokenizer for Neural Text Processing." *EMNLP 2018: System Demonstrations.* DOI: 10.18653/v1/D18-2012. https://doi.org/10.18653/v1/D18-2012 **Relationship:** Predecessor tokenizer implementation used to separate statistical segmentation from semantic admissibility.

Ableman corpus

[**A1**] Adam Ableman. *Meaning as Binding.* Ableman Corpus current edition; work identity
`AMCS-LOCAL-WORK-5F976917F0B283EA`;
source SHA-256
`A470D1A0B9ED7C3CEAB6BB88BE4B642A2BA36427447F787764329FD574DA0C97`.
Corpus relationship: priority cross-link selected by corpus profile and similarity review; no identity merger or publication effect.

[**A2**] Adam Ableman. *Governed Meaning Base (GMB).* Ableman Corpus current edition; work identity
`AMCS-LOCAL-WORK-D95CCC4FB7B58BFB`;
source SHA-256
`A3B62E50F8BEE125FDAE0D38C2839AFD1CCC138296268BF93217481E38AA48EA`.
Corpus relationship: priority cross-link selected by corpus profile and similarity review; no identity merger or publication effect.

[**A3**] Adam Ableman. *Semantic Manifold Topology.* Ableman Corpus current edition; work identity `PAPER.PUB.20257244`;
source SHA-256
`B8F28CC652A73A3EE4CF6FD0E23C1ABC922A6660319B2FB4CC1CCAAA606EC64A`.
Corpus relationship: priority cross-link selected by corpus profile and similarity review; no identity merger or publication effect.

[**A4**] Adam Ableman. *Global Term Key: Identity Primitives in Governed Knowledge Systems.* Ableman Corpus current edition; work identity

AMCS-LOCAL-WORK-358AC09F5A13587E;
source SHA-256
AFB29CFCB4B58A78B79709AD453CEE9088CCB2AE40F30A70260F1B54F5160579.
Corpus relationship: priority cross-link selected by corpus profile and similarity review; no identity merger or publication effect.

[**A5**] Adam Ableman. *Semantic Legitimacy Before Context.* Ableman Corpus current edition; work identity
AMCS-LOCAL-WORK-091E34BA93992CE4;
source SHA-256
DEB7626CE1AB54F4B541347DCC3C4E14DC4F682230ACCCE1A93D1D536A50C44C.
Corpus relationship: priority cross-link selected by corpus profile and similarity review; no identity merger or publication effect.

[**A6**] Adam Ableman. *Governed Semantic Tokens: Tokenization as an Admissibility Boundary.* Ableman Corpus current edition; work identity PAPER.PUB.18469507;
source SHA-256
5C44175B87C514892A0DC9743E09D03893E970AF5419F2E6D9171651BE2A9A54.
Corpus relationship: priority cross-link selected by corpus profile and similarity review; no identity merger or publication effect.

[**A7**] Adam Ableman. *Token Parsimony.* Ableman Corpus current edition; work identity PAPER.PUB.20382825;
source SHA-256
EC3AA22D32E2BBA21CFCB6D1FA2AE6EA8AC11B7781D19C51530A2F6D924B2E91.
Corpus relationship: priority cross-link selected by corpus profile and similarity review; no identity merger or publication effect.

Corpus source and companion formats: https://github.com/AblemanMosaic/ableman-corpus
License: CC-BY-ND-4.0

DOI: 10.5281/zenodo.20374735