```
// megafunction wizard: %RAM: 2-PORT%
// GENERATION: STANDARD
// VERSION: WM1.0
// MODULE: altsyncram

// ============================================================
// File Name: car_tracker8x16.v
// Megafunction Name(s):
//          altsyncram
//
// Simulation Library Files(s):
//          altera_mf
// ============================================================
// ************************************************************
// THIS IS A WIZARD-GENERATED FILE. DO NOT EDIT THIS FILE!
//
// 17.0.0 Build 595 04/25/2017 SJ Lite Edition
// ************************************************************


//Copyright (C) 2017  Intel Corporation. All rights reserved.
//Your use of Intel Corporation's design tools, logic functions
//and other software and tools, and its AMPP partner logic
//functions, and any output files from any of the foregoing
//(including device programming or simulation files), and any
//associated documentation or information are expressly subject
//to the terms and conditions of the Intel Program License
//Subscription Agreement, the Intel Quartus Prime License Agreement,
//the Intel MegaCore Function License Agreement, or other
//applicable license agreement, including, without limitation,
//that your use is for the sole purpose of programming logic
//devices manufactured by Intel and sold by Intel or its
//authorized distributors.  Please refer to the applicable
//agreement for further details.


// synopsys translate_off
`timescale 1 ps / 1 ps
// synopsys translate_on
module car_tracker8x16 (
   clock,
   data,
   rdaddress,
   wraddress,
   wren,
   q);

   input   clock;
   input [15:0]  data;
   input [2:0]  rdaddress;
   input [2:0]  wraddress;
   input   wren;
   output   [15:0]  q;
`ifndef ALTERA_RESERVED_QIS
// synopsys translate_off
`endif
   tri1    clock;
   tri0    wren;
`ifndef ALTERA_RESERVED_QIS
// synopsys translate_on
`endif

   wire [15:0] sub_wire0;
   wire [15:0] q = sub_wire0[15:0];

   altsyncram  altsyncram_component (
            .address_a (wraddress),
            .address_b (rdaddress),
            .clock0 (clock),
            .data_a (data),
            .wren_a (wren),
            .q_b (sub_wire0),
            .aclr0 (1'b0),
            .aclr1 (1'b0),
```

```
75                .addressstall_a (1'b0),
76                .addressstall_b (1'b0),
77                .byteena_a (1'b1),
78                .byteena_b (1'b1),
79                .clock1 (1'b1),
80                .clocken0 (1'b1),
81                .clocken1 (1'b1),
82                .clocken2 (1'b1),
83                .clocken3 (1'b1),
84                .data_b ({16{1'b1}}),
85                .eccstatus (),
86                .q_a (),
87                .rden_a (1'b1),
88                .rden_b (1'b1),
89                .wren_b (1'b0));
90        defparam
91           altsyncram_component.address_aclr_b = "NONE",
92           altsyncram_component.address_reg_b = "CLOCK0",
93           altsyncram_component.clock_enable_input_a = "BYPASS",
94           altsyncram_component.clock_enable_input_b = "BYPASS",
95           altsyncram_component.clock_enable_output_b = "BYPASS",
96           altsyncram_component.intended_device_family = "Cyclone V",
97           altsyncram_component.lpm_type = "altsyncram",
98           altsyncram_component.numwords_a = 8,
99           altsyncram_component.numwords_b = 8,
100          altsyncram_component.operation_mode = "DUAL_PORT",
101          altsyncram_component.outdata_aclr_b = "NONE",
102          altsyncram_component.outdata_reg_b = "UNREGISTERED",
103          altsyncram_component.power_up_uninitialized = "FALSE",
104          altsyncram_component.ram_block_type = "M10K",
105          altsyncram_component.read_during_write_mode_mixed_ports = "DONT_CARE",
106          altsyncram_component.widthad_a = 3,
107          altsyncram_component.widthad_b = 3,
108          altsyncram_component.width_a = 16,
109          altsyncram_component.width_b = 16,
110          altsyncram_component.width_byteena_a = 1;
111
112
113    endmodule
114
115    // ============================================================
116    // CNX file retrieval info
117    // ============================================================
118    // Retrieval info: PRIVATE: ADDRESSSTALL_A NUMERIC "0"
119    // Retrieval info: PRIVATE: ADDRESSSTALL_B NUMERIC "0"
120    // Retrieval info: PRIVATE: BYTEENA_ACLR_A NUMERIC "0"
121    // Retrieval info: PRIVATE: BYTEENA_ACLR_B NUMERIC "0"
122    // Retrieval info: PRIVATE: BYTE_ENABLE_A NUMERIC "0"
123    // Retrieval info: PRIVATE: BYTE_ENABLE_B NUMERIC "0"
124    // Retrieval info: PRIVATE: BYTE_SIZE NUMERIC "8"
125    // Retrieval info: PRIVATE: BlankMemory NUMERIC "1"
126    // Retrieval info: PRIVATE: CLOCK_ENABLE_INPUT_A NUMERIC "0"
127    // Retrieval info: PRIVATE: CLOCK_ENABLE_INPUT_B NUMERIC "0"
128    // Retrieval info: PRIVATE: CLOCK_ENABLE_OUTPUT_A NUMERIC "0"
129    // Retrieval info: PRIVATE: CLOCK_ENABLE_OUTPUT_B NUMERIC "0"
130    // Retrieval info: PRIVATE: CLRdata NUMERIC "0"
131    // Retrieval info: PRIVATE: CLRq NUMERIC "0"
132    // Retrieval info: PRIVATE: CLRrdaddress NUMERIC "0"
133    // Retrieval info: PRIVATE: CLRrren NUMERIC "0"
134    // Retrieval info: PRIVATE: CLRwraddress NUMERIC "0"
135    // Retrieval info: PRIVATE: CLRwren NUMERIC "0"
136    // Retrieval info: PRIVATE: Clock NUMERIC "0"
137    // Retrieval info: PRIVATE: Clock_A NUMERIC "0"
138    // Retrieval info: PRIVATE: Clock_B NUMERIC "0"
139    // Retrieval info: PRIVATE: IMPLEMENT_IN_LES NUMERIC "0"
140    // Retrieval info: PRIVATE: INDATA_ACLR_B NUMERIC "0"
141    // Retrieval info: PRIVATE: INDATA_REG_B NUMERIC "0"
142    // Retrieval info: PRIVATE: INIT_FILE_LAYOUT STRING "PORT_B"
143    // Retrieval info: PRIVATE: INIT_TO_SIM_X NUMERIC "0"
144    // Retrieval info: PRIVATE: INTENDED_DEVICE_FAMILY STRING "Cyclone V"
145    // Retrieval info: PRIVATE: JTAG_ENABLED NUMERIC "0"
146    // Retrieval info: PRIVATE: JTAG_ID STRING "NONE"
147    // Retrieval info: PRIVATE: MAXIMUM_DEPTH NUMERIC "0"
148    // Retrieval info: PRIVATE: MEMSIZE NUMERIC "128"
```

```
// Retrieval info: PRIVATE: MEM_IN_BITS NUMERIC "0"
// Retrieval info: PRIVATE: MIFfilename STRING ""
// Retrieval info: PRIVATE: OPERATION_MODE NUMERIC "2"
// Retrieval info: PRIVATE: OUTDATA_ACLR_B NUMERIC "0"
// Retrieval info: PRIVATE: OUTDATA_REG_B NUMERIC "0"
// Retrieval info: PRIVATE: RAM_BLOCK_TYPE NUMERIC "2"
// Retrieval info: PRIVATE: READ_DURING_WRITE_MODE_MIXED_PORTS NUMERIC "2"
// Retrieval info: PRIVATE: READ_DURING_WRITE_MODE_PORT_A NUMERIC "3"
// Retrieval info: PRIVATE: READ_DURING_WRITE_MODE_PORT_B NUMERIC "3"
// Retrieval info: PRIVATE: REGdata NUMERIC "1"
// Retrieval info: PRIVATE: REGq NUMERIC "1"
// Retrieval info: PRIVATE: REGrdaddress NUMERIC "1"
// Retrieval info: PRIVATE: REGrren NUMERIC "1"
// Retrieval info: PRIVATE: REGwraddress NUMERIC "1"
// Retrieval info: PRIVATE: REGwren NUMERIC "1"
// Retrieval info: PRIVATE: SYNTH_WRAPPER_GEN_POSTFIX STRING "0"
// Retrieval info: PRIVATE: USE_DIFF_CLKEN NUMERIC "0"
// Retrieval info: PRIVATE: UseDPRAM NUMERIC "1"
// Retrieval info: PRIVATE: VarWidth NUMERIC "0"
// Retrieval info: PRIVATE: WIDTH_READ_A NUMERIC "16"
// Retrieval info: PRIVATE: WIDTH_READ_B NUMERIC "16"
// Retrieval info: PRIVATE: WIDTH_WRITE_A NUMERIC "16"
// Retrieval info: PRIVATE: WIDTH_WRITE_B NUMERIC "16"
// Retrieval info: PRIVATE: WRADDR_ACLR_B NUMERIC "0"
// Retrieval info: PRIVATE: WRADDR_REG_B NUMERIC "0"
// Retrieval info: PRIVATE: WRCTRL_ACLR_B NUMERIC "0"
// Retrieval info: PRIVATE: enable NUMERIC "0"
// Retrieval info: PRIVATE: rden NUMERIC "0"
// Retrieval info: LIBRARY: altera_mf altera_mf.altera_mf_components.all
// Retrieval info: CONSTANT: ADDRESS_ACLR_B STRING "NONE"
// Retrieval info: CONSTANT: ADDRESS_REG_B STRING "CLOCK0"
// Retrieval info: CONSTANT: CLOCK_ENABLE_INPUT_A STRING "BYPASS"
// Retrieval info: CONSTANT: CLOCK_ENABLE_INPUT_B STRING "BYPASS"
// Retrieval info: CONSTANT: CLOCK_ENABLE_OUTPUT_B STRING "BYPASS"
// Retrieval info: CONSTANT: INTENDED_DEVICE_FAMILY STRING "Cyclone V"
// Retrieval info: CONSTANT: LPM_TYPE STRING "altsyncram"
// Retrieval info: CONSTANT: NUMWORDS_A NUMERIC "8"
// Retrieval info: CONSTANT: NUMWORDS_B NUMERIC "8"
// Retrieval info: CONSTANT: OPERATION_MODE STRING "DUAL_PORT"
// Retrieval info: CONSTANT: OUTDATA_ACLR_B STRING "NONE"
// Retrieval info: CONSTANT: OUTDATA_REG_B STRING "UNREGISTERED"
// Retrieval info: CONSTANT: POWER_UP_UNINITIALIZED STRING "FALSE"
// Retrieval info: CONSTANT: RAM_BLOCK_TYPE STRING "M10K"
// Retrieval info: CONSTANT: READ_DURING_WRITE_MODE_MIXED_PORTS STRING "DONT_CARE"
// Retrieval info: CONSTANT: WIDTHAD_A NUMERIC "3"
// Retrieval info: CONSTANT: WIDTHAD_B NUMERIC "3"
// Retrieval info: CONSTANT: WIDTH_A NUMERIC "16"
// Retrieval info: CONSTANT: WIDTH_B NUMERIC "16"
// Retrieval info: CONSTANT: WIDTH_BYTEENA_A NUMERIC "1"
// Retrieval info: USED_PORT: clock 0 0 0 0 INPUT VCC "clock"
// Retrieval info: USED_PORT: data 0 0 16 0 INPUT NODEFVAL "data[15..0]"
// Retrieval info: USED_PORT: q 0 0 16 0 OUTPUT NODEFVAL "q[15..0]"
// Retrieval info: USED_PORT: rdaddress 0 0 3 0 INPUT NODEFVAL "rdaddress[2..0]"
// Retrieval info: USED_PORT: wraddress 0 0 3 0 INPUT NODEFVAL "wraddress[2..0]"
// Retrieval info: USED_PORT: wren 0 0 0 0 INPUT GND "wren"
// Retrieval info: CONNECT: @address_a 0 0 3 0 wraddress 0 0 3 0
// Retrieval info: CONNECT: @address_b 0 0 3 0 rdaddress 0 0 3 0
// Retrieval info: CONNECT: @clock0 0 0 0 0 clock 0 0 0 0
// Retrieval info: CONNECT: @data_a 0 0 16 0 data 0 0 16 0
// Retrieval info: CONNECT: @wren_a 0 0 0 0 wren 0 0 0 0
// Retrieval info: CONNECT: q 0 0 16 0 @q_b 0 0 16 0
// Retrieval info: GEN_FILE: TYPE_NORMAL car_tracker8x16.v TRUE
// Retrieval info: GEN_FILE: TYPE_NORMAL car_tracker8x16.inc FALSE
// Retrieval info: GEN_FILE: TYPE_NORMAL car_tracker8x16.cmp FALSE
// Retrieval info: GEN_FILE: TYPE_NORMAL car_tracker8x16.bsf FALSE
// Retrieval info: GEN_FILE: TYPE_NORMAL car_tracker8x16_inst.v FALSE
// Retrieval info: GEN_FILE: TYPE_NORMAL car_tracker8x16_bb.v TRUE
// Retrieval info: LIB_FILE: altera_mf

```