

Nested list ergonomics

ListBuilder.addItem(label, body) appends a list item with a builder callback that scopes children. Per-depth markers, source-order preservation across mixed flat / nested entries, and a built-in marker cascade ship out of the box.

1. Default depth cascade (3 levels)

- Engineering Roadmap
 - Document Engine
 - * Nested lists with a per-depth marker cascade
 - * Table cells that compose a whole flow
 - * Templates v2 with visual parity gate
 - Backend SPI
 - * PdfFragmentRenderHandler is now public
 - * DOCX semantic backend skeleton
- Documentation
 - Migration guide for the layered presets
 - ADRs 0011-0013 published

2. markerFor(depth) overrides + per-item marker

markerFor(0) wins over the cascade default at depth 0, *markerFor(1)* wins at depth 1, and a per-item marker wins over both.

- Templates v2 (Phase A landed)
 - > CV presets — 14 with V1 visual parity
 - > Cover-letter pair presets — 14 paired
- Layout primitives
 - > Nested lists (this example)
 - > Composed table cells (Phase B)

3. Mixed flat and nested authoring (source order preserved)

Flat addItem(String) and *addItem(label, body)* calls *interleave*; the resulting list keeps depth-0 entries in the order they were added.

- Reviewed PR: nested list ergonomics
- Reviewed PR with nested children
 - Followed up on inline-run wrap
 - Ran mvnw verify locally
- Closed bug: marker double-space rendering
- Triaged backlog
 - Shipped: hanging indent on wrapped items
 - CanvasLayerNode parked

4. Depth 4+ falls back to mid-dot

- Plan
 - Phase
 - * Subphase
 - > Step
 - + Sub-step (depth 4)
 - + Another sub-step at depth 4

5. hangingIndent(true) + markerGap(points)

Off by default, a wrapped line is indented with spaces measured to clear the marker, which lands it a fraction of a space past the first line's text. Opting in gives the marker its own measured column, so every line of an item — including one that continues on the next page — starts at one content origin.

- Default: this wrapped item indents its continuation lines with a run of spaces, so they sit slightly right of the first line's text.
 - *hangingIndent(true)*: every line of this item begins directly beneath the first word of its own first line, however many lines it takes and wherever the page break falls.
- => A wider marker takes a wider column — measured, not guessed — and the wrapped lines follow it there.
- Nested lists indent as an outline
 - A child's marker starts where its parent's text starts, and its own wrapped lines hang under its own text.