



20-R-VIB-DY-34

Advanced

A bus has handles for passengers to use while standing up. The handle consists of a bar, sphere at the end, and a spring ^{$k=10 \text{ N/m}$} placed at the midpoint of the bar. The bar is 2m long and 5kg while the sphere has a mass $m = 5 \text{ kg}$. While driving, the transmission breaks down causing a jerking motion and acceleration $a = \sin^2 t$. Assume small angle.

Solution



find equation of motion.

$$a = \sin^2 t \quad \omega = \frac{1}{12} \quad \dots$$

$$l_{\text{com}} = \frac{m_{\text{bar}} \frac{1}{2} l + l m_{\text{sphere}}}{m_{\text{tot}}} = 1.5 \text{ m}$$

$$k \left(\frac{l}{2} \right)^2 \sin \theta - l_{\text{com}} m_{\text{tot}} a_{\text{sys}} + \sin \theta \left(m_{\text{bar}} g \frac{l}{2} + m_{\text{sphere}} g l \right) = I_o \ddot{\theta}$$

small angle

$$I_o = \frac{1}{3} m_{\text{bar}} l^2 + m_{\text{sphere}} l^2$$

$$= l^2 \left(\frac{1}{3} m_{\text{bar}} + m_{\text{sphere}} \right)$$

$$\ddot{\theta} + \theta \left(\frac{m_{\text{bar}} g \frac{l}{2} + m_{\text{sphere}} g l + k \left(\frac{l}{2} \right)^2}{I_o} \right) = \frac{l_{\text{com}} m_{\text{tot}} a_{\text{sys}}}{I_o}$$

$$\theta_p = D \sin \omega_0 t$$

$$\ddot{\theta}_p = -D \omega^2 \sin \omega_0 t$$

$$\omega_n = \sqrt{\frac{157.15}{26.67}} = 2.427 \text{ rad/s}$$

$$\theta(t) = \frac{F_0/k}{1 - \left(\frac{\omega_0}{\omega_n} \right)^2} \sin \omega t$$

$$\theta(t) = 0.397 \sin 2t$$

$$F_0 = l_{\text{com}} m_{\text{tot}} a_{\text{sys}} = 20$$

$$k = m_{\text{bar}} g \frac{l}{2} + m_{\text{sphere}} g l + k \left(\frac{l}{2} \right)^2 = 157.15$$