

[All Collections](#) > [API](#) > [Using parameters to interact with the NationBuilder API](#)

Using parameters to interact with the NationBuilder API

Learn how to get the data you need from the NationBuilder API by appending URL parameters to your requests

Updated over a year ago

- [Filtering](#)
- [Pagination](#)
- [Sparse Fields](#)
- [Sorting](#)
- [Sideload](#)
- [Sideposting](#)

[Filtering](#)[Examples](#)[Pagination](#)[Sparse](#)[Fields](#)[Sorting](#)[Sideload](#)[Sideposting](#)

Filtering

Filtering allows you to narrow down the results returned by the API based on specific attributes. The `filter` parameter can be used with any attribute to return a subset of results.

Basic Filters:

- Simple: `/api/v2/signups?filter[note]=my note`
- Case Sensitive: `/api/v2/signups?filter[note][eq]=My note`
- Prefix: `/api/v2/signups?filter[note][prefix]=my`
- Suffix: `/api/v2/signups?filter[note][suffix]=my`

- Contains: `/api/v2/signups?filter[note][match]=ot`

Numeric Filters:

- Greater than: `/api/v2/signups?filter[donations_amount_in_cents][gt]=500`
- Greater than or equal to: `/api/v2/signups?filter[donations_amount_in_cents][gte]=500`
- Less than: `/api/v2/signups?filter[donations_amount_in_cents][lt]=1000`
- Less than or equal to: `/api/v2/signups?filter[donations_amount_in_cents][lte]=1000`

Null Checks:

- Exists (is not null): `/api/v2/signups?filter[middle_name][not_eq]=null`
- Does not exist (is null): `/api/v2/signups?filter[middle_name]=null`

Nested Filtering: You can also filter sideloaded resources by nesting filter parameters.

- `/api/v2/signups?include=primary_address,work_address,registered_address&filter[addresses][state]=MT`

Important Note: The filter does not remove unassociated Signups from the response. Signups that do not have addresses matching the criteria of the filter will still be included in the payload.

Examples

1. Filter by Note:

```
GET /api/v2/signups?filter[note]=meeting
```

2. Filter by Donations Greater Than a Certain Amount:

```
GET /api/v2/signups?filter[donations_amount_in_cents][gt]=1000
```

3. Filter by Address State:

```
GET /api/v2/signups?include=primary_address&filter[addresses][state]=CA
```

Pagination

By default, index endpoints return 20 results per response. The response includes `self`, `prev`, and `next` links for pagination.

Customizing Page Size and Number:

- Specify size: `/api/v2/signups?page[size]=10`
- Specify page: `/api/v2/signups?page[number]=3`

Sparse Fields

To optimize data transfer, you can use the `fields` parameter to specify only the attributes you need in the response.

Example:

```
GET /api/v2/signups?fields[signups]=first_name,last_name,email
```

Sorting

The `sort` parameter allows you to order the results.

Ascending Order:

```
GET /api/v2/signups?sort=first_name
```

Descending Order:

```
GET /api/v2/signups?sort=-first_name
```

Sideloads

Sideloads enables you to include related resources in the same response. This is

done using the `include` parameter.

Example:

```
GET /api/v2/signups?include=primary_address,work_address
```

Sideposting

Sideposting allows you to create or update a resource alongside a connected resource within the same request.

Creating a Signup with a Recruiter and Tags:

```
{ "data": { "type": "signups", "attributes": { "first_name": "Kim", "last_name":
```

Related Articles

- NationBuilder v2 API Core Concepts >
- NationBuilder API QuickStart Guide >
- API v2 walkthrough >
- Connecting Zapier to NationBuilder >
- Interactive API Documentation | Endpoint Explorer >

Did this answer your question?





[Demos & webinars](#)

[Courses](#)

[Website themes](#)

[API documentation](#)