

Problem Set 1 and First Assignment

Sohaib Sohail

28994

```
sohaib@DESKTOP-9RA7LU4:~/xv6-labs-2025$ git checkout problemSet1
Switched to branch 'problemSet1'
Your branch is up to date with 'origin/problemSet1'.
sohaib@DESKTOP-9RA7LU4:~/xv6-labs-2025$ make grade
make clean
make[1]: Entering directory '/home/sohaib/xv6-labs-2025'
rm -rf *.tex *.dvi *.idx *.aux *.log *.ind *.ilg *.dSYM *.zip *.pcap \
*/*.o */*.d */*.asm */*.sym \
kernel/kernel fs.img \
mkfs/mkfs .gdbinit \
user/usys.S \

```

```
(Old xv6.out.sleep_no_args failure log removed)
== Test sleep, returns ==
$ make qemu-gdb
sleep, returns: OK (0.8s)
== Test sleep, makes syscall ==
$ make qemu-gdb
sleep, makes syscall: OK (1.0s)
== Test sixfive_test ==
$ make qemu-gdb
sixfive_test: OK (1.0s)
== Test sixfive_readme ==
$ make qemu-gdb
sixfive_readme: OK (1.9s)
(Old xv6.out.sixfive_readme failure log removed)
== Test sixfive_all ==
$ make qemu-gdb
sixfive_all: FAIL (0.6s)
...
init: starting sh
$ sixfive sixfive.txt README
GOOD 5
GOOD 100
GOOD 18
GOOD 6
$ qemu-system-riscv64: terminating on signal 15 from pid 3309 (make)
MISSING '^1810'
MISSING '^1810'
QEMU output saved to xv6.out.sixfive_readme
== Test memdump, examples ==
$ make qemu-gdb
memdump, examples: OK (0.7s)
(Old xv6.out.memdump_examples failure log removed)
== Test memdump, format ii, S, p ==
$ make qemu-gdb
memdump, format ii, S, p: OK (1.0s)
== Test find, in current directory ==
$ make qemu-gdb
find, in current directory: OK (1.0s)
(Old xv6.out.find_curdir failure log removed)
== Test find, in sub-directory ==
$ make qemu-gdb
find, in sub-directory: OK (1.0s)
(Old xv6.out.find_subdir failure log removed)
== Test find, recursive ==
$ make qemu-gdb
find, recursive: OK (1.5s)
(Old xv6.out.find_recursive failure log removed)
== Test exec ==
$ make qemu-gdb
exec: OK (0.8s)
== Test exec, multiple args ==
$ make qemu-gdb
exec, multiple args: OK (1.0s)
(Old xv6.out.find_exec_args failure log removed)
== Test exec, recursive find ==
$ make qemu-gdb
exec, recursive find: OK (1.4s)
(Old xv6.out.test_find_sh failure log removed)
== Test time ==
time: FAIL
Cannot read time.txt
Score: 120/131
make: *** [Makefile:361: grade] Error 1
```

Tests

```
xv6 kernel is booting
hart 1 starting
hart 2 starting
init: starting sh
$ sleep 15
$ uptime
exec uptime failed
$ sleep 50
$ echo "5 -10 hello 18/6, xv6 12.13.14" > nums.txt
$ sixfive nums.txt
0
10
0
18
6
0
12
$ memdump
Example 1:
61810
2025
Example 2:
a string
Example 3:
another
Example 4:
B40
1819438967
100
z
xyzzzy
Example 5:
hello
w
o
r
l
d
$ echo > b
$ mkdir a
$ echo > a/b
$ mkdir a/aa
$ echo > a/aa/b
$ find . b
./b
./a/b
./a/aa/b
$ sh < findtest.sh
$ mkdir: a failed to create
$ $ $ $ $ hello
hello
hello
$ $
```