Per-Tier Synchronisation Under a Byte Quota in Federated Learning: A Closed-Form Gain Bound, Peak-Load Control and Schedule Leakage

Abraheem Rashid and Mehwish Mahmood

***Abstract*—Federated learning over constrained links must respect a byte quota, and under client-level differential privacy (DP) every synchronisation is also a privacy release. This article asks whether synchronising model parts at different rates beats a single period. The scheduler TierFed sets one interval per parameter tier by minimising a measured drift surrogate under the quota, keeps the classifier head private and staggers tiers to cap the payload of a single round. Its relaxed programme has a closed form, and a Hölder bound Ψ, measurable at the end of warm-up, limits how far any per-tier schedule can lower the surrogate below a uniform period. In seven settings (specialty groups of a readmission dataset, four label-skew levels, a ResNet, four clinical centres) TierFed showed no relevant gain over the best uniform period at matched bytes. Where Ψ was at most 2.2% it behaved as a uniform period; on the ResNet, with $\Psi = 71.4\%$, it split the tiers as predicted, without a gain in accuracy. On the readmission data this period matched full-rate FedPer to within 0.0007 AUROC, uploading 28% less up to the validation-selected round and 70% less over 60 rounds; at the clinical centres it was 0.0085 AUROC lower unless clients uploaded their locally trained tiers. Staggering reduced the rounds that miss a transfer window from 0.30 to 0.08, at the cost of more wake-ups. Under client-level DP with 20 clients every releasing schedule ended below local training, and an adaptive schedule, LAG, revealed a client's label shift through traffic metadata alone.**

***Index Terms*—Federated learning, communication-efficient learning, local SGD, multi-rate aggregation, network resource allocation, differential privacy, traffic analysis, clinical prediction.**

I. Introduction

FEDERATED learning (FL) trains one predictive model across institutions that do not exchange records [1], [2]. In cross-silo healthcare the participants are a small number of institutions, each connected through a link that its own network team provisions [3], [4]. For the operator of such a link the training job is one more tenant on an uplink with a fixed capacity and a scheduled transfer window, whether the uplink is an institutional WAN, a cellular edge slice or a satellite backhaul, and the job is judged by the number of bytes it sends in each window [5], [6].

The setting considered here is a server that coordinates N clients over R rounds and requests, in each round, some, all or none of the shared parameters. The mean fraction of the shared model transmitted per round must stay within a quota ρ, the accuracy of each client's personalised model should not fall below that of full-rate personalisation, and, where client-level differential privacy (DP) is required, a budget (ε, δ) must hold. Three observations motivate the design studied in this article. Different parts of a network drift apart at different rates between synchronisations. A quota is useful to an operator only if it can be mapped onto a slice allocation or a transfer window, which depends on the payload of individual rounds as well as on their mean. Under client-level DP every transmitting round is a release, so the schedule determines the noise, and a schedule that is computed from the clients' updates is itself an output of the private data.

TABLE I
Classes of Communication-Reducing Methods and the Properties That Each Addresses (–: Not Addressed)

Class	Timing	Budget	Head	DP-eligible
Full-rate averaging [1], [7], [8]	every round	–	shared	yes
Partial personalisation [9]–[11]	every round	–	private	yes
Fixed local period [12], [13]	one, fixed	implicit	shared	yes
Resource-adaptive frequency [14]	one, from model	resources	shared	no
Adaptive period [15]	one, from loss	–	shared	no
Lazy upload [16]	per client, from update	–	shared	no
Layer-wise adaptive [17], [18]	per layer, from data	–	shared	no
TierFed (this article)	per tier, from dispersion	ρ, peak π	private	no
Fixed multi-rate period, TierFed-DP	per tier, planned	ρ, ε	private	yes

Existing work treats these aspects separately. Compression [19], [20] reduces the size of each upload but still sends one in every round. Local SGD with a fixed period [12], [13], [21], AdaComm [15], LAG [16] and the resource-constrained aggregation frequency of Wang *et al.* [14], which is the closest prior work for edge systems, transmit less often and use one period for the whole model. Partial personalisation [9]–[11] keeps a head or a representation local, and layer-wise schemes derive per-layer intervals from a discrepancy measure [17] or freeze layers that have converged [18]. FL over wireless and satellite links has been studied through the joint design of learning and communication [6] and through visibility-aware aggregation [22]. Client-level DP follows [23] with Rényi accounting [24], [25]; correlated noise [26], [27] and adaptive clipping [28] improve its utility, and record-level guarantees may be better suited to cross-silo FL [29], [30]. Gradient inversion [31], [32] and membership inference [33], [34] quantify what an adversary can recover from the exchanged updates. As Table I shows, none of these methods accepts a byte quota, sets per-tier intervals from measurements together with a condition under which such intervals can improve on a uniform period, withholds the head, and is evaluated under one link model and one DP accountant.

A. Rashid is with the Department of Computer Science, Brunel University London, Uxbridge UB8 3PH, U.K. (e-mail: 2546393@brunel.ac.uk).
M. Mahmood is with Queen's University Belfast, Belfast, U.K.
Corresponding author: Abraheem Rashid.

The contributions of this article are as follows.

1) **A quota-constrained multi-rate scheduler and a bound on its benefit** (Section III). TierFed minimises a measured surrogate $\sum_g K_g^2 \hat{\Gamma}_g$ of the drift between the clients' copies of each tier, subject to $\sum_g w_g/K_g \le \rho$, and never transmits the classifier head. The relaxed programme has the closed form $K_g \propto (w_g/\Gamma_g)^{1/3}$, and a Hölder bound Ψ, which can be measured at the end of warm-up, limits how far any per-tier schedule can lower the surrogate below a uniform period. Phases chosen by a gcd condition bound the payload of a single round at the same long-run payload fraction.
2) **An analysis of the schedule as a privacy release** (Sections III-D and V-G). A schedule computed from client updates is not covered by the client-level Gaussian accountant and is visible in the traffic metadata. A timing experiment measures what a passive observer learns from it, and the schedules that the accountant does cover are compared with local training at a matched budget.
3) **An evaluation designed to detect the absence of a gain** (Sections II, IV and V). The reported round is selected on per-client validation data, every baseline is tuned over its own communication parameter, and local, centralised and gradient-boosting references bound the task. The comparison is repeated under label skew, on a deeper backbone, on a dataset whose clients are real clinical centres, and with a second synchronisation step. A consistency check recomputes every planned release, uncompressed upload and DP charge from the stated rules, and part of the runs is repeated on a second machine.

The main findings can be summarised briefly. In none of the seven settings was TierFed more accurate than the best uniform period at matched bytes. Where Ψ is small the scheduler selects a uniform period, as the bound predicts, and on the ResNet, where Ψ is 71.4%, the tiers are split close to the predicted ratio but the AUROC does not improve. How a sparse uniform period compares with full-rate personalisation depends on the dataset and on how a tier is synchronised. The tier structure is useful for a different purpose, the control of the payload of a single round. Under client-level DP with 20 clients, every schedule that releases anything ends below local training.

II. System Model and Study Design

This section defines the setting in which the scheduler operates: the federation, its parameter tiers and the synchronisation step, the cost of a round on a constrained uplink, the data and the clients, and the metrics by which every method is judged. It ends with the problem that a schedule has to solve.

A. Federation, Tiers and Synchronisation

The federation has N clients. Client k holds a private dataset $\mathcal{D}_k$ of n_k records, with $n = \sum_k n_k$ and $p_k = n_k/n$, and the shared objective is $F(\theta) = \sum_k p_k F_k(\theta)$ with $F_k(\theta) = \mathbb{E}_{\xi\sim\mathcal{D}_k}[f(\theta;\xi)]$. The parameters are partitioned into disjoint tiers $\mathcal{G} = \{\mathrm{s},\mathrm{m},\mathrm{f}\}$ (slow, medium, fast) according to their position in the forward computation graph: the input projection, the hidden blocks and the classifier head. The fast tier is private to each client and is never transmitted, so the shared tiers are $\mathcal{G}_{\mathrm{sh}} = \{\mathrm{s},\mathrm{m}\}$, and FedPer-style personalisation [9] is the special case in which both are synchronised in every round.

The server keeps one copy $\theta_g^{(r)}$ of each shared tier, and client k keeps its own copy $\theta_{k,g}$ of every tier. Let $\mathcal{A}_r \subseteq \mathcal{G}_{\mathrm{sh}}$ denote the tiers that are due in round r and $\mathcal{S}_r$ the participating clients. A round consists of three steps. First, each client replaces its copy of every due tier by the server copy and leaves its other tiers as they are,

$$\theta_{k,g}^{(r,0)} = \begin{cases} \theta_g^{(r)}, & g \in \mathcal{A}_r, \\ \theta_{k,g}^{(r-1,+)}, & g \notin \mathcal{A}_r, \end{cases} \tag{1}$$

where $\theta_{k,g}^{(r-1,+)}$ is its copy at the end of the previous round. Second, the client performs one local epoch of $s_k = \lceil n_k/B \rceil$ optimiser steps with batch size B on all of its tiers, which yields $\theta_k^{(r,s_k)}$, and uploads the due tiers. Third, the server averages the tiers it has received, and every client adopts the result,

$$\theta_g^{(r+1)} = \begin{cases} \sum_{k\in\mathcal{S}_r} n_k\, \theta_{k,g}^{(r,s_k)} \big/ \sum_{k\in\mathcal{S}_r} n_k, & g \in \mathcal{A}_r, \\ \theta_g^{(r)}, & g \notin \mathcal{A}_r, \end{cases} \tag{2}$$

$$\theta_{k,g}^{(r,+)} = \begin{cases} \theta_g^{(r+1)}, & g \in \mathcal{A}_r, \\ \theta_{k,g}^{(r,s_k)}, & g \notin \mathcal{A}_r. \end{cases} \tag{3}$$

Three properties of this rule are used in the rest of the article. A tier that is not due is neither reset nor frozen: the client continues to train its own copy, and the server copy does not change. When the tier next becomes due, (1) replaces the client's copy by the server copy, so the steps that a client takes on a tier between two of its synchronisations adapt the client's own model, which is the model evaluated in Section II-D, but are not uploaded. As a result, every upload is one local epoch away from a value that all clients share, whatever the interval, and both the update that is clipped under DP (Section III-D) and the dispersion that the scheduler measures (Section III-A) are defined on it. This is referred to as the *restart step*. The alternative, in which (1) is skipped after the first round so that a tier is uploaded after all the local epochs since its last synchronisation, is local SGD with one period per tier [12], [21]; it is referred to as the *carry-over step* and is evaluated in Section V-E. Finally, the optimiser state belongs to the client. The experiments use Adam, whose moment estimates and step count each client keeps from round to round for all of its parameters; they are not reset when (1) or (3) replaces the values of a tier.

With w_g the share of the shared payload carried by tier g, round r transmits the fraction $P_r = \sum_{g\in\mathcal{A}_r} w_g$ of it. The payload fraction over the R rounds and its limit after warm-up are

$$\Pi_R(\mathbf{K}) = \frac{1}{R}\sum_{r=1}^{R} P_r, \qquad \Pi_\infty(\mathbf{K}) = \sum_{g\in\mathcal{G}_{\mathrm{sh}}} \frac{w_g}{K_g}, \tag{4}$$

where $\mathbf{K} = (K_g)_g$ collects the intervals. A round with $\mathcal{A}_r = \emptyset$ transmits nothing, and such local-only rounds make a quota below $\min_g w_g$ attainable.

B. Links and Network Cost

The job is costed on a link profile (β, ℓ, P) that consists of an uplink rate, a round-trip latency and a transmit power. With independent links, a round in which client k sends b_k bits costs

$$t_r = \max_k \frac{b_k}{\beta} + \ell, \qquad E_r = \sum_k \frac{b_k}{\beta} P, \tag{5}$$

and nothing when no client sends. When the clients share one uplink in time division, $t_r = \sum_k b_k/\beta + \ell$ instead, and a saving in bytes is a saving in time in the same proportion. Three further quantities describe the load on the link,

$$v(W) = \frac{1}{R}\sum_{r=1}^{R} \mathbb{1}[t_r > W], \qquad \hat{P} = \max_{r>T_w} P_r, \qquad u_k = \sum_{r=1}^{R} \mathbb{1}[b_{k,r} > 0], \tag{6}$$

namely the share of rounds that miss a transfer window W, the largest payload fraction of a round after the warm-up of T_w rounds (Section III), and the number of radio wake-ups of client k. On cellular radios each wake-up costs a promotion delay and a high-power tail that do not depend on the payload [35], [36], so u_k is reported together with the bytes. Three profiles are used, with values chosen for this study: a cell-edge 5G NR uplink (5 Mbit/s, 30 ms, 0.2 W; NR deployment scenarios in [37]), an LEO satellite uplink (10 Mbit/s, 40 ms, 2 W) and a wired institutional WAN (100 Mbit/s, 10 ms). These are representative targets and not measurements. The model translates the logged uplink bits into time and energy and does not include scheduling, fading or retransmission; its implementation is checked against paced TCP in Section V-F.

C. Data and Clients

Diabetes 130-US Hospitals [38] is the main benchmark. The task is the prediction of readmission within 30 days from encounter-level features. Cleaning follows Strack *et al.*: encounters that ended in death or discharge to hospice are removed and the first encounter of each patient is kept, which leaves one encounter for each of 69,990 patients, 160 encoded features and a positive rate of 9.0%. A patient-grouped fifth of the data (13,998 patients) is set aside and enters no reported result; the other 55,992 patients are assigned to the clients. The public release carries no hospital identifier, so the clients of this benchmark are not hospitals. They are 20 groups of patients formed from the medical-specialty column by longest-processing-time bucketing with a share cap of 15% (specialties above the cap are split, patient-grouped), and they are referred to as *specialty groups* throughout. The largest group holds 12% of the training data, and the mean total-variation distance between the label distributions of two groups is 0.009. Because this partition is close to IID, the same patients are also partitioned by Dirichlet label skew with $\alpha \in \{0.1, 0.3, 1, 10\}$.

TABLE II
EXPERIMENTAL CONFIGURATION

Item	Value
Main data	Diabetes 130-US: 69,990 patients, 55,992 of them at the clients, 160 features, positive rate 9.0%; 20 specialty groups (share cap 15%) or Dirichlet $\alpha \in \{0.1, 0.3, 1, 10\}$
Clinical centres	Fed-Heart-Disease: 920 patients, 736 of them at 4 centres, 36 features, positive rate 55%
Backbones	MLP 128–128–64 (45,506 parameters on the main data; tier shares 45.3/54.4/0.3%); tabular ResNet (width 128, depth 6)
Training	60 rounds, one local epoch, batch 64 (32 at the centres), Adam 10^{-3} with state kept per client, inverse-frequency class weights; per-client patient-grouped split 70/10/20%
TierFed	$T_w = 5$, $K_{\max} = 8$, $\rho = 0.25$ (post-warm-up) unless stated; exact solver
Baselines	FedProx $\mu = 10^{-2}$; FedLAMA-style interval 5, factor 2; AdaComm initial period $\{4, 8, 16\}$; LAG $\xi \in \{1, 2{\cdot}10^3, 5{\cdot}10^3, 10^4\}$; uniform periods $K \in \{1, 2, 4, 6, 8\}$ and staggered $(4, 4)$ on (16), $T_w = 5$
DP	$C = 1$, $\delta = 10^{-5}$, $\varepsilon^\star = 4$, $q = 1$; z calibrated per method; planner $\lambda = 1$

All values are read from the configuration file and the run logs.

Fed-Heart-Disease [39], [40] provides clients that are real institutions. It consists of the four collections of the UCI Heart Disease data, which were recorded at the Cleveland Clinic Foundation, the Hungarian Institute of Cardiology in Budapest, the university hospitals of Zurich and Basel (one collection) and the VA Medical Center in Long Beach. Each collection is one client, and they are referred to as the four *clinical centres*. The data comprise 920 patients, one record each, with 36 encoded features (indicators of missing values included) and the presence of angiographic disease as the label. As on the main benchmark a fifth of the patients is set aside, which leaves 736 patients at the centres, between 95 and 248 per centre, with a prevalence between 37% and 93%. This dataset is run under the protocol of the main benchmark, with a batch size of 32 because of the small centres. On both datasets numeric features are standardised, and missing values imputed, with statistics of the pooled data that do not involve the labels. PneumoniaMNIST [41] under Dirichlet label skew is reported in the supplement.

D. Metrics

The patients of each client are split into training, validation and test sets (70/10/20%, patient-grouped), and $\mathcal{V}_k$ and $\mathcal{T}_k$ denote the last two. With $\mathrm{AUC}_k^{\mathcal{T}}(r)$ the AUROC of client k's own model after round r on $\mathcal{T}_k$, the personalised AUROC and the reported round are

$$A^{\mathcal{T}}(r) = \frac{\sum_k |\mathcal{T}_k| \,\mathrm{AUC}_k^{\mathcal{T}}(r)}{\sum_k |\mathcal{T}_k|}, \qquad \hat{r} = \min\Big\{ \arg\max_{r \le R} A^{\mathcal{V}}(r) \Big\}, \tag{7}$$

where $A^{\mathcal{V}}$ is the same average over the validation splits. Clients whose split contains a single class are left out of




Fig. 1. Pipeline of the study, from the public data to the reported numbers. All stages are run by one command, which first checks that repeated runs are bit-identical.

the corresponding average, identically for every method. The primary metric is $A^{\mathcal{T}}(\hat{r})$, and test data are never used to select anything.

The cost paired with it is the upload. With $b_{k,t}$ the bits that client k sends in round t, the cumulative upload after round r is

$$B(r) = \frac{1}{8 \cdot 10^6} \sum_{t=1}^{r} \sum_{k} b_{k,t} \quad \text{(MB)}. \tag{8}$$

Two readings of (8) are reported and are kept apart throughout. $B(\hat{r})$ is the upload needed to obtain the reported model and is the cost that belongs to the primary metric. $B(R)$ is the upload of the whole training budget of $R = 60$ rounds, which a deployment without early stopping would send. A full-rate method continues to transmit after its selected round, so $B(R)$ shows a larger saving for sparse schedules than $B(\hat{r})$ does, and every statement about a saving names the reading on which it is based.

Secondary metrics are the mean of $A^{\mathcal{T}}$ over the last ten rounds, over the rounds of the last twenty that directly follow a synchronisation, and at $r = R$; the expected calibration error (ECE) and the Brier score [42] before and after Platt scaling [43] fitted on $\mathcal{V}_k$; and the AUROC of the worst client, $\min_k \mathrm{AUC}_k^{\mathcal{T}}(\hat{r})$. Fig. 1 summarises the study.

E. Problem Statement

Given a quota ρ on the payload fraction (4), optionally a cap π on the payload of any single round and a privacy budget $(\varepsilon^\star, \delta)$, the scheduler chooses intervals $\mathbf{K}$ and phases $\boldsymbol{\phi}$ for

$$\max_{\mathbf{K},\boldsymbol{\phi}} \; A^{\mathcal{T}}(\hat{r}) \quad \text{s.t.} \quad \Pi_\infty(\mathbf{K}) \le \rho, \quad \hat{P} \le \pi, \quad \varepsilon(\mathbf{K}) \le \varepsilon^\star. \tag{9}$$

A schedule is regarded as successful if $A^{\mathcal{T}}(\hat{r})$ is non-inferior to that of full-rate personalisation and at least as high as that of the best uniform period at the same bytes. The objective is not known before training, so Section III optimises a surrogate. The quantity $\varepsilon(\mathbf{K})$ is defined only for a schedule that is fixed before training, because the accountant charges only data-independent releases.

III. Quota-Constrained Multi-Rate Scheduling

The scheduler separates four decisions: which parameters are sent (the tiers), when they are sent (per-tier intervals chosen under the quota), how large an upload is (an optional compressor), and how private it is (the DP mechanism and its accountant). Fig. 2 shows the architecture.

A. Dispersion Measurement

TierFed estimates how strongly the clients disagree on each tier from the slices that it receives. For tier g with tensors $j \in g$,

$$\hat{\Gamma}_g^{(r)} = \frac{\sum_{j \in g} \frac{1}{|\mathcal{S}_r|} \sum_{k \in \mathcal{S}_r} \left\| \theta_{k,j}^{(r,s_k)} - \bar{\theta}_j^{(r)} \right\|_2^2}{\sum_{j \in g} \left\| \bar{\theta}_j^{(r)} \right\|_2^2 + \xi_0}, \tag{10}$$

where $\bar{\theta}_j^{(r)}$ is the unweighted mean of the received tensors and $\xi_0 = 10^{-12}$. The ratio is scale-free, which makes tiers of different magnitude comparable. It is available only for the tiers received in round r, and the last value is carried forward for the others.

Under the restart step the received slices are one local epoch away from a common value, so $\hat{\Gamma}_g$ does not depend on the interval that preceded the upload, and the controller does not measure the effect of its own earlier decisions. The logs confirm this. For uniform periods K from 1 to 8 on the main benchmark, the mean of $\hat{\Gamma}_g$ over the synchronisation rounds after warm-up lies between 4.59 and 5.93 ($\times 10^{-3}$) for the slow tier and between 6.93 and 7.71 for the medium tier (supplement, Table S-IV). Under the carry-over step the same quantity grows with the interval, by factors of 7.5 and 5.3 for the two tiers at $K = 4$ and of 26.9 and 11.9 at $K = 8$.

B. Cost of an Interval, Programme and Closed Form

Assumptions. The analysis concerns the shared tiers with the private heads held fixed, local SGD with step size η in place of Adam, the same number s of local steps at every client, and equal aggregation weights $1/N$. Each F_k is assumed to be block separable, $F_k(\theta) = \sum_g F_{k,g}(\theta_g)$, with L-smooth blocks, so that the gradient of a tier does not depend on the other tiers; this removes the coupling between tiers and is the main idealisation. Stochastic gradients are unbiased with variance at most σ_g^2 on tier g, the heterogeneity of tier g is bounded, $\frac{1}{N}\sum_k \|\nabla_g F_k(\theta) - \nabla_g F(\theta)\|^2 \le \Gamma_g$, and $F_g = \frac{1}{N}\sum_k F_{k,g}$ is bounded below by $F_g^\star$ [12], [21]. The experiments depart from these assumptions in that they use Adam, $s_k = \lceil n_k/B \rceil$ steps, sample weights and a coupled network, and with unequal s_k plain averaging converges towards a reweighted objective [44]. The two propositions describe the idealised system. They motivate the schedule and are not used to predict accuracy.

Proposition 1 (Cost of an interval under the restart step)**.** *Let tier g be synchronised every K_g rounds by (1)–(3). There are*




Fig. 2. Architecture of the scheduler and its environment. Solid arrows carry data and policy inputs, and dashed arrows carry measurements that are fed back. Only the active tiers are broadcast and replaced at the client (1); the other tiers stay at the client and continue to be trained. Under DP the dashed path from the received slices to the solver is removed, and the schedule is planned before training (Section III-D).

absolute constants c_0, c_1, c_2 such that the following holds for $\eta \le c_0/(LK_{\max}s)$.
(a) Client copies. *After $m \ge 1$ local epochs from a common value of tier g, with $\bar{\theta}_g = \frac{1}{N}\sum_k \theta_{k,g}$,*

$$\frac{1}{N}\sum_{k=1}^{N} \mathbb{E}\big\|\theta_{k,g} - \bar{\theta}_g\big\|^2 \le c_2\,\eta^2 s^2 m^2 \big(\Gamma_g + \sigma_g^2\big), \tag{11}$$

and $m \le \max(1, K_g - 1) \le K_g$ at every point of the schedule.
(b) Server copy. *Let $r_1 < \cdots < r_{J_g}$ be the rounds up to R in which tier g is due, and $D_g = F_g(\theta_g^{(1)}) - F_g^\star$. Then*

$$\min_{1\le j\le J_g} \mathbb{E}\big\|\nabla_g F(\theta^{(r_j)})\big\|^2 \le \frac{c_1 D_g}{\eta s J_g} + c_1 \eta L\,\frac{\sigma_g^2}{N} + c_2\,\eta^2 L^2 s^2 \big(\Gamma_g + \sigma_g^2\big). \tag{12}$$

The proof is given in the supplement (Section S1). Part (a) is the drift lemma of local SGD [12], [45] applied to one tier. Part (b) holds because, under block separability, the steps that a client takes on a tier between two synchronisations of that tier never enter the server copy, so the synchronisations of tier g form a sequence of J_g rounds of federated averaging with s local steps [8], [44]. The variance in the second term of (12) is divided by N because every step of the averaged model combines one stochastic gradient from each client. These N gradients are independent, each has a variance of at most σ_g^2, and their average with equal weights therefore has a variance of at most σ_g^2/N, which is the linear speed-up of local SGD in the number of clients. With the sample weights p_k of (2) the factor $1/N$ becomes $\sum_k p_k^2 = 1/N_{\text{eff}}$. On the main benchmark $\sum_k p_k^2 = 0.085$, which corresponds to $N_{\text{eff}} = 11.8$ for $N = 20$, and at the clinical centres $N_{\text{eff}} = 3.6$ for $N = 4$.

Under the restart step an interval therefore has two costs. By (12), the server copy of tier g receives $J_g \approx T_w + (R - T_w)/K_g$ aggregation rounds instead of R, so the first term grows in proportion to K_g while the last term does not depend on K_g. By (11), the clients' own copies, which are the models that are evaluated, drift apart between synchronisations by an amount that grows as K_g^2. Under the carry-over step the two costs merge into the bound of local SGD with period $K_g s$ [21]: the K_g local epochs enter the average, J_g is replaced by R, and the last term of (12) becomes $c_2\eta^2 L^2 s^2 K_g^2(\Gamma_g + \sigma_g^2)$. In both cases $K_g^2(\Gamma_g + \sigma_g^2)$ measures what a long interval costs on tier g, and it is small only for a tier on which the clients agree.

Programme. Given a quota ρ, the controller solves

$$\mathbf{K}^\star = \arg\min_{K_g \in \{1,\dots,K_{\max}\}} \sum_{g\in\mathcal{G}_{\text{sh}}} K_g^2\,\hat{\Gamma}_g \quad \text{s.t.} \quad \sum_{g\in\mathcal{G}_{\text{sh}}} \frac{w_g}{K_g} \le \rho. \tag{13}$$

The objective is the right-hand side of (11) at its largest value $m = K_g$, summed over the shared tiers, with the measured $\hat{\Gamma}_g$ in the place of $\Gamma_g + \sigma_g^2$; the factor $c_2\eta^2 s^2$ is common to the tiers and does not change the minimiser. The proxy is not an estimate of $\Gamma_g + \sigma_g^2$. Its numerator is the dispersion after one local epoch, in which the noise and the heterogeneity enter with different powers of s, and its denominator is the squared norm of the tier, which differs between tiers. The programme does not contain the server-side cost of (12) either. The programme is thus a heuristic surrogate, and every statement below about (13) concerns this surrogate. With the head private, $\mathcal{G}_{\text{sh}} = \{\text{s}, \text{m}\}$ and $K_{\max} = 8$, the programme has 64 candidates and is solved by enumeration, with ties broken in favour of the denser schedule.

Proposition 2 (Closed form and the value of differentiation)**.** *Let $\Gamma_g > 0$, $w_g > 0$, $\sum_g w_g = 1$, and relax K_g to the positive reals. Then (13) has the unique minimiser*

$$K_g^\star = \Big(\frac{w_g}{\Gamma_g}\Big)^{1/3} \frac{S}{\rho}, \qquad S = \sum_h w_h^{2/3}\Gamma_h^{1/3}, \tag{14}$$

with value $J^\star = S^3/\rho^2$. The uniform interval $K = 1/\rho$ costs $J_{\text{u}} = \sum_g \Gamma_g/\rho^2$, and

$$\Psi = 1 - \frac{J^\star}{J_{\text{u}}} = 1 - \frac{S^3}{\sum_g \Gamma_g} \in [0, 1), \tag{15}$$

with $\Psi = 0$ if and only if w_g/Γ_g is the same for all tiers. When $1/\rho$ is an integer, no integer schedule lowers the objective of (13) below that of the uniform period by more than the fraction Ψ.

The proof (supplement, Section S1) uses the KKT conditions of the convex programme, Hölder's inequality with

exponents $3/2$ and 3 for $\Psi \geq 0$, and the integer feasibility of $K = 1/\rho$. Two properties of the closed form are used in the evaluation. First, the ratio of two intervals, $K_a/K_b = (w_a\Gamma_b/w_b\Gamma_a)^{1/3}$, compresses differences between tiers: a factor of eight in the ratio of payload to dispersion is needed for a factor of two in the interval, so tiers with similar ratios receive the same interval after rounding. Second, the proposition holds for any positive weights and therefore applies exactly to (13) with $\hat{\Gamma}_g$ in the place of Γ_g. Ψ is invariant to a factor common to all tiers. Evaluated on $\hat{\Gamma}_g$ at the end of warm-up, it states, before any sparse round has taken place, by how much a per-tier schedule can lower the surrogate below a uniform one. It does not state how much accuracy such a reduction is worth.

C. Schedule Rule, Phases and the Quota

Rounds are indexed $r = 1, \ldots, R$. The first T_w rounds synchronise every shared tier, and thereafter tier g is due when

$$\mathcal{A}_r = \begin{cases} \mathcal{G}_{\mathrm{sh}}, & r \leq T_w, \\ \{g : \ (r - T_w - \phi_g) \bmod K_g = 0\}, & r > T_w, \end{cases} \quad (16)$$

with phase $\phi_g = 0$ unless the tiers are staggered. The fixed periods, the DP planner and the accountant all use this rule, and the consistency check of Section V-A recomputes every release from it. Adaptive TierFed sends tier g when at least K_g rounds have passed since its last synchronisation, which coincides with (16) whenever $\mathbf{K}$ is constant after warm-up. $T_w = 5$ and $K_{\max} = 8$ throughout. Fig. 3 shows one round at the server.

Phases and the peak. A quota on the mean does not bound the payload P_r of a single round, because tiers with aligned phases are due together and then send the full shared payload. Two tiers with phases ϕ_a and ϕ_b are never due in the same round if and only if $\phi_a - \phi_b \not\equiv 0 \pmod{\gcd(K_a, K_b)}$ (supplement, Section S1). With $\gcd(K_a, K_b) \geq 2$ the offset $\lfloor \gcd/2 \rfloor$ separates them and bounds the peak after warm-up by $\max_g w_g$ at the same long-run payload fraction Π_∞; over a finite horizon Π_R can differ slightly, because the phase changes which synchronisations fall inside it. With co-prime intervals no phase separates the tiers. The staggered variant adds the constraint $\max_{r>T_w} P_r \leq \pi$ to (13) and checks it over one hyper-period $\mathrm{lcm}(\mathbf{K})$. The warm-up rounds still send the whole payload, and they can be sent with eight-bit quantisation to lower their peak as well.

The quota. Solving (13) with ρ bounds Π_∞ of (4) and not the realised Π_R: a warm-up of T_w rounds at payload fraction c_w adds $T_w(c_w - \Pi_\infty)/R$ to the realised fraction. A quota over all rounds is met by solving with $\rho' = (\rho R - c_w T_w)/(R - T_w)$. Both forms are reported, and the realised Π_R is read from the logs.

Compression. An optional compressor acts on each client's update relative to the broadcast, with error feedback. It emits a fraction $\kappa \in (0, 1]$ of the float32 bits, and the bits that it emits are the bits that are counted.

D. Privacy: Threat Model, Mechanism and Eligible Schedules

Threat model. Clients send their updates over TLS to an aggregator that is trusted to apply the mechanism and sees the raw updates, as in central DP-FedAvg [23]. Central DP protects the released aggregates against those who receive them, the other clients among them. A passive network observer cannot read the payloads but sees when each client transmits and how many bytes it sends, which is exactly the schedule. A schedule that depends on client data can leak for this reason even when every payload is encrypted. Secure aggregation with distributed noise [46] would remove the trust in the aggregator but not this metadata. Poisoning is outside the scope of this article.




Fig. 3. Flow of one round at the server. In a local-only round the clients still train their own copies. Under DP the schedule is fixed before training, and the dispersion is never computed from the private slices.

Mechanism. In each round every client joins the cohort $\mathcal{S}_r$ independently with probability q. Full participation, $q = 1$, is the primary cross-silo setting, and $q < 1$ is examined as a sensitivity analysis. The server clips the update $\Delta_k = \theta_k^{(r,s_k)} - \theta^{(r)}$ of every participating client on the due tiers and adds noise to the sum before dividing by the *fixed* expected cohort size,

$$\tilde{\Delta} = \frac{1}{qN}\Big(\sum_{k \in \mathcal{S}_r} \Delta_k \min\big(1, \tfrac{C}{\|\Delta_k\|_2}\big) + \mathcal{N}(0, z^2C^2I) \Big), \quad (17)$$

which is the fixed-denominator estimator of DP-FedAvg [23]. Adding or removing one client changes the sum by at most C in ℓ_2 norm, and the denominator reveals nothing about the realised cohort; a planned release whose cohort is empty still adds noise. Because of the restart step, Δ_k is the result of one local epoch for every schedule, so the clipping norm C has the same meaning for all of them. The server applies the mechanism to every method in the same way.

Accountant. Over the R_{tx} planned releases, the Rényi DP of the Poisson-subsampled Gaussian mechanism is composed

at integer orders [25],

$$\varepsilon_\alpha = \frac{R_{\mathrm{tx}}}{\alpha-1}\log\sum_{k=0}^{\alpha}\binom{\alpha}{k}(1-q)^{\alpha-k}q^k e^{\frac{k^2-k}{2z^2}},$$
$$\varepsilon = \min_\alpha\Big\{\varepsilon_\alpha + \frac{\log(1/\delta)}{\alpha-1}\Big\}, \tag{18}$$

with $\delta = 10^{-5}$; for $q = 1$ this reduces to $R_{\mathrm{tx}}\alpha/(2z^2)$ [24]. The implementation is checked against the TensorFlow-Privacy reference and the closed form for $q = 1$ (supplement, Section S2). At $q = 1$ the exact privacy of R_{tx} Gaussian releases is μ-Gaussian DP with $\mu = \sqrt{R_{\mathrm{tx}}}/z$ [47], [48]. This exact accountant and (18) both depend on R_{tx} only through R_{tx}/z^2, so the exact one would lower the noise multiplier of every method by the same factor, between 13% and 24% for $\varepsilon^\star$ from 8 to 1 (supplement, Section S2). The comparison at matched ε is unaffected by the choice of accountant, and every reported ε is an upper bound. The multiplier z is calibrated to the release count of each method by bisection on (18).

Which schedules are covered. The accountant covers a release only if the decision to release does not depend on the private data. This holds for FedAvg, FedProx, FedPer, local training, a fixed period and the planner described below, whose release rounds are fixed before training. It does not hold for adaptive TierFed, AdaComm, LAG or the FedLAMA-style rule, whose schedules are functions of client updates or losses, and the released code refuses to run these under DP. Privacy filters and odometers [49] and the sparse vector technique [50] charge for data-dependent release decisions, whereas FL schedulers take such decisions without charging for them. DP-FTRL [26] and matrix-factorisation mechanisms [51] are suited to full participation but also require data-independent release rounds, and they are not evaluated here.

Planning under a privacy budget (TierFed-DP). A planner that respects the accountant chooses $\mathbf{K}$ before training from public quantities only: $(\varepsilon^\star, \delta)$, q, R, T_w, w_g and ρ. For each candidate it computes the release set of (16) and the smallest $z(\mathbf{K})$ that keeps these releases $(\varepsilon^\star, \delta)$-DP, and it minimises

$$J(\mathbf{K}) = \frac{\sum_g w_g K_g^2}{K_{\max}^2} + \lambda\,\frac{\sum_r P_r(\mathbf{K})\,z(\mathbf{K})^2}{\sum_r P_r(\mathbf{1})\,z(\mathbf{1})^2} \tag{19}$$

over the candidates whose realised payload fraction Π_R, warm-up included, is within the quota. The first term is the drift cost of (13) under a flat prior $\Gamma_g \propto w_g$, the second is the injected noise energy, and each is normalised by its largest value; fewer releases need less noise but allow more drift. Under the flat prior Proposition 2 gives $\Psi = 0$, so the relaxed minimiser of the first term is a uniform period. The integer planner is not restricted to equal intervals, however. Evaluated on a grid of 35 combinations of the prior weight λ and the quota (supplement, Table S-III), it returns equal intervals in 31 of them, among which are all those in which the quota does not bind, and the unequal pair (5,6) in the remaining 4, all at $\rho = 0.25$, where the warm-up rounds make $(4, 4)$ infeasible; the choice does not depend on $\varepsilon^\star$. In the DP experiments of this article, which use $\rho = 1$ and $\lambda = 1$, the planner selects $(3, 3)$ in every seed. It is evaluated as an ablation of planning under a budget and is not claimed as a contribution.

IV. Experimental Setup

Every method is run under the protocol of Section II on the same seeds and data splits, and every number is read from the logs. This section lists the experiment families, the baselines and reference bounds, the privacy and timing experiments, and the statistical procedure that decides each comparison.

Experiment families. The main protocol comprises 946 runs, which are listed by family in the supplement (Table S-V): the main comparison on the specialty groups and at the clinical centres, the accuracy–upload frontier with the communication parameter of every method swept, the label-skew sweep and the ResNet backbone, which examine the regimes to which Proposition 2 points, the round-sparse schedules with the carry-over step of Section II-A, and the matched-ε, timing and peak-aware runs. Additional experiments that were read at the final round without a validation split are reported in Section S9 of the supplement and are identified there as such.

Baselines and bounds. The full-rate methods are FedAvg [1], FedProx [7] and FedPer [9], the last of which is the reference of the non-inferiority tests. The round-sparse methods are AdaComm [15], LAG [16], a FedLAMA-style per-layer interval rule reimplemented from its published description [17], and fixed periods on (16) with the private head and the warm-up of TierFed. LAG is run with the sample weights of (2) and, as a variant, with equal client weights. All round-sparse methods run on the protocol of Section II-A, restart step included, so that the comparison isolates the schedule; AdaComm and the fixed local period as published upload the result of all local steps since the last synchronisation, which corresponds to the carry-over step of Section V-E. Three references bound the task: local training without communication, a centralised MLP trained on the pooled training splits of all clients for the same number of passes, and gradient boosting [52]. All three are scored on the same per-client test splits, with the round, epoch or iteration chosen on validation. SCAFFOLD [8], whose control variates are defined for SGD, is reported with an SGD local solver in the supplement.

Differential privacy. FedPer, the fixed periods $K = 4$ and $K = 8$, one-shot federation (no warm-up and a single release in round R, after a data-independent broadcast of the initial model) and the planner are run at $\varepsilon^\star = 4$, $\delta = 10^{-5}$, $q = 1$ and $C = 1$, each with z calibrated to its own release count. Local training is the reference with $\varepsilon = 0$ on the same splits. Sweeps with $q < 1$ over $\varepsilon^\star \in \{1, 2, 4, 8\}$ for 20 and 100 clients are reported in the supplement.

Timing side channel. One target client holds half of its labels flipped (shifted world) or none (clean world). A passive observer sees which rounds carry traffic and how many bytes each client sends, and summarises a run by one of four observables o: the number of rounds with traffic, the number of rounds in which the target transmits, the bytes of the target, or the bytes of all clients. The power of the observer is the Mann–Whitney AUC over the n_1 shifted and n_0 clean runs,

$$\mathrm{AUC} = \frac{1}{n_1 n_0}\sum_{i=1}^{n_1}\sum_{j=1}^{n_0}\Big(\mathbb{1}\big[o_i^{(1)} > o_j^{(0)}\big] + \tfrac{1}{2}\mathbb{1}\big[o_i^{(1)} = o_j^{(0)}\big]\Big), \tag{20}$$

which equals 0.5 when the schedule reveals nothing. Its significance is assessed by a permutation test: the statistic is the largest value of $|\mathrm{AUC} - 0.5|$ over the four observables, and its null distribution is obtained from 10,000 random reassignments of the runs to the two worlds, which accounts for the choice among observables. A schedule is reported as leaking when $|\mathrm{AUC} - 0.5| \geq 0.25$ on at least one observable and the permutation p-value is below 0.05.

Statistics. All comparisons are paired across seeds. Two primary contrasts were fixed in the code before the runs, together with the metric and both thresholds: TierFed against FedPer, and TierFed against the best uniform period at matched bytes. With $\mathcal{U}$ the uniform periods run in a setting, B_K the mean upload $B(R)$ of period K, B_{TF} that of TierFed and $\bar{A}^{\mathcal{V}}_K$ the mean validation AUROC at $\hat{r}$, the best uniform period and the gain over it are

$$K_{\mathrm{u}} = \arg \max_{K \in \mathcal{U}:\, B_K \leq 1.05\, B_{\mathrm{TF}}} \bar{A}^{\mathcal{V}}_K, \qquad \Delta_{\mathrm{u}} = \frac{1}{S} \sum_{s=1}^{S} \left(A^{\mathcal{T}}_{\mathrm{TF},s} - A^{\mathcal{T}}_{K_{\mathrm{u}},s} \right), \tag{21}$$

over the S seeds that both share. Every other comparison is exploratory. Tests are two-sided Wilcoxon signed-rank tests, and intervals are percentile bootstrap intervals over seeds with 10,000 resamples. The second contrast was first specified with a Holm-corrected $p < 0.05$, which the smallest families cannot reach by construction, so Δ_{u} is judged by its interval instead: a setting counts as a gain only if the 95% interval excludes zero and $\Delta_{\mathrm{u}} \geq 0.005$ AUROC. No setting meets either rule. A difference below 0.005 AUROC is not called relevant, whatever its p-value. Non-inferiority to FedPer is tested one-sided,

$$H_0 : \ \mathbb{E}[d] \leq -\Delta_{\mathrm{NI}}, \qquad d = A^{\mathcal{T}}_{\text{method}}(\hat{r}) - A^{\mathcal{T}}_{\text{FedPer}}(\hat{r}), \tag{22}$$

by the signed-rank test on $d + \Delta_{\mathrm{NI}}$ with $\Delta_{\mathrm{NI}} = 0.01$ and, as a sensitivity margin, 0.005. Repeated runs are bit-identical on one machine. On a second machine every data-independent schedule sends the same bytes, but the AUROC of a single run can change by up to 0.0893 (Section V-A), so every comparison is computed within one machine.

V. Results

This section reports the checks of the protocol, the main comparison on both benchmarks, the settings in which a per-tier schedule could be expected to help, the effect of the synchronisation step, the cost on constrained links, and privacy. Unless stated otherwise, values are means over seeds on the readmission data with the MLP and the specialty groups, and p-values are from paired Wilcoxon tests.

A. Protocol Checks

The consistency check recomputes, from the stated rules, the transmitting rounds of every data-independent schedule, the bits of every uncompressed round with full participation and the releases charged by the accountant, over all 2,760 logs of this article. It finds 0 mismatches in 1,249 schedule checks, 1,144 byte checks and 250 accountant checks.

All runs of the main protocol were made on one Linux machine, and 136 of the label-skew and timing runs were repeated on a Windows laptop. Every data-independent schedule sends the same bytes in every round on both machines, and so do 31 of the 44 adaptive runs; the others differ by up to 2.9%, because their decisions depend on floating-point values computed from client data. The AUROC at the selected round changes by a median of 0.0003 and by at most 0.0893. The maximum occurs under strong label skew, where the validation curve is flat and a small numerical difference selects another round (39 runs). The outcome of the second primary contrast is the same on both machines, and for every schedule the observer AUC of the timing experiment lies on the same side of 0.75.

Because the selected round can move in this way, both primary contrasts are repeated under two other rules: the first maximum of the trailing three-round mean of $A^{\mathcal{V}}$, and the mean of $A^{\mathcal{T}}$ over the last ten rounds, which involves no selection (supplement, Section S3). Under none of the three rules is TierFed ahead of the best uniform period by 0.005 AUROC with an interval above zero in any setting. Its agreement with FedPer is less robust. Under the smoothed rule it is below FedPer by more than 0.005, with an interval below zero, in two of the seven settings (Dirichlet $\alpha = 10$: -0.0125 [-0.0168, -0.0090]; ResNet backbone: -0.0055 [-0.0088, -0.0025]), because the first-maximum rule can select the peak that follows a synchronisation.

B. Main Comparison on the Specialty Groups

Table III reports the main comparison. At the validation-selected round the federated methods are close to one another. FedPer reaches 0.6385, and, with the exception of AdaComm, no method differs from it by more than 0.0032 AUROC, which is below the threshold of 0.005 that this study treats as relevant (the largest difference is that of Fixed (4,4), staggered, $p = 0.049$). AdaComm differs from FedPer by -0.0056 ($p = 0.004$) with an upload of 27.7 MB up to its selected round, and local training differs by -0.0239 ($p = 0.002$), so federation improves on local training in this task.

TierFed chooses $\mathbf{K} = (4, 4)$ in every seed. After warm-up its schedule coincides with that of the fixed period $(4, 4)$ in every round, the two runs are identical, and Table III lists them in one row. This is the behaviour that Proposition 2 predicts: Ψ at the end of warm-up is 0.1%, so no per-tier schedule can lower the surrogate by more than that fraction. TierFed is non-inferior to FedPer at $\Delta_{\mathrm{NI}} = 0.01$ ($p < 10^{-3}$) and at 0.005 ($p = 0.007$); AdaComm is non-inferior at 0.01 ($p = 0.007$) but not at 0.005 ($p = 0.615$).

The two readings of the upload give different savings, and they are stated separately. Up to the selected round TierFed uploads 45.7 MB and FedPer 63.2 MB, a saving of 28%. TierFed selects round 36 on average and FedPer round 17, so this saving is obtained with about twice as many rounds. Over the 60 rounds the uploads are 65.3 and 217.8 MB, a saving of 70%, most of which comes from the rounds in which FedPer continues to transmit after its selected round (Fig. 4(b)).

The round at which a method is read has a large effect on the comparison. Full-rate training reaches its best validation

TABLE III
COMPARISON OF THE METHODS ON THE 20 SPECIALTY GROUPS

Method	AUROC at $\hat{r}$ [95% CI]	MB to $\hat{r}$	MB, 60 rounds	Last 10	Phase	+FT 3	ECE raw/Platt	Worst site	Δ FedPer	p
Local only	0.6145 [0.6090, 0.6204]	0.0	0.0	0.5557	0.5564	0.5548	0.363/0.023	0.431	−0.0239	0.002
FedAvg	0.6391 [0.6341, 0.6448]	50.6	218.4	0.6230	0.6252	0.6069	0.365/0.024	0.468	+0.0006	0.064
FedProx	0.6391 [0.6348, 0.6438]	77.9	218.4	0.6283	0.6306	0.6108	0.361/0.025	0.488	+0.0006	0.432
FedPer	0.6385 [0.6337, 0.6437]	63.2	217.8	0.6261	0.6279	0.6083	0.367/0.024	0.468	–	–
FedLAMA-style	0.6396 [0.6344, 0.6457]	49.4	154.1	0.6314	0.6329	0.6119	0.363/0.024	0.476	+0.0011	0.131
AdaComm	0.6329 [0.6273, 0.6391]	27.7	29.1	0.6302	0.6300	0.6234	0.363/0.023	0.463	−0.0056	0.004
LAG, equal weights	0.6373 [0.6327, 0.6417]	116.9	218.4	0.6344	0.6350	0.6218	0.362/0.024	0.480	−0.0012	0.492
LAG	0.6395 [0.6342, 0.6458]	44.4	218.4	0.6237	0.6259	0.6079	0.366/0.024	0.470	+0.0011	0.064
Fixed (8,8)	0.6372 [0.6317, 0.6440]	35.9	39.9	0.6280	0.6379	0.6003	0.363/0.024	0.457	−0.0013	0.275
TierFed ≡ Fixed (4,4)	0.6377 [0.6327, 0.6440]	45.7	65.3	0.6346	0.6396	0.6122	0.361/0.024	0.463	−0.0007	0.557
TierFed, staggered ≡ Staggered (4,4)	0.6353 [0.6309, 0.6399]	40.2	67.0	0.6289	0.6327	0.6112	0.359/0.024	0.447	−0.0032	0.049
Centralised MLP	0.6435 [0.6373, 0.6506]	–	–	0.5936	–	–	0.363/–	–	+0.0050	0.004
Gradient boosting	0.6413 [0.6348, 0.6491]	–	–	0.6272	–	–	0.019/–	–	+0.0029	0.160

MLP, means over 10 seeds. AUROC at $\hat{r}$: personalised test AUROC at the validation-selected round with its bootstrap 95% interval. MB to $\hat{r}$ and MB, 60 rounds: the readings $B(\hat{r})$ and $B(R)$ of the upload (8). Last 10 and Phase: mean AUROC over the last ten rounds and over the post-synchronisation rounds of the last twenty. +FT 3: final model after three further local epochs. ECE: without and with Platt scaling. Worst group: lowest AUROC of a group at $\hat{r}$. Δ FedPer and p: paired difference from FedPer at $\hat{r}$ and its Wilcoxon p-value. The symbol ≡ joins schedules that send the same tiers in every round and therefore produce identical runs.




Fig. 4. Training on the specialty groups (MLP, means over 10 seeds). (a) Personalised test AUROC $A^{\mathcal{T}}(r)$ with its 95% interval; the dot on each curve marks the mean selected round $\hat{r}$. The TierFed curve is also that of Fixed $(4, 4)$, and the LAG curve coincides with that of FedPer. (b) Cumulative upload $B(r)$ of all clients. (c) Upload of one client per round as a fraction of its shared payload, for the aligned and the staggered period $(4, 4)$ (seed 42, rounds 1–21, of which rounds 1–5 are the warm-up).

round early, and its test AUROC then declines. Under a sparse schedule the test AUROC rises at each synchronisation and falls between synchronisations (Fig. 4(a)). Both effects follow from the restart step: the server copy advances by one aggregated epoch per synchronisation, so a period of four reaches a given state of the shared tiers about four times later, and the local epochs in between fit each client's copy to its own data. Over the last ten rounds the sparse schedules are consequently ahead (TierFed 0.6346, FedPer 0.6261), and a comparison at the final round would favour them, whereas at the validation-selected round the difference is −0.0007. Fine-tuning each client's final model for three further local epochs lowers the AUROC of every method, by 0.0006 to 0.0169, which indicates that additional local adaptation does not account for the late-round difference. The two LAG rows of Table III differ only in the aggregation weights. At its default threshold LAG never skips an upload; with sample weights its final-round AUROC is 0.6212, level with FedAvg (0.6199), and with equal client weights it is 0.6337.

The AUPRC follows the same pattern (FedPer 0.177, TierFed 0.174, local training 0.155, against a prevalence of 0.09). Inverse-frequency class weighting shifts the scores of every method, so the raw ECE is between 0.359 and 0.367; Platt scaling on each client's validation split lowers it to between 0.023 and 0.025 for every method at no communication cost. The AUROC of the worst group is between 0.431 and 0.488, so the sample-weighted mean conceals groups for which no method is useful.

A direct paired comparison of TierFed with each baseline is given in the supplement (Table S-II). TierFed is above local training on 10/10 seeds and above AdaComm on 9/10; against every other federated method the difference is at most 0.0024 in absolute value, and no Holm-corrected test is significant.

C. Comparison at the Four Clinical Centres

Table IV and Fig. 7(a,b) repeat the comparison with clients that are real institutions. The full-rate methods and the densest period lie between 0.8179 and 0.8215 AUROC, and FedPer reaches 0.8179. Local training reaches 0.8055; its difference from FedPer, −0.0124 ($p = 0.294$), and that from FedAvg are not significant with 20 seeds, so a benefit of federation over local training is not established on this small dataset.

TierFed again selects $\mathbf{K} = (4, 4)$ in every seed, with $\Psi = 0.7\%$ on average and at most 1.0%, and its runs are

TABLE IV
COMPARISON OF THE METHODS AT THE FOUR CLINICAL CENTRES

Method	AUROC at $\hat{r}$ [95% CI]	MB to $\hat{r}$	MB, 60 rounds	Last 10	Worst centre	Δ FedPer	p
Local only	0.8055 [0.7900, 0.8214]	0.0	0.0	0.7831	0.503	−0.0124	0.294
FedAvg	0.8208 [0.7990, 0.8421]	8.7	28.4	0.8237	0.586	+0.0029	0.701
FedProx	0.8192 [0.7963, 0.8412]	8.7	28.4	0.8239	0.580	+0.0013	1.000
FedPer	0.8179 [0.7964, 0.8386]	9.2	28.3	0.8179	0.581	–	–
FedLAMA-style	0.8193 [0.7977, 0.8412]	6.7	20.2	0.8255	0.574	+0.0014	1.000
AdaComm	0.8046 [0.7844, 0.8246]	1.7	4.2	0.8094	0.537	−0.0133	0.036
LAG	0.8208 [0.7988, 0.8425]	8.7	28.4	0.8237	0.586	+0.0029	0.701
Fixed (2,2)	0.8215 [0.8002, 0.8427]	7.7	15.1	0.8252	0.591	+0.0036	0.554
Fixed (8,8)	0.8077 [0.7915, 0.8236]	3.7	5.2	0.8161	0.545	−0.0102	0.064
TierFed ≡ Fixed (4,4)	0.8094 [0.7896, 0.8303]	5.3	8.5	0.8243	0.547	−0.0085	0.015
TierFed, staggered ≡ Staggered (4,4)	0.8125 [0.7916, 0.8329]	5.0	8.6	0.8260	0.560	−0.0054	0.163

Fed-Heart-Disease, MLP, means over 20 seeds. The columns are those of Table III, without fine-tuning and calibration. Worst centre: lowest AUROC of a centre at $\hat{r}$.

identical to those of the fixed period. Unlike on the specialty groups, this period lowers the accuracy at the selected round. The difference from FedPer is -0.0085 AUROC [-0.0158, -0.0009] ($p = 0.015$), which exceeds the relevance threshold, and non-inferiority at 0.01 is not shown ($p = 0.263$). The shorter period $(2, 2)$ is level with FedPer ($+0.0036$, $p = 0.554$) with 15.1 MB over 60 rounds against 28.3 MB, while the longer period $(8, 8)$ and AdaComm differ from FedPer by -0.0102 ($p = 0.064$) and -0.0133 ($p = 0.036$). In bytes, TierFed uploads 5.3 MB up to its selected round against 9.2 MB for FedPer, and 8.5 against 28.3 MB over 60 rounds. Over the last ten rounds the order is reversed, as on the main benchmark (TierFed 0.8243, FedPer 0.8179).

These results have to be read with the size of the dataset in mind. The smallest centre holds 95 patients, in 30% of the runs one centre has a test split with a single class and is left out of the average, the AUROC of the worst centre is between 0.50 and 0.59 for every method, and the intervals of Table IV are about ± 0.02 wide. Within these limits the two benchmarks agree that the scheduler reduces to a uniform period. They differ in what that period costs at the selected round: no measurable amount on the specialty groups, and 0.0085 AUROC at the clinical centres. Section V-E shows that this cost depends on the synchronisation step.

D. Conditions for a Gain From Per-Tier Scheduling

Fig. 5(a) places every method on one plane of accuracy against upload (5 shared seeds). Above 40 MB the 18 configurations form a plateau between 0.6393 and 0.6462 AUROC, just below the centralised MLP (0.6489) and gradient boosting (0.6470) on the same seeds. AdaComm with an initial period of 4 is ahead of TierFed ($\rho = 0.25$) with a smaller upload, 54.6 against 65.3 MB, by $+0.0036$ [$+0.0007$, $+0.0078$] ($p = 0.125$), which is below the relevance threshold, and TierFed at $\rho = 0.15$ differs by -0.0020 [-0.0051, $+0.0009$] from the uniform period $K = 8$ with a larger upload. TierFed lies within the relevance threshold of the frontier of this benchmark and does not extend it.

Table V and Fig. 5(b,c) apply the second primary contrast in every setting. At $\alpha = 0.1$ only 14 to 16 of the 20 clients receive data, and 7 to 12 of them have a test split with a single class, so that setting rests on few clients. Across the 4 Dirichlet settings Ψ at the end of warm-up is at most 2.2%, TierFed gives the two tiers different intervals in at most a fraction 0.04 of the rounds after warm-up, and its gain over the best uniform period at matched bytes lies between -0.0113 and $+0.0000$ AUROC, with no interval above zero. Label skew does not separate the payload-to-dispersion ratios of the tiers on this model. The backbone does. On the ResNet (Fig. 6(a,b)) Ψ is 71.4%, and TierFed chooses $\mathbf{K} = (1, 5)$ directly after warm-up in every seed, close to the interval ratio of 4.6 that (14) predicts, and gives the tiers different intervals in a fraction 0.88 of the rounds after warm-up. Its difference from the best uniform period at matched bytes ($K = 4$) is -0.0023 AUROC [-0.0061, $+0.0011$] over 10 seeds, which is not a gain by the rule of Section IV. A fixed period frozen at $(1, 5)$ after warm-up follows the same trajectory until round 52 at the earliest, which is later than every selected round, so adaptation during training has no part in this result. The per-tier split itself does not improve accuracy in this setting.

E. Effect of the Synchronisation Step

The restart step discards the local epochs that a client spends on a tier between two synchronisations, whereas the carry-over step uploads their result. Table VI and Fig. 7(c,d) compare the two. On the specialty groups the step does not change the outcome of the comparison between schedules. TierFed selects $(4, 4)$ in every seed under the carry-over step as well, both with the measured dispersion and with the rescaled one, and its runs are identical to those of the fixed period $(4, 4)$ under that step.

The step does change how a sparse schedule trains. Under the carry-over step all local epochs reach the server copy, so the fixed period $(4, 4)$ attains its best validation round after 13 instead of 36 rounds, with 24.7 instead of 45.7 MB of upload. Its AUROC at that round differs by -0.0032 [-0.0061, -0.0007] ($p = 0.049$) from that under the restart step, and for the period $(8, 8)$ the difference is -0.0049 [-0.0065, -0.0033]; both are below the relevance threshold. After the selected round the carry-over runs lose accuracy in the way full-rate training does (Fig. 7(c)), and their mean AUROC over the last ten rounds is lower than under the restart step by 0.0310 to 0.0391. Against FedPer, the period $(4, 4)$ under the carry-over step differs by -0.0040 [-0.0066, -0.0014] at the




Fig. 5. Accuracy, upload and the bound. (a) $A^{\mathcal{T}}(\hat{r})$ against the total upload $B(R)$, with the communication parameter of every method swept (mean and 95% interval; grey lines: local training, centralised MLP and gradient boosting). (b) $A^{\mathcal{T}}(\hat{r})$ against the Dirichlet parameter α for TierFed, FedPer and the best uniform period at matched bytes; the series are offset horizontally so that equal values remain visible, and the dotted line is local training. (c) Gain Δ_{u} of (21) with its 95% interval in every setting, ordered by Ψ at the end of warm-up (right-hand axis); open markers: identical runs, shaded band: ± 0.005. (d) Share $v(W)$ of rounds that miss the transfer window on the 5-Mbit/s link, against the window length relative to the upload time of the full payload; TierFed produces the same curves as the fixed period with the same phases.

TABLE V
TIERFED AGAINST THE BEST UNIFORM PERIOD AT MATCHED BYTES IN EVERY SETTING

Setting	Ψ (%)	$\mathbf{K}$	TierFed	MB	Best uniform	AUROC	MB	Gain Δ_{u} [95% CI]	p	Seeds
Specialty groups	0.1	(4,4)	0.6377	65	$K = 4$	0.6377	65	identical runs	–	10
Dirichlet $\alpha = 0.1$	0.2	(4,4)	0.5858	52	$K = 8$	0.5971	31	-0.0113 [-0.0270, $+0.0040$]	0.625	5
Dirichlet $\alpha = 0.3$	0.7	(4,4)	0.6003	65	$K = 4$	0.6003	65	identical runs	–	5
Dirichlet $\alpha = 1$	2.2	(4,4)	0.6176	65	$K = 4$	0.6176	65	identical runs	–	5
Dirichlet $\alpha = 10$	0.2	(4,4)	0.6445	65	$K = 4$	0.6445	65	identical runs	–	5
ResNet backbone	71.4	(1,5)	0.6365	604	$K = 4$	0.6388	602	-0.0023 [-0.0061, $+0.0011$]	0.557	10
Clinical centres	0.7	(4,4)	0.8094	8	$K = 4$	0.8094	8	identical runs	–	20

Second primary contrast (21), with $\rho = 0.25$. Ψ: measured at the end of warm-up. $\mathbf{K}$: intervals (slow, medium) that TierFed uses in the first round after warm-up, as the most frequent pair over seeds. MB: upload $B(R)$ over 60 rounds. Gain Δ_{u}: with its bootstrap 95% interval and Wilcoxon p-value. Identical runs: TierFed chose the intervals of the best uniform period and sent the same tiers in every round.

selected round, with 24.7 MB of upload against 63.2 MB. On this benchmark the restart step thus gives a sparse schedule a later optimum and a stable late phase at the price of more rounds and more upload up to the selected round, whereas the carry-over step reaches a comparable optimum sooner and with less upload and then depends on early stopping.

At the clinical centres the step has a larger effect. TierFed again selects $(4, 4)$ in every seed and is identical to the fixed period, so the finding about per-tier scheduling is unchanged. The uniform period itself is more accurate under the carry-over step. The AUROC of the period $(4, 4)$ at the selected round rises by $+0.0101$ [$+0.0027$, $+0.0188$] ($p = 0.022$) and is then level with that of FedPer (difference $+0.0016$ [-0.0067, $+0.0140$]), with 4.1 MB of upload up to that round against 9.2 MB; the period $(8, 8)$ and AdaComm improve by $+0.0103$ and $+0.0147$. The loss of 0.0085 AUROC reported in Section V-C is therefore tied to the restart step on this small dataset and is not a property of the sparse period as such.

On the ResNet, where the tiers differ, the carry-over step was run for TierFed, for its variant with the rescaled dispersion and for the uniform period $(4, 4)$ on five seeds. TierFed uses the intervals $(1, 5)$ directly after warm-up and gives the tiers different intervals in a fraction 0.34 of the later rounds ($(1, 5)$ and 0.93 with the rescaled dispersion). Its difference from the uniform period $(4, 4)$ at the selected round is $+0.0027$ [$+0.0007$, $+0.0058$] AUROC with an upload of 583 against 602 MB over 60 rounds, and $+0.0000$ [-0.0034, $+0.0041$] with 607 MB for the rescaled variant. The first interval excludes zero, but the difference is below the relevance threshold of 0.005, and the second interval includes zero. Neither is a gain by the rule of Section IV, so the finding of Section V-D does not depend on the synchronisation step.

F. Peak Load, Radio Wake-Ups and Link Cost

A quota on the mean leaves the payload of a single round unconstrained. Every transmitting round of the aligned period $(4, 4)$ sends the full shared payload (Fig. 4(c)), and 0.30 of all rounds miss a window of 0.6 times the upload time of the full payload on the cell-edge link (Table VII, Fig. 5(d)). Staggering the two tiers limits every round after warm-up to 0.55 of the payload at the same long-run payload fraction; over 60 rounds the upload is 67.0 MB against 65.3 MB, because the phase places one more synchronisation inside the horizon. Only the warm-up rounds then miss the window (0.08), and an eight-bit warm-up lowers the share to 0.00. The AUROC changes by -0.0024 ($p = 0.105$).

The cost of staggering is paid in radio wake-ups, 32 per client instead of 18, and in transmit energy, 21.4 against 20.9 J on the cell-edge link before any radio overhead per wake-up is counted [35], [36]; that overhead would increase the difference. Staggering helps to meet a transfer window; it does not save energy. It requires at least two tiers with separate




Fig. 6. Backbone and privacy. (a) $A^{\mathcal{T}}(r)$ on the ResNet (means over 10 seeds; dots mark the mean $\hat{r}$; axis starts at 0.60); the curves of TierFed and Fixed $(1, 5)$ coincide until round 52. (b) Intervals chosen by TierFed on the ResNet, as means over seeds. (c) $A^{\mathcal{T}}(r)$ under client-level DP with $\varepsilon^\star = 4$ and $q = 1$ (10 seeds), with local training without DP for reference. (d) Total upload of all clients in each run of the timing experiment, relative to the median of the clean runs of the same schedule, for the clean world and for the world in which the target client holds flipped labels (symmetric-log axis); the last row is TierFed on the ResNet.

TABLE VI
ROUND-SPARSE SCHEDULES UNDER THE RESTART AND THE CARRY-OVER SYNCHRONISATION STEP

		Restart step				Carry-over step					
Setting (seeds)	Schedule	AUROC at $\hat{r}$	$\hat{r}$	MB to $\hat{r}$	Last 10	AUROC at $\hat{r}$	$\hat{r}$	MB to $\hat{r}$	Last 10	Difference at $\hat{r}$ [95% CI]	p
Specialty groups (10)	Fixed (4,4)	0.6377	36	45.7	0.6346	0.6345	13	24.7	0.6036	−0.0032 [−0.0061, −0.0007]	0.049
	Fixed (8,8)	0.6372	45	35.9	0.6280	0.6323	11	20.7	0.5889	−0.0049 [−0.0065, −0.0033]	0.002
	TierFed	0.6377	36	45.7	0.6346	0.6345	13	24.7	0.6036	−0.0032 [−0.0061, −0.0007]	0.049
	TierFed, rescaled dispersion	–	–	–	–	0.6345	13	24.7	0.6036	–	–
	AdaComm	0.6329	55	27.7	0.6302	0.6313	10	7.3	0.5919	−0.0017 [−0.0040, +0.0008]	0.232
Clinical centres (20)	Fixed (4,4)	0.8094	32	5.3	0.8243	0.8195	22	4.1	0.8144	+0.0101 [+0.0027, +0.0188]	0.022
	Fixed (8,8)	0.8077	32	3.7	0.8161	0.8180	23	3.2	0.8118	+0.0103 [+0.0017, +0.0203]	0.098
	TierFed	0.8094	32	5.3	0.8243	0.8195	22	4.1	0.8144	+0.0101 [+0.0027, +0.0188]	0.022
	TierFed, rescaled dispersion	–	–	–	–	0.8195	22	4.1	0.8144	–	–
	AdaComm	0.8046	24	1.7	0.8094	0.8193	17	1.4	0.8183	+0.0147 [+0.0058, +0.0240]	0.011
ResNet backbone (5)	Fixed (4,4)	0.6446	41	468.1	0.6332	0.6395	15	247.4	0.5986	−0.0051 [−0.0086, −0.0018]	0.062
	TierFed	0.6427	24	312.3	0.6270	0.6423	16	257.0	0.5961	−0.0004 [−0.0022, +0.0017]	0.812
	TierFed, rescaled dispersion	–	–	–	–	0.6395	15	240.5	0.6004	–	–

The restart step (1) is used by every other experiment; under the carry-over step a tier is uploaded after all local epochs since its last synchronisation. For each step: $A^{\mathcal{T}}(\hat{r})$, mean selected round $\hat{r}$, upload $B(\hat{r})$ in MB, and mean AUROC over the last ten rounds. Difference at $\hat{r}$: carry-over minus restart, paired over seeds, with its bootstrap 95% interval and Wilcoxon p-value. Full-rate methods are identical under both steps. The rescaled variant of TierFed was run under the carry-over step only.

phases, since a schedule that synchronises the whole model at once has nothing to offset, and on these benchmarks it is the measurable benefit of the tier structure. When the clients share one uplink, a saving in bytes is a saving in time: the communication time over 60 rounds is 350 s for FedPer and 105 s for TierFed on the cell-edge link. Replaying the logged per-client uploads over TCP paced at the rate of the model reproduced the modelled times to within 2.1% (supplement, Table S-XIV), which tests the implementation of the model; it says nothing about how realistic the model is.

G. Privacy: Matched Budgets and the Schedule as a Side Channel

The selection of a round on the validation splits reads the clients' data and is not charged by the accountant, so under DP the final round is the primary value (Table VIII). At the same budget every releasing schedule ends between 0.5024 and 0.5314 AUROC, below local training on the same seeds, which releases nothing and ends at 0.5554; a releasing schedule is below local training in 49 of the 50 pairs of seed and method. With the uncharged selection the gap is wider for every schedule except one-shot federation, 0.5408 at best against 0.6145, and at no round does the mean AUROC of a releasing schedule other than one-shot exceed 0.5525 (Fig. 6(c)). One-shot federation appears to match local training under selection, but in every seed its selected round (round 4 on average) precedes its single release, and after the release its AUROC is 0.5024. Up to its selected round it is local training from a common initial model and involves no federation.

The cause is the size of the federation. With 20 clients the noise on the average is zC/N per release, and at $\varepsilon^\star = 4$ it dominates the update for every schedule, while 0.44 of FedPer's updates are clipped at $C = 1$. The exact accountant would lower z by 17% for every method alike, which does not close a gap of this size. At this federation size the comparison does not rank the schedules. Its practical implication is that federation under client-level DP should be avoided here, or that records should be protected instead of clients. A larger federation alone did not change this in a supplementary experiment with 100 clients, read at the final round, in which every private arm stays between 0.5062 and 0.5421 (supplement, Table S-XVI).

Table IX reports what the schedule reveals to a passive observer. The fixed period sends the same bytes in both worlds




Fig. 7. Clinical centres and synchronisation step. (a) $A^{\mathcal{T}}(r)$ at the four clinical centres (means over 20 seeds; dots mark the mean $\hat{r}$). (b) Cumulative upload $B(r)$ at the clinical centres. (c) $A^{\mathcal{T}}(r)$ of the fixed period $(4, 4)$ on the specialty groups under the restart and the carry-over step, with FedPer for reference. (d) Dispersion $\hat{\Gamma}_g$ of the uploaded slices in the synchronisation rounds after warm-up against the uniform period K, for both steps and both shared tiers (logarithmic axis).

TABLE VII
PEAK LOAD, RADIO WAKE-UPS AND LINK COST ON THE SPECIALTY GROUPS

					5G NR, cell edge			LEO satellite		WAN
Method	MB	Peak	Missed	Wake-ups	t (s)	t_{sh} (s)	E (J)	t_{sh} (s)	E (J)	t_{sh} (s)
FedPer	217.8	1.00	1.00	60	19.2	350	69.7	177	348	18.0
AdaComm	29.1	1.00	0.13	8	2.6	47	9.3	24	47	2.4
LAG	218.4	1.00	1.00	60	19.3	351	69.9	177	349	18.1
Fixed (8,8)	39.9	1.00	0.18	11	3.5	64	12.8	32	64	3.3
TierFed $\equiv$ Fixed (4,4)	65.3	1.00	0.30	18	5.8	105	20.9	53	105	5.4
Staggered (4,4)	67.0	0.55	0.08	32	6.3	108	21.4	55	107	5.7
Staggered (4,4), 8-bit warm-up	53.4	0.55	0.00	32	5.2	86	17.1	44	85	4.6

MLP, means over 10 seeds (5 seeds for the row with an 8-bit warm-up). MB: upload $B(R)$. Peak: largest payload fraction $\hat{P}$ of a round after warm-up. Missed: share $v(W)$ of rounds that miss a window of 0.6 times the upload time of the full payload on the cell-edge link. Wake-ups: u_k per client (6). t and t_{sh}: communication time with independent links and with one shared uplink (5). E: uplink transmit energy.

TABLE VIII
SCHEDULES AT A MATCHED PRIVACY BUDGET WITH 20 CLIENTS

Method	Releases	z	Clipped	Final round	At $\hat{r}$	$\hat{r}$
FedPer	60	10.04	0.44	0.5185	0.5246	24
Fixed (4,4)	18	5.50	0.39	0.5264	0.5343	25
Fixed (8,8)	11	4.30	0.39	0.5314	0.5408	24
One-shot	1	1.30	0.48	0.5024	0.6153	4
TierFed-DP	23	6.22	0.40	0.5210	0.5338	24
Local training	0	–	–	0.5554	0.6145	4

$\varepsilon^{\star} = 4$, $\delta = 10^{-5}$, $q = 1$, $C = 1$; means over 10 seeds. z: noise multiplier calibrated to the number of releases. Clipped: share of updates that are clipped. Final round: the value covered by the accountant. At $\hat{r}$ and $\hat{r}$: validation-selected value and round, given for reference only, because the selection is not charged. Local training releases nothing ($\varepsilon = 0$) and is evaluated on the same seeds.

TABLE IX
OBSERVER AUC OF THE TIMING SIDE CHANNEL FOR EACH SCHEDULE AND OBSERVABLE

Schedule	Model	Rounds with traffic	Target's rounds	Target's bytes	All bytes	Runs per world	p
Fixed (4,4)	MLP	0.50	0.50	0.50	0.50	10	1.000
TierFed	MLP	0.50	0.50	0.50	0.50	10	1.000
AdaComm	MLP	0.50	0.50	0.50	0.50	10	1.000
LAG, $\xi = 2000$	MLP	0.50	0.50	0.50	0.84	10	0.009
LAG, $\xi = 5000$	MLP	0.96	0.97	0.97	0.95	10	< 0.001
TierFed	ResNet	0.47	0.47	0.45	0.45	8	0.807

AUC (20) with which a passive observer distinguishes the world in which the target client holds flipped labels from the clean world; 0.5 corresponds to chance. p: permutation p-value of the largest deviation from 0.5 over the four observables.

by construction, and so does TierFed on the MLP, whose intervals do not change during training; a schedule that does not adapt reveals nothing. AdaComm, whose period depends on the training loss, also produced identical traffic in both worlds in these runs.

LAG with $\xi = 2000$ never skips an upload of the target client, but the other clients skip 56% of theirs, and how often they do so depends on the data of the target through the shared model. The total upload of all clients therefore separates the two worlds with an AUC of 0.84 ($p = 0.009$; Fig. 6(d)), which means that a client cannot protect itself by never skipping an upload. With $\xi = 5000$ the target's own rounds reveal it (AUC 0.97, $p < 0.001$). Both observers use timing and volume alone, since every payload is encrypted.

On the ResNet, where TierFed changes its intervals during training, its traffic differs between the two worlds in some runs, but with eight runs per world the worlds are not separated reliably (largest deviation: AUC 0.45, $p = 0.807$). A scheduler cannot guarantee before training that it will not adapt, which is why the accountant has to refuse every adaptive schedule.

VI. DISCUSSION

The results are discussed in three parts: the claims that the evidence does not support, the limitations of the study, and

recommendations for practice.

Claims not supported. In no setting tested, and under neither synchronisation step, is TierFed more accurate than a well-chosen uniform period by the relevance threshold of 0.005 AUROC. Its quota is not an advantage in itself, because a uniform period meets a quota ρ with $K = \lceil 1/\rho \rceil$. The evidence on Ψ is one-sided. A small Ψ was followed by no gain in every setting, which is what the bound predicts, but the only setting with a large Ψ, the ResNet, showed no gain either. A large Ψ is necessary for a per-tier schedule to lower the surrogate; whether it is necessary for a gain in accuracy remains untested, because no setting showed such a gain, and the ResNet shows that it is not sufficient. No tested setting supports the use of Ψ as a recommendation for per-tier scheduling.

Limitations. The clients of the main benchmark are specialty groups and not hospitals, and the dataset with real clinical centres is small: it has four clients, the smallest of which holds 95 patients. Proposition 1 assumes block-separable smoothness, equal local steps, equal weights and SGD, whereas the experiments use a coupled network, unequal steps, sample weights and Adam. Proposition 2 is exact for the programme and says nothing about accuracy, and the programme uses a norm-normalised proxy and ignores the server-side cost of an interval. The restart step, on which all main results rest, discards local computation. The carry-over step was examined for the round-sparse schedules only and without DP, and its effect on the accuracy of a sparse period relative to FedPer had opposite signs on the two datasets, which the present experiments do not explain. The label-skew sweep and the frontier use five seeds, and the ResNet timing experiment uses eight runs per world. The privacy unit is the client. Under record-level DP-SGD [29], [30] every local step is charged, so the synchronisation schedule would not change ε under standard composition.

Recommendations. The reported round should be selected on validation data, and the upload should be stated for that round as well as for the whole budget. Ψ can be measured at the end of warm-up at no cost; when it is small, a uniform period $K = \lceil 1/\rho \rceil$ is sufficient, and it can be staggered if the payload of a single round matters and the additional radio wake-ups are acceptable. The period and the synchronisation step should be validated against full-rate personalisation on the data at hand, since the period that cost nothing on the specialty groups cost accuracy at the clinical centres under the restart step and none under the carry-over step. Under client-level DP the schedule should be fixed before training, z calibrated to its release count, the final round reported or the selection charged, and the result compared with local training before federation is adopted.

VII. Conclusion

This article examined whether per-tier synchronisation improves on a uniform period in cross-silo federated learning under a byte quota, using TierFed, a quota-constrained multi-rate scheduler. The closed form of its programme bounds the reduction of the drift surrogate that any per-tier schedule can achieve by Ψ, which is measurable before any sparse round. In seven settings, which include clients formed from medical specialties, label-skewed partitions, a deeper backbone and four real clinical centres, TierFed showed no gain over the best uniform period at matched bytes; with a second synchronisation step the largest difference in its favour, 0.0027 AUROC on the ResNet, is below the relevance threshold. Where Ψ was at most 2.2% the scheduler selected a uniform period, and on the ResNet, where Ψ is 71.4%, it split the tiers as predicted without a gain. On the readmission benchmark the uniform period that it selects matches full-rate personalisation at the validation-selected round with 28% less upload up to that round and 70% less over the 60 rounds. At the clinical centres the same period is 0.0085 AUROC lower when a due tier is restarted from the server copy and level with full-rate personalisation when the locally trained tier is uploaded. The benefit of the tier structure that could be measured is the control of the load of a single round: staggered phases lower the share of rounds that miss a transfer window from 0.30 to 0.08, with more radio wake-ups. Under client-level DP the schedule is part of the mechanism. A schedule that adapts to client data is not covered by the accountant and can be read from the traffic, and with 20 clients every releasing schedule ended below local training, so the quota and the privacy budget have to be planned before training and compared with the option of not federating.

Data, Code and Declarations

Code, configuration, per-seed logs and the one-command reproduction of every table, figure and number are available at https://github.com/Abraheem13/tierfed. All datasets are public and de-identified, and no ethics approval was required. Generative AI tools were used for code refactoring, figure layout and language editing; the authors verified all content, code, numbers and figures. The authors declare no competing interests and no funding.

References

[1] H. B. McMahan, E. Moore, D. Ramage, S. Hampson, and B. Agüera y Arcas, "Communication-efficient learning of deep networks from decentralized data," in *Proc. Int. Conf. Artif. Intell. Statist. (AISTATS)*, 2017, pp. 1273–1282.

[2] P. Kairouz *et al.*, "Advances and open problems in federated learning," *Found. Trends Mach. Learn.*, vol. 14, no. 1–2, pp. 1–210, 2021.

[3] N. Rieke *et al.*, "The future of digital health with federated learning," *npj Digit. Med.*, vol. 3, 2020, Art. no. 119.

[4] I. Dayan *et al.*, "Federated learning for predicting clinical outcomes in patients with COVID-19," *Nat. Med.*, vol. 27, no. 10, pp. 1735–1743, 2021.

[5] W. Y. B. Lim *et al.*, "Federated learning in mobile edge networks: A comprehensive survey," *IEEE Commun. Surveys Tuts.*, vol. 22, no. 3, pp. 2031–2063, 2020.

[6] M. Chen, Z. Yang, W. Saad, C. Yin, H. V. Poor, and S. Cui, "A joint learning and communications framework for federated learning over wireless networks," *IEEE Trans. Wireless Commun.*, vol. 20, no. 1, pp. 269–283, 2021.

[7] T. Li, A. K. Sahu, M. Zaheer, M. Sanjabi, A. Talwalkar, and V. Smith, "Federated optimization in heterogeneous networks," in *Proc. Mach. Learn. Syst. (MLSys)*, 2020, pp. 429–450.

[8] S. P. Karimireddy, S. Kale, M. Mohri, S. J. Reddi, S. U. Stich, and A. T. Suresh, "SCAFFOLD: Stochastic controlled averaging for federated learning," in *Proc. Int. Conf. Mach. Learn. (ICML)*, 2020, pp. 5132–5143.

[9] M. G. Arivazhagan, V. Aggarwal, A. K. Singh, and S. Choudhary, "Federated learning with personalization layers," *arXiv preprint arXiv:1912.00818*, 2019.

[10] L. Collins, H. Hassani, A. Mokhtari, and S. Shakkottai, "Exploiting shared representations for personalized federated learning," in *Proc. Int. Conf. Mach. Learn. (ICML)*, 2021, pp. 2089–2099.

[11] K. Pillutla, K. Malik, A.-R. Mohamed, M. Rabbat, M. Sanjabi, and L. Xiao, "Federated learning with partial model personalization," in *Proc. Int. Conf. Mach. Learn. (ICML)*, 2022, pp. 17 716–17 758.

[12] S. U. Stich, "Local SGD converges fast and communicates little," in *Proc. Int. Conf. Learn. Represent. (ICLR)*, 2019.

[13] T. Lin, S. U. Stich, K. K. Patel, and M. Jaggi, "Don't use large mini-batches, use local SGD," in *Proc. Int. Conf. Learn. Represent. (ICLR)*, 2020.

[14] S. Wang *et al.*, "Adaptive federated learning in resource constrained edge computing systems," *IEEE J. Sel. Areas Commun.*, vol. 37, no. 6, pp. 1205–1221, 2019.

[15] J. Wang and G. Joshi, "Adaptive communication strategies to achieve the best error-runtime trade-off in local-update SGD," in *Proc. Mach. Learn. Syst. (MLSys)*, 2019.

[16] T. Chen, G. B. Giannakis, T. Sun, and W. Yin, "LAG: Lazily aggregated gradient for communication-efficient distributed learning," in *Proc. Adv. Neural Inf. Process. Syst. (NeurIPS)*, 2018, pp. 5050–5060.

[17] S. Lee, T. Zhang, and A. S. Avestimehr, "Layer-wise adaptive model aggregation for scalable federated learning," in *Proc. AAAI Conf. Artif. Intell.*, 2023, pp. 8491–8499.

[18] E. Malan, V. Peluso, A. Calimera, E. Macii, and P. Montuschi, "Automatic layer freezing for communication efficiency in cross-device federated learning," *IEEE Internet Things J.*, vol. 11, no. 4, pp. 6072–6083, 2024.

[19] D. Alistarh, D. Grubic, J. Li, R. Tomioka, and M. Vojnovic, "QSGD: Communication-efficient SGD via gradient quantization and encoding," in *Proc. Adv. Neural Inf. Process. Syst. (NIPS)*, 2017, pp. 1709–1720.

[20] F. Sattler, S. Wiedemann, K.-R. Müller, and W. Samek, "Robust and communication-efficient federated learning from non-i.i.d. data," *IEEE Trans. Neural Netw. Learn. Syst.*, vol. 31, no. 9, pp. 3400–3413, 2020.

[21] J. Wang and G. Joshi, "Cooperative SGD: A unified framework for the design and analysis of local-update SGD algorithms," *J. Mach. Learn. Res.*, vol. 22, no. 213, pp. 1–50, 2021.

[22] N. Razmi, B. Matthiesen, A. Dekorsy, and P. Popovski, "Ground-assisted federated learning in LEO satellite constellations," *IEEE Wireless Commun. Lett.*, vol. 11, no. 4, pp. 717–721, 2022.

[23] H. B. McMahan, D. Ramage, K. Talwar, and L. Zhang, "Learning differentially private recurrent language models," in *Proc. Int. Conf. Learn. Represent. (ICLR)*, 2018.

[24] I. Mironov, "Rényi differential privacy," in *Proc. IEEE Comput. Secur. Found. Symp. (CSF)*, 2017, pp. 263–275.

[25] I. Mironov, K. Talwar, and L. Zhang, "Rényi differential privacy of the sampled Gaussian mechanism," *arXiv preprint arXiv:1908.10530*, 2019.

[26] P. Kairouz, B. McMahan, S. Song, O. Thakkar, A. Thakurta, and Z. Xu, "Practical and private (deep) learning without sampling or shuffling," in *Proc. Int. Conf. Mach. Learn. (ICML)*, 2021, pp. 5213–5225.

[27] C. A. Choquette-Choo, K. Dvijotham, K. Pillutla, A. Ganesh, T. Steinke, and A. G. Thakurta, "Correlated noise provably beats independent noise for differentially private learning," in *Proc. Int. Conf. Learn. Represent. (ICLR)*, 2024.

[28] G. Andrew, O. Thakkar, H. B. McMahan, and S. Ramaswamy, "Differentially private learning with adaptive clipping," in *Proc. Adv. Neural Inf. Process. Syst. (NeurIPS)*, 2021, pp. 17 455–17 466.

[29] K. Z. Liu, S. Hu, Z. S. Wu, and V. Smith, "On privacy and personalization in cross-silo federated learning," in *Proc. Adv. Neural Inf. Process. Syst. (NeurIPS)*, 2022, pp. 5925–5940.

[30] J. Liu, J. Lou, L. Xiong, J. Liu, and X. Meng, "Cross-silo federated learning with record-level personalized differential privacy," in *Proc. ACM SIGSAC Conf. Comput. Commun. Secur. (CCS)*, 2024, pp. 303–317.

[31] L. Zhu, Z. Liu, and S. Han, "Deep leakage from gradients," in *Proc. Adv. Neural Inf. Process. Syst. (NeurIPS)*, 2019, pp. 14 774–14 784.

[32] J. Geiping, H. Bauermeister, H. Dröge, and M. Moeller, "Inverting gradients – How easy is it to break privacy in federated learning?" in *Proc. Adv. Neural Inf. Process. Syst. (NeurIPS)*, 2020, pp. 16 937–16 947.

[33] S. Yeom, I. Giacomelli, M. Fredrikson, and S. Jha, "Privacy risk in machine learning: Analyzing the connection to overfitting," in *Proc. IEEE Comput. Secur. Found. Symp. (CSF)*, 2018, pp. 268–282.

[34] N. Carlini, S. Chien, M. Nasr, S. Song, A. Terzis, and F. Tramèr, "Membership inference attacks from first principles," in *Proc. IEEE Symp. Secur. Privacy (S&P)*, 2022, pp. 1897–1914.

[35] J. Huang, F. Qian, A. Gerber, Z. M. Mao, S. Sen, and O. Spatscheck, "A close examination of performance and power characteristics of 4G LTE networks," in *Proc. ACM Int. Conf. Mobile Syst., Appl., Services (MobiSys)*, 2012, pp. 225–238.

[36] A. Narayanan *et al.*, "A variegated look at 5G in the wild: Performance, power, and QoE implications," in *Proc. ACM SIGCOMM*, 2021, pp. 610–625.

[37] 3GPP, "Study on scenarios and requirements for next generation access technologies," 3rd Generation Partnership Project, Tech. Rep. TR 38.913 V17.0.0, Mar. 2022.

[38] B. Strack *et al.*, "Impact of HbA1c measurement on hospital readmission rates: Analysis of 70,000 clinical database patient records," *BioMed Res. Int.*, vol. 2014, 2014, Art. no. 781670.

[39] R. Detrano *et al.*, "International application of a new probability algorithm for the diagnosis of coronary artery disease," *Amer. J. Cardiol.*, vol. 64, no. 5, pp. 304–310, 1989.

[40] J. Ogier du Terrail *et al.*, "FLamby: Datasets and benchmarks for cross-silo federated learning in realistic healthcare settings," in *Proc. Adv. Neural Inf. Process. Syst. (NeurIPS), Datasets Benchmarks Track*, 2022, pp. 5315–5334.

[41] J. Yang *et al.*, "MedMNIST v2 – A large-scale lightweight benchmark for 2D and 3D biomedical image classification," *Sci. Data*, vol. 10, 2023, Art. no. 41.

[42] B. Van Calster, D. J. McLernon, M. van Smeden, L. Wynants, and E. W. Steyerberg, "Calibration: the Achilles heel of predictive analytics," *BMC Med.*, vol. 17, 2019, Art. no. 230.

[43] J. C. Platt, "Probabilities for SV machines," in *Advances in Large Margin Classifiers*, A. J. Smola, P. L. Bartlett, B. Schölkopf, and D. Schuurmans, Eds. Cambridge, MA: MIT Press, 2000, pp. 61–74.

[44] J. Wang, Q. Liu, H. Liang, G. Joshi, and H. V. Poor, "Tackling the objective inconsistency problem in heterogeneous federated optimization," in *Proc. Adv. Neural Inf. Process. Syst. (NeurIPS)*, 2020, pp. 7611–7623.

[45] A. Khaled, K. Mishchenko, and P. Richtárik, "Tighter theory for local SGD on identical and heterogeneous data," in *Proc. Int. Conf. Artif. Intell. Statist. (AISTATS)*, 2020, pp. 4519–4529.

[46] P. Kairouz, Z. Liu, and T. Steinke, "The distributed discrete Gaussian mechanism for federated learning with secure aggregation," in *Proc. Int. Conf. Mach. Learn. (ICML)*, 2021, pp. 5201–5212.

[47] J. Dong, A. Roth, and W. J. Su, "Gaussian differential privacy," *J. Roy. Statist. Soc. B*, vol. 84, no. 1, pp. 3–37, 2022.

[48] B. Balle and Y.-X. Wang, "Improving the Gaussian mechanism for differential privacy: Analytical calibration and optimal denoising," in *Proc. Int. Conf. Mach. Learn. (ICML)*, 2018, pp. 394–403.

[49] R. Rogers, A. Roth, J. Ullman, and S. Vadhan, "Privacy odometers and filters: Pay-as-you-go composition," in *Proc. Adv. Neural Inf. Process. Syst. (NIPS)*, 2016, pp. 1921–1929.

[50] M. Lyu, D. Su, and N. Li, "Understanding the sparse vector technique for differential privacy," *Proc. VLDB Endowment*, vol. 10, no. 6, pp. 637–648, 2017.

[51] C. A. Choquette-Choo *et al.*, "(Amplified) banded matrix factorization: A unified approach to private training," in *Proc. Adv. Neural Inf. Process. Syst. (NeurIPS)*, 2023, pp. 74 856–74 889.

[52] G. Ke *et al.*, "LightGBM: A highly efficient gradient boosting decision tree," in *Proc. Adv. Neural Inf. Process. Syst. (NIPS)*, 2017, pp. 3146–3154.