Supplementary Material: When Does Per-Tier Synchronisation Pay?

Abraheem Rashid

S1. Relation to the superseded version

An earlier manuscript ("Nested Federated Learning" / "TierFed" v2) reported results produced by code with the following defects, found in an internal audit and corrected here:

1) Differential privacy was applied inside two strategies only and clipped the aggregate rather than each client's update, so FedAvg/FedPer/FedProx ran without noise and the reported budgets were invalid; the TierFed DP runs crashed on local-only rounds and the table was unsupported.
2) The SCAFFOLD baseline was FedAvg with doubled bit accounting.
3) The scalability table contained no TierFed runs and its values were not those of the logs.
4) The architecture sweep compared different depths across methods.
5) The imaging result used an undisclosed configuration on a binarised 97%-positive task.
6) The inversion attack targeted the fixed schedule at initialisation and was labelled TierFed.
7) The model described (93 inputs) was not the model trained (162 inputs).
8) Repeated runs were not deterministic.
9) No patient-level deduplication was performed and one "missing specialty" client held 49% of the data.
10) The greedy controller reached only powers of two.
11) The fixed multi-rate schedule sent a fallback tier whenever no tier was due, which made its medium-tier period ineffective.
12) Compressors were applied to raw weights instead of updates.
13) In v3, the DP comparison ran data-dependent schedulers (adaptive TierFed, AdaComm) under the Gaussian accountant, which does not charge for the information their schedules reveal, so their reported budgets were not valid DP guarantees; v4 refuses such strategies under DP, adds the data-independent TierFed-DP planner, and replaces the equal-σ table by a matched-ε comparison with Poisson sampling (Section S3).
14) The v4 planner objective compared raw K^2 against σ^2 in units of C^2, so its prior λ was scale-dependent; v5 normalises both terms, and the v4 planner runs were deleted and rerun.
15) The per-round history files recorded, in their `round` field, the round of the last synchronisation rather than the current round, so the v5 time-to-target values of the emulation table were matched to the wrong rounds for multi-rate methods; v6 fixes the logger, reads histories by position, and recomputes time-to-target from the logged per-round bits and compute times (the emulated totals are unaffected).
16) LAG averaged the freshest update of every site with *equal* weights, so at its default threshold, where it never skips, it was uniform-weight rather than sample-weighted FedAvg; the earlier text called it level with FedPer while its table showed it ahead. Sample weighting is now an option, and both variants are reported.
17) The fixed period of the v3–v12 runs synchronised in round 1 and then whenever $r \bmod K_g = 0$, with no warm-up unless one was set, while the text stated the shared due rule (Eq. (12) of the main text); its transmitting-round counts (37 for $(5, 2)$, 19 and 12 in the DP arms) were therefore one or more above that rule. The accountant charged the releases the code made, so the stated ε were correct. The new runs use one rule for every planned schedule, and a consistency check recomputes every release count, upload volume and DP charge of all logs from the stated rules.
18) TierFed's quota bounded the post-warm-up payload fraction, while the text defined it over all rounds; the realised all-round fraction at $\rho = 0.25$ was 0.30. Both definitions are now stated, and a quota over all rounds is available.
19) The feasible set of the solver has 64 points, not 512.
20) Upload volumes were the total over all sites, and two sentences called them per site.
21) The early-stopped AUROC chose its round on the same split it reported, which overstates it; the new runs select on a separate validation split.
22) The DP comparison read the validation-selected round, whose selection the accountant does not charge, and compared it with local training on ten seeds while the DP arms used six; the final round is now the primary private reading, and local training is read on the same six seeds.
23) The text said that TierFed lies on the accuracy–upload frontier; AdaComm with initial period 4 is ahead of it at fewer bytes, by less than the relevance threshold.
24) The text said that a common bias of the dispersion proxy cancels in Ψ; the proxy is normalised by each tier's own norm, so the programme is now stated as a surrogate of the bound, and Ψ as a statement about that surrogate.
25) The superseded equal-σ table of Section S3 had a header with one column more than its rows, which shifted every value one column to the left.
26) The text recommended federating hundreds of sites under site-level DP, which the 100-site results (Table S-

XIV) do not support; it also called the staggered peak cap one at an unchanged mean, while the 60-round upload rises from 65.3 to 67.0 MB.

Items (1)–(10) were found in an audit of the earlier manuscript, items (11)–(12) during the v3 runs, item (13) in the v4 revision, item (14) in the v5 revision, item (15) in the v6 revision and items (16)–(21) in an external audit of v12, and items (22)–(26) in a further external audit of v14; all affected runs were deleted and rerun or, for (16)–(21), superseded by the v13 runs, whose protocol is in the main text. With these corrections the earlier central finding, that fixed multi-rate schedules lose about 0.05 AUROC to personalised baselines, does not reproduce and is retracted. Every item maps to a code change in the released repository (`ROADMAP.md`, section 0) and to a test.

S2. Proofs

A. Proposition 1

Proof sketch. The perturbed-iterate argument of [1] is applied blockwise. Between two synchronisations of tier g a site takes $K_g s$ local steps on that block, so the squared deviation of its block iterate from the virtual average is bounded by $\eta^2 K_g^2 s^2(\Gamma_g + \sigma_g^2)$ up to the constants of the cited theorem; the blocks are disjoint and, by the block-separable smoothness assumption, the gradient of one block does not depend on the others, so the deviations add, and the descent lemma with the step-size condition absorbs the cross terms. Without block separability a coupling term $\sum_{g\neq h} L_{gh}^2(\cdot)$ appears, which the analysis does not control. $K_g = 1$ for a single block recovers the local-SGD rate.

The derivation follows the cooperative-SGD framework of Wang and Joshi [JMLR 2021, Thm. 1], which bounds the averaged gradient norm of local-update SGD in terms of the per-round deviation of client iterates from the virtual average. Write the shared parameter as $\theta = (\theta_g)_g$ with disjoint blocks. For site k and block g let $\theta_{k,g}^{(t)}$ be the iterate after t local steps since block g was last synchronised and $\bar\theta_g^{(t)}$ the (virtual) average across sites.

Lemma 1 (Blockwise deviation)**.** *Under the assumptions of Proposition 1 of the main text (block-separable L-smoothness, unbiased stochastic gradients with per-tier variance σ_g^2, per-tier heterogeneity bounded by Γ_g), for $\eta \le c_0/(LK_{\max}s)$ and any $t \le K_g s$,*

$$\frac{1}{N}\sum_k \mathbb{E}\big\|\theta_{k,g}^{(t)} - \bar\theta_g^{(t)}\big\|^2 \le c\,\eta^2 t^2\,(\Gamma_g + \sigma_g^2) \le c\,\eta^2 K_g^2 s^2 (\Gamma_g + \sigma_g^2).$$

Proof. Identical to Lemma 2 of Wang and Joshi restricted to the coordinates of block g: the deviation after t steps is a sum of t stochastic-gradient differences, each with second moment bounded by $\Gamma_g + \sigma_g^2$ by the variance and heterogeneity assumptions, and the smoothness term is absorbed by the step-size condition. The restriction to a block is valid because the gradient of block g is bounded blockwise by the same assumptions. □

The descent-lemma step of the cited theorem bounds $\mathbb{E}\|\nabla F(\bar\theta_r)\|^2$ by the progress term, the variance term and L^2 times the *total* deviation $\frac{1}{N}\sum_k \|\theta_k - \bar\theta\|^2$. Because the blocks are disjoint, the total deviation is the sum over g of the blockwise deviations, each bounded by the lemma with its own K_g; summing and averaging over rounds gives Proposition 1 of the main text with constants inherited from the cited theorem. No claim is made about the constants beyond their existence. Setting $K_g = 1$ for a single block returns the cited bound with s local steps.

What the controller sees. By the same lemma the dispersion of the received slices of tier g after K_g rounds is bounded by a term of order $\eta^2 K_g^2 s^2(\Gamma_g + \sigma_g^2)$; normalising by $\sum_j \|\bar\theta_j\|^2$ gives the scale-free $\hat\Gamma_g$ of the main text. The controller therefore minimises $\sum_g K_g^2 \hat\Gamma_g$ where $\hat\Gamma_g$ can already carry the factor K_g^2 of the interval that produced it; the debiased proxy $\tilde\Gamma_g$ divides it out. Either way the controller is a feedback loop on a proxy, and its stability is observed, not proved.

B. Proposition 2 and staggered phases

Write $x_g = K_g > 0$. The objective $f(x) = \sum_g \Gamma_g x_g^2$ is strictly convex, the constraint $h(x) = \sum_g w_g/x_g - \rho \le 0$ is convex on $x > 0$, and Slater's condition holds, so the KKT conditions are necessary and sufficient and the minimiser is unique. f increases and h decreases in every coordinate, so the constraint binds: if $h(x) < 0$, some x_g can be lowered and f decreases. Stationarity $2\Gamma_g x_g = \lambda w_g/x_g^2$ gives $x_g = (\lambda w_g/2\Gamma_g)^{1/3}$; substituting into $\sum_g w_g/x_g = \rho$ gives $(\lambda/2)^{1/3} = S/\rho$ with $S = \sum_h w_h^{2/3}\Gamma_h^{1/3}$, hence $K_g^\star = (w_g/\Gamma_g)^{1/3} S/\rho$ and $f(K^\star) = \frac{S^2}{\rho^2}\sum_g \Gamma_g (w_g/\Gamma_g)^{2/3} = S^3/\rho^2$. Hölder's inequality with $p = 3/2$, $q = 3$, $a_g = w_g^{2/3}$, $b_g = \Gamma_g^{1/3}$ gives $S \le (\sum_g w_g)^{2/3}(\sum_g \Gamma_g)^{1/3} = (\sum_g \Gamma_g)^{1/3}$, with equality if and only if $a_g^p \propto b_g^q$, i.e. $w_g \propto \Gamma_g$. The uniform point $x_g = 1/\rho$ satisfies the constraint with equality and costs $\sum_g \Gamma_g/\rho^2$. Finally, the integer feasible set is contained in the real one, so the integer optimum $J_{\rm int} \ge J^\star$; when $1/\rho \in \{1, \dots, K_{\max}\}$ the uniform period is integer-feasible, and $1 - J_{\rm int}/J_{\rm u} \le 1 - J^\star/J_{\rm u} = \Psi$. Ψ is invariant under $\Gamma \mapsto c\Gamma$ because S^3 and $\sum_g \Gamma_g$ are both linear in c. □

Staggered phases. After warm-up, tier a is due at the rounds $r = T_w + \phi_a + nK_a > T_w$ and tier b at $r = T_w + \phi_b + mK_b > T_w$, for integers $n, m \ge 0$ ($n \ge 1$ when $\phi_a = 0$, $m \ge 1$ when $\phi_b = 0$). A common round requires $nK_a - mK_b = \phi_b - \phi_a$, a linear Diophantine equation that is solvable if and only if $\gcd(K_a, K_b)$ divides $\phi_b - \phi_a$; when it is solvable, it has infinitely many solutions with $n, m \ge 1$. Hence the two due sets are disjoint if and only if $\phi_a - \phi_b \not\equiv 0 \pmod{\gcd(K_a, K_b)}$.

S3. Differential-privacy accounting

Per-client clipping to C makes the ℓ_2 sensitivity of the sum to the addition or removal of one client exactly C, and the fixed denominator qN does not depend on the realised cohort. With Poisson sampling at rate q each release is the subsampled Gaussian mechanism, whose RDP at integer order α is $\frac{1}{\alpha-1}\log\sum_{k=0}^{\alpha}\binom{\alpha}{k}(1-q)^{\alpha-k}q^k \exp\frac{k^2-k}{2\sigma^2}$ [Mironov, Talwar

TABLE S-I
SUPERSEDED EQUAL-σ COMPARISON OF V3 (PER-CLIENT CLIPPING $C = 1$, 10 SEEDS, $q = 1$). THE BUDGETS OF THE ADAPTIVE SCHEDULERS (TIERFED, ADACOMM) DO NOT ACCOUNT FOR THEIR DATA-DEPENDENT SCHEDULES AND ARE THEREFORE NOT VALID DP GUARANTEES: $(\varepsilon, \delta = 10^{-5})$ FROM THE EXACT RÉNYI ACCOUNTANT, NUMBER OF CHARGED (TRANSMITTING) ROUNDS, FINAL AUROC AND AUPRC. THE SAME MECHANISM IS APPLIED TO EVERY METHOD.

Method / σ	ε	Charged rounds	AUROC	AUPRC
AdaComm / 0.5	43.2	8	0.6223 ± 0.0083	0.158
AdaComm / 1.0	17.6	8	0.6076 ± 0.0115	0.148
AdaComm / 2.0	7.8	8	0.5469 ± 0.0135	0.123
AdaComm / 4.0	3.6	8	0.5460 ± 0.0159	0.108
FedAvg / 0.5	194.4	60	0.5990 ± 0.0156	0.147
FedAvg / 1.0	67.2	60	0.5008 ± 0.0096	0.096
FedAvg / 2.0	26.1	60	0.5143 ± 0.0227	0.099
FedAvg / 4.0	11.2	60	0.5150 ± 0.0151	0.094
FedPer / 0.5	194.4	60	0.6250 ± 0.0081	0.161
FedPer / 1.0	67.2	60	0.5669 ± 0.0136	0.133
FedPer / 2.0	26.1	60	0.5196 ± 0.0151	0.111
FedPer / 4.0	11.2	60	0.5198 ± 0.0101	0.109
Fixed schedule / 0.5	132.4	37	0.6248 ± 0.0107	0.159
Fixed schedule / 1.0	47.7	37	0.5923 ± 0.0163	0.142
Fixed schedule / 2.0	19.2	37	0.5372 ± 0.0185	0.118
Fixed schedule / 4.0	8.5	37	0.5155 ± 0.0167	0.109
TierFed / 0.5	76.8	18	0.6230 ± 0.0100	0.160
TierFed / 1.0	29.4	18	0.6100 ± 0.0095	0.151
TierFed / 2.0	12.4	18	0.5644 ± 0.0114	0.131
TierFed / 4.0	5.7	18	0.5282 ± 0.0094	0.114

and Zhang 2019, Sec. 3.3]; for $q = 1$ it is $\alpha/(2\sigma^2)$ [Mironov 2017, Prop. 7]. Composition over the R_{tx} planned releases is additive, and (ε, δ)-DP follows from [Mironov 2017, Prop. 3], minimised over $\alpha \in \{2, \ldots, 256\}$ (and a fine fractional grid for $q = 1$). The accountant is valid only if the set of release rounds is independent of the private data, which is why only FedAvg, FedProx, FedPer, the fixed period and TierFed-DP are run under DP in the main text. The sum is computed in log space; the implementation matches the TensorFlow-Privacy MNIST reference ($\varepsilon \approx 3.0$ at $q = 256/60000$, $\sigma = 1.1$, 60 epochs) to within 0.05. Model selection on held-out data is not covered by the budget, so the DP tables of this supplement report final-round values; Table VIII of the main text gives the final round as its primary reading and the validation-selected value only as an uncharged reference.

The superseded equal-σ comparison. Version 3 of this article compared every method at equal noise multiplier with full participation. It is reproduced below because it was circulated, with the caveat that the budgets reported for adaptive TierFed and AdaComm are not valid: both choose when to transmit from client updates or losses, and that choice is not charged by the accountant.

Table S-I and Fig. 1 were presented in v3 as the clearest effect of the study. Under client-level DP, every transmitting round is a release that the accountant charges for and into which noise is injected, so the number of transmitting rounds sets both the budget and the cumulative noise. At $\sigma = 1$, full-rate FedAvg collapses to 0.5008 and FedPer reaches 0.5669, both at $\varepsilon = 67.2$; TierFed reaches 0.6100 at $\varepsilon = 29.4$ (TierFed minus FedPer +0.043, $p < 10^{-4}$). At $\sigma = 2$ the margin over FedPer is +0.045 ($p < 10^{-4}$) at less than half the budget. Against AdaComm, the strongest round-sparse baseline, the comparison is mixed and is reported as such: level at $\sigma = 0.5$ (+0.001, $p = 0.604$) and $\sigma = 1$ (+0.002, $p = 0.443$), better




Fig. 1. Utility against the DP noise multiplier for every method under the identical mechanism (main text, Eq. (13)).

at $\sigma = 2$ (+0.018, $p < 10^{-4}$), and worse at $\sigma = 4$ (-0.018, $p = 0.008$), where AdaComm's eight releases incur less noise than TierFed's eighteen. The operational reading is that, under DP, the number of rounds a site transmits is the dominant design variable, and a communication quota is also a privacy quota. None of the budgets reported is claimed to constitute meaningful privacy; they are reported as computed so that the trade-off is measured correctly.

S4. SENSITIVITY TO THE ROUND-SELECTION RULE

The primary reading selects the first round that maximises the mean validation AUROC (Eq. (5) of the main text). A sparse schedule's test curve rises in a sawtooth that peaks after each synchronisation, so this rule can read a post-synchronisation peak, and on a flat validation curve a small numerical difference can move the selected round (the cross-machine check of Section V-A). Table S-II repeats both primary contrasts under two further readings computed from the same per-round logs: the first round that maximises the trailing three-round mean of the validation AUROC, and the mean test AUROC over the last ten rounds, which selects nothing. The argmax reading reproduces every logged value exactly. Intervals are percentile bootstrap over seeds (10,000 resamples), computed by `scripts/tmlcn/selection_table.py`; they can differ from those of the main text in the fourth decimal because the resampling stream differs.

No reading shows TierFed ahead of the best uniform period by the relevance threshold of 0.005 in any setting, and on the ResNet the last-ten-round reading puts it behind. The comparison with FedPer depends on the reading: under the smoothed rule TierFed trails FedPer by more than the threshold, with an interval below zero, at $\alpha = 10$ and on the ResNet (at $\alpha = 0.1$ the point estimate is -0.0091 but its interval spans zero), so its parity with FedPer at the selected round relies on reading a post-synchronisation peak; over the last ten rounds it is ahead, with an interval above zero, in four of the six settings, because full-rate training has overfitted by then (Section V-B of the main text).

TABLE S-II
BOTH PRIMARY CONTRASTS UNDER THREE READINGS OF THE SAME RUNS: MEAN PAIRED DIFFERENCE IN AUROC WITH BOOTSTRAP 95% INTERVAL. BEST UNIFORM PERIOD AS CHOSEN IN TABLE VI OF THE MAIN TEXT

Setting, seeds, best uniform	Reading	TierFed − FedPer [95% CI]	TierFed − best uniform [95% CI]
Specialty sites, 10 seeds, $K = 4$	Argmax (paper)	−0.0007 [−0.0033, +0.0018]	+0.0000 [+0.0000, +0.0000]
	Smoothed, 3 rounds	−0.0030 [−0.0056, −0.0005]	+0.0000 [+0.0000, +0.0000]
	Last ten rounds	+0.0085 [+0.0051, +0.0118]	+0.0000 [+0.0000, +0.0000]
Dirichlet $\alpha = 0.1$, 5 seeds, $K = 8$	Argmax (paper)	−0.0010 [−0.0182, +0.0215]	−0.0113 [−0.0270, +0.0040]
	Smoothed, 3 rounds	−0.0091 [−0.0224, +0.0058]	−0.0099 [−0.0289, +0.0004]
	Last ten rounds	−0.0052 [−0.0208, +0.0084]	−0.0096 [−0.0219, −0.0008]
Dirichlet $\alpha = 0.3$, 5 seeds, $K = 4$	Argmax (paper)	+0.0354 [+0.0075, +0.0788]	+0.0000 [+0.0000, +0.0000]
	Smoothed, 3 rounds	+0.0342 [+0.0089, +0.0726]	+0.0000 [+0.0000, +0.0000]
	Last ten rounds	+0.0100 [+0.0002, +0.0221]	+0.0000 [+0.0000, +0.0000]
Dirichlet $\alpha = 1$, 5 seeds, $K = 4$	Argmax (paper)	+0.0029 [−0.0049, +0.0112]	+0.0000 [+0.0000, +0.0000]
	Smoothed, 3 rounds	+0.0038 [−0.0086, +0.0161]	+0.0000 [+0.0000, +0.0000]
	Last ten rounds	+0.0140 [+0.0041, +0.0239]	+0.0000 [+0.0000, +0.0000]
Dirichlet $\alpha = 10$, 5 seeds, $K = 4$	Argmax (paper)	+0.0000 [−0.0021, +0.0028]	+0.0000 [+0.0000, +0.0000]
	Smoothed, 3 rounds	−0.0125 [−0.0168, −0.0090]	+0.0000 [+0.0000, +0.0000]
	Last ten rounds	+0.0017 [−0.0005, +0.0043]	+0.0000 [+0.0000, +0.0000]
ResNet backbone, 6 seeds, $K = 4$	Argmax (paper)	−0.0030 [−0.0069, −0.0005]	−0.0020 [−0.0073, +0.0021]
	Smoothed, 3 rounds	−0.0071 [−0.0116, −0.0030]	+0.0024 [−0.0033, +0.0074]
	Last ten rounds	+0.0078 [+0.0056, +0.0093]	−0.0064 [−0.0084, −0.0046]

S5. ADDITIONAL TABLES OF THE EARLIER PROTOCOL

Tables S-III to S-XVI hold the sweeps and secondary comparisons of the earlier (v5) protocol: a 80/20 per-site split without a validation set, final-round AUROC, and the fixed period on the legacy rule of item (17) of Section S1. They are kept because they cover settings the main protocol does not (compression, real institutions, imaging, scaling, a wide model, matched-privacy sweeps; the superseded equal-σ comparison is Table S-I in Section S3), and they should be read with that protocol in mind; the final-round reading favours sparse schedules, as the main text shows. Every body is generated from the per-seed logs by the same script as the main tables, with the best value in each group in bold.

S6. PER-SEED TABLES

Every run's final metrics are in `results/tables/collected_all_raw.csv` in the released repository. Total runs at build time: 2218.

S7. SGD ARM

The SGD arm (learning rate 5×10^{-2}) is reported, under the earlier protocol, in Table S-IV (baseline sweeps).

S8. EXCLUDED SITES ON THE IMAGING BENCHMARK

Number of sites whose patient-grouped held-out split contained a single class (identical for every method, per seed): between 3 and 9 of 20 depending on the seed (read from `n_clients_single_class_final` in the logs).

TABLE S-III
FIXED-PERIOD SWEEP $(K_\mathrm{s}, K_\mathrm{m})$ WITH LOCAL-ONLY ROUNDS (TOP) AND EXACT VERSUS GREEDY SOLVER FOR TIERFED AT EVERY QUOTA (BOTTOM); 10 SEEDS

$(K_\mathrm{s}, K_\mathrm{m})$ or quota, solver	AUROC	Upload (MB)
(2, 1)	0.6317 ± 0.0097	170.0
(2, 2)	**0.6362** ± 0.0110	112.5
(4, 1)	0.6314 ± 0.0102	145.3
(4, 2)	0.6370 ± 0.0112	87.8
(4, 4)	**0.6407** ± 0.0114	58.1
(8, 1)	0.6130 ± 0.0079	132.1
(8, 2)	0.6155 ± 0.0077	74.6
(8, 4)	**0.6254** ± 0.0073	44.9
(8, 8)	0.6250 ± 0.0088	29.0
$\rho = 0.15$, exact	**0.6070** ± 0.0119	45.7
$\rho = 0.25$, exact	**0.6269** ± 0.0082	65.3
$\rho = 0.25$, greedy	**0.6269** ± 0.0082	65.3
$\rho = 0.40$, exact	**0.6366** ± 0.0119	84.9
$\rho = 0.40$, greedy	0.6283 ± 0.0112	95.7
$\rho = 0.60$, exact	**0.6290** ± 0.0093	116.2
$\rho = 0.80$, exact	**0.6296** ± 0.0094	167.2

REFERENCES

[1] J. Wang and G. Joshi, "Cooperative SGD: A unified framework for the design and analysis of local-update SGD algorithms," *J. Mach. Learn. Res.*, vol. 22, no. 213, pp. 1–50, 2021.

TABLE S-IV
BASELINE SWEEPS (10 SEEDS): ADACOMM INITIAL PERIOD τ_0, LAG THRESHOLD ξ, AND THE SGD LOCAL SOLVER

Configuration	AUROC	AUPRC	Upload (MB)	Tx rounds
AdaComm, $\tau_0 = 16$	0.6125 ± 0.0111	0.152	18.2	5
AdaComm, $\tau_0 = 2$	0.6301 ± 0.0095	0.177	109.2	30
AdaComm, $\tau_0 = 4$	0.6275 ± 0.0068	0.174	54.6	15
AdaComm, $\tau_0 = 8$	**0.6302** ± 0.0071	0.168	29.1	8
FedAvg, SGD solver	**0.6396** ± 0.0109	0.172	218.4	60
FedPer, SGD solver	**0.6379** ± 0.0110	0.170	217.8	60
LAG, $\xi = 10$	0.6351 ± 0.0124	0.179	218.4	60
LAG, $\xi = 100$	0.6351 ± 0.0124	0.179	218.4	60
LAG, $\xi = 1000$	**0.6352** ± 0.0126	0.179	168.4	60
LAG, $\xi = 10000$	0.5673 ± 0.0498	0.135	6.8	7
SCAFFOLD, SGD solver	**0.6383** ± 0.0106	0.173	436.9	60
TierFed, SGD solver	**0.6251** ± 0.0095	0.157	65.3	18

TABLE S-V
NETWORK COST OF THE MAIN CASE UNDER THE FIVE LINK PROFILES: TOTAL COMMUNICATION TIME ON CELL-EDGE NR, LEO AND THE 6G SLICE TARGET, UPLINK ENERGY ON CELL-EDGE NR, AND SHARE OF ROUNDS FITTING A 60-S WINDOW; 10 SEEDS, FROM MEASURED BITS

Method	Upload (MB)	t NR-edge (s)	t LEO (s)	t 6G (s)	E NR-edge (J)	Window (%)
FedAvg	218.4	19	11	0.4	69.9	100
FedProx	218.4	19	11	0.4	69.9	100
SCAFFOLD	436.9	37	20	0.5	139.8	100
FedPer	217.8	19	11	0.4	69.7	100
FedLAMA	154.1	14	9	0.4	49.3	100
AdaComm	29.1	3	1	0.1	9.3	100
LAG	218.4	19	11	0.4	69.9	100
Fixed schedule	82.9	8	5	0.2	26.5	100
TierFed	65.3	6	3	0.1	20.9	100

TABLE S-VI
SENSITIVITY OF THE PLANNER TO ITS PRIOR λ (10 SEEDS): CHOSEN INTERVAL, CALIBRATED σ, RELEASES, AUROC, UPLOAD. TOP: 20 SITES AT $q = 1$, $\varepsilon^\star = 4$. BOTTOM: 100 SITES AT $q = 0.2$, $\varepsilon^\star = 4$

λ	K	σ	Releases	AUROC	Upload (MB)
0.3	2	7.33	32	0.5237 ± 0.0150	116.2
1.0	3	6.22	23	0.5211 ± 0.0121	83.5
3.0	4	5.50	18	**0.5318** ± 0.0081	65.3
10.0	5	5.18	16	0.5200 ± 0.0071	58.1
0.3	2	1.85	32	**0.5158** ± 0.0256	116.3
1.0	3	1.67	23	0.5122 ± 0.0226	83.0
3.0	4	1.56	18	0.5084 ± 0.0192	64.5
10.0	6	1.47	14	0.5114 ± 0.0283	50.8

TABLE S-VII
ATTACK SURFACE WITHOUT DP (10 SEEDS): PARAMETERS EXPOSED PER TRANSMITTING ROUND, UPDATE-INVERSION NORMALISED ERROR AND FEATURE CORRELATION ON THE REAL TRANSMITTED SLICES, MEMBERSHIP-INFERENCE AUC ON THE DEPLOYED MODELS (0.5: NO LEAKAGE), AND UPLOAD

Method	Params exposed	NMSE ↑	Corr. ↓	MIA AUC ↓	Upload (MB)
AdaComm	45,506	11.58	0.065	0.534	29.1
FedAvg	45,506	9.04	0.103	0.534	218.4
FedPer	45,376	9.04	0.088	0.535	217.8
Fixed schedule	27,509	11.93	0.048	0.526	82.9
TierFed	45,376	10.45	0.089	0.540	65.3

TABLE S-VIII
ABLATIONS (10 SEEDS). TOP: PRIVATE HEAD × SCHEDULE, AND TIERFED WITH AND WITHOUT THE HEAD. MIDDLE: WARM-UP T_w. BOTTOM: CLASS-IMBALANCE LOSS FOR FEDPER AND TIERFED

Configuration	AUROC	AUPRC	Upload (MB)
FedAvg: shared head, every round	0.6203 ± 0.0100	0.171	218.4
FedPer: private head, every round	0.6215 ± 0.0087	0.171	217.8
Fixed schedule, private head	**0.6339** ± 0.0100	0.177	82.9
Fixed schedule, shared head	0.6336 ± 0.0102	0.177	83.5
TierFed, private head	0.6269 ± 0.0082	0.175	65.3
TierFed, shared head	0.6264 ± 0.0073	0.174	65.5
TierFed, $T_w = 0$	0.6270 ± 0.0080	0.173	54.5
TierFed, $T_w = 2$	0.6323 ± 0.0092	0.176	58.1
TierFed, $T_w = 5$	0.6269 ± 0.0082	0.175	65.3
TierFed, $T_w = 10$	0.6289 ± 0.0093	0.176	79.9
TierFed, $T_w = 20$	**0.6354** ± 0.0112	0.179	108.9
Class-balanced, FedPer	0.6232 ± 0.0108	0.173	217.8
Class-balanced, TierFed	**0.6264** ± 0.0071	0.173	65.3
Focal, FedPer	0.6198 ± 0.0100	0.170	217.8
Focal, TierFed	**0.6237** ± 0.0089	0.173	65.3
LDAM, FedPer	0.6150 ± 0.0114	0.164	217.8
LDAM, TierFed	**0.6276** ± 0.0091	0.171	65.3
Inverse-frequency CE, FedPer	0.6215 ± 0.0087	0.171	217.8
Inverse-frequency CE, TierFed	**0.6269** ± 0.0082	0.175	65.3

TABLE S-IX
BACKBONES ON DIABETES (5 SEEDS); THE TRANSFORMER ARM USED A NON-DETERMINISTIC FUSED ATTENTION KERNEL

Backbone, method	AUROC	AUPRC	Upload (MB)	Params
MLP / FedAvg	0.6236 ± 0.0103	0.171	218.4	45,506
MLP / FedPer	0.6240 ± 0.0087	0.172	217.8	45,506
MLP / Fixed schedule	**0.6373** ± 0.0117	0.176	82.9	45,506
MLP / TierFed	0.6298 ± 0.0128	0.175	65.3	45,506
ResNet / FedAvg	0.6258 ± 0.0192	0.168	2007.3	418,178
ResNet / FedPer	0.6137 ± 0.0107	0.161	2006.0	418,178
ResNet / Fixed schedule	**0.6382** ± 0.0150	0.177	1006.8	418,178
ResNet / TierFed	0.6279 ± 0.0130	0.175	603.5	418,178
FT-Transformer / FedAvg	**0.6401** ± 0.0134	0.177	581.8	121,218
FT-Transformer / FedPer	0.6352 ± 0.0115	0.173	581.2	121,218
FT-Transformer / Fixed schedule	0.6386 ± 0.0116	0.172	270.7	121,218
FT-Transformer / TierFed	0.6345 ± 0.0083	0.171	165.2	121,218

TABLE S-X
IMAGING (PNEUMONIAMNIST, 20 DIRICHLET SITES, 10 SEEDS): FINAL AUROC WITH BCA 95% INTERVAL, AUPRC, UPLOAD, TRANSMITTING ROUNDS AND NON-INFERIORITY p ON AUROC AGAINST FEDPER. BETWEEN 3 AND 9 SITES PER SEED HAVE A SINGLE-CLASS HELD-OUT SPLIT AND ARE EXCLUDED IDENTICALLY FOR EVERY METHOD

Method	AUROC [95% CI]	AUPRC	Upload (MB)	Tx	NI p
FedAvg	0.9959 [0.9944, 0.9972]	0.991	1214.8	60	0.037
FedPer	0.9643 [0.8952, 0.9917]	0.986	1213.7	60	(ref.)
FedLAMA	**0.9965** [0.9953, 0.9975]	0.995	877.4	60	0.036
Fixed schedule	0.9642 [0.8938, 0.9934]	0.989	614.8	37	$< 10^{-4}$
TierFed	0.9698 [0.9536, 0.9820]	0.984	364.1	18	0.182

TABLE S-XI
SCALING (DIABETES, DIRICHLET $\alpha = 1$, 30 ROUNDS, 3 SEEDS): AUROC, UPLOAD PER SITE, WALL-CLOCK SECONDS PER ROUND AND PEAK MEMORY ON ONE CPU

Sites, method	AUROC	Upload (MB)	s/round	Peak MB
10 sites, FedAvg	**0.6127** ± 0.0206	54.6	3.07	80
10 sites, FedLAMA	0.6056 ± 0.0117	43.1	3.03	80
10 sites, FedPer	0.5935 ± 0.0072	54.5	3.03	80
10 sites, TierFed	0.6118 ± 0.0100	20.0	3.01	80
20 sites, FedAvg	0.6187 ± 0.0110	109.2	3.12	87
20 sites, FedLAMA	0.6187 ± 0.0183	85.4	3.09	87
20 sites, FedPer	0.6189 ± 0.0235	108.9	3.11	87
20 sites, TierFed	**0.6205** ± 0.0242	39.9	3.04	87
50 sites, FedAvg	0.6128 ± 0.0224	273.0	3.40	108
50 sites, FedLAMA	0.6108 ± 0.0203	219.3	3.33	108
50 sites, FedPer	**0.6188** ± 0.0240	272.3	3.37	108
50 sites, TierFed	0.6048 ± 0.0170	99.8	3.21	108
100 sites, FedAvg	**0.6068** ± 0.0210	546.1	3.99	142
100 sites, FedLAMA	0.6061 ± 0.0230	437.1	3.86	142
100 sites, FedPer	0.5929 ± 0.0255	544.5	3.86	142
100 sites, TierFed	0.5883 ± 0.0157	199.7	3.57	142

TABLE S-XII
SOCKET REPLAY OF THE WIDE-MLP RUNS (1,740,290 PARAMETERS, 3 SEEDS; CELL-EDGE PROFILE FOR ONE SEED): EACH RUN'S LOGGED PER-SITE UPLOADS SENT OVER LOOPBACK TCP PACED AT THE PROFILE'S RATE. TOTAL REPLAYED UPLOAD TIME, THE ANALYTIC PREDICTION, THEIR RELATIVE DIFFERENCE, TOTAL COMPUTE TIME OF THE SLOWEST SITE, AND WALL-CLOCK TIME TO AUROC 0.60 AND 0.62 ("NEVER": NOT REACHED IN 60 ROUNDS)

Profile	Method	Emulated (s)	Analytic (s)	Diff. (%)	Compute (s)	$t_{0.60}$ (s)	$t_{0.62}$ (s)
Wired WAN	AdaComm	5.2	5.1	-1.7	10	1	never
Wired WAN	FedAvg	34.6	34.0	-1.7	10	1	2
Wired WAN	FedPer	34.6	34.0	-1.6	10	1	2
Wired WAN	Fixed schedule	9.2	9.1	-1.7	10	1	2
Wired WAN	TierFed	10.4	10.2	-1.9	10	1	2
5G NR, typical	AdaComm	10.2	10.2	-0.2	10	1	never
5G NR, typical	FedAvg	68.2	68.0	-0.2	10	2	3
5G NR, typical	FedPer	68.1	68.0	-0.2	10	3	4
5G NR, typical	Fixed schedule	18.2	18.1	-0.2	10	1	4
5G NR, typical	TierFed	20.4	20.4	-0.2	10	3	4
5G NR, cell edge	AdaComm	100.5	100.5	0.1	10	11	never
5G NR, cell edge	FedAvg	669.6	670.1	0.1	11	13	24
5G NR, cell edge	FedPer	669.2	669.7	0.1	10	23	34
5G NR, cell edge	Fixed schedule	178.5	178.6	0.1	10	12	35
5G NR, cell edge	TierFed	200.8	200.9	0.1	10	23	34

TABLE S-XIII
MATCHED-PRIVACY COMPARISON ON THE 20 SPECIALTY SITES, ALL SETTINGS INCLUDING $q = 1$ (10 SEEDS, $C = 1$, $\delta = 10^{-5}$); COLUMNS AS IN THE MAIN TEXT

q, $\varepsilon^\star$, method	σ	Releases	AUROC
0.5, 1, FedAvg	19.14	60	0.5073 ± 0.0163
0.5, 1, FedPer	19.14	60	0.5102 ± 0.0092
0.5, 1, Fixed $K = 4$	10.95	19	0.5150 ± 0.0083
0.5, 1, Fixed $K = 8$	8.83	12	**0.5208** ± 0.0086
0.5, 1, TierFed-DP	12.00	23	0.5115 ± 0.0094
0.5, 2, FedAvg	9.84	60	0.5079 ± 0.0193
0.5, 2, FedPer	9.84	60	0.5090 ± 0.0092
0.5, 2, Fixed $K = 4$	5.72	19	0.5178 ± 0.0149
0.5, 2, Fixed $K = 8$	4.66	12	**0.5248** ± 0.0113
0.5, 2, TierFed-DP	6.25	23	0.5118 ± 0.0105
0.5, 4, FedAvg	5.18	60	0.5104 ± 0.0198
0.5, 4, FedPer	5.18	60	0.5135 ± 0.0089
0.5, 4, Fixed $K = 4$	3.09	19	0.5218 ± 0.0134
0.5, 4, Fixed $K = 8$	2.57	12	**0.5292** ± 0.0110
0.5, 4, TierFed-DP	3.36	23	0.5127 ± 0.0106
0.5, 8, FedAvg	2.84	60	0.5148 ± 0.0173
0.5, 8, FedPer	2.84	60	0.5162 ± 0.0107
0.5, 8, Fixed $K = 4$	1.76	19	0.5300 ± 0.0163
0.5, 8, Fixed $K = 8$	1.48	12	**0.5460** ± 0.0164
0.5, 8, TierFed-DP	1.89	23	0.5144 ± 0.0083
1.0, 4, FedAvg	10.04	60	0.5100 ± 0.0192
1.0, 4, FedPer	10.04	60	0.5174 ± 0.0103
1.0, 4, Fixed $K = 4$	5.65	19	**0.5294** ± 0.0083
1.0, 4, Fixed $K = 8$	4.49	12	0.5272 ± 0.0104
1.0, 4, TierFed-DP	6.22	23	0.5211 ± 0.0121

TABLE S-XIV
MATCHED-PRIVACY COMPARISON ON THE 100-SITE DIRICHLET FEDERATION (10 SEEDS, $C = 1$, $\delta = 10^{-5}$); COLUMNS AS IN THE MAIN TEXT

q, $\varepsilon^\star$, method	σ	Releases	AUROC
0.2, 1, FedAvg	7.86	60	0.5062 ± 0.0197
0.2, 1, FedPer	7.86	60	0.5069 ± 0.0115
0.2, 1, Fixed $K = 4$	4.73	19	0.5109 ± 0.0203
0.2, 1, Fixed $K = 8$	3.95	12	0.5112 ± 0.0148
0.2, 1, TierFed-DP	5.12	23	**0.5114** ± 0.0219
0.2, 2, FedAvg	4.15	60	0.5126 ± 0.0216
0.2, 2, FedPer	4.15	60	0.5076 ± 0.0117
0.2, 2, Fixed $K = 4$	2.64	19	0.5108 ± 0.0206
0.2, 2, Fixed $K = 8$	2.28	12	**0.5139** ± 0.0188
0.2, 2, TierFed-DP	2.83	23	0.5100 ± 0.0246
0.2, 4, FedAvg	2.31	60	0.5159 ± 0.0200
0.2, 4, FedPer	2.31	60	0.5064 ± 0.0147
0.2, 4, Fixed $K = 4$	1.59	19	0.5117 ± 0.0201
0.2, 4, Fixed $K = 8$	1.42	12	**0.5180** ± 0.0232
0.2, 4, TierFed-DP	1.67	23	0.5122 ± 0.0226
0.2, 8, FedAvg	1.39	60	0.5175 ± 0.0211
0.2, 8, FedPer	1.39	60	0.5064 ± 0.0142
0.2, 8, Fixed $K = 4$	1.04	19	0.5112 ± 0.0204
0.2, 8, Fixed $K = 8$	0.93	12	**0.5217** ± 0.0216
0.2, 8, TierFed-DP	1.09	23	0.5101 ± 0.0220
0.5, 4, FedAvg	5.18	60	0.5196 ± 0.0203
0.5, 4, FedPer	5.18	60	0.5135 ± 0.0094
0.5, 4, Fixed $K = 4$	3.09	19	0.5304 ± 0.0151
0.5, 4, Fixed $K = 8$	2.57	12	**0.5421** ± 0.0159
0.5, 4, TierFed-DP	3.36	23	0.5274 ± 0.0281

TABLE S-XV
FED-HEART-DISEASE, ONE CLIENT PER REAL INSTITUTION (4 INSTITUTIONS, 10 SEEDS, NO DP). TARGET: ANY ANGIOGRAPHIC DISEASE; MISSINGNESS INDICATORS ARE ADDED BECAUSE TWO FEATURES ARE MOSTLY MISSING OUTSIDE CLEVELAND

Method	AUROC	AUPRC	Upload (MB)	Tx rounds
AdaComm	0.7994 ± 0.0397	0.878	4.2	9
FedAvg	0.8128 ± 0.0356	0.876	28.4	60
FedLAMA	**0.8184** ± 0.0337	0.881	20.4	60
FedPer	0.8016 ± 0.0305	0.873	28.3	60
FedProx	0.8136 ± 0.0352	0.877	28.4	60
Fixed schedule	0.8171 ± 0.0350	0.886	7.6	16
LAG	0.8102 ± 0.0324	0.876	28.4	60
SCAFFOLD	0.7533 ± 0.0479	0.832	56.9	60
TierFed	0.8131 ± 0.0314	0.884	8.5	18

TABLE S-XVI
EARLIER PROTOCOL, FINAL-ROUND READING (SUPERSEDED; IT FAVOURS SPARSE SCHEDULES, SECTION V-B OF THE MAIN TEXT). PAIRED COMPARISON OF FINAL AUROC AGAINST FEDPER ON THE MAIN CASE (10 SEEDS): MEAN DIFFERENCE, BCA 95% INTERVAL, HOLM-CORRECTED p OVER THE EIGHT CONTRASTS, PAIRED d_z

Comparison	Δ	95% CI	p_{Holm}	d_z	Sig.
AdaComm vs FedPer	+0.0087	[0.0070, 0.0105]	< 0.001	2.66	✓
FedAvg vs FedPer	-0.0012	[-0.0038, 0.0004]	0.578	-0.33	
FedLAMA vs FedPer	+0.0076	[0.0058, 0.0101]	0.001	1.91	✓
FedProx vs FedPer	+0.0065	[0.0042, 0.0085]	0.005	1.57	✓
Fixed schedule vs FedPer	+0.0124	[0.0101, 0.0156]	< 0.001	2.44	✓
LAG vs FedPer	+0.0136	[0.0100, 0.0166]	< 0.001	2.23	✓
SCAFFOLD vs FedPer	-0.0284	[-0.0397, -0.0196]	0.005	-1.57	✓
TierFed vs FedPer	+0.0054	[0.0023, 0.0079]	0.036	1.03	✓