XJ-2000 Control Cabinet — Installation and Maintenance Manual

Document number: XJ2000-MAN-EN-04 | Revision: C

1.1 General

This manual describes the installation, commissioning and maintenance procedures for the XJ-2000 control cabinet. Read the safety instructions carefully before unpacking the equipment.

The control cabinet must be installed in a dry, well-ventilated room where the ambient temperature remains between 5 °C and 40 °C and the relative humidity does not exceed 85 percent.

Connect the cabinet to the rated power supply and allow it to stabilise for 30 minutes before any measurement is taken. Verify that the protective earth conductor is connected properly.

The thermal efficiency reaches 42.7 percent at full load. Deviations of more than 2 percentage points indicate a blocked air filter or a defective cooling fan.

Warning: do not open the enclosure while the equipment is running. Residual voltage remains on the DC bus capacitors for at least 60 seconds after the main switch has been turned off.

Please refer to Figure 3 for the wiring diagram of the control cabinet. Terminal assignments are listed in Table 2. Tighten all screw terminals to a torque of 1.2 newton metres.

Maintenance intervals depend on the duty cycle. Under continuous operation, inspect the cooling system every three months and replace the air filter at least once a year.

The warranty does not cover damage caused by unauthorised modification, improper installation, or operation outside the specified ambient conditions.

1.2 Checklist

1. Verify the protective earth connection.
2. Check the torque of all screw terminals.
3. Record the ambient temperature and humidity.
4. Confirm the firmware revision in the service log.

Table 2. Technical data

Parameter	Value	Unit
Rated voltage	400	V AC
Rated power	3.2	kW
Thermal efficiency	42.7	%
Protection class	IP54	-
Weight	38.5	kg

2. Technical Specifications

2.1 General

This manual describes the installation, commissioning and maintenance procedures for the XJ-2000 control cabinet. Read the safety instructions carefully before unpacking the equipment.

The control cabinet must be installed in a dry, well-ventilated room where the ambient temperature remains between 5 °C and 40 °C and the relative humidity does not exceed 85 percent.

Connect the cabinet to the rated power supply and allow it to stabilise for 30 minutes before any measurement is taken. Verify that the protective earth conductor is connected properly.

The thermal efficiency reaches 42.7 percent at full load. Deviations of more than 2 percentage points indicate a blocked air filter or a defective cooling fan.

Warning: do not open the enclosure while the equipment is running. Residual voltage remains on the DC bus capacitors for at least 60 seconds after the main switch has been turned off.

Please refer to Figure 3 for the wiring diagram of the control cabinet. Terminal assignments are listed in Table 2. Tighten all screw terminals to a torque of 1.2 newton metres.

Maintenance intervals depend on the duty cycle. Under continuous operation, inspect the cooling system every three months and replace the air filter at least once a year.

The warranty does not cover damage caused by unauthorised modification, improper installation, or operation outside the specified ambient conditions.

2.2 Checklist

1. Verify the protective earth connection.
2. Check the torque of all screw terminals.
3. Record the ambient temperature and humidity.
4. Confirm the firmware revision in the service log.

3. Mechanical Installation

3.1 General

This manual describes the installation, commissioning and maintenance procedures for the XJ-2000 control cabinet. Read the safety instructions carefully before unpacking the equipment.

The control cabinet must be installed in a dry, well-ventilated room where the ambient temperature remains between 5 °C and 40 °C and the relative humidity does not exceed 85 percent.

Connect the cabinet to the rated power supply and allow it to stabilise for 30 minutes before any measurement is taken. Verify that the protective earth conductor is connected properly.

The thermal efficiency reaches 42.7 percent at full load. Deviations of more than 2 percentage points indicate a blocked air filter or a defective cooling fan.

Warning: do not open the enclosure while the equipment is running. Residual voltage remains on the DC bus capacitors for at least 60 seconds after the main switch has been turned off.

Please refer to Figure 3 for the wiring diagram of the control cabinet. Terminal assignments are listed in Table 2. Tighten all screw terminals to a torque of 1.2 newton metres.

Maintenance intervals depend on the duty cycle. Under continuous operation, inspect the cooling system every three months and replace the air filter at least once a year.

The warranty does not cover damage caused by unauthorised modification, improper installation, or operation outside the specified ambient conditions.

3.2 Checklist

1. Verify the protective earth connection.
2. Check the torque of all screw terminals.
3. Record the ambient temperature and humidity.
4. Confirm the firmware revision in the service log.

4. Electrical Connection

4.1 General

This manual describes the installation, commissioning and maintenance procedures for the XJ-2000 control cabinet. Read the safety instructions carefully before unpacking the equipment.

The control cabinet must be installed in a dry, well-ventilated room where the ambient temperature remains between 5 °C and 40 °C and the relative humidity does not exceed 85 percent.

Connect the cabinet to the rated power supply and allow it to stabilise for 30 minutes before any measurement is taken. Verify that the protective earth conductor is connected properly.

The thermal efficiency reaches 42.7 percent at full load. Deviations of more than 2 percentage points indicate a blocked air filter or a defective cooling fan.

Warning: do not open the enclosure while the equipment is running. Residual voltage remains on the DC bus capacitors for at least 60 seconds after the main switch has been turned off.

Please refer to Figure 3 for the wiring diagram of the control cabinet. Terminal assignments are listed in Table 2. Tighten all screw terminals to a torque of 1.2 newton metres.

Maintenance intervals depend on the duty cycle. Under continuous operation, inspect the cooling system every three months and replace the air filter at least once a year.

The warranty does not cover damage caused by unauthorised modification, improper installation, or operation outside the specified ambient conditions.

4.2 Checklist

1. Verify the protective earth connection.
2. Check the torque of all screw terminals.
3. Record the ambient temperature and humidity.
4. Confirm the firmware revision in the service log.

Table 2. Technical data

Parameter	Value	Unit
Rated voltage	400	V AC
Rated power	3.2	kW
Thermal efficiency	42.7	%
Protection class	IP54	-
Weight	38.5	kg

5. Commissioning Procedure

5.1 General

This manual describes the installation, commissioning and maintenance procedures for the XJ-2000 control cabinet. Read the safety instructions carefully before unpacking the equipment.

The control cabinet must be installed in a dry, well-ventilated room where the ambient temperature remains between 5 °C and 40 °C and the relative humidity does not exceed 85 percent.

Connect the cabinet to the rated power supply and allow it to stabilise for 30 minutes before any measurement is taken. Verify that the protective earth conductor is connected properly.

The thermal efficiency reaches 42.7 percent at full load. Deviations of more than 2 percentage points indicate a blocked air filter or a defective cooling fan.

Warning: do not open the enclosure while the equipment is running. Residual voltage remains on the DC bus capacitors for at least 60 seconds after the main switch has been turned off.

Please refer to Figure 3 for the wiring diagram of the control cabinet. Terminal assignments are listed in Table 2. Tighten all screw terminals to a torque of 1.2 newton metres.

Maintenance intervals depend on the duty cycle. Under continuous operation, inspect the cooling system every three months and replace the air filter at least once a year.

The warranty does not cover damage caused by unauthorised modification, improper installation, or operation outside the specified ambient conditions.

5.2 Checklist

1. Verify the protective earth connection.
2. Check the torque of all screw terminals.
3. Record the ambient temperature and humidity.
4. Confirm the firmware revision in the service log.

6. Thermal Performance

6.1 General

This manual describes the installation, commissioning and maintenance procedures for the XJ-2000 control cabinet. Read the safety instructions carefully before unpacking the equipment.

The control cabinet must be installed in a dry, well-ventilated room where the ambient temperature remains between 5 °C and 40 °C and the relative humidity does not exceed 85 percent.

Connect the cabinet to the rated power supply and allow it to stabilise for 30 minutes before any measurement is taken. Verify that the protective earth conductor is connected properly.

The thermal efficiency reaches 42.7 percent at full load. Deviations of more than 2 percentage points indicate a blocked air filter or a defective cooling fan.

Warning: do not open the enclosure while the equipment is running. Residual voltage remains on the DC bus capacitors for at least 60 seconds after the main switch has been turned off.

Please refer to Figure 3 for the wiring diagram of the control cabinet. Terminal assignments are listed in Table 2. Tighten all screw terminals to a torque of 1.2 newton metres.

Maintenance intervals depend on the duty cycle. Under continuous operation, inspect the cooling system every three months and replace the air filter at least once a year.

The warranty does not cover damage caused by unauthorised modification, improper installation, or operation outside the specified ambient conditions.

6.2 Checklist

1. Verify the protective earth connection.
2. Check the torque of all screw terminals.
3. Record the ambient temperature and humidity.
4. Confirm the firmware revision in the service log.

7. Maintenance Schedule

7.1 General

This manual describes the installation, commissioning and maintenance procedures for the XJ-2000 control cabinet. Read the safety instructions carefully before unpacking the equipment.

The control cabinet must be installed in a dry, well-ventilated room where the ambient temperature remains between 5 °C and 40 °C and the relative humidity does not exceed 85 percent.

Connect the cabinet to the rated power supply and allow it to stabilise for 30 minutes before any measurement is taken. Verify that the protective earth conductor is connected properly.

The thermal efficiency reaches 42.7 percent at full load. Deviations of more than 2 percentage points indicate a blocked air filter or a defective cooling fan.

Warning: do not open the enclosure while the equipment is running. Residual voltage remains on the DC bus capacitors for at least 60 seconds after the main switch has been turned off.

Please refer to Figure 3 for the wiring diagram of the control cabinet. Terminal assignments are listed in Table 2. Tighten all screw terminals to a torque of 1.2 newton metres.

Maintenance intervals depend on the duty cycle. Under continuous operation, inspect the cooling system every three months and replace the air filter at least once a year.

The warranty does not cover damage caused by unauthorised modification, improper installation, or operation outside the specified ambient conditions.

7.2 Checklist

1. Verify the protective earth connection.
2. Check the torque of all screw terminals.
3. Record the ambient temperature and humidity.
4. Confirm the firmware revision in the service log.

Table 2. Technical data

Parameter	Value	Unit
Rated voltage	400	V AC
Rated power	3.2	kW
Thermal efficiency	42.7	%
Protection class	IP54	-
Weight	38.5	kg

8. Troubleshooting

8.1 General

This manual describes the installation, commissioning and maintenance procedures for the XJ-2000 control cabinet. Read the safety instructions carefully before unpacking the equipment.

The control cabinet must be installed in a dry, well-ventilated room where the ambient temperature remains between 5 °C and 40 °C and the relative humidity does not exceed 85 percent.

Connect the cabinet to the rated power supply and allow it to stabilise for 30 minutes before any measurement is taken. Verify that the protective earth conductor is connected properly.

The thermal efficiency reaches 42.7 percent at full load. Deviations of more than 2 percentage points indicate a blocked air filter or a defective cooling fan.

Warning: do not open the enclosure while the equipment is running. Residual voltage remains on the DC bus capacitors for at least 60 seconds after the main switch has been turned off.

Please refer to Figure 3 for the wiring diagram of the control cabinet. Terminal assignments are listed in Table 2. Tighten all screw terminals to a torque of 1.2 newton metres.

Maintenance intervals depend on the duty cycle. Under continuous operation, inspect the cooling system every three months and replace the air filter at least once a year.

The warranty does not cover damage caused by unauthorised modification, improper installation, or operation outside the specified ambient conditions.

8.2 Checklist

1. Verify the protective earth connection.
2. Check the torque of all screw terminals.
3. Record the ambient temperature and humidity.
4. Confirm the firmware revision in the service log.

9. Spare Parts

9.1 General

This manual describes the installation, commissioning and maintenance procedures for the XJ-2000 control cabinet. Read the safety instructions carefully before unpacking the equipment.

The control cabinet must be installed in a dry, well-ventilated room where the ambient temperature remains between 5 °C and 40 °C and the relative humidity does not exceed 85 percent.

Connect the cabinet to the rated power supply and allow it to stabilise for 30 minutes before any measurement is taken. Verify that the protective earth conductor is connected properly.

The thermal efficiency reaches 42.7 percent at full load. Deviations of more than 2 percentage points indicate a blocked air filter or a defective cooling fan.

Warning: do not open the enclosure while the equipment is running. Residual voltage remains on the DC bus capacitors for at least 60 seconds after the main switch has been turned off.

Please refer to Figure 3 for the wiring diagram of the control cabinet. Terminal assignments are listed in Table 2. Tighten all screw terminals to a torque of 1.2 newton metres.

Maintenance intervals depend on the duty cycle. Under continuous operation, inspect the cooling system every three months and replace the air filter at least once a year.

The warranty does not cover damage caused by unauthorised modification, improper installation, or operation outside the specified ambient conditions.

9.2 Checklist

1. Verify the protective earth connection.
2. Check the torque of all screw terminals.
3. Record the ambient temperature and humidity.
4. Confirm the firmware revision in the service log.

10. Disposal and Recycling

10.1 General

This manual describes the installation, commissioning and maintenance procedures for the XJ-2000 control cabinet. Read the safety instructions carefully before unpacking the equipment.

The control cabinet must be installed in a dry, well-ventilated room where the ambient temperature remains between 5 °C and 40 °C and the relative humidity does not exceed 85 percent.

Connect the cabinet to the rated power supply and allow it to stabilise for 30 minutes before any measurement is taken. Verify that the protective earth conductor is connected properly.

The thermal efficiency reaches 42.7 percent at full load. Deviations of more than 2 percentage points indicate a blocked air filter or a defective cooling fan.

Warning: do not open the enclosure while the equipment is running. Residual voltage remains on the DC bus capacitors for at least 60 seconds after the main switch has been turned off.

Please refer to Figure 3 for the wiring diagram of the control cabinet. Terminal assignments are listed in Table 2. Tighten all screw terminals to a torque of 1.2 newton metres.

Maintenance intervals depend on the duty cycle. Under continuous operation, inspect the cooling system every three months and replace the air filter at least once a year.

The warranty does not cover damage caused by unauthorised modification, improper installation, or operation outside the specified ambient conditions.

10.2 Checklist

1. Verify the protective earth connection.
2. Check the torque of all screw terminals.
3. Record the ambient temperature and humidity.
4. Confirm the firmware revision in the service log.

Table 2. Technical data

Parameter	Value	Unit
Rated voltage	400	V AC
Rated power	3.2	kW
Thermal efficiency	42.7	%
Protection class	IP54	-
Weight	38.5	kg

11. Safety Instructions

11.1 General

This manual describes the installation, commissioning and maintenance procedures for the XJ-2000 control cabinet. Read the safety instructions carefully before unpacking the equipment.

The control cabinet must be installed in a dry, well-ventilated room where the ambient temperature remains between 5 °C and 40 °C and the relative humidity does not exceed 85 percent.

Connect the cabinet to the rated power supply and allow it to stabilise for 30 minutes before any measurement is taken. Verify that the protective earth conductor is connected properly.

The thermal efficiency reaches 42.7 percent at full load. Deviations of more than 2 percentage points indicate a blocked air filter or a defective cooling fan.

Warning: do not open the enclosure while the equipment is running. Residual voltage remains on the DC bus capacitors for at least 60 seconds after the main switch has been turned off.

Please refer to Figure 3 for the wiring diagram of the control cabinet. Terminal assignments are listed in Table 2. Tighten all screw terminals to a torque of 1.2 newton metres.

Maintenance intervals depend on the duty cycle. Under continuous operation, inspect the cooling system every three months and replace the air filter at least once a year.

The warranty does not cover damage caused by unauthorised modification, improper installation, or operation outside the specified ambient conditions.

11.2 Checklist

1. Verify the protective earth connection.
2. Check the torque of all screw terminals.
3. Record the ambient temperature and humidity.
4. Confirm the firmware revision in the service log.

12. Technical Specifications

12.1 General

This manual describes the installation, commissioning and maintenance procedures for the XJ-2000 control cabinet. Read the safety instructions carefully before unpacking the equipment.

The control cabinet must be installed in a dry, well-ventilated room where the ambient temperature remains between 5 °C and 40 °C and the relative humidity does not exceed 85 percent.

Connect the cabinet to the rated power supply and allow it to stabilise for 30 minutes before any measurement is taken. Verify that the protective earth conductor is connected properly.

The thermal efficiency reaches 42.7 percent at full load. Deviations of more than 2 percentage points indicate a blocked air filter or a defective cooling fan.

Warning: do not open the enclosure while the equipment is running. Residual voltage remains on the DC bus capacitors for at least 60 seconds after the main switch has been turned off.

Please refer to Figure 3 for the wiring diagram of the control cabinet. Terminal assignments are listed in Table 2. Tighten all screw terminals to a torque of 1.2 newton metres.

Maintenance intervals depend on the duty cycle. Under continuous operation, inspect the cooling system every three months and replace the air filter at least once a year.

The warranty does not cover damage caused by unauthorised modification, improper installation, or operation outside the specified ambient conditions.

12.2 Checklist

1. Verify the protective earth connection.
2. Check the torque of all screw terminals.
3. Record the ambient temperature and humidity.
4. Confirm the firmware revision in the service log.

13. Mechanical Installation

13.1 General

This manual describes the installation, commissioning and maintenance procedures for the XJ-2000 control cabinet. Read the safety instructions carefully before unpacking the equipment.

The control cabinet must be installed in a dry, well-ventilated room where the ambient temperature remains between 5 °C and 40 °C and the relative humidity does not exceed 85 percent.

Connect the cabinet to the rated power supply and allow it to stabilise for 30 minutes before any measurement is taken. Verify that the protective earth conductor is connected properly.

The thermal efficiency reaches 42.7 percent at full load. Deviations of more than 2 percentage points indicate a blocked air filter or a defective cooling fan.

Warning: do not open the enclosure while the equipment is running. Residual voltage remains on the DC bus capacitors for at least 60 seconds after the main switch has been turned off.

Please refer to Figure 3 for the wiring diagram of the control cabinet. Terminal assignments are listed in Table 2. Tighten all screw terminals to a torque of 1.2 newton metres.

Maintenance intervals depend on the duty cycle. Under continuous operation, inspect the cooling system every three months and replace the air filter at least once a year.

The warranty does not cover damage caused by unauthorised modification, improper installation, or operation outside the specified ambient conditions.

13.2 Checklist

1. Verify the protective earth connection.
2. Check the torque of all screw terminals.
3. Record the ambient temperature and humidity.
4. Confirm the firmware revision in the service log.

Table 2. Technical data

Parameter	Value	Unit
Rated voltage	400	V AC
Rated power	3.2	kW
Thermal efficiency	42.7	%
Protection class	IP54	-
Weight	38.5	kg

14. Electrical Connection

14.1 General

This manual describes the installation, commissioning and maintenance procedures for the XJ-2000 control cabinet. Read the safety instructions carefully before unpacking the equipment.

The control cabinet must be installed in a dry, well-ventilated room where the ambient temperature remains between 5 °C and 40 °C and the relative humidity does not exceed 85 percent.

Connect the cabinet to the rated power supply and allow it to stabilise for 30 minutes before any measurement is taken. Verify that the protective earth conductor is connected properly.

The thermal efficiency reaches 42.7 percent at full load. Deviations of more than 2 percentage points indicate a blocked air filter or a defective cooling fan.

Warning: do not open the enclosure while the equipment is running. Residual voltage remains on the DC bus capacitors for at least 60 seconds after the main switch has been turned off.

Please refer to Figure 3 for the wiring diagram of the control cabinet. Terminal assignments are listed in Table 2. Tighten all screw terminals to a torque of 1.2 newton metres.

Maintenance intervals depend on the duty cycle. Under continuous operation, inspect the cooling system every three months and replace the air filter at least once a year.

The warranty does not cover damage caused by unauthorised modification, improper installation, or operation outside the specified ambient conditions.

14.2 Checklist

1. Verify the protective earth connection.
2. Check the torque of all screw terminals.
3. Record the ambient temperature and humidity.
4. Confirm the firmware revision in the service log.

15. Commissioning Procedure

15.1 General

This manual describes the installation, commissioning and maintenance procedures for the XJ-2000 control cabinet. Read the safety instructions carefully before unpacking the equipment.

The control cabinet must be installed in a dry, well-ventilated room where the ambient temperature remains between 5 °C and 40 °C and the relative humidity does not exceed 85 percent.

Connect the cabinet to the rated power supply and allow it to stabilise for 30 minutes before any measurement is taken. Verify that the protective earth conductor is connected properly.

The thermal efficiency reaches 42.7 percent at full load. Deviations of more than 2 percentage points indicate a blocked air filter or a defective cooling fan.

Warning: do not open the enclosure while the equipment is running. Residual voltage remains on the DC bus capacitors for at least 60 seconds after the main switch has been turned off.

Please refer to Figure 3 for the wiring diagram of the control cabinet. Terminal assignments are listed in Table 2. Tighten all screw terminals to a torque of 1.2 newton metres.

Maintenance intervals depend on the duty cycle. Under continuous operation, inspect the cooling system every three months and replace the air filter at least once a year.

The warranty does not cover damage caused by unauthorised modification, improper installation, or operation outside the specified ambient conditions.

15.2 Checklist

1. Verify the protective earth connection.
2. Check the torque of all screw terminals.
3. Record the ambient temperature and humidity.
4. Confirm the firmware revision in the service log.

16. Thermal Performance

16.1 General

This manual describes the installation, commissioning and maintenance procedures for the XJ-2000 control cabinet. Read the safety instructions carefully before unpacking the equipment.

The control cabinet must be installed in a dry, well-ventilated room where the ambient temperature remains between 5 °C and 40 °C and the relative humidity does not exceed 85 percent.

Connect the cabinet to the rated power supply and allow it to stabilise for 30 minutes before any measurement is taken. Verify that the protective earth conductor is connected properly.

The thermal efficiency reaches 42.7 percent at full load. Deviations of more than 2 percentage points indicate a blocked air filter or a defective cooling fan.

Warning: do not open the enclosure while the equipment is running. Residual voltage remains on the DC bus capacitors for at least 60 seconds after the main switch has been turned off.

Please refer to Figure 3 for the wiring diagram of the control cabinet. Terminal assignments are listed in Table 2. Tighten all screw terminals to a torque of 1.2 newton metres.

Maintenance intervals depend on the duty cycle. Under continuous operation, inspect the cooling system every three months and replace the air filter at least once a year.

The warranty does not cover damage caused by unauthorised modification, improper installation, or operation outside the specified ambient conditions.

16.2 Checklist

1. Verify the protective earth connection.
2. Check the torque of all screw terminals.
3. Record the ambient temperature and humidity.
4. Confirm the firmware revision in the service log.

Table 2. Technical data

Parameter	Value	Unit
Rated voltage	400	V AC
Rated power	3.2	kW
Thermal efficiency	42.7	%
Protection class	IP54	-
Weight	38.5	kg

17. Maintenance Schedule

17.1 General

This manual describes the installation, commissioning and maintenance procedures for the XJ-2000 control cabinet. Read the safety instructions carefully before unpacking the equipment.

The control cabinet must be installed in a dry, well-ventilated room where the ambient temperature remains between 5 °C and 40 °C and the relative humidity does not exceed 85 percent.

Connect the cabinet to the rated power supply and allow it to stabilise for 30 minutes before any measurement is taken. Verify that the protective earth conductor is connected properly.

The thermal efficiency reaches 42.7 percent at full load. Deviations of more than 2 percentage points indicate a blocked air filter or a defective cooling fan.

Warning: do not open the enclosure while the equipment is running. Residual voltage remains on the DC bus capacitors for at least 60 seconds after the main switch has been turned off.

Please refer to Figure 3 for the wiring diagram of the control cabinet. Terminal assignments are listed in Table 2. Tighten all screw terminals to a torque of 1.2 newton metres.

Maintenance intervals depend on the duty cycle. Under continuous operation, inspect the cooling system every three months and replace the air filter at least once a year.

The warranty does not cover damage caused by unauthorised modification, improper installation, or operation outside the specified ambient conditions.

17.2 Checklist

1. Verify the protective earth connection.
2. Check the torque of all screw terminals.
3. Record the ambient temperature and humidity.
4. Confirm the firmware revision in the service log.

18. Troubleshooting

18.1 General

This manual describes the installation, commissioning and maintenance procedures for the XJ-2000 control cabinet. Read the safety instructions carefully before unpacking the equipment.

The control cabinet must be installed in a dry, well-ventilated room where the ambient temperature remains between 5 °C and 40 °C and the relative humidity does not exceed 85 percent.

Connect the cabinet to the rated power supply and allow it to stabilise for 30 minutes before any measurement is taken. Verify that the protective earth conductor is connected properly.

The thermal efficiency reaches 42.7 percent at full load. Deviations of more than 2 percentage points indicate a blocked air filter or a defective cooling fan.

Warning: do not open the enclosure while the equipment is running. Residual voltage remains on the DC bus capacitors for at least 60 seconds after the main switch has been turned off.

Please refer to Figure 3 for the wiring diagram of the control cabinet. Terminal assignments are listed in Table 2. Tighten all screw terminals to a torque of 1.2 newton metres.

Maintenance intervals depend on the duty cycle. Under continuous operation, inspect the cooling system every three months and replace the air filter at least once a year.

The warranty does not cover damage caused by unauthorised modification, improper installation, or operation outside the specified ambient conditions.

18.2 Checklist

1. Verify the protective earth connection.
2. Check the torque of all screw terminals.
3. Record the ambient temperature and humidity.
4. Confirm the firmware revision in the service log.

19. Spare Parts

19.1 General

This manual describes the installation, commissioning and maintenance procedures for the XJ-2000 control cabinet. Read the safety instructions carefully before unpacking the equipment.

The control cabinet must be installed in a dry, well-ventilated room where the ambient temperature remains between 5 °C and 40 °C and the relative humidity does not exceed 85 percent.

Connect the cabinet to the rated power supply and allow it to stabilise for 30 minutes before any measurement is taken. Verify that the protective earth conductor is connected properly.

The thermal efficiency reaches 42.7 percent at full load. Deviations of more than 2 percentage points indicate a blocked air filter or a defective cooling fan.

Warning: do not open the enclosure while the equipment is running. Residual voltage remains on the DC bus capacitors for at least 60 seconds after the main switch has been turned off.

Please refer to Figure 3 for the wiring diagram of the control cabinet. Terminal assignments are listed in Table 2. Tighten all screw terminals to a torque of 1.2 newton metres.

Maintenance intervals depend on the duty cycle. Under continuous operation, inspect the cooling system every three months and replace the air filter at least once a year.

The warranty does not cover damage caused by unauthorised modification, improper installation, or operation outside the specified ambient conditions.

19.2 Checklist

1. Verify the protective earth connection.
2. Check the torque of all screw terminals.
3. Record the ambient temperature and humidity.
4. Confirm the firmware revision in the service log.

Table 2. Technical data

Parameter	Value	Unit
Rated voltage	400	V AC
Rated power	3.2	kW
Thermal efficiency	42.7	%
Protection class	IP54	-
Weight	38.5	kg

20. Disposal and Recycling

20.1 General

This manual describes the installation, commissioning and maintenance procedures for the XJ-2000 control cabinet. Read the safety instructions carefully before unpacking the equipment.

The control cabinet must be installed in a dry, well-ventilated room where the ambient temperature remains between 5 °C and 40 °C and the relative humidity does not exceed 85 percent.

Connect the cabinet to the rated power supply and allow it to stabilise for 30 minutes before any measurement is taken. Verify that the protective earth conductor is connected properly.

The thermal efficiency reaches 42.7 percent at full load. Deviations of more than 2 percentage points indicate a blocked air filter or a defective cooling fan.

Warning: do not open the enclosure while the equipment is running. Residual voltage remains on the DC bus capacitors for at least 60 seconds after the main switch has been turned off.

Please refer to Figure 3 for the wiring diagram of the control cabinet. Terminal assignments are listed in Table 2. Tighten all screw terminals to a torque of 1.2 newton metres.

Maintenance intervals depend on the duty cycle. Under continuous operation, inspect the cooling system every three months and replace the air filter at least once a year.

The warranty does not cover damage caused by unauthorised modification, improper installation, or operation outside the specified ambient conditions.

20.2 Checklist

1. Verify the protective earth connection.
2. Check the torque of all screw terminals.
3. Record the ambient temperature and humidity.
4. Confirm the firmware revision in the service log.