

JavaScript DOM Events

Compact revision notes • concepts + working examples

1. click Event

Runs a function when an element is clicked.

```
let h1 = document.querySelector("h1");

h1.addEventListener("click", function () {
  h1.style.color = "red";
});
```

dblclick — runs when an element is double-clicked.

```
function dblclick() {
  p.style.color = "yellow";
}

let p = document.querySelector("p");

p.addEventListener("dblclick", dblclick);
```

removeEventListener() removes an event listener. The same function reference must be used.

```
p.removeEventListener("dblclick", dblclick);
```

2. input Event

Fires whenever the user enters or changes text in an input.

```
let inp = document.querySelector("input");

inp.addEventListener("input", function () {
  console.log("typed");
});
```

Event object: contains information about the event.

```
inp.addEventListener("input", function (evt) {
  console.log(evt);
});
```

evt.data gets the character entered. It can be **null** for actions such as deleting.

```
inp.addEventListener("input", function (evt) {
  if (evt.data !== null) {
    console.log(evt.data);
  }
});
```

3. change Event

Used when the value of an input, select, or textarea changes.

```
let sel = document.querySelector("select");
let device = document.querySelector("#device");

sel.addEventListener("change", function (details) {
  device.textContent = `${details.target.value} Device Selected!`;
});
```

target.value gets the current value of the element that triggered the event.

```
details.target.value
```

4. keydown Event

Fires when a keyboard key is pressed.

```
window.addEventListener("keydown", function (details) {
  console.log(details);
});
```

Get the key pressed:

```
window.addEventListener("keydown", function (details) {
  console.log(details.key);
});
```

Examples: **a** → "a" **Enter** → "Enter" **ArrowUp** → "ArrowUp"

Handling the Space key:

```
let char = document.querySelector("h1");

window.addEventListener("keydown", function (details) {
  if (details.key === " ") {
    char.textContent = "SPC";
  } else {
    char.textContent = details.key;
  }
});
```

Important: assigning `char = details.key` changes the variable, not the HTML element. Use `char.textContent = details.key` to change the element.

5. Custom File Upload Button

Hide the real file input and use your own button.

```
input {
  display: none;
}
```

Trigger the file input through JavaScript:

```
let btn = document.querySelector("#btn");
let fileinp = document.querySelector("#fileinp");

btn.addEventListener("click", function () {
  fileinp.click();
});
```

Get the selected file:

```

fileinp.addEventListener("change", function (details) {
  const file = details.target.files[0];

  if (file) {
    btn.textContent = file.name;
  }
});

```

Important parts

Code	Meaning
details.target	The element that triggered the event
details.target.value	Current value of the element
details.target.files	List of selected files
details.target.files[0]	First selected file
file.name	Name of the selected file

Complete file-upload version

```

let btn = document.querySelector("#btn");
let fileinp = document.querySelector("#fileinp");

btn.addEventListener("click", function () {
  fileinp.click();
});

fileinp.addEventListener("change", function (details) {
  const file = details.target.files[0];

  if (file) {
    btn.textContent = file.name;
  }
});

```

Quick Event Revision

Event	Used for
click	Single click
dblclick	Double click
input	Every input/change while typing
change	Value/selection changed
keydown	Keyboard key pressed

Core pattern

```

element.addEventListener("event", function (event) {
  // code
});

```

Event-object properties used: event.key • event.data • event.target • event.target.value • event.target.files