

### Overview

### **HP ProLiant ML10 Server**

The HP ProLiant ML10 Server is a single-socket 4U tower server, delivering excellent value in a large form factor that small businesses require to run a small network environment. It is outstanding for businesses looking for improved performance, number of available slots, and flexible storage options while staying within a tight budget.





#### **Front View:**

- 1. Optical Media Drive
- 2. USB Connectors
- 3. NIC Status LED
- 4. Drive Status LED
- 5. System Power Button/LED
- 6. LFF Drive
- 7. DIMM
- 8. CPU Fan
- 9. System Fan
- 10. PCIe2x16 (8,4,1) Slot
- 11. Power Supply
- 12. Access Panel

#### **Rear View:**

- 1. Power Supply Connector
- 2. Slot 1 PCIe
- 3. Slot 2 PCIe
- 4. Slot 3 PCIe
- 5. Slot 4 PCIe
- 6. USB Connector
- 7. NIC Connector
- 8. Video Connector

### What's New

- Supports up to 4 large form factor SATA drives
- Allows businesses to increase local storage as needed
- Provides low cost, reliable data storage solution

## Standard Features

Processor	Dual-Core Processor			
	Intel® Pentium® G2	2130 (3.20GHz/2-core/3MB/55W, 1600) Processor		
Cache Memory	Integrated 1x3MB	Level3 Intel® Smart Cache		
Chipset	Intel® C204 Series			
	<b>NOTE:</b> For more information regarding Intel® chipsets, please see the following URL: http://www.intel.com/products/server/chipsets/.			
Upgradeability	Up to 4 DIMM slots available for higher memory capacity Up to 4 LFF Hard Drives 4 PCIe 2.0 I/O slots for additional communications and storage expansion Optical Drive Bay			
0.6.1	· · · · · · · · · · · · · · · · · · ·			
On System Management Chipset				
Memory Protection	ECC			
Memory	Туре	PC3-12800E-11 unbuffered DDR3 ECC up to 1600MT/s		
	DIMM Slots	Total 4 DIMM slots		
	Standard	2GB GB (1x2GB)		
	Maximum	32GB		
Network Controller	HP NC112i 1-Port Ethernet Server Adapter (X1)			

<b>Expansion Slots</b>	Expansion Slot #	Technology	Bus Width***	Connector Width	Form Factor
	1	PCIe G2	x16	x16	Full height & Half- length slot
	2	PCIe G2	X4	Х8	Full height & Half- length slot
	3	PCIe G2	X4	Х8	Full height & Half- length slot
	4	PCIe G2	X1	X4	Full height & Half- length slot

<sup>\*\*</sup> Slots are enumerated differently based on OS. MS OS's enumerate from lowest to highest Device ID by bus (starting with the lowest bus).

## **HP Server ROM**

HP ROM (Read Only Memory) is now digitally signed using HP's Corporate Signing Service. This signature is verified before the flash process starts, reducing accidental programming and preventing malicious efforts to corrupt system ROM.

HP ROM provides for essential initialization and validation of hardware components before control is passed to the customer-installed operating system. The ROM also provides the capability of booting from various fixed media (HDD, CD-ROM) and removable media (USB), to continue operation to the operating system.

<sup>\*\*\*</sup> Indicates the number of physical electrical lanes running to a PCI-e connector.

### Standard Features

HP ROM performs very early configuration of the video controller, to allow monitoring of initialization progress via an attached monitor. If configuration or hardware errors are discovered during this early phase of hardware initialization, suitable messages are now displayed on the connected monitor. Additionally, these configuration or hardware errors are logged to the Integrated Management Log (IML) to assist in diagnosis.

HP's ProLiant ROM is used to configure the following:

- Processor and chipset status registers
- System memory, memory map, and memory initialization
- System hardware configuration (Integrated PCI devices and optional PCIe cards).
- Customer-specific BIOS configuration (using the HP ROM-Based Setup Utility (RBSU).

**NOTE:** For further information, please refer to HP's RBSU (ROM based setup utility) user guide: www.hp.com/support/rbsu.

## Storage Controller

HP Embedded Smart Array B110i SATA RAID Controller (RAID 0/1/10)

**NOTE:** Supports up to two (2) 3.0Gb/s SATA hard disk drives only

NOTE: For set up instructions, please refer to the HP ProLiant ML100 series server user guide at: http://bizsupport1.austin.hp.com/bc/docs/support/SupportManual/c01708878/c01708878.pdf NOTE: For general information about HP Smart Array B110i SATA RAID Controller, please go to: http://h18004.www1.hp.com/products/servers/proliantstorage/arraycontrollers/smartarrayb110i/ index.html

#### Internal Storage Devices Optical Drive

HP Half-Height SATA DVD (Optional)

Standard Hard Drive (1) Non hot-plug LFF SATA

Hard Drive Bay

Configurations (depending

on option)

2 HDDs (no optical) Convert optical bay to 2nd LFF HDD bay

NOTE: Requires purchase of HP ML10 Hard Drive Enablement Kit

(#730641-B21)

3 HDDs (with optical) Replace internal single HDD carrier with a 3 x LFF carrier (leaving optical

bav available)

**NOTE:** Requires purchase of HP ML10 4 LFF Hard Drive Enablement Kit

(#742971-B21)

NOTE: The ML10 4LFF Hard Drive Enablement Kit: includes one carrier to convert the Optical Drive bay to one LFF Drive and includes a second carrier to support 3 internal LFF HDDs. The 3 x LFF carrier replaces the standard 1 x LFF carrier. For 3HDD Configurations, the carrier to convert the Optical

Drive day to one LFF Drive is left unused.

4 HDDs (no optical) Replace internal single HDD carrier with a 3 x LFF carrier and convert

optical bay to support 1 x LFF HDD

**NOTE:** Requires purchase of HP ML10 4 LFF Hard Drive Enablement Kit

(#742971-B21)

NOTE: The ML10 4LFF Hard Drive Enablement Kit: includes one carrier to convert the Optical Drive bay to one LFF Drive and includes a second carrier to support 3 internal LFF HDDs. The 3 x LFF carrier replaces the standard 1

x LFF carrier. Both carriers need to be installed.

Maximum Internal Storage Non-Hot Plug LFF SATA

8TB

4 x 2TB

NOTE: Requires purchase of optional HP ML10 4 LFF Hard Drive Enablement Kit (#742971-B21)



## **Standard Features**

Interfaces	Video Port	1				
	USB 2.0 Ports	7 total (4 rear, 2 front panel, 1 internal)				
	Network RJ-45 (Ethernet)	1 (shared for HP Integrated Lights-Out)				
	Remote Management	iLO3 remote management support				
Industry Standard Compliance	ACPI V3.0b Compliant PCI Express Rev 2.0 PXE Support					
	WOL Support IPMI 2.0 compliance					
	DCMI 1.0					
	Microsoft® Logo certificati Red Hat Enterprise Linux L					
	SUSE Linux Enterprise Ser					
	USB 2.0					
Server Power Cords	1.83m C13NEMA Power Co	ord				
Power Supply	300 Watts 80+ Bronze Nor	300 Watts 80+ Bronze Non-Hot Plug, Non redundant Power Supply				
System Fans	One Non-redundant system fan ships standard					
	One Non-redundant CPU h	eatsink fan ships standard				
Operating Systems and Virtualization Software	Microsoft Windows Server					
Support for ProLiant	SUSE Linux Enterprise Server (SLES)  NOTE: For more information on HD's Cortified and Supported ProLight Servers for OS and Virtualization					
Servers	<b>NOTE:</b> For more information on HP's Certified and Supported ProLiant Servers for OS and Virtualization Software and latest listing of software drivers available for your server, please visit our Support Matrix at: http://www.hp.com/go/ossupport and our driver download page: HP ProLiant ML10					
Form Factor	Micro ATX Tower (4U).					
HP Insight Management	HP Integrated Lights-Out 3 (3)	HP Integrated Lights-Out 3 (iLO) simplifies server setup, health monitoring, and lights-out remote administration of ProLiant ML, DL, and BL servers. HP iLO functions without additional software and can be accessed from any location via a web browser. HP iLO works hand-in-hand with HP Systems Insight Manager, Insight Control suites, and Insight Dynamics for ProLiant, helping customers unleash the value of the ProLiant platform and deliver the highest possible quality of IT service. For more information, visit: www.hp.com/go/iLO				
Security	Power-on password					
	Setup password					
	Secure Sockets Layer (SSL)					
	Secure Shell (SSH)					
	iLO 3 (Integrated Lights-Out 3) has 12 customizable user accounts and SSL encryption					
	iLO 3 can be disabled via a Global Setting					
	iLO Advanced supports dir	ectory services integration				
Warranty	This product is covered by a global limited warranty and supported by HP Services and a worldwide network of HP Authorized Channel Partners. Hardware diagnostic support and repair are available for					

## Standard Features

one year from date of purchase. Support for software and initial setup is available for 90 days from date of purchase. Enhancements to warranty services are available through HP Care Pack services or customized service agreements. Hard drives have one year warranty; refer to the specific hard drive QuickSpecs for details.

**NOTE:** Server Warranty includes 1 year parts, 1 year labor, 1-year on-site support with next business day response. Warranty repairs may be accomplished through the use of Customer Self Repair (CSR) parts. These parts fall into two categories: 1) Mandatory CSR parts are designed for easy replacement. A travel and labor charge will result when customers decline to replace a Mandatory CSR part; 2) Optional CSR parts are also designed for easy replacement but may involve added complexity. Customers may choose to have HP replace Optional CSR parts at no charge. Additional information regarding worldwide limited warranty and technical support is available at: http://h18004.www1.hp.com/products/servers/platforms/warranty/index.html



## **Optional Features**

**HP Insight management** HP Insight Control **software** 

HP Insight Control, a product option, delivers essential infrastructure management that can help save time and money by making it easy to deploy, migrate, monitor, remote control, and optimize your IT infrastructure through a single, simple management console. For more information, visit: www.hp.com/qo/insightcontrol.

HP Insight Control includes one year of 24 x 7 HP Software Technical Support and Update Service ensuring rapid access to HP support staff and proactive delivery of software updates. For more information about this service, please visit: http://www.hp.com/services/insight.

**NOTE:** HP Insight Control 7.2 introduces Insight Control server provisioning, a new capability ideal for multi-server OS and firmware provisioning to ProLiant and BladeSystem servers. Insight Control server provisioning is included and licensed as part of HP Insight Control. A media kit, "HP Insight Control server provisioning USB media kit" (# BD883A), including a USB, is available for customers who require a physical copy of the media loaded with Insight Control server provisioning software. Please note that this media kit is separate and in addition to the "HP Insight Management DVD media kit" (#C6N31A).



## Service and Support

#### **Service and Support**

## **HP Technology Services for Industry Standard Servers**

HP Technology Services delivers confidence, reduces risk and helps customers realize agility and stability. Connect to HP to help prevent problems and solve issues faster. Our support technology lets you to tap into the knowledge of millions of devices and thousands of experts to stay informed and in control, anywhere, any time.

## Protect your business beyond warranty with HP Care Pack Services

HP Care Pack Services enable you to order the right service level, length of coverage and response time as you purchase your new server, giving you full entitlement for the term you select.

#### **Optimized Care**

Supports maintaining servers at optimum performance availability

## HP Proactive Care with 24x7 coverage, three year Care Pack Service

HP Proactive Care helps prevent problems and stabilize IT by utilizing secure, real-time, predictive analytics and proactive consultations when your products are connected to HP. This Care Pack Service combines three years' proactive reporting and advice with our 24x7 coverage and enhanced escalation management, four hour hardware response time and two hour call back for software questions on leading industry standard software running on your HP ProLiant server.

http://h20195.www2.hp.com/v2/GetPDF.aspx/4AA3-8855ENW.pdf

#### **Standard Care Package**

Supports maintaining high level of server availability

## Foundation Care 24x7, three-year Care Pack Service

HP Foundation Care 24x7 connects you to HP 24 hours a day, seven days a week for assistance on resolving issues. Hardware onsite response within four hours if needed; collaborative software included in this Care Pack service provides troubleshooting assistance on industry leading software running on your HP server. Simplify your support experience and make HP your first call for hardware or software questions.

http://h20195.www2.hp.com/V2/GetDocument.aspx?docname=4AA4-8876ENW&cc=us&lc=en

#### **Basic Care Package**

Delivers minimum recommended support service level

## Foundation Care NBD, three-year Care Pack Service

HP Foundation Care Next Business Day connects you to HP during business hours for assistance on resolving issues - features next business day hardware onsite response if needed and software call back within two hours. Collaborative software support is included and provides troubleshooting assistance on industry leading software running on your server. Simplify your support experience and make HP your first call for hardware or software questions.

http://h20195.www2.hp.com/V2/GetDocument.aspx?docname=4AA4-8876ENW&cc=us&lc=en

#### **Related Services**

#### **HP ProLiant Server Hardware Installation**

Provides for the basic hardware installation of HP branded servers, storage devices and networking options to assist you in bringing your new hardware into operation in a timely and professional manner.

http://h20195.www2.hp.com/V2/GetPDF.aspx/5981-9356EN.pdf

#### Factory Express for Servers and storage

HP Factory Express offers configuration, customization, integration and deployment services for HP servers and storage products. Customers can choose how their factory solutions are built, tested, integrated, shipped and deployed. For more information on Factory Express services for your specific server model please contact your sales representative or go to: http://www.hp.com/go/factory-



## Service and Support

#### express.

#### **Data Privacy Services**

Protect your data through better media management. HP Data privacy services help manage and protect sensitive data to reduce the risk of unauthorized access to private information and help meet compliance requirements. Our retention services allow you to keep drives and other devices upon failure, our removal services provide convenient data sanitization and our recovery services allow you to safely retire IT assets and capture any remaining value from the hardware.

www.hp.com/services/dataprivacy

Additional HP Care Pack services can be found at: http://www.hp.com/go/cpc

## Get connected to HP to improve your support experience

Prevent problems with innovative, automated monitoring tools and proactive services. Combining Proactive Care Services with our remote support technology such as Insight Online provides you with expert advice and personalized, cloud-based automated IT support, helping to prevent unplanned down time and solve problems quickly. For more information, visit:

www.hp.com/go/proactiveinsightexperience

## **HP Support Center**

Personalized online support portal with access to information, tools and experts to support HP business products. Submit support cases online, chat with HP experts, access support resources or collaborate with peers. Learn more <a href="http://www.hp.com/go/hpsc">http://www.hp.com/go/hpsc</a>

HP's Support Center Mobile App\*\* allows you to resolve issues yourself or quickly connect to an agent for live support. Now, you can get access to personalized IT support anywhere, anytime.

HP Insight Remote Support and HP Support Center are available at no additional cost with a HP warranty, HP Care Pack or HP contractual support agreement.

\*\* HP Support Center Mobile App is subject to local availability

#### **Parts and Materials**

HP will provide HP-supported replacement parts and materials necessary to maintain the covered hardware product in operating condition, including parts and materials for available and recommended engineering improvements.

Parts and components that have reached their maximum supported lifetime and/or the maximum usage limitations as set forth in the manufacturer's operating manual, product QuickSpecs, or the technical product data sheet will not be provided, repaired, or replaced as part of these services.

The defective media retention service feature option applies only to Disk or eligible SSD/Flash Drives replaced by HP due to malfunction.

#### For more information

To learn more on HP ProLiant servers, please contact your HP sales representative or HP Authorized Channel Partner or visit: http://www.hp.com/services/proliant



## **Pre-configured Models**

## **SATA Model**

**NOTE:** Pre-configured models ship with the configurations below. Options can be selected from the Core or Additional options section of this QuickSpecs.

NOTE: HP does not allow factory integration of options into pre-configured models. Any additional options purchased will be shipped separately.

NOTE: For general information about HP Smart Array B110i SATA RAID Controller, please visit:

http://h18004.www1.hp.com/products/servers/proliantstorage/arraycontrollers/smartarrayb110i/index.html

## **Entry Model**

HP ProLiant ML10 G2130 Processor 1P 2GB-U B110i 300W PS

**Entry Server** 

730651-001

(1) Intel® Pentium® Processor G2130 (3.20GHz/2-core/3MB/55W, 1600)

Processor

**Cache Memory** 

3MB Intel® Smart Cache

Memory

2GB (1x2GB) PC3-12800E (DDR3-1600) Unbuffered DIMM

32GB Maximum memory capacity

NOTE: Total 4 DIMM slots.

**Network Controller** Storage Controller

HP NC112i 1-Port Ethernet Server Adapter (x1) HP Embedded Smart Array B110i SATA RAID Controller None ships standard (Single LFF carrier included)

**Hard Drive Optical Drive** 

HP Half-Height SATA DVD ROM JackBlack Optical Drive (Optional) HP Half-Height SATA DVD RW JackBlack Optical Drive (Optional)

**Power Supply** 

300 Watts 80+ Bronze Non-Hot Plug, Non redundant Power Supply

**Fans** 

One (1) - Non-redundant system fan ships standard

One (1) - Non-redundant CPU heatsink fan ships standard

**Accessories** 

Keyboard/mouse optional

Management

HP Integrated Lights-Out Standard (iLO 3)

**Form Factor** 

Micro ATX Tower (4U)

Warrantv

Server Warranty includes 1 year parts, 1 year labor, 1-year on-site support

with next business day response.



## **Smart Buys**

HP ProLiant ML10 E3-1220v2 1P 2GB-U US Server/S-Buy 737649-S01 **Processor** (1) Intel® Xeon® E3-1220v2 (3.1GHz/4-core/8MB/69W, HT) Processor

Cache Memory 8MB (1 x 8MB) L3 cache

Memory 2GB (1 x 2GB) PC3-12800E DDR3 UDIMM

**NOTE:** Total 4 DIMM slots.

**Network Controller** HP NC112i 1-Port Ethernet Server Adapter (x1)

Storage Controller HP Embedded Smart Array B110i SATA RAID Controller

**Hard Drive** None ships standard

Internal Storage Up to 2TB Non-hot plug LFF SATA (Maximum)

Optical Drive None ships standard

HP Half-Height SATA DVD ROM JackBlack Optical Drive (Optional) HP Half-Height SATA DVD RW JackBlack Optical Drive (Optional)

**Power Supply** 300 Watts 80+ Bronze Non-Hot Plug, Non redundant Power Supply

**Fans** One (1) - Non-redundant system fan ships standard

One (1) - Non-redundant CPU heatsink fan ships standard

Management HP Integrated Lights-Out Standard (iLO 3)

Form Factor Micro ATX Tower (4U)

Warranty Server Warranty includes 1 year parts, 1 year labor, 1-year on-site support

with next business day response.



## **Core Options**

HP Unique Options	HP ML10 Hard Drive Enablement Kit  NOTE: The ML10 HDD enablement Kit converts the Optical Drive bay to one LFF HDD  Carrier			
	HP ML10 4 LFF Hard Drive Enablement Kit <b>NOTE:</b> The ML10-4LFF Hard Drive Enablement Kit: includes one carrier to convert the Optical Drive bay to one LFF Drive and includes a second carrier to support 3 internal LFF HDDs. The 3 x LFF carrier replaces the standard 1 x LFF carrier.	742971-B21		
HP Memory	Unbuffered with ECC DIMMs (UDIMMs)			
	HP 2GB (1x2GB) Single Rank x8 PC3-12800E (DDR3-1600) Unbuffered CAS-11 Memory Kit	669320-B21		
	HP 4GB (1x4GB) Dual Rank x8 PC3-12800E (DDR3-1600) Unbuffered CAS-11 Memory Kit	669322-B21		
	HP 8GB (1x8GB) Dual Rank x8 PC3-12800E (DDR3-1600) Unbuffered CAS-11 Memory Kit	669324-B21		
	<b>NOTE:</b> All DDR3 memory option kits consist of one DIMM per kit. For detailed memory configuration rules and guidelines, please use the Online DDR3 Memory Configuration Tool: www.hp.com/go/ddr3memory-configurator. <b>NOTE:</b> Depending on the memory configuration and processor model, 1600MHz			
	memory may operate at a lower speed. Please see the see the "Memory" section later in this document and the Online Memory Configuration Tool for details at			
	www.hp.com/go/ddr3memory-configurator.  NOTE: For additional memory rules and guidelines, see the "Memory" section later in this document.  NOTE: For more information on ProLiant Energy Efficient Features, see:  www.hp.com/go/proliant-energy-efficient			
HP Optical Drives	HP Half-Height SATA DVD ROM JackBlack Optical Drive	624189-B21		
m optical bridges	HP Half-Height SATA DVD RW JackBlack Optical Drive	624192-B21		
HP Hard Drives	NOTE: The components of a storage subsystem (e.g. the drive, the HBA/controller, and firmware) should operate at the same data transfer rate or the system bandwidth will be negotiated down to an acceptable level for all components.  NOTE: Hard drives have either a one year or three year warranty; refer to the specific hard drive QuickSpecs for details.			
	SATA Non-Hot Plug LFF (3.5-inch) Midline (MDL) Drives			
	HP 2TB 3G SATA 7.2K rpm LFF (3.5-inch) Non-hot Plug Midline 1yr Warranty Hard Drive	507774-B21		
	HP 1TB 3G SATA 7.2K rpm LFF (3.5-inch) Non-hot Plug Midline 1yr Warranty Hard Drive	507772-B21		
	HP 500GB 3G SATA 7.2K rpm LFF (3.5-inch) Non-hot Plug Midline 1yr Warranty Hard Drive	458941-B21		
	NOTE: Please see the QuickSpecs for Technical Specifications and additional information: http://h18000.www1.hp.com/products/quickspecs/13021_na/13021_na.html			
HP ML10 HDD enablement Kit	<b>NOTE:</b> The ML10 HDD enablement Kit convert Optical Drive to one LFF Drive Carrier x 1	730641-B21		



## **Core Options**

SATA Cable x1 Mini SAS Cable x1

### **HP Networking**

### **Gigabit Ethernet Adapters**

HP NC112T PCI Express Gigabit Server Adapter503746-B21HP NC365T 4-port Ethernet Server Adapter593722-B21

 $\textbf{NOTE:} \ Please see the \ Quick Specs for \ Technical \ Specifications \ and \ additional$ 

information: www.hp.com/go/ProLiantNICs



## **Additional Options**

<b>HP Insight Software</b>	HP Insight Control					
	HP Insight Control including 1yr 24x7 Technical Support and Updates Electronic License	C6N28AAE				
	HP Insight Control Server Provisioning Media Kit	BD883A				
	HP Insight Management Media Kit	C6N31A				
	NOTE: Insight Software DVD media without licenses. Contains HP Systems Insight Manager, HP Insight Control, HP Insight Dynamics, HP Insight Control for Microsoft System Center, and Virtual Connect Enterprise Manager software. Uses an integrated installer to perform quick and accurate software installation and updates.  NOTE: Electronic and Flexible-Quantity licenses can be used to purchase multiple licenses with a single activation key.  NOTE: Customer will receive a license entitlement certificate. The license entitlement certificate must be redeemed online or via fax in order to obtain the license activation key(s). Includes one year of 24 x 7 HP Software Technical Support and Update Service.  NOTE: Licenses ship without media. The HP Insight Control Media Kit can be ordered separately, or can be downloaded at: http://www.hp.com/go/insightupdates  NOTE: For additional license options please see the QuickSpecs at: http://h18000.www1.hp.com/products/quickspecs/12631_na/12631_na.html.					
	<b>NOTE:</b> Licenses ship without media. The HP Insight Management Media Kit can be ordered separately, or can be downloaded at:					
	http://www.hp.com/go/insightupdates.  NOTE: Customer will receive a license entitlement certificate, which must be redeemed online or via fax in order to obtain the license activation key(s). Includes one year of 24 x 7 HP Software Technical Support Service.  NOTE: For additional license kits please see the Insight Control QuickSpecs at: http://h18004.www1.hp.com/products/quickspecs/12631_na/12631_na.html.					
	HP Integrated Lights-Out (iLO) HP Integrated Lights-Out (iLO) Advanced for ProLiant					
	HP iLO Advanced including 1yr 24x7 Technical Support and Updates Electronic License	TA850AAE				
HP Remote Monitoring	HP Remote Monitored Power Distribution Unit: Full Height Version					
Power Distribution Units (mPDU)	HP 17.3kVA 208 Volt IEC309 60A 3-Phase Watertight Input (12xC13/12xC19) NA/JP Monitored PDU	G9Z07A				
	NOTE: Please see the QuickSpecs for additional information: http://h18000.www1.hp.com/products/quickspecs/14669_na/14669_na.html					
<b>HP Rack Options</b>	HP USB Keyboard and Mouse					
	HP USB BFR with PVC Free US Keyboard/Mouse Kit	631341-B21				
	NOTE: Please see the QuickSpecs for Technical Specifications and additional information: http://h18000.www1.hp.com/products/quickspecs/13972_na/13972_na.html					
	HP Server Console Switches					
	HP Server Console 0x2x8 Port Analog Switch	AF616A				
	HP Server Console 0x2x16 Port Analog Switch	AF617A				
	HP KVM Console USB 2.0 Virtual Media CAC Interface Adapter	AF629A				
	<b>NOTE:</b> Please see the QuickSpecs for Technical Specifications and additional information:					
	information: http://h18000.www1.hp.com/products/quickspecs/11834_na/11834_na.html					



## **Additional Options**

### **HP Server Console Switch G2 with Virtual Media & CAC**

HP 0x2x16 KVM Server Console Switch G2 with Virtual Media CAC Software

HP 0x2x32 KVM Server Console Switch G2 with Virtual Media CAC Software

HP KVM Console USB 2.0 Virtual Media CAC Interface Adapter

AF629A

**NOTE:** Please see the QuickSpecs for Technical Specifications and additional information:

http://h18000.www1.hp.com/products/quickspecs/13475\_na/13475\_na.html



## Memory

### **HP ProLiant ML10 Models**

### **Standard Memory**

2GB PC3-12800E-11 unbuffered DDR3 ECC up to 1600MT/s

## **Maximum Memory with Optional Memory**

Up to 32GB of memory is available with the installation of optional memory, 4x 8 GB PC3-12800E un-buffered ECC DDR3 SDRAM DIMM Memory kits.

**NOTE:** The below chart does not represent all possible memory configurations.

**NOTE:** For best performance, it is recommended that customer installs memory in identical pairs (Slots 2A and 4B are interleaving pair. Slots 1C and 3D are interleaving pair).

Memory		Slot				
		DIMM1C	DIMM1C DIMM2A DIMM3D DIMM4B			
Standard (Entry Model)	2 GB	Empty	2 GB	Empty	Empty	
Maximum	32 GB	8 GB	8 GB	8 GB	8 GB	

## Following are memory options available from HP:

<b>HP Memory</b> HP 2GB (1x2GB) Single Rank x8 PC3-12800E (DDR3-1600) Unbuffered CAS-11	669320-B21
---	------------

Memory Kit

HP 4GB (1x4GB) Dual Rank x8 PC3-12800E (DDR3-1600) Unbuffered CAS-11 669322-B21

Memory Kit

HP 8GB (1x8GB) Dual Rank x8 PC3-12800E (DDR3-1600) Unbuffered CAS-11 669324-B21

Memory Kit

**NOTE:** All DDR3 memory option kits consist of one DIMM per kit. For detailed memory configuration rules and guidelines, please use the Online DDR3 Memory

Configuration Tool: www.hp.com/go/ddr3memory-configurator.



## Storage



## 1 Media Drive Bay

Optional: DVD Drive or DVD-RW Drive Optional: HDD cage for single HDD

Internal Optional: 3 bay LFF HDD cage. Internal access, replaces single LFF HDD

## **Drive Support**

Media	Quantity	Position	Controller
	Supported	Supported	
DVD Drive	1	1	Integrated SATA
DVD-RW Drive	1	1	Integrated SATA
LFF SATA HDD	1	1	B110i

Maximum Storage Capacity - SATA Models	
Internal	8TB (4 x 2TB) With optional 4LFF HDD Cage Option Kit

Gamay 300W ATX, E-star*6 PSU, BronzeF							
Part Number	699549-0	699549-001					
Operational Input Voltage Range (Vrms)	100 to 240	)					
Frequency Range (Nominal) (Hz)	50/60						
Nominal Input Voltage (Vrms)	100	120	200	208	220	230	240
Max Rated Output Wattage Rating	299.659	299.529	299.342	298.996	298.809	298.643	298.477
Nominal Input Current (A rms)	3.6942	3.0526	1.8369	1.7685	1.68	1.6149	1.555
Max Rated Input Wattage Rating (Watts)	362.401	357.197	350.015	349.342	348.86	348.381	347.917
Max. Rated VA (Volt-Amp)	369.42	366.769	367.509	367.883	369.751	371.685	373.542
Efficiency (%)	82.69	83.86	85.52	85.59	85.65	85.72	85.79
Power Factor	0.981	0.9739	0.9524	0.9496	0.9435	0.9373	0.9314
Leakage Current (mA)	0.26	0.3	0.44	0.46	0.49	0.52	0.54
Maximum British Thermal Unit Rating (BTU-Hr)	1243.4	1225.54	1200.9	1198.59	1196.94	1195.29	1193.7

**NOTE:** To review typical system power ratings use the HP Power Advisor which is available via the online tool located at URL: www.hp.com/go/proliant-energy-efficient or www.hp.com/go/hppoweradvisor

## **Technical Specifications**

System Unit	<b>Dimensions</b> (H x W x D) (with feet)	14.3 x 6.5 x 15 in (36.39 x	16.5 x 38.1 cm)
	Weight (approximate)	Non Hot Plug LFF Full Loading Single Package weight	9.74 kg (21.45 lb)
		Non Hot Plug LFF Full Loading without Package	7.80kg (17.18 lb)
		Non Hot Plug LFF light Loading without Package	5.94kg (13.08 lb)
	300W Input Requirements	Rated Line Voltage	90 to 140 VAC, 180 to 264 VAC
	(per power supply)	Rated Input Current	8A (at 100 VAC) 4A (at 200 VAC)
		Rated Input Frequency	47 to 63 Hz
		Rated Input Power	410W (at 115 VAC), 410W (at 200 VAC)
	Power Specifications	To review typical system pavailable via the online to http://www.hp.com/go/h	
	Power Supply Output (per power supply)	Rated Steady-State Powe	r 300 W (at 100 VAC), 300 W (at 200 VAC)
		Maximum Peak Power	320 W (at 100 VAC), 320 W (at 200 VAC)
	System Inlet Temperature	Operating	10° to 35°C (50° to 95°F) at sea level with an altitude derating of 1.0°C per every 305 m (1.8°F per every 1000 ft) above sea level to a maximum of 3050 m (10,000 ft), no direct sustained sunlight. Maximum rate of change is 10°C/hr (18°F/hr). The upper limit may be limited by the type and number of options installed.  System may shut down if operating with a fan
			fault or above 42°C (107.6°F).
		Non-operating	-30° to 60°C (-22° to 140°F). Maximum rate of change is 20°C/r (36°F/hr)
	Relative Humidity (non-condensing)	Operating	10% to 90% relative humidity (Rh), 28°C (82.4°F) maximum wet bulb temperature, noncondensing.
		Non-operating	5% to 95% relative humidity (Rh), 38.7°C (101.7°F) maximum wet bulb temperature, noncondensing.
	Altitude	Operating	Maximum allowable altitude change rate is 457 m/min (1500 ft/min).
		Non-operating	Maximum allowable altitude change rate is 457 m/min (1500 ft/min).
	Acoustic Noise		Weighted sound power levels (LWAd) and

declared average bystander position A-Weighted sound pressure levels (LpAm) when the product is operating in a 23°C ambient environment. Noise emissions were measured in accordance with ISO 7779 (ECMA 74) and

## Technical Specifications

declared in accordance with ISO 9296 (ECMA 109).

Level C (idle 5.6 bel/OP 6.0 bel)

**NOTE:** The listed sound levels above apply to standard SATA

configurations. Additional options may result in increased sound levels.

**Emissions Classification** 

(EMC)

FCC Rating Class B

Normative Standards CISPR 22; EN55022; EN55024; FCC CFR 47, Pt

15; ICES-003; CNS13438; GB9254; EN 61000-3-2: EN 61000-3-3: EN 60950-1: IEC 60950-1

**NOTE:** Product conformance to cited product specifications is based on sample (type) testing, evaluation, or assessment. This product or family of

products is eligible to bear the appropriate compliance logos and

statements.

Integrated Lights-Out Standard (iLO 3) integrated on system board Architecture PCI Express based health and remote management ASIC

**Processor** PCI Express RISC processor core running at 250MHz

**Upgradeability** Option firmware upgradeable via Flash ROM.

**Video Support** 1600 x 1200 DVR max resolution

Interfaces One Ethernet Sideband connection (10/100/1000 Mb/s)

Memory128-MB SDRAM with ECCOperating SystemMicrosoft Windows 2008 R2

**Support** Microsoft Windows 2008 (32 bit and 64 bit)

Microsoft Windows Server 2008 Standard Edition (32bit and 64bit)
Microsoft Windows Server 2008 Enterprise Edition (32bit and 64bit)

SUSE LINUX Enterprise Server 11 (32bit and 64bit) SUSE LINUX Enterprise Server 10 (32bit and 64bit)

**Client System Support** Microsoft Windows 7

Microsoft Windows XP Professional Edition

Microsoft Windows Vista Business and Ultimate Editions

SUSE Linux Enterprise Desktop 11 SUSE Linux Enterprise Desktop 10

Client Browser Support Microsoft Internet Explorer 8

Microsoft Internet Explorer 7
Microsoft Internet Explorer 6

Firefox 3.5 (on supported Windows and Linux systems) Firefox 3.0 (on supported Windows and Linux systems)

**Command Line Support** 

Security

Secure Shell and serial port access

Secure Socket Layer

Secure Shell version 2 (Password and certificate)

Advanced Encryption Standard (AES) and Triple Data Encryption Standard

(3DES) on browser, CLP and XML scripting interface

AES encryption of video RC4 encryption of video

**Directory Support** 

Services

Active Directory v1.0 (Windows 2008)

**Driver Support** HP ProLiant iLO 3 Management Controller Driver Package

iLO Management Channel Interface Driver

Management protocols

supported

SNMP, IPMI 2.0 (System and LAN interface), DMTF Systems Management Architecture for Server Hardware Command Line Protocol (SMASH CLP), HP

RIBCL XML

## **Technical Specifications**

**Environment-friendly Products and Approach** 

and Recycling

End-of-life Management Hewlett-Packard offers end-of-life HP product return, trade-in, and recycling programs in many geographic areas. For trade-in information, please go to: http://www.hp.com/go/green. To recycle your product, please go to: http://www.hp.com/go/green or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.

> The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: http://www.hp.com/go/green. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.



## **Summary of Changes**

Date	Version History	Action	Description of Change
09-Feb-2015	From Version 12 to 13	Added	New Hard Drives, DirectFlow UPS, Rack and Tower G4 Models, LCD8500 1U Rackmount Models and Options were added to the Additional Options section.
		Changed	HP Uninterruptible Power Systems, HP Rack Options, and HP Care Pack Services in Additional Options section were revised.
01-Nov-2014	From Version 11 to 12	Changed	Service and Support section was revised.
10-Jun-2014 From Version 10 to 11		Added	HP Remote Monitoring Power Distribution Units (mPDU) was added to Additional Options. HP Server Console Switches and HP Server Console Switch G2 with Virtual Media & CAC were added to Additional Options. Gamay 300W ATX, E-star*6 PSU, BronzeF was added to Storage.
		Changed	Front view image callout number 1 was updated. Updates made to HP Hard Drives, Insight Software and Memory sections.
18-Apr-2014	From Version 9 to 10	Changed	Basic Care Package and Memory were revised.
31-Mar-2014	From Version 8 to 9	Removed	HP Insight Control server deployment was removed from HP Insight Control.
25-Feb-2014	From Version 7 to 8	Changed	Changes made to the Models section only.

<sup>©</sup> Copyright 2015 Hewlett-Packard Development Company, L.P.

The information contained herein is subject to change without notice.

Microsoft and Windows NT are US registered trademarks of Microsoft Corporation.

AMD, the AMD Arrow logo, AMD Opteron™, and combinations thereof, are trademarks of Advanced Micro Devices, Inc.

The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

For hard drives, 1GB = 1 billion bytes. Actual formatted capacity is less.

