

the text-align css property is applied to what elements??

`text-align` is applied to a **block (or block-like) container element**, and it controls how the **inline content inside that element** is aligned horizontally.

What `text-align` affects

Inside the element you put it on, it aligns:

- **Text** (normal text)
- **inline elements** like: `span`, `a`, `strong`, `em`
- **inline-block elements** like: `img`, `button`, `input` (because they behave like inline/inline-block)

✔ So it does **not** “move the element itself” — it aligns the **content inside** the element.

Example 1: Center text and links inside a `div`

html

```
<div class="box">
  Hello
  <a href="#">Link</a>
</div>
```

css

```
.box {
  text-align: center;
  border: 1px solid black;
}
```

This centers **Hello** and the **link**.

Example 2: Center an image using `text-align`

Copy code

html

```
<div class="img-wrap">
  
</div>
```

css

```
.img-wrap {
  text-align: center;
```

```
}
```

Because `img` is `inline/inline-block` by default, it will be centered.

 Copy code

What `text-align` does NOT apply to (common confusion)

✗ It doesn't center a block element itself

CSS

```
div {
  text-align: center;
}
```

This will **not** center the `div` on the page.

To center a **block element**, usually do:

 Copy code

CSS

```
div {
  width: 300px;
  margin: 0 auto;
}
```

✗ It won't align flex/grid items

If the parent is `display: flex` or `display: grid`, `text-align` won't position the items. You'd use:

- Flex: `justify-content`, `align-items`
- Grid: `justify-items`, `align-items`

 Copy code

Quick rule to remember

- `text-align` → aligns **inline content inside an element**
- `margin: 0 auto` → centers the **block element itself**
- `justify-content` / `align-items` → for **flex/grid layouts**

If you want, paste your HTML/CSS and I'll tell you exactly why `text-align` is (or isn't) working there.



similar to this response , do it for all the commonly used css rules

Got it — here's a **beginner-friendly cheat sheet** of the **most commonly used CSS properties**, written like my `text-align` explanation: **what you put it on + what it affects + small examples**.

1) Text & Font (works on any element that contains text)

color

Put it on: any element
Affects: text color of that element (and usually inherited by children)

CSS

```
p { color: red; }
```

font-size, font-family, font-weight, font-style

 Copy code

Put it on: text elements or containers
Affects: text styling (inherited by children)

CSS

```
body { font-family: Arial; font-size: 16px; }  
h1 { font-weight: 700; }
```

line-height

Put it on: text elements/containers  Copy code
Affects: space between text lines

CSS

```
p { line-height: 1.6; }
```

text-align

 Copy code

Put it on: a container (block/block-like element)
Affects: inline content inside it (text, links, inline/inline-block like images)

CSS

```
.box { text-align: center; }
```

text-decoration

 Copy code

Put it on: text/links
Affects: underline/line-through, etc.

CSS

```
a { text-decoration: none; }
```

 Copy code

text-transform

Put it on: text elements

Affects: uppercase/lowercase/capitalize

CSS

```
h2 { text-transform: uppercase; }
```

letter-spacing, word-spacing

 Copy code

Put it on: text elements

Affects: spacing

CSS

```
h1 { letter-spacing: 2px; }
```

 Copy code

2) Box Model (works on almost all elements)

width, height

Put it on: any element

Affects: element size (for inline elements like span, width/height usually won't work unless you change display)

CSS

```
.card { width: 300px; height: 150px; }
```

padding

 Copy code

Put it on: any element

Affects: space inside the border

CSS

```
.card { padding: 16px; }
```

margin

 Copy code

Put it on: any element

Affects: space outside the border

✔ Center a block element with margin: 0 auto (needs width)

CSS

```
.card { width: 300px; margin: 0 auto; }
```

border

 Copy code

Put it on: any element
Affects: border line around element

CSS

```
.card { border: 2px solid black; }
```

box-sizing

Copy code

Put it on: usually all elements with `*`
Affects: how width/height is calculated (VERY common)

CSS

```
* { box-sizing: border-box; }
```

Copy code

3) Display (this decides how an element behaves)

display: block

Put it on: any element
Affects: element becomes block (takes full line)

CSS

```
a { display: block; }
```

display: inline

Copy code

Put it on: any element
Affects: element behaves inline (width/height don't apply normally)

CSS

```
div { display: inline; }
```

display: inline-block

Copy code

Put it on: any element
Affects: inline + allows width/height

CSS

```
span { display: inline-block; width: 120px; }
```

display: none

Copy code

Put it on: any element
Affects: element disappears (takes no space)

CSS

```
.hide { display: none; }
```

 Copy code

4) Background (works on most elements)

background-color

Put it on: any element

Affects: background fill

CSS

```
header { background-color: #eee; }
```

background-image, background-repeat, background-size, background-position

 Copy code

Put it on: any element

Affects: background image behavior

CSS

```
.hero {
  background-image: url(bg.jpg);
  background-size: cover;
  background-position: center;
}
```

5) Border & Corners

border-radius

 Copy code

Put it on: any element

Affects: rounded corners

CSS

```
button { border-radius: 8px; }
```

 Copy code

6) Overflow (when content is bigger than the box)

overflow

Put it on: elements with a fixed size

Affects: what happens to extra content

CSS

```
.box { width: 200px; height: 120px; overflow: auto; }
```

7) Visibility vs Display

[Copy code](#)

`visibility: hidden`

Put it on: any element

Affects: hides it BUT it still takes space

CSS

```
.item { visibility: hidden; }
```

[Copy code](#)

8) Positioning (moving elements)

`position`

Put it on: the element you want to position

Values: `static` (default), `relative`, `absolute`, `fixed`, `sticky`

CSS

```
.box { position: relative; top: 10px; }
```

`top`, `right`, `bottom`, `left`

[Copy code](#)

Put it on: elements that are NOT `position: static`

Affects: offset position

CSS

```
.badge { position: absolute; top: 0; right: 0; }
```

`z-index`

[Copy code](#)

Put it on: positioned elements (or flex/grid items often)

Affects: stacking order

CSS

```
.modal { position: fixed; z-index: 999; }
```

[Copy code](#)

9) Flexbox (VERY common)

Flex container properties (put on the parent)

`display: flex`

Put it on: parent

Affects: children become flex items

CSS

```
.row { display: flex; }
```

 Copy code

flex-direction

Put it on: flex parent

Affects: row/column direction

CSS

```
.row { display: flex; flex-direction: column; }
```

justify-content

 Copy code

Put it on: flex parent

Affects: main-axis alignment (horizontal in row)

CSS

```
.row { display: flex; justify-content: center; }
```

align-items

 Copy code

Put it on: flex parent

Affects: cross-axis alignment (vertical in row)

CSS

```
.row { display: flex; align-items: center; }
```

gap

 Copy code

Put it on: flex parent (also grid parent)

Affects: spacing between children

CSS

```
.row { display: flex; gap: 12px; }
```

Flex item properties (put on the children)

 Copy code

flex

Put it on: flex child

Affects: how it grows/shrinks

CSS

```
.left { flex: 1; }
.right { flex: 2; }
```

align-self

Put it on: flex child

 Copy code

Affects: overrides align-items for that one item

CSS

```
.item { align-self: flex-end; }
```

 Copy code

10) CSS Grid (also very common)

Grid container properties (put on the parent)

display: grid

CSS

```
.grid { display: grid; }
```

grid-template-columns

 Copy code

Put it on: grid parent

Affects: columns

CSS

```
.grid { display: grid; grid-template-columns: 1fr 1fr 1fr; }
```

grid-template-rows

 Copy code

CSS

```
.grid { grid-template-rows: 100px auto; }
```

gap

 Copy code

CSS

```
.grid { gap: 16px; }
```

Grid item properties (put on the child)

 Copy code

grid-column, grid-row

Put it on: grid child

Affects: where it sits/spans

CSS

```
.item { grid-column: 1 / 3; }
```

 Copy code

11) Lists

list-style

Put it on: ul / ol

Affects: bullets/numbers

CSS

```
ul { list-style: none; padding: 0; }
```

12) Images & Object fitting

 Copy code

`object-fit`

Put it on: `img` / `video` (when width/height set)

Affects: how media fits inside its box

CSS

```
img { width: 200px; height: 200px; object-fit: cover; }
```

 Copy code

13) Cursor & User interaction

`cursor`

Put it on: clickable elements

Affects: mouse cursor shape

CSS

```
button { cursor: pointer; }
```

 Copy code

14) Transforms & Animations

`transform`

Put it on: any element

Affects: rotate/scale/move visually (doesn't change document flow)

CSS

```
.box { transform: scale(1.1); }
```

`transition`

 Copy code

Put it on: element you want smooth change on

Affects: animation between states (like hover)

CSS

```
.btn { transition: 0.2s; }
.btn:hover { transform: scale(1.05); }
```

15) Shadows

 Copy code

box-shadow

Put it on: boxes

Affects: shadow around element

CSS

```
.card { box-shadow: 0 4px 12px rgba(0,0,0,0.15); }
```

text-shadow

Copy code

Put it on: text elements

Affects: shadow on text

CSS

```
h1 { text-shadow: 1px 1px 2px black; }
```

Copy code

16) Opacity

opacity

Put it on: any element

Affects: transparency (also affects children!)

CSS

```
.fade { opacity: 0.5; }
```

Copy code

The fastest way to remember

Put it on the parent

- text-align → aligns inline content inside
- display: flex/grid + justify-content + align-items + gap → layout children

Put it on the element itself

- width/height , padding/margin/border , background , position , transform

If you want, I can turn this into a **one-page printable cheat sheet** (super compact) OR I can do the same list but **with a small “works on: block/inline/flex/grid” label for every property.**



I can do the same list but with a small “works on: block/inline/flex/grid” label for every property.

do it

Sure — here’s the same common CSS list, but each one has a quick label:

Works on: block / inline / flex / grid
 (“inline” here means *inline elements like span, a* without changing display.)

Text & Font

color

Works on: block  | inline  | flex  | grid 
Affects text color (inherits).

CSS

```
p { color: #e11d48; }
```

font-size

 Copy code

Works on: block  | inline  | flex  | grid 

CSS

```
body { font-size: 16px; }
```

font-family

 Copy code

Works on: block  | inline  | flex  | grid 

CSS

```
body { font-family: system-ui, Arial, sans-serif; }
```

font-weight

 Copy code

Works on: block  | inline  | flex  | grid 

CSS

```
h1 { font-weight: 700; }
```

 Copy code

font-style

Works on: block  | inline  | flex  | grid 

CSS

Copy code

```
em { font-style: italic; }
```

line-height

Works on: block  | inline  | flex  | grid 

CSS

Copy code

```
p { line-height: 1.6; }
```

text-align

Works on: block  | inline  | flex  | grid 

(Use on a container; aligns inline content inside.)

CSS

Copy code

```
.header { text-align: center; }
```

text-decoration

Works on: block  | inline  | flex  | grid 

CSS

Copy code

```
a { text-decoration: none; }
```

text-transform

Works on: block  | inline  | flex  | grid 

CSS

Copy code

```
h2 { text-transform: uppercase; }
```

Box Model

width

Works on: block  | inline  | flex  | grid 

(Inline elements ignore width unless you change display.)

CSS

Copy code

```
.card { width: 320px; }
```

height

Works on: block  | inline  | flex  | grid 

CSS

Copy code

```
.card { height: 150px; }
```

max-width, min-width, max-height, min-height

Works on: block  | inline  | flex  | grid 

CSS

Copy code

```
img { max-width: 100%; height: auto; }
```

padding

Works on: block  | inline  | flex  | grid 

(Inline padding works, but top/bottom can behave “weird” visually.)

CSS

Copy code

```
.badge { padding: 4px 10px; }
```

margin

Works on: block  | inline  | flex  | grid 

Inline: left/right works, top/bottom usually doesn’t push layout.

CSS

Copy code

```
.card { margin: 20px auto; } /* centers block if width is set */
```

border

Works on: block  | inline  | flex  | grid 

CSS

Copy code

```
.box { border: 2px solid #111; }
```

box-sizing

Works on: block  | inline  | flex  | grid 

CSS

Copy code

```
* { box-sizing: border-box; }
```

Background & Corners

background-color

Works on: block  | inline  | flex  | grid 

CSS

Copy code

```
nav { background-color: #f1f5f9; }
```

background-image

Works on: block  | inline  | flex  | grid 

(Usually used on block-like elements.)

CSS

 Copy code

```
.hero { background-image: url(bg.jpg); }
```

background-size

Works on: block  | inline  | flex  | grid 

CSS

 Copy code

```
.hero { background-size: cover; }
```

background-position

Works on: block  | inline  | flex  | grid 

CSS

 Copy code

```
.hero { background-position: center; }
```

border-radius

Works on: block  | inline  | flex  | grid 

CSS

 Copy code

```
button { border-radius: 10px; }
```

Display & Visibility

display

Works on: block  | inline  | flex  | grid 

(Changes how the element behaves.)

CSS

 Copy code

```
a { display: inline-block; }
```

display: none

Works on: block  | inline  | flex  | grid 

(Removes element completely.)

CSS

 Copy code

```
.hide { display: none; }
```

visibility: hidden

Works on: block  | inline  | flex  | grid 

(Hides but keeps space.)

CSS

 Copy code

```
.item { visibility: hidden; }
```

Overflow

overflow

Works on: block  | inline  | flex  | grid 

(Most useful when size is limited.)

CSS

 Copy code

```
.box { height: 120px; overflow: auto; }
```

Positioning (move elements)

position

Works on: block  | inline  | flex  | grid 

CSS

 Copy code

```
.badge { position: absolute; }
```

top/right/bottom/left

Works on: block  | inline  | flex  | grid 

(Only if position is not `static`.)

CSS

 Copy code

```
.badge { position: absolute; top: 0; right: 0; }
```

z-index

Works on: block  | inline  | flex  | grid 

(Usually needs positioned element; also works on flex/grid items.)

CSS

 Copy code

```
.modal { position: fixed; z-index: 999; }
```

Flexbox (Parent vs Child)

display: flex

Works on: block  | inline  (as inline-flex) | flex  | grid 

(Applied to parent to control children.)

CSS

 Copy code

```
.row { display: flex; }
```

flex-direction

Works on: block  | inline  | flex  | grid 

(Apply to flex container only.)

CSS

 Copy code

```
.row { display: flex; flex-direction: column; }
```

justify-content

Works on: block  | inline  | flex  | grid 

(Flex/grid container only.)

CSS

 Copy code

```
.row { display: flex; justify-content: space-between; }
```

align-items

Works on: block  | inline  | flex  | grid 

CSS

 Copy code

```
.row { display: flex; align-items: center; }
```

gap

Works on: block  | inline  | flex  | grid 

CSS

 Copy code

```
.row { display: flex; gap: 12px; }
```

flex

Works on: block  | inline  | flex  | grid 

(Flex item only.)

CSS

 Copy code

```
.left { flex: 1; }
.right { flex: 2; }
```

align-self

Works on: block ❌ | inline ❌ | flex ✅ | grid ✅

(Flex/grid item only.)

CSS

Copy code

```
.item { align-self: flex-end; }
```

Grid (Parent vs Child)

display: grid

Works on: block ✅ | inline ✅ (as inline-grid) | flex ✅ | grid ✅

CSS

Copy code

```
.grid { display: grid; }
```

grid-template-columns

Works on: block ❌ | inline ❌ | flex ❌ | grid ✅

(Grid container only.)

CSS

Copy code

```
.grid { display: grid; grid-template-columns: 1fr 1fr 1fr; }
```

grid-template-rows

Works on: block ❌ | inline ❌ | flex ❌ | grid ✅

CSS

Copy code

```
.grid { grid-template-rows: 100px auto; }
```

grid-column, grid-row

Works on: block ❌ | inline ❌ | flex ❌ | grid ✅

(Grid item only.)

CSS

Copy code

```
.item { grid-column: 1 / 3; }
```

Lists

list-style

Works on: block ✅ (ul/ol) | inline ❌ | flex ✅ | grid ✅

CSS

Copy code

```
ul { list-style: none; padding: 0; }
```

Images / Media

object-fit

Works on: block  | inline  | flex  | grid 

(For `img/video` when width & height are set.)

CSS

Copy code

```
img { width: 200px; height: 200px; object-fit: cover; }
```

Effects & Interaction

cursor

Works on: block  | inline  | flex  | grid 

CSS

Copy code

```
button { cursor: pointer; }
```

opacity

Works on: block  | inline  | flex  | grid 

(Also affects children.)

CSS

Copy code

```
.disabled { opacity: 0.5; }
```

transform

Works on: block  | inline  | flex  | grid 

(Inline transforms can behave unexpectedly; `inline-block` is safer.)

CSS

Copy code

```
.box { transform: translateY(-4px); }
```

transition

Works on: block  | inline  | flex  | grid 

CSS

Copy code

```
.btn { transition: 0.2s; }
.btn:hover { transform: scale(1.05); }
```

box-shadow

Works on: block  | inline  | flex  | grid 

CSS

 Copy code

```
.card { box-shadow: 0 8px 20px rgba(0,0,0,0.15); }
```

Quick “one-liner” rule

- Block-like layout properties (width/height/overflow) → usually  on pure inline
- Flex/Grid alignment (justify-content , gap) → only  on flex/grid containers
- Flex/grid item props (flex , grid-column) → only  on children inside those layouts

If you want, I can also add “works on: parent / child” labels (super helpful for flex/grid), or turn this into a compact printable cheat sheet.



I can also add “works on: parent / child” labels (super helpful for flex/grid),

do it

Below is the same “common CSS rules” list, but now each property has:

- Works on display: block / inline / flex / grid
- Use on: Parent / Child / Both (VERY useful for Flex/Grid)

Quick note: “flex / grid” in *Works on display* means “the element can be a flex/grid container or item”.

“Use on: Parent/Child” means **where you should write it**.

1) Text & Font

color

Works on display: block  | inline  | flex  | grid 

Use on: Both

CSS

 Copy code

```
.card { color: #111; }
```

font-size, font-family, font-weight, font-style

Works on display: block  | inline  | flex  | grid 

Use on: Both (often on parent for inheritance)

CSS

 Copy code

```
body { font-family: Arial; font-size: 16px; }
h1 { font-weight: 700; }
```

line-height

Works on display: block  | inline  | flex  | grid 

Use on: Both

CSS

 Copy code

```
p { line-height: 1.6; }
```

text-align

Works on display: block  | inline  | flex  | grid 

Use on: Parent (container)

CSS

 Copy code

```
.header { text-align: center; }
```

text-decoration

Works on display: block  | inline  | flex  | grid 

Use on: Both

CSS

 Copy code

```
a { text-decoration: none; }
```

text-transform

Works on display: block  | inline  | flex  | grid 

Use on: Both

CSS

 Copy code

```
h2 { text-transform: uppercase; }
```

2) Box Model (Spacing & Size)

width, height

Works on display: block  | inline  | flex  | grid 

Use on: Child (or any element you are sizing)

CSS

Copy code

```
.card { width: 320px; height: 200px; }
```

max-width, min-width, max-height, min-height

Works on display: block  | inline  | flex  | grid 

Use on: Child / Both

CSS

Copy code

```
img { max-width: 100%; height: auto; }
```

padding

Works on display: block  | inline  | flex  | grid 

Use on: Both

CSS

Copy code

```
.card { padding: 16px; }
```

margin

Works on display: block  | inline  | flex  | grid 

Use on: Both

 To center a block element: needs width

CSS

Copy code

```
.card { width: 320px; margin: 0 auto; }
```

border

Works on display: block  | inline  | flex  | grid 

Use on: Both

CSS

Copy code

```
.card { border: 1px solid #ccc; }
```

box-sizing

Works on display: block  | inline  | flex  | grid 

Use on: Both (commonly global)

CSS

Copy code

```
* { box-sizing: border-box; }
```

3) Background & Corners

background-color

Works on display: block  | inline  | flex  | grid 

Use on: Both

CSS

Copy code

```
nav { background-color: #f1f5f9; }
```

background-image , background-size , background-position , background-repeat

Works on display: block  | inline  | flex  | grid 

Use on: Both (usually block-like)

CSS

Copy code

```
.hero {
  background-image: url(bg.jpg);
  background-size: cover;
  background-position: center;
  background-repeat: no-repeat;
}
```

border-radius

Works on display: block  | inline  | flex  | grid 

Use on: Both

CSS

Copy code

```
button { border-radius: 10px; }
```

4) Display & Visibility

display

Works on display: block  | inline  | flex  | grid 

Use on: Both

CSS

Copy code

```
a { display: inline-block; }
```

display: none

Works on display: block  | inline  | flex  | grid 

Use on: Both

CSS

Copy code

```
.hide { display: none; }
```

visibility: hidden

Works on display: block  | inline  | flex  | grid 

Use on: Both

CSS

Copy code

```
.item { visibility: hidden; }
```

5) Overflow

overflow

Works on displav: block  | inline  | flex  | arid 

= ChatGPT 5.2 Thinking 

 

CSS

Copy code

```
.box { height: 120px; overflow: auto; }
```

6) Positioning (Moving elements)

position

Works on display: block  | inline  | flex  | grid 

Use on: Child (the element you want to move)

CSS

Copy code

```
.badge { position: absolute; }
```

top/right/bottom/left

Works on display: block  | inline  | flex  | grid 

Use on: Child (only if position is not `static`)

CSS

Copy code

```
.badge { position: absolute; top: 0; right: 0; }
```

z-index

Works on display: block  | inline  | flex  | grid 

Use on: Child (stacking)

CSS

Copy code

```
.modal { position: fixed; z-index: 999; }
```

7) FLEXBOX (Parent vs Child)

Flex container (Parent)

`display: flex` / `display: inline-flex`

Works on display: block  | inline  | flex  | grid 

Use on: Parent

CSS

```
.row { display: flex; }
```

Copy code

`flex-direction`

Works on display: flex  (as container)

Use on: Parent

CSS

```
.row { display: flex; flex-direction: column; }
```

Copy code

`justify-content`

Works on display: flex  | grid 

Use on: Parent (container alignment)

CSS

```
.row { display: flex; justify-content: center; }
```

Copy code

`align-items`

Works on display: flex  | grid 

Use on: Parent

CSS

```
.row { display: flex; align-items: center; }
```

Copy code

`flex-wrap`

Works on display: flex 

Use on: Parent

CSS

```
.row { display: flex; flex-wrap: wrap; }
```

Copy code

`gap`

Works on display: flex  | grid 

Use on: Parent

CSS

Copy code

```
.row { display: flex; gap: 12px; }
```

Flex items (Child)

`flex` (shorthand for grow/shrink/basis)

Works on display: flex  (item only)

Use on: Child

CSS  Copy code

```
.left { flex: 1; }  
.right { flex: 2; }
```

`flex-grow`, `flex-shrink`, `flex-basis`

Works on display: flex  (item only)

Use on: Child

CSS  Copy code

```
.item { flex-grow: 1; flex-basis: 200px; }
```

`align-self`

Works on display: flex  | grid  (item)

Use on: Child

CSS  Copy code

```
.item { align-self: flex-end; }
```

`order`

Works on display: flex  | grid  (item)

Use on: Child

CSS  Copy code

```
.item2 { order: -1; }
```

8) GRID (Parent vs Child)

Grid container (Parent)

`display: grid` / `display: inline-grid`

Works on display: block  | inline  | flex  | grid 

Use on: Parent

CSS

 Copy code

```
.grid { display: grid; }
```

grid-template-columns

Works on display: grid  (container)

Use on: Parent

CSS

 Copy code

```
.grid { display: grid; grid-template-columns: 1fr 1fr 1fr; }
```

grid-template-rows

Works on display: grid  (container)

Use on: Parent

CSS

 Copy code

```
.grid { grid-template-rows: 80px auto; }
```

place-items (align-items + justify-items)

Works on display: grid  (container)

Use on: Parent

CSS

 Copy code

```
.grid { place-items: center; }
```

justify-items

Works on display: grid  (container)

Use on: Parent

CSS

 Copy code

```
.grid { justify-items: center; }
```

align-content / justify-content (grid version)

Works on display: grid  (container)

Use on: Parent (moves the whole grid tracks, not each item)

CSS

 Copy code

```
.grid { justify-content: center; align-content: start; }
```

gap

Works on display: grid  | flex 

Use on: Parent

CSS

 Copy code

```
.grid { gap: 16px; }
```

Grid items (Child)

grid-column , grid-row

Works on display: grid  (item)

Use on: Child

CSS

 Copy code

```
.item { grid-column: 1 / 3; grid-row: 2 / 3; }
```

justify-self , align-self , place-self

Works on display: grid  (item)

Use on: Child

CSS

 Copy code

```
.item { justify-self: end; align-self: center; }
```

9) Lists

list-style

Works on display: block  | inline  | flex  | grid 

Use on: Parent (ul / ol)

CSS

 Copy code

```
ul { list-style: none; padding: 0; margin: 0; }
```

10) Images / Media

object-fit

Works on display: block  | inline  | flex  | grid 

Use on: Child (img / video itself, needs width+height)

CSS

 Copy code

```
img { width: 200px; height: 200px; object-fit: cover; }
```

11) Interaction & Effects

cursor

Works on display: block  | inline  | flex  | grid 

Use on: Both

CSS

 Copy code

```
button { cursor: pointer; }
```

opacity

Works on display: block  | inline  | flex  | grid 

Use on: Both (affects children too)

CSS

 Copy code

```
.disabled { opacity: 0.5; }
```

transform

Works on display: block  | inline  | flex  | grid 

Use on: Child/Both (the element you animate/move)

CSS

 Copy code

```
.box { transform: translateY(-6px); }
```

transition

Works on display: block  | inline  | flex  | grid 

Use on: Both

CSS

 Copy code

```
.btn { transition: 0.2s; }  
.btn:hover { transform: scale(1.05); }
```

box-shadow

Works on display: block  | inline  | flex  | grid 

Use on: Both

CSS

 Copy code

```
.card { box-shadow: 0 8px 18px rgba(0,0,0,0.15); }
```

Super-fast memory trick (for Flex/Grid)

- Parent controls layout: display , gap , justify-* , align-* , grid-template-*
- Child controls itself: flex , order , align-self , grid-row/column , justify-self

If you want, I can also include **real mini layouts** (1 flex example + 1 grid example) showing exactly which lines are “parent” and which are “child”.

