

CSS Quiz Question Paper (MCQ)

Topic: CSS Basics (Transitions, Animations, Variables, Positioning)

Time: 20 minutes **Marks:** 10 × 1 = 10

Instructions:

- Choose the most correct option for each question.
- Write only the option letter (A / B / C / D).

1) What is the correct syntax for performing addition using calc() in CSS?	A) width: calc(100px + 20px); B) width: calc(100px add 20px); C) width: calc(100px +20px); D) width: calc(100px plus 20px);
2) Select the most appropriate CSS declaration(s) to set an element to absolute positioning in the top right corner.	A) position: absolute; top: 0; left: 0; B) position: top right; C) position: absolute; top: 0; right: 0; D) None of the above.
3) Which CSS property is used to rotate an element?	A) scale() B) rotate() C) transform: skew() D) transform: rotate(degree)
4) What should you check before using third-party images from the web on your website?	A) Image resolution only B) Copyright and licensing C) Image size D) File format
5) How do you declare a CSS variable?	A) @variable B) #variable C) --variable D) \$variable
6) What is the purpose of @keyframes in CSS animations?	A) To define a media query B) To define a grid layout C) To specify animation behavior at different stages D) To add responsive styles
7) Which CSS property is used to specify the start delay of a transition?	A) transition-delay B) transition-property C) transition-type D) transition-effect
8) Which CSS property is NOT animatable using transitions?	A) opacity B) font-size C) display D) background-color
9) Which CSS property is used to pause or resume an animation?	A) animation-fill-mode B) animation-direction C) animation-delay D) animation-play-state

10) How can you create a continuous loop of CSS animation on an element?

- A) Use the animation-iteration-count property with the value 0
 - B) Use the animation-loop property with the value true
 - C) Use the transition property instead of animations
 - D) Use the animation-iteration-count property with the value infinite
-

CSS Quiz Answer Sheet

Answers with short explanations:

Q#	Answer	Short Explanation
1	A	calc(100px + 20px) is valid; spaces around operators are recommended.
2	C	top: 0 and right: 0 with position: absolute places it in the top-right.
3	D	Rotation is done using transform: rotate(...deg).
4	B	You must confirm copyright/license and any attribution requirements.
5	C	CSS variables (custom properties) start with --.
6	C	@keyframes defines how styles change at different percentages of the animation.
7	A	transition-delay sets how long the browser waits before starting the transition.
8	C	display can't animate smoothly; it switches instantly (none/block/etc.).
9	D	animation-play-state can be running or paused.
10	D	animation-iteration-count: infinite repeats the animation forever.