

What is the correct syntax for performing addition using `calc()` in CSS?



To do **addition** with `calc()` in CSS, the correct syntax is:

CSS Copy code

```
width: calc(100px + 20px);
```

Key rules (important)

- You **must** put **spaces** around the operator: `+` `-` `*` `/`
 - ✓ `calc(100% - 20px)`
 - ✗ `calc(100%-20px)` (often fails)

More examples

1) Make an element full width minus padding

CSS Copy code

```
.box {
  width: calc(100% - 40px);
}
```

2) Add a fixed value to a percentage

CSS Copy code

```
.title {
  font-size: calc(1rem + 6px);
}
```

3) Add CSS variables

CSS Copy code

```
:root {
  --gap: 12px;
}

.card {
  padding: calc(var(--gap) + 8px);
}
```

If you tell me what you’re trying to calculate (width? height? margin?), I can write the exact line for your case.



Select the most appropriate CSS declaration(s) to set an element to absolute positioning in the top right corner.

A

position: absolute; top: 0; left: 0;

B

position: top right;

C

position: absolute; top: 0; right: 0;

D

None of the above.

✔ Correct answer: C

CSS

Copy code

```
position: absolute;
top: 0;
right: 0;
```

Why not the others?

- A puts it at **top-left** (`left: 0`)
- B is **not valid CSS**
- D is wrong because **C works**

📄 👍 💬 ↗️ ↺ ...

Which CSS property is used to rotate an element?

A

scale()

B

rotate()

C

transform: skew()

D

transform: rotate(degree)

✔ Correct answer: D

transform is the CSS property, and you rotate using the rotate() function inside it:

CSS

Copy code

```
.box{
  transform: rotate(45deg);
}
```

Why not the others?

- A scale() changes size, not rotation.
- B rotate() alone is not a CSS property by itself (it must be inside transform).
- C transform: skew() tilts (skews) the element, not rotates.



What should you check before using third-party images from the web on your website?

- A
- Image resolution only
- B
- Copyright and licensing
- C
- Image size
- D
- File format

✔ Correct answer: B — Copyright and licensing

Before using any third-party image from the web, you should check **whether you’re legally allowed to use it** (license, permissions, attribution requirements, commercial use rules, etc.).

Why the others aren’t enough:

- A (resolution) affects quality, not legality

- **C (size)** affects performance, not permission
- **D (format)** affects compatibility, not permission



How do you declare a CSS variable?

- A
- @variable
- B
- #variable
- C
- variable
- D
- \$variable

✔ **Correct answer: C — --variable**

You declare CSS variables (custom properties) using `--name` , usually inside a selector like `:root :`

CSSCopy code

```
:root {
  --main-color: #30B868;
  --gap: 12px;
}
```

And use them with `var()` :

CSSCopy code

```
button {
  background: var(--main-color);
  padding: var(--gap);
}
```



What is the purpose of @keyframes in CSS animations?

A

To define a media query

B

To define a grid layout

C

To specify animation behavior at different stages

D

To add responsive styles

✔ Correct answer: C — To specify animation behavior at different stages

`@keyframes` lets you define **how an animation changes over time** (like at 0%, 50%, 100%).

Example:

CSS

Copy code

```
@keyframes moveRight {
  0%   { transform: translateX(0); }
  100% { transform: translateX(200px); }
}

.box {
  animation: moveRight 2s infinite alternate;
}
```

So the element changes step-by-step based on the percentages you define.



Which CSS property is used to specify the start delay of a transition?

A

transition-delay

B

transition-property

C

transition-type

D

transition-effect

✔ **Correct answer: A** — transition-delay

It controls **how long to wait before the transition starts**.

Example:

CSS

Copy code

```
.box {
  transition: transform 0.5s;
  transition-delay: 0.3s;
}

.box:hover {
  transform: scale(1.2);
}
```

So when you hover, it waits **0.3s**, then the transition begins.



Which CSS property is NOT animatable using transitions?

- A
- opacity
- B
- font-size
- C
- display
- D
- background-color

✔ **Correct answer: C** — display

`display` cannot be smoothly transitioned because it switches instantly (like `none` ↔ `block`).

The others **are animatable** with transitions:

- `opacity` ✓
- `font-size` ✓
- `background-color` ✓

Tip: If you want a “show/hide” animation, usually use:

- `opacity` + `visibility` , or
- `opacity` + `transform` (like `scale()`), instead of `display` .



Which CSS property is used to pause or resume an animation?

- A

animation-fill-mode
- B

animation-direction
- C

animation-delay
- D

animation-play-state

✓ Correct answer: D — `animation-play-state`

It controls whether an animation is **running** or **paused**.

Example:

CSS Copy code

```
.box {
  animation: spin 2s linear infinite;
  animation-play-state: running;
}

.box:hover {
  animation-play-state: paused;
}

@keyframes spin {
  to { transform: rotate(360deg); }
}
```

So when you hover, the animation pauses; when you stop hovering, it resumes.



How can you create a continuous loop of CSS animation on an element?

A

Use the "animation-iteration-count" property with the value "0"

B

Use the "animation-loop" property with the value "true"

C

Use the "transition" property instead of animations

D

Use the "animation-iteration-count" property with the value "infinite"

 **Correct answer: D — Use** `animation-iteration-count: infinite`

Example:

CSS

 Copy code

```
.box {  
  animation: bounce 1s ease-in-out infinite;  
}  
  
@keyframes bounce {  
  0%   { transform: translateY(0); }  
  50%  { transform: translateY(-20px); }  
  100% { transform: translateY(0); }  
}
```

This makes the animation repeat forever.



make a question paper with all the questions

CSS Quiz Question Paper (MCQ)

Subject: CSS Basics (Transitions, Animations, Variables, Positioning)

Time: 20 minutes

Marks: 10 × 1 = 10

Instructions:

- Choose the **most correct** option for each question.
 - Write only the option letter (A/B/C/D).
-

1) What is the correct syntax for performing addition using `calc()` in CSS?

- A) `width: calc(100px + 20px);`
 - B) `width: calc(100px add 20px);`
 - C) `width: calc(100px +20px);`
 - D) `width: calc(100px plus 20px);`
-

2) Select the most appropriate CSS declaration(s) to set an element to absolute positioning in the top right corner.

- A) `position: absolute; top: 0; left: 0;`
 - B) `position: top right;`
 - C) `position: absolute; top: 0; right: 0;`
 - D) None of the above.
-

3) Which CSS property is used to rotate an element?

- A) `scale()`
 - B) `rotate()`
 - C) `transform: skew();`
 - D) `transform: rotate(degree)`
-

4) What should you check before using third-party images from the web on your website?

- A) Image resolution only
 - B) Copyright and licensing
 - C) Image size
 - D) File format
-

5) How do you declare a CSS variable?

- A) `@variable`
- B) `#variable`

- C) `--variable`
 - D) `$variable`
-

6) What is the purpose of `@keyframes` in CSS animations?

- A) To define a media query
 - B) To define a grid layout
 - C) To specify animation behavior at different stages
 - D) To add responsive styles
-

7) Which CSS property is used to specify the start delay of a transition?

- A) `transition-delay`
 - B) `transition-property`
 - C) `transition-type`
 - D) `transition-effect`
-

8) Which CSS property is NOT animatable using transitions?

- A) `opacity`
 - B) `font-size`
 - C) `display`
 - D) `background-color`
-

9) Which CSS property is used to pause or resume an animation?

- A) `animation-fill-mode`
 - B) `animation-direction`
 - C) `animation-delay`
 - D) `animation-play-state`
-

10) How can you create a continuous loop of CSS animation on an element?

- A) Use the `animation-iteration-count` property with the value `0`
 - B) Use the `animation-loop` property with the value `true`
 - C) Use the `transition` property instead of animations
 - D) Use the `animation-iteration-count` property with the value `infinite`
-

If you want, I can also make an **answer sheet + short explanations** for each MCQ.



yes

Answer Sheet (With Short Explanations)

1) Correct syntax for addition using `calc()`

✓ Answer: A

Why: `calc(100px + 20px)` is valid. (Spaces around `+` are the safe standard.)

2) Absolute positioning in the top-right corner

✓ Answer: C

Why: `top: 0; right: 0;` places it in the top-right (with `position: absolute`).

3) Property used to rotate an element

✓ Answer: D

Why: Rotation is done using `transform: rotate(45deg)`.

4) Before using third-party images, check

✓ Answer: B

Why: You must check **copyright/licensing** to avoid legal issues.

5) Declare a CSS variable

✓ Answer: C

Why: CSS variables are declared like `--main-color: red;`

6) Purpose of `@keyframes`

✓ Answer: C

Why: It defines animation steps (0%, 50%, 100%).

7) Transition start delay property

✓ Answer: A

Why: `transition-delay` delays the start of a transition.

8) NOT animatable using transitions

✔ Answer: C

Why: `display` changes instantly (no smooth transition).

9) Pause/resume an animation

✔ Answer: D

Why: `animation-play-state: paused;` or `running;`

10) Continuous loop animation

✔ Answer: D

Why: `animation-iteration-count: infinite;` repeats forever.

If you want, I can also format this as a **printable PDF-style question paper + answer sheet** (same content, clean layout).



yes

Thought for 1m 29s >

Done — I made a clean, printable PDF that includes **(1) the full question paper** and **(2) the answer sheet with short explanations.**

[Download the PDF](#) `</>`



