

Docker CLI and Commands

Table of Contents

1. Docker CLI Overview
 2. How the CLI Works
 3. Docker Image Commands
 4. Docker Container Commands
 5. Docker Network Commands
 6. Docker Volume Commands
 7. Docker System Commands
 8. Additional Docker Commands
-

Docker CLI Overview

What is Docker CLI?

The **Docker Command Line Interface (CLI)** is the primary way users interact with Docker. It sends commands to the Docker daemon via REST API.

Basic Syntax

```
docker [OPTIONS] COMMAND [ARG...]
```

Examples:

```
docker ps                # No options, simple command
docker run -d nginx      # Option (-d) with command (run) and argument (nginx)
docker build -t myapp:1.0 . # Multiple options and arguments
```

Getting Help

General help

```
docker --help
```

Help for specific command

```
docker run --help
```

```
docker build --help
```

View Docker version

```
docker --version
```

```
docker version # More detailed
```

View system-wide information

```
docker info
```

How the CLI Works

Architecture Flow

User Types
Command

Docker CLI
(Parser)

REST API Request

Docker Daemon
(dockerd)

Container/Image
Operations

Example Flow

```
# User command  
docker run -d --name web nginx
```

```
# What happens:  
1. Docker CLI receives command  
2. CLI validates syntax  
3. CLI sends REST API request to daemon:  
   POST /containers/create  
   {  
     "Image": "nginx",  
     "name": "web",  
     "Detach": true  
   }  
4. Daemon processes request:  
   - Checks if image exists  
   - Pulls image if needed
```

- Creates container
 - Starts container
5. Daemon sends response to CLI
 6. CLI displays output to user

Docker Context

View current context (where commands are sent)

```
docker context ls
```

Output:

NAME	DESCRIPTION	DOCKER ENDPOINT
default	* Current context	unix:///var/run/docker.sock

Use remote Docker host

```
docker context create remote --docker "host=tcp://192.168.1.100:2376"
```

```
docker context use remote
```

Switch back to local

```
docker context use default
```

Docker Image Commands

Listing Images

List all images

```
docker images
```

```
docker image ls
```

Output:

REPOSITORY	TAG	IMAGE ID	CREATED	SIZE
nginx	latest	a1b2c3d4e5f6	2 weeks ago	142MB
ubuntu	22.04	b2c3d4e5f6g7	3 weeks ago	77MB
node	18	c3d4e5f6g7h8	1 month ago	993MB

List images with digests

```
docker images --digests
```

List images with specific repository

```
docker images nginx
```

List images with filter

docker images --filter "dangling=true"	# Untagged images
docker images --filter "before=nginx"	# Before nginx was created
docker images --filter "since=ubuntu"	# After ubuntu was created

```
# Format output
docker images --format "table {{.Repository}}\t{{.Tag}}\t{{.Size}}"
```

Pulling Images

```
# Pull latest version
docker pull nginx

# Pull specific version
docker pull nginx:1.25
docker pull nginx:1.25-alpine

# Pull from specific registry
docker pull docker.io/library/nginx
docker pull ghcr.io/username/myapp

# Pull all tags of a repository
docker pull --all-tags nginx

# Pull image for specific platform
docker pull --platform linux/amd64 nginx
docker pull --platform linux/arm64 nginx
```

Searching Images

```
# Search Docker Hub
docker search nginx

# Output:
# NAME                DESCRIPTION                STARS  OFFICIAL  AUTOMATED
# nginx               Official build of Nginx.    18000  [OK]
# jwilder/nginx...    2000                      [OK]

# Search with filters
docker search --filter "stars=1000" nginx
docker search --filter "is-official=true" nginx

# Limit results
docker search --limit 5 nginx
```

Downloading Docker Images

```
# How image pull works:
docker pull redis:7.0

# Output:
```

```
# 7.0: Pulling from library/redis
# a2abf6c4d29d: Pull complete      + Layer 1
# c7a4e4382001: Pull complete      + Layer 2
# 4044b9ba67c9: Pull complete      + Layer 3
# c8388a79482f: Pull complete      + Layer 4
# 413c8bb60be2: Pull complete      + Layer 5
# 1abfd3011519: Pull complete      + Layer 6
# Digest: sha256:db485f2e245b5b3329fdc7eff4eb00f913e09d8feb9ca720788059fdc2ed8339
# Status: Downloaded newer image for redis:7.0
# docker.io/library/redis:7.0

# What's happening:
# 1. Docker contacts registry (hub.docker.com)
# 2. Downloads image manifest
# 3. Downloads each layer (if not already cached)
# 4. Verifies integrity using SHA256
# 5. Stores in local image store
```

How a Docker Image Works

```
# Images are built from layers
docker history nginx
```

```
# Output:
# IMAGE          CREATED          CREATED BY                                      SIZE
# a1b2c3d4e5f6   2 weeks ago     /bin/sh -c #(nop)  CMD ["nginx" "-g" "daemon... 0B
# <missing>      2 weeks ago     /bin/sh -c #(nop)  STOPSIGNAL SIGQUIT          0B
# <missing>      2 weeks ago     /bin/sh -c #(nop)  EXPOSE 80                               0B
# <missing>      2 weeks ago     /bin/sh -c #(nop)  ENTRYPOINT ["/docker-entr... 0B
# <missing>      2 weeks ago     /bin/sh -c #(nop)  COPY file:...                          4.62kB
# <missing>      2 weeks ago     /bin/sh -c apt-get update && apt-get install... 57.4MB
# <missing>      3 weeks ago     /bin/sh -c #(nop)  CMD ["bash"]                             0B
# <missing>      3 weeks ago     /bin/sh -c #(nop)  ADD file:... in /                       77.8MB
```

```
# Each layer is immutable and cached
# Layers are shared between images to save space
```

```
# Inspect image details
docker image inspect nginx
```

```
# Output (JSON):
# {
#   "Id": "sha256:a1b2c3...",
#   "RepoTags": ["nginx:latest"],
#   "Size": 142000000,
#   "Architecture": "amd64",
```

```
#   "Os": "linux",
#   "Layers": [
#       "sha256:layer1...",
#       "sha256:layer2...",
#       "sha256:layer3..."
#   ],
#   ...
# }
```

Building Images

Build from Dockerfile

```
docker build -t myapp:1.0 .
```

Build with build arguments

```
docker build --build-arg VERSION=1.0 -t myapp .
```

Build with no cache

```
docker build --no-cache -t myapp .
```

Build with specific Dockerfile

```
docker build -f Dockerfile.prod -t myapp:prod .
```

Build for multiple platforms

```
docker buildx build --platform linux/amd64,linux/arm64 -t myapp .
```

Build and push

```
docker build -t username/myapp:latest . && docker push username/myapp:latest
```

Tagging Images

Tag an existing image

```
docker tag nginx myregistry.com/nginx:v1
```

Create multiple tags

```
docker tag myapp:latest myapp:1.0
```

```
docker tag myapp:latest myapp:stable
```

Tag for Docker Hub

```
docker tag myapp username/myapp:latest
```

View all tags

```
docker images myapp
```

Pushing Images

```
# Login to Docker Hub
docker login
# Enter username and password

# Login to private registry
docker login myregistry.com

# Push image
docker push username/myapp:latest

# Push all tags
docker push --all-tags username/myapp
```

Removing Docker Images

```
# Remove specific image
docker rmi nginx
docker image rm nginx

# Remove image by ID
docker rmi a1b2c3d4e5f6

# Force remove (even if container using it)
docker rmi -f nginx

# Remove multiple images
docker rmi nginx redis postgres

# Remove all unused images
docker image prune

# Remove all images
docker image prune -a

# Remove images with filter
docker image prune --filter "until=24h"
```

Saving and Loading Images

```
# Save image to tar file
docker save nginx > nginx.tar
docker save -o nginx.tar nginx

# Save multiple images
docker save -o images.tar nginx redis postgres
```

```
# Load image from tar file
docker load < nginx.tar
docker load -i nginx.tar

# Export container filesystem
docker export mycontainer > container.tar

# Import as image
docker import container.tar myimage:latest
```

Docker Container Commands

Running Containers

```
# Basic run
docker run nginx

# Run in detached mode (background)
docker run -d nginx

# Run with name
docker run --name web nginx

# Run with port mapping
docker run -p 8080:80 nginx
docker run -p 127.0.0.1:8080:80 nginx # Bind to specific IP

# Run with multiple ports
docker run -p 8080:80 -p 8443:443 nginx

# Run with environment variables
docker run -e "ENV=production" -e "DEBUG=false" myapp

# Run with volume
docker run -v /host/path:/container/path nginx
docker run -v myvolume:/data nginx

# Run with resource limits
docker run --cpus="1.5" --memory="512m" nginx

# Run with restart policy
docker run --restart=always nginx
docker run --restart=on-failure:3 nginx
```



```

# Run with network
docker run --network mynetwork nginx

# Run in interactive mode
docker run -it ubuntu bash

# Run with automatic removal after exit
docker run --rm ubuntu echo "Hello"

# Complete example
docker run -d \
  --name myapp \
  --restart=always \
  -p 8080:80 \
  -e "ENV=production" \
  -v mydata:/data \
  --memory="512m" \
  --cpus="1" \
  nginx:latest

```

Listing Containers

```

# List running containers
docker ps
docker container ls

# Output:
# CONTAINER ID   IMAGE     COMMAND                  CREATED     STATUS      PORTS
# a1b2c3d4e5f6   nginx    "/docker-entrypoint...."  5 minutes ago  Up 5 minutes  0.0.0.0:

# List all containers (including stopped)
docker ps -a
docker container ls -a

# List only container IDs
docker ps -q

# List with size
docker ps -s

# List with custom format
docker ps --format "table {{.Names}}\t{{.Status}}\t{{.Ports}}"

# List latest created container
docker ps -l

```

```
# Filter containers
docker ps --filter "status=running"
docker ps --filter "name=web"
docker ps --filter "label=env=production"
```

Managing Running Containers

```
# Start stopped container
docker start mycontainer

# Stop running container
docker stop mycontainer

# Stop with timeout
docker stop -t 30 mycontainer # Wait 30 seconds before force kill

# Restart container
docker restart mycontainer

# Pause container
docker pause mycontainer

# Unpause container
docker unpause mycontainer

# Kill container (immediate termination)
docker kill mycontainer

# Kill with specific signal
docker kill --signal=SIGTERM mycontainer

# Rename container
docker rename oldname newname

# Update container configuration
docker update --cpus="2" --memory="1g" mycontainer
```

Accessing a Container Locally

```
# Execute command in running container
docker exec mycontainer ls /app

# Interactive bash shell
docker exec -it mycontainer bash
docker exec -it mycontainer sh # For Alpine-based images
```

```

# Execute as specific user
docker exec -u root -it mycontainer bash

# Execute with environment variable
docker exec -e "VAR=value" mycontainer env

# Run multiple commands
docker exec mycontainer sh -c "cd /app && ls -la"

# Example: Database operations
docker exec mysql_container mysql -u root -p'password' -e "SHOW DATABASES;"

# Example: View logs
docker exec mycontainer cat /var/log/app.log

# Example: Check process
docker exec mycontainer ps aux

```

Viewing Container Logs

```

# View logs
docker logs mycontainer

# Follow logs (like tail -f)
docker logs -f mycontainer

# Show timestamps
docker logs -t mycontainer

# Show last 100 lines
docker logs --tail 100 mycontainer

# Show logs since specific time
docker logs --since 2023-01-01 mycontainer
docker logs --since 30m mycontainer # Last 30 minutes

# Show logs until specific time
docker logs --until 2023-01-01 mycontainer

# Combine options
docker logs -f --tail 50 --since 10m mycontainer

```

Container Inspection

```

# Inspect container details
docker inspect mycontainer

```

```

# Get specific info with format
docker inspect --format='{{.NetworkSettings.IPAddress}}' mycontainer
docker inspect --format='{{.State.Status}}' mycontainer
docker inspect --format='{{.Config.Image}}' mycontainer

# View container processes
docker top mycontainer

# View resource usage statistics
docker stats
docker stats mycontainer

# View real-time events
docker events --filter container=mycontainer

# View port mappings
docker port mycontainer

# View container changes
docker diff mycontainer
# Output:
# A /app/newfile.txt      (Added)
# C /app/config.json      (Changed)
# D /app/oldfile.txt      (Deleted)

```

Docker Commit

```

# Create image from container
docker commit mycontainer mynewimage:v1

# Commit with message and author
docker commit -m "Added new feature" -a "John Doe" mycontainer mynewimage:v1

# Commit with changes
docker commit --change="ENV DEBUG=true" mycontainer mynewimage:v1

# Example workflow:
# 1. Start container
docker run -it --name mycontainer ubuntu bash

# 2. Make changes inside container
apt-get update && apt-get install -y curl

# 3. Exit container
exit

```

```
# 4. Commit changes to new image  
docker commit mycontainer ubuntu-with-curl:latest
```

```
# 5. Run new image  
docker run ubuntu-with-curl:latest curl --version
```

Copying Files

```
# Copy from container to host  
docker cp mycontainer:/app/file.txt ./local-file.txt  
docker cp mycontainer:/app/ ./local-folder/  
  
# Copy from host to container  
docker cp ./local-file.txt mycontainer:/app/file.txt  
docker cp ./local-folder/ mycontainer:/app/  
  
# Copy with ownership preservation  
docker cp --archive mycontainer:/app/ ./backup/  
  
# Example: Backup database  
docker cp mysql_container:/var/lib/mysql/backup.sql ./backup.sql  
  
# Example: Deploy new config  
docker cp ./new-config.yml app_container:/app/config.yml  
docker restart app_container
```

Removing Containers

```
# Remove stopped container  
docker rm mycontainer  
  
# Force remove running container  
docker rm -f mycontainer  
  
# Remove multiple containers  
docker rm container1 container2 container3  
  
# Remove all stopped containers  
docker container prune  
  
# Remove containers with filter  
docker container prune --filter "until=24h"  
  
# Remove all containers (running and stopped)  
docker rm -f $(docker ps -aq)
```

Docker Network Commands

Listing Networks

```
# List networks  
docker network ls
```

```
# Output:  
# NETWORK ID      NAME      DRIVER      SCOPE  
# a1b2c3d4e5f6    bridge    bridge      local  
# b2c3d4e5f6g7    host      host        local  
# c3d4e5f6g7h8    none      null        local
```

```
# Inspect network  
docker network inspect bridge
```

Creating Networks

```
# Create bridge network  
docker network create mynetwork
```

```
# Create with specific driver  
docker network create --driver bridge mynetwork
```

```
# Create with subnet  
docker network create --subnet=172.18.0.0/16 mynetwork
```

```
# Create with gateway  
docker network create --subnet=172.18.0.0/16 --gateway=172.18.0.1 mynetwork
```

```
# Create with custom options  
docker network create \  
  --driver=bridge \  
  --subnet=172.28.0.0/16 \  
  --ip-range=172.28.5.0/24 \  
  --gateway=172.28.5.254 \  
  mynetwork
```

Connecting Containers to Networks

```
# Connect running container to network  
docker network connect mynetwork mycontainer
```

```
# Connect with specific IP  
docker network connect --ip 172.18.0.10 mynetwork mycontainer
```

```
# Connect with alias
docker network connect --alias web mynetwork mycontainer

# Disconnect from network
docker network disconnect mynetwork mycontainer

# Run container on specific network
docker run -d --network mynetwork --name web nginx
```

Network Use Cases

```
# Example: Multi-tier application
```

```
# 1. Create network
```

```
docker network create app-network
```

```
# 2. Run database
```

```
docker run -d \
  --name db \
  --network app-network \
  -e POSTGRES_PASSWORD=secret \
  postgres:14
```

```
# 3. Run backend (can access db by hostname "db")
```

```
docker run -d \
  --name backend \
  --network app-network \
  -e DATABASE_HOST=db \
  mybackend:latest
```

```
# 4. Run frontend (can access backend by hostname "backend")
```

```
docker run -d \
  --name frontend \
  --network app-network \
  -p 80:80 \
  myfrontend:latest
```

```
# Containers can communicate using their names!
# backend can connect to: postgresql://db:5432
# frontend can connect to: http://backend:3000
```

Removing Networks

```
# Remove network
```

```
docker network rm mynetwork
```

```
# Remove all unused networks
docker network prune

# Force remove (disconnect containers first)
docker network rm -f mynetwork
```

Docker Volume Commands

Listing Volumes

```
# List volumes
docker volume ls

# Output:
# DRIVER      VOLUME NAME
# local       mydata
# local       postgres_data
# local       redis_cache

# Inspect volume
docker volume inspect mydata
```

```
# Output:
# [{
#   "CreatedAt": "2023-10-28T10:00:00Z",
#   "Driver": "local",
#   "Mountpoint": "/var/lib/docker/volumes/mydata/_data",
#   "Name": "mydata",
#   "Options": null,
#   "Scope": "local"
# }]
```

Creating Volumes

```
# Create volume
docker volume create mydata

# Create with driver
docker volume create --driver local mydata

# Create with labels
docker volume create --label env=production mydata

# Create with options
```



```
docker volume create \  
  --driver local \  
  --opt type=nfs \  
  --opt o=addr=192.168.1.1,rw \  
  --opt device=/path/to/dir \  
  nfs_volume
```

Using Volumes

Run container with volume

```
docker run -d -v mydata:/app/data nginx
```

Run with multiple volumes

```
docker run -d \  
  -v mydata:/app/data \  
  -v logs:/app/logs \  
  nginx
```

Run with read-only volume

```
docker run -d -v mydata:/app/data:ro nginx
```

Anonymous volume (Docker creates name)

```
docker run -d -v /app/data nginx
```

Bind mount (mount host directory)

```
docker run -d -v /host/path:/container/path nginx
```

Example: Database with persistent storage

```
docker run -d \  
  --name postgres \  
  -v pgdata:/var/lib/postgresql/data \  
  -e POSTGRES_PASSWORD=secret \  
  postgres:14
```

Data persists even if container is removed!

```
docker rm -f postgres
```

```
docker run -d --name postgres -v pgdata:/var/lib/postgresql/data postgres:14
```

Data is still there!

Volume Backup and Restore

Backup volume

```
docker run --rm \  
  -v mydata:/data \  
  -v $(pwd):/backup \  
  ubuntu
```

```
tar czf /backup/mydata-backup.tar.gz /data

# Restore volume
docker run --rm \
  -v mydata:/data \
  -v $(pwd):/backup \
  ubuntu \
  tar xzf /backup/mydata-backup.tar.gz -C /
```

Removing Volumes

```
# Remove volume
docker volume rm mydata

# Remove all unused volumes
docker volume prune

# Remove volumes with filter
docker volume prune --filter "label=env=development"

# Remove container and its volumes
docker rm -v mycontainer
```

Docker System Commands

System Information

```
# Show system-wide information
docker info

# Show version information
docker version

# Show disk usage
docker system df

# Output:
# TYPE          TOTAL    ACTIVE   SIZE     RECLAIMABLE
# Images        10       5        2.5GB    1.2GB (48%)
# Containers    15       3        500MB    400MB (80%)
# Local Volumes 8        4        1.5GB    800MB (53%)
# Build Cache   25       0        3.2GB    3.2GB (100%)

# Detailed view
docker system df -v
```

System Cleanup

```
# Remove all unused data
docker system prune

# Remove all unused data including volumes
docker system prune --volumes

# Remove everything (including unused images)
docker system prune -a

# Remove with filter
docker system prune --filter "until=24h"

# Remove without confirmation
docker system prune -f

# Complete cleanup (DANGER: Removes everything!)
docker system prune -a --volumes -f
```

Monitoring Events

```
# Show real-time events
docker events

# Filter events
docker events --filter type=container
docker events --filter event=start
docker events --filter container=mycontainer

# Show events since specific time
docker events --since '2023-10-28'
docker events --since '1h'

# Show events in JSON format
docker events --format '{{json .}}'
```

Additional Docker Commands

Docker Registry

```
# Login to registry
docker login
docker login myregistry.com
docker login -u username -p password
```

```
# Logout
docker logout

# Search Docker Hub
docker search nginx --limit 5
```

Docker Plugin

```
# List plugins
docker plugin ls

# Install plugin
docker plugin install plugin-name

# Enable/disable plugin
docker plugin enable plugin-name
docker plugin disable plugin-name

# Remove plugin
docker plugin rm plugin-name
```

Docker Config

```
# Create config (for Swarm)
docker config create myconfig config-file.conf

# List configs
docker config ls

# Inspect config
docker config inspect myconfig

# Remove config
docker config rm myconfig
```

Docker Secret

```
# Create secret (for Swarm)
echo "mypassword" | docker secret create db_password -

# List secrets
docker secret ls

# Inspect secret
docker secret inspect db_password
```

```
# Remove secret
docker secret rm db_password
```

Docker Context

```
# List contexts
docker context ls

# Create context
docker context create mycontext --docker "host=tcp://192.168.1.100:2376"

# Use context
docker context use mycontext

# Inspect context
docker context inspect mycontext

# Remove context
docker context rm mycontext
```

Docker Checkpoint (Experimental)

```
# Enable experimental features
export DOCKER_EXPERIMENTAL=1

# Create checkpoint
docker checkpoint create mycontainer checkpoint1

# List checkpoints
docker checkpoint ls mycontainer

# Restore from checkpoint
docker start --checkpoint checkpoint1 mycontainer

# Remove checkpoint
docker checkpoint rm mycontainer checkpoint1
```

Useful Command Combinations

Container Management

```
# Stop and remove all containers
docker stop $(docker ps -aq) && docker rm $(docker ps -aq)

# Remove all containers with specific name pattern
```

```
docker rm -f $(docker ps -aq --filter "name=test_")
```

```
# Restart all running containers
```

```
docker restart $(docker ps -q)
```

```
# View logs from all containers
```

```
docker ps -q | xargs -L1 docker logs --tail 10
```

Image Management

```
# Remove all untagged images
```

```
docker rmi $(docker images -f "dangling=true" -q)
```

```
# Remove all images with specific pattern
```

```
docker rmi $(docker images | grep "myapp" | awk '{print $3}')
```

```
# Pull all tags of an image
```

```
docker images --format "{{.Repository}}:{{.Tag}}" | grep myapp | xargs -L1 docker pull
```

System Information

```
# Show running containers with resource usage
```

```
docker stats $(docker ps --format={{.Names}})
```

```
# Show container IPs
```

```
docker ps -q | xargs docker inspect --format '{{.Name}} - {{range .NetworkSettings.Networks}}
```

```
# Show container port mappings
```

```
docker ps --format "table {{.Names}}\t{{.Ports}}"
```

Quick Reference Cheat Sheet

Most Common Commands

```
# Images
```

```
docker pull <image>
```

```
# Download image
```

```
docker images
```

```
# List images
```

```
docker rmi <image>
```

```
# Remove image
```

```
docker build -t <name> .
```

```
# Build image
```

```
# Containers
```

```
docker run <image>
```

```
# Run container
```

```
docker ps
```

```
# List running containers
```

```
docker ps -a
```

```
# List all containers
```

```
docker stop <container>
```

```
# Stop container
```

```
docker start <container>      # Start container
docker rm <container>         # Remove container
docker logs <container>       # View logs
docker exec -it <container> bash # Access shell

# System
docker info                   # System information
docker system prune           # Clean up
docker volume prune           # Remove unused volumes
docker network prune          # Remove unused networks
```

Key Takeaways

1. **Docker CLI** communicates with Docker daemon via REST API
 2. **Images** are templates; **containers** are running instances
 3. **Volumes** provide persistent storage for containers
 4. **Networks** enable container communication
 5. **System commands** help monitor and clean up resources
 6. Use **--help** with any command to see options and usage
-

What's Next?

Now that you know the CLI commands, you're ready to: - Create your first Dockerfile - Build custom images - Work with Docker Compose - Implement real-world projects

Master the CLI, master Docker!