DAPPER DETAILING PROS

ADD ON SERVICES SOP

Date: 3rd April 2026

Dapper Detailing Pros
660 The Kingsway, Peterborough
+1 (705) 977-6217 | info@dapperdetailing.ca
BIN: 1000966855
GST/HST: 75395 2563 RT0001

Table of Contents

1 SOP — ADD-ON SERVICES 2
1.1 PURPOSE 2
2 INTERIOR-RELATED ADD-ONS 2
2.1 PET HAIR REMOVAL 2
2.2 WINTER SALT REMOVAL 2
2.3 FABRIC PROTECTION 3
3 EXTERIOR-RELATED ADD-ONS 3
3.1 CLAY BAR TREATMENT 3
3.2 WAX APPLICATION 3
3.3 HEADLIGHT RESTORATION 3
3.4 ENGINE BAY CLEANING 4
4 COMBINATION ADD-ON 4
4.1 CLAY + POLISH + WAX 4
5 SPECIAL VEHICLE TYPES 4
5.1 Golf Carts 4
5.2 Small Off-Road Vehicles (e.g., Jeeps) 4
5.3 Large Off-Road / Heavy-Duty Vehicles 5
6 SYSTEM INTEGRATION RULE 5
7 FINAL QC STANDARD (ALL ADD-ONS) 5

Dapper Detailing Pros
660 The Kingsway, Peterborough
+1 (705) 977-6217 | info@dapperdetailing.ca
BIN: 1000966855
GST/HST: 75395 2563 RT0001

1 SOP — ADD-ON SERVICES

1.1 PURPOSE

This SOP standardizes the execution of add-on detailing services to ensure consistent quality, proper integration into the main workflow, and efficient technician performance. These services are not standalone jobs but are performed alongside core detailing processes.

---

2 INTERIOR-RELATED ADD-ONS

2.1 PET HAIR REMOVAL

Pet hair removal focuses on extracting embedded hair from carpets, seats, and tight areas without damaging surfaces.

The process must begin with dry preparation. Surfaces should not be wetted before removal. Loose debris must be vacuumed first to expose embedded hair.

Hair extraction is performed using rubber brushes or specialized pet hair tools. Short, consistent strokes should be used in one direction while compressed air can assist in lifting hair from seams and fibers.

Vacuuming must follow immediately after loosening the hair. This process should be repeated until no visible hair remains.

Quality Standard:

Area	Requirement
Seat seams	No visible hair
Carpet edges	Fully clean
Trunk area	Hair-free

2.2 WINTER SALT REMOVAL

Salt removal is performed to eliminate stains without leaving residue or damaging carpets.

The process begins with vacuuming to remove loose debris. A mixture of warm water and carpet cleaner is then lightly applied to affected areas.

Agitation must be done using a medium brush, focusing on visible salt lines. The area should then be extracted or wiped with microfiber.

Multiple passes are often required, as salt can be deeply embedded.

Key Rule: Avoid oversaturating carpets.

2.3 FABRIC PROTECTION

Fabric guard is applied to protect upholstery from stains and spills after cleaning is complete.

The surface must be completely dry before application. The product should be applied evenly using a light mist to ensure full coverage.

The treated area must be allowed to cure as per product instructions.

Key Rule: Do not oversaturate fabric.

3 EXTERIOR-RELATED ADD-ONS

3.1 CLAY BAR TREATMENT

Clay bar treatment removes bonded contaminants from the paint surface.

The vehicle must be fully washed before starting. A clay lubricant must be applied to prevent scratching.

Clay should be used with light pressure in straight-line motions. After treatment, the surface must be wiped clean with a microfiber towel.

Key Rule: If the clay bar is dropped, it must be discarded.

3.2 WAX APPLICATION

Wax provides gloss and short-term protection.

The surface must be clean and dry before application. Wax should be applied in a thin, even layer using an applicator pad.

After allowing proper curing time (5–10 minutes), the residue should be buffed off using a clean microfiber towel.

Key Rule: Apply thin layers only.

3.3 HEADLIGHT RESTORATION

Headlight restoration improves clarity and removes oxidation.

The process begins with cleaning the surface, followed by wet sanding if oxidation is present using progressive grits (800 → 1500 → 2000).

Polishing is then performed to restore clarity, and a protective layer is applied to prevent future damage.

Quality Standard:

Requirement

- Even clarity
- No haze

- No sanding marks

3.4 ENGINE BAY CLEANING

Engine bay cleaning must be performed carefully to avoid damage to sensitive components.

All exposed electronics and critical areas must be covered before cleaning. A low-pressure rinse is used, followed by application of APC.

Agitation is done using brushes, after which the area is rinsed and dried using air or microfiber towels. A dressing can then be applied to restore plastic components.

Key Rule: High-pressure water must never be used.

---

4 COMBINATION ADD-ON

4.1 CLAY + POLISH + WAX

This combination service enhances paint condition and protection.

The process must follow a strict sequence:

Order	Step
1	Wash
2	Clay bar
3	Polish
4	Wax

Skipping or changing the order will affect results and is not allowed.

---

5 SPECIAL VEHICLE TYPES

5.1 Golf Carts

Focus should be on smaller surfaces such as seats, roof, and tight crevices. Reduced water usage and smaller tools should be used to maintain efficiency.

5.2 Small Off-Road Vehicles (e.g., Jeeps)

These vehicles require additional attention to mud removal, undercarriage splash areas, and interior dirt buildup. A heavy pre-rinse is often required, and washing may need to be repeated.

5.3 Large Off-Road / Heavy-Duty Vehicles

These vehicles involve extreme dirt and larger surface areas. Longer pre-rinse times, increased chemical dwell time, and section-based cleaning are required.

Time Adjustment: Expect an additional 30–50% time requirement.

---

6 SYSTEM INTEGRATION RULE

All add-on services must be integrated into the main detailing workflow rather than treated as separate jobs.

Add-On	When to Perform
Pet Hair Removal	During interior phase
Clay Bar	After wash stage
Wax	Final stage
Fabric Guard	After interior cleaning

---

7 FINAL QC STANDARD (ALL ADD-ONS)

All add-on services must meet the following standards before completion:

Category	Requirement
Cleanliness	No residue or leftover contamination
Coverage	No missed areas
Finish	Even and consistent appearance
Result	Visible improvement to customer