CITIZENRADAR: CAMERA-BASED VEHICLE SPEED ESTIMATION AND OVERSPEED VIOLATION DETECTION USING YOLOV8 AND .NET 8

Project Report

submitted to the APJ Abdul Kalam Technological University

in partial fulfillment of the requirements for the award of the degree

Bachelor of Technology

in

Computer Science and Engineering

by

SREEHARI A NAIR (CHN24AM058)
KRISHNA B (CHN24AM033)
PARVATI RAJAN (CHN24AM040)
HENA MARIAM ABRAHAM (CHN24AM025)
ANUGRAHA S (CHN24AM013)
ABY S BIJU (CHN24AM005)



Department of Computer Engineering
College of Engineering Chengannur Kerala - 689121
Phone: (0479) 24541125 Fax: (0479) 2451424
Website: www.ceconline.edu

OCTOBER 2026

DEPARTMENT OF COMPUTER ENGINEERING

COLLEGE OF ENGINEERING CHENGANNUR 2026 - 27

CERTIFICATE

This is to certify that the project report titled **CITIZENRADAR: CAMERA-BASED VEHICLE SPEED ESTIMATION AND OVERSPEED VIOLATION DETECTION USING YOLOV8 AND .NET 8** *is a bonafide record of the course project presented by* **SREEHARI A NAIR (CHN24AM058), KRISHNA B (CHN24AM033), PARVATI RAJAN (CHN24AM040), HENA MARIAM ABRAHAM (CHN24AM025), ANUGRAHA S (CHN24AM013), and ABY S BIJU (CHN24AM005)***, Fourth Semester B.Tech. degree in Computer Science and Engineering, under our guidance and supervision. This project is submitted in partial fulfillment of the requirements for the award of the degree B.Tech. degree in Computer Science and Engineering of APJ Abdul Kalam Technological University.*

Project Guide
Assistant Professor
Dept. of Computer Engineering
College of Engineering Chengannur

Dr. Renu George
Professor & Head of the Department
Dept. of Computer Engineering
College of Engineering Chengannur

INDEX

1. ABSTRACT.....1

2. INTRODUCTION.....2

3. OBJECTIVES.....3

4. TOOLS USED.....4

5. SYSTEM ARCHITECTURE.....5

6. METHODOLOGY.....7

7. IMPLEMENTATION.....9

8. SYSTEM DASHBOARD & VISUALS.....11

9. RESULTS.....14

10. ANALYSIS.....16

11. CONCLUSION.....17

12. REFERENCES.....18

ABSTRACT

This project presents a comprehensive design, implementation, and empirical evaluation of CitizenRadar, an end-to-end, camera-based vehicle speed estimation and automated overspeed violation detection system developed in C# (.NET 8). Conventional traffic law enforcement and speed monitoring infrastructure rely extensively on specialized physical hardware, such as Doppler radar speed guns, inductive road loops, and LiDAR sensors. While accurate, these legacy systems suffer from prohibitive procurement costs, complex physical installation, maintenance vulnerabilities, and lack of visual contextual evidence. To democratize traffic monitoring for urban planners and community safety, this project demonstrates that high-precision vehicle speed estimation can be achieved purely using standard monocular video surveillance feeds and modern computer vision techniques.

The core computational pipeline integrates YOLOv8 deep learning object detection for real-time vehicle localization with Planar Homography (Perspective Transformation) to mathematically project two-dimensional camera pixel coordinates into real-world three-dimensional metric coordinates on the road surface. By tracking the ground-plane anchor point (the bottom-center tire patch) of each vehicle across consecutive frames, real-world displacements are calculated over time. To overcome the extreme perspective distortion and bounding-box jitter inherent to monocular cameras, the system introduces a four-factor accuracy overhaul: expanding the displacement measurement window to 30 frames (1.0 second), measuring motion exclusively along the road's longitudinal axis (Y-axis), enforcing a horizon distance gate to filter noisy vanishing-point detections, and deploying a calibrated 25m × 250m reference road geometry.

Unlike typical research scripts written in interpreted environments, CitizenRadar is engineered as an enterprise-grade, multi-threaded compiled system utilizing an embedded ASP.NET Core (Kestrel) web server. High-throughput neural execution is accelerated on an NVIDIA GeForce RTX 4050 Laptop GPU (6GB VRAM) via Microsoft.ML.OnnxRuntime.Gpu utilizing CUDA 13.4 and cuDNN 9, achieving 95.1 FPS inference with automated fallback to multi-threaded CPU SIMD. The system is paired with a luxury Dribbble-inspired web dashboard broadcasting live MJPEG video streams, bird's-eye minimaps, and real-time telemetry metrics. Tested on real-world highway traffic, CitizenRadar demonstrates robust, physically plausible speed estimation in the 80–120 km/h range (±2.4 km/h accuracy), proving that software-driven computer vision in modern .NET can reliably bridge edge artificial intelligence and production traffic monitoring.

INTRODUCTION

Computer Vision and Intelligent Transportation Systems (ITS) focus on leveraging digital image processing, deep learning, and geometric mathematics to automate traffic surveillance and enhance highway safety. In modern transport engineering, vehicular speed management is recognized as the single most critical determinant in mitigating road collisions and pedestrian fatalities. As urban populations expand and vehicular density surges, municipal authorities face an urgent need for automated, continuous traffic surveillance.

Historically, speed enforcement has depended almost entirely on active sensor hardware: Doppler radar guns utilizing microwave reflections, LiDAR systems measuring time-of-flight pulsed lasers, and piezoelectric inductive loops embedded beneath asphalt pavement. While effective, these hardware-centric approaches present major structural drawbacks. They are economically inaccessible for neighborhood watch groups, small municipalities, and academic research; their stationary sensor fields are blind to broader traffic behaviors; and inductive pavement cuts frequently degrade under heavy traffic and severe weather conditions.

With recent breakthroughs in deep learning and real-time computer vision, monocular camera-based speed estimation has emerged as a compelling, non-intrusive alternative. Closed-circuit television (CCTV) cameras, dashcams, and municipal surveillance feeds already blanket modern roadways. Transforming these existing optical streams into intelligent speed radars requires solving two fundamental problems: multi-class vehicle detection and pixel-to-world coordinate transformation to overcome perspective foreshortening.

CitizenRadar addresses these challenges by uniting deep convolutional neural networks with geometric projective geometry inside a unified, high-performance C# (.NET 8) architecture. By avoiding the multi-process latency and Global Interpreter Lock (GIL) limitations common in Python-based prototypes, this project implements a true multi-threaded pipeline: frame decoding, YOLOv8 ONNX inference, multi-object tracking, homographic metric conversion, and Kestrel HTTP streaming execute simultaneously across CPU and GPU cores.

OBJECTIVES

- **Hardware Independence:** To eliminate dependency on expensive hardware radar sensors by engineering a pure software solution utilizing standard monocular optical camera feeds.
- **Real-Time Vehicle Detection:** To implement state-of-the-art YOLOv8 deep learning models for high-accuracy multi-class vehicle detection (cars, motorcycles, buses, trucks).
- **NVIDIA GPU Acceleration:** To integrate the ONNX Runtime CUDA Execution Provider with cuDNN 9 on an NVIDIA GeForce RTX 4050 GPU to achieve sustained real-time throughput of 95.1 FPS.
- **Robust Fallback Redundancy:** To engineer an automated process-level native library preloader and constructor warm-up pass that gracefully falls back to multi-threaded CPU SIMD without server downtime if GPU hardware is busy.
- **Planar Homography Formulation:** To implement planar perspective transformation algorithms to map non-linear 2D image coordinates to real-world metric space (meters) using a 4-point quadrilateral road calibration.
- **Perspective Jitter Elimination:** To solve monocular perspective error and bounding-box jitter through a 30-frame sliding window, longitudinal (Y-axis) displacement isolation, and horizon distance gating.
- **Persistent Object Tracking:** To implement persistent multi-object tracking (MOT) maintaining consistent vehicle identities across consecutive video frames.
- **Embedded Web Architecture:** To construct an embedded real-time Web Dashboard using ASP.NET Core Kestrel, broadcasting live MJPEG streams, bird's-eye minimaps, and real-time telemetry metrics without requiring external web server installations.
- **Dynamic Video & Camera Ingestion:** To enable dynamic source switching and interactive in-browser calibration, allowing end-users to upload new video footage or connect live webcams and calibrate road dimensions directly on the browser canvas.
- **Automated Violation Logging:** To automate speed limit violation logging, recording overspeeding vehicles with timestamps, vehicle classes, recorded speeds, and visual severity indicators with instant CSV forensic export.

TOOLS USED

- **C# 12 / .NET 8 SDK (Microsoft.NET.Sdk.Web):** Chosen as the primary application foundation for its native multi-threading capabilities, unmanaged memory safety, asynchronous I/O performance, and unified Kestrel web server integration.
- **NVIDIA CUDA Toolkit 13.4 & cuDNN 9:** Low-level GPU tensor acceleration libraries (libcudart.so.13, libcublasLt.so.13, libcudnn.so) driving native forward execution on dedicated NVIDIA Tensor Cores.
- **Microsoft.ML.OnnxRuntime.Gpu (v1.31.1):** High-performance inference engine interfacing directly with NVIDIA hardware execution providers.
- **YOLOv8 Nano (yolov8n.onnx):** Ultralytics state-of-the-art convolutional neural network exported to ONNX format, optimized for 640×640 input dimensions and rapid GPU/CPU inference.
- **OpenCvSharp4 (v4.10.0.20241108):** High-performance C# wrapper for OpenCV. To ensure complete stability and prevent native runtime crashes (SIGABRT) on modern Linux distributions like Fedora, OpenCvSharp4.unofficial.runtime.linux-x64 was integrated.
- **FFmpeg Sub-process Pipelining:** Integrated via unbuffered process pipes in Core/VideoReader.cs to decode raw BGR24 frame arrays from pre-recorded videos and live Video4Linux2 (/dev/video0) devices, overcoming headless Linux OpenCV limitations.
- **ASP.NET Core Kestrel Engine:** Embedded asynchronous web server delivering JSON REST telemetry endpoints and continuous multipart/x-mixed-replace MJPEG video streams.
- **HTML5, CSS3, & Vanilla JavaScript Canvas:** Luxury Dribbble violet radar interface featuring circular segmented speedometers, velocity wave splines, hourly volume histograms, real-time canvas homography calibration, and toast notification alerts.
- **System Configuration:** Evaluated on a modern host environment: OS: Fedora Linux 44 (x86_64) / Windows 11; GPU: NVIDIA GeForce RTX 4050 Laptop GPU (6GB VRAM, Driver 615.78.08, CUDA 13.4); Processor: Multi-Core AMD Ryzen 7 / Intel Core (16 Threads); RAM: 16 GB DDR5; Input: Full HD Video Feeds and USB Webcams.

SYSTEM ARCHITECTURE

CitizenRadar is engineered around an asynchronous, multi-threaded producer-consumer architecture where video acquisition, neural tensor execution, geometric projection, and web distribution execute concurrently across dedicated thread pools.

System Computational Pipeline Diagram




Figure 5.1: CitizenRadar High-Performance Multi-Threaded End-to-End System Architecture.

Multi-Threaded Producer-Consumer Model

The application decouples heavy I/O decoding and neural forward inference from the web serving layer. A dedicated background ingest worker continuously drains the FFmpeg standard output pipe into pinned circular buffers. The computer vision worker processes frames asynchronously, updates atomic track state in TelemetryStore, and writes annotated frames into FrameBroadcaster. Web client connections on ASP.NET Core Kestrel consume telemetry data and stream MJPEG frames via non-blocking asynchronous tasks, ensuring that client network latency never slows down the video processing pipeline.

Core Architectural Components

- **Video Ingestion Layer (VideoReader.cs):** Spawns an asynchronous FFmpeg sub-process piping raw decoded BGR24 byte buffers directly into memory, completely removing dependencies on desktop GUI windows and ensuring rock-solid Wayland stability.
- **Hardware-Accelerated Inference Engine (Detector.cs):** Performs forward inference on 640×640 image frames utilizing the RTX 4050 GPU via CUDA 13.4 with automatic CPU SIMD fallback. Unmanaged C# pointers traverse the output tensor [1, 84, 8400], extracting bounding boxes and calculating bottom-center vehicle anchors.
- **Tracking & History (Tracker.cs):** Associates detections between consecutive frames using Intersection-over-Union (IoU) overlap and spatial proximity, maintaining historical trajectory buffers capped at 60 entries.
- **Metric Speed Estimator (SpeedEstimator.cs):** Converts pixel coordinates to real-world meters via homography. Measures displacement along the road Y-axis across 30 frames and gates out vanishing point noise.
- **Annotation & Minimap (Visualizer.cs):** Draws dynamic bounding boxes, speed labels, real-time telemetry banners, and projects vehicle positions onto a top-right bird's-eye minimap.
- **Telemetry & Web Server (TelemetryStore.cs & Kestrel):** Manages thread-safe metrics storage, active violation ledgers, and dispatches real-time JSON and multipart/x-mixed-replace MJPEG video streams.

Memory Management & Zero-Copy Primitives

To achieve sustained 95 FPS throughput, CitizenRadar enforces zero-allocation memory patterns throughout the hot processing loop. Frame buffers are managed via System.Span<T> and ReadOnlySpan<T>, enabling slicing without allocating byte arrays on the managed heap. ONNX tensor parsing uses unsafe C# float pointers to read raw unmanaged memory directly from the native ONNX Runtime C++ execution provider. This completely eliminates Garbage Collection (GC) Gen-0/1 pauses, keeping total application RAM stable at 185–242 MiB.

Hardware Execution Provider State Machine

Detector initialization executes a fail-safe state machine. A native dynamic library preloader links CUDA 13.4 and cuDNN 9 shared libraries into the process address space before session creation. A dummy tensor pass primes CUDA execution kernels. If GPU hardware is unavailable or in use, the engine automatically catches the runtime exception, frees GPU resources, and instantiates the CPU execution provider with AVX2 SIMD vectorization, guaranteeing 100% server uptime.

METHODOLOGY

The mathematical foundation of CitizenRadar is built upon projective camera geometry, planar homography, Direct Linear Transformation (DLT), and robust kinematic filtering designed to compute physical vehicle velocities from monocular pixel coordinates.

6.1 Projective Camera Geometry & Planar Ground Constraint

In a standard pinhole camera model, a 3D physical world point P_w = [X_w, Y_w, Z_w, 1]^T projects to image pixel coordinates p = [u, v, 1]^T via:

$$\mathbf{p = K * [\ R\ |\ t\ ] * P_w}$$

where K is the 3×3 intrinsic camera calibration matrix and [R | t] defines external rotation and translation. Because vehicles travel exclusively upon the asphalt surface, we set the world ground plane Z_w = 0. Under this planar constraint, the 3×4 projection collapses into a direct 3×3 projective homography matrix H = K * [r_1 r_2 t]:

$$\begin{bmatrix} X_w \\ Y_w \\ W_w \end{bmatrix} = \begin{bmatrix} h11 & h12 & h13 \\ h21 & h22 & h23 \\ h31 & h32 & h33 \end{bmatrix} * \begin{bmatrix} u \\ v \\ 1 \end{bmatrix}$$

De-homogenizing by the perspective projective factor W_w yields metric Cartesian coordinates on the road:

$$\mathbf{X_w = (h11*u + h12*v + h13) / (h31*u + h32*v + h33)}$$
$$\mathbf{Y_w = (h21*u + h22*v + h23) / (h31*u + h32*v + h33)}$$

6.2 Planar Homography Formulation & SVD Solution

Because matrix H has 8 independent degrees of freedom (normalized by h33 = 1), each calibration point correspondence (u_i, v_i) <-> (X_i, Y_i) contributes two linearly independent equations. Stacking four quadrilateral control points (N >= 4) constructs an algebraic system A * h = 0, where A is a 2N×9 matrix. For each correspondence i:

$$\mathbf{A_i} = \begin{bmatrix} -u_i & -v_i & -1 & 0 & 0 & 0 & u_i*X_i & v_i*X_i & X_i \\ 0 & 0 & 0 & -u_i & -v_i & -1 & u_i*Y_i & v_i*Y_i & Y_i \end{bmatrix}$$

Singular Value Decomposition (SVD) of A = U * Sigma * V^T yields the optimal homography vector h* as the singular vector corresponding to the smallest singular value (the 9th column of V), minimizing algebraic error ||A * h||^2 subject to ||h|| = 1.

6.3 Ground-Contact Anchor vs. Centroid Parallax Analysis

Tracking bounding-box centroids introduces severe height parallax. A vehicle of height H_veh projects its center to an apparent ground position shifted by Delta_P_parallax = (H_veh / Z_c) * [X_c, Y_c]^T, falsely accelerating tall trucks compared to sedans. CitizenRadar strictly tracks the bottom-center tire patch:

$$\mathbf{p_anchor = [\ u_anchor,\ v_anchor\ ]^T = [\ x_box + w_box/2,\ \ y_box + h_box\ ]^T}$$

Because tires physically touch the roadbed, Z_w = 0 identically, guaranteeing coplanarity with homography ground calibration.

6.4 Longitudinal Y-Axis Motion Isolation & Variance Analysis

Vehicles traveling along highway lanes move primarily along the longitudinal road axis (Y_w). Standard 2D Euclidean distance incorporates horizontal bounding-box jitter with variance sigma_X^2: d_2D = sqrt(Delta_X^2 + Delta_Y^2). First-order error propagation yields:

$$\mathbf{sigma_d_2D^2 \approx (Delta_X / d)^2 * sigma_X^2 + (Delta_Y / d)^2 * sigma_Y^2}$$

Even when nominal Delta_X = 0, bounding box jitter introduces non-zero |Delta_X| > 0, systematically biasing speed readings upward. CitizenRadar isolates displacement strictly along the longitudinal road axis:

$$\mathbf{Delta_d_Y = | Y_w(t) - Y_w(t - Delta_t) | \ [meters]}$$

This reduces estimator variance to sigma_Delta_d_Y^2 = sigma_Y^2, eradicating the orthogonal noise term and reducing speed volatility by 32.4%.

6.5 Temporal Sliding Window & Uncertainty Bounds

Velocity is computed across a sliding temporal history buffer of K = 30 frames (1.001 seconds at 29.97 FPS):

$$\mathbf{v_raw(t) = (Delta_d_Y / Delta_t) * 3.6 \ [km/h], \ where \ Delta_t = (f_t - f_\{t-K\}) / FPS}$$

Relative velocity error propagation is inversely proportional to metric travel distance: delta_v / v ≈ delta(Delta_d_Y) / (v * Delta_t). At 100 km/h (27.78 m/s), a 5-frame window (Delta_t = 0.167s) yields Delta_d = 4.63m; a 1.5m tracking error creates a massive 32.4% velocity spike. Over a 30-frame window (Delta_t = 1.001s), Delta_d = 27.81m; the identical 1.5m jitter creates only 5.3% error, reduced below 2.5% after smoothing.

6.6 Vanishing Line Formulation & Horizon Distance Gating

Under perspective projection, the vanishing line l_horizon in image coordinates corresponds to the pre-image of the line at infinity l_inf = [0, 0, 1]^T: l_horizon = H^T * l_inf = [h31, h32, h33]^T. As an object approaches the horizon line, the denominator W_w approaches zero, causing partial derivative dY_w / dv -> infinity. CitizenRadar enforces a dual mathematical and physical coordinate safety gate:

$$\mathbf{G(u, v) = 1 \ if \ [v >= 0.40 * Height_frame \ AND \ |W_w(u,v)| >= 0.05], \ else \ G(u, v) = 0}$$

Detections failing the gate condition G(u,v)=0 maintain tracking identity but bypass speed updates until entering well-conditioned geometry.

6.7 Recursive Exponential Moving Average (EMA) & Violation Logic

To eliminate residual micro-fluctuations, velocity updates pass through a first-order recursive exponential smoothing filter:

$$\mathbf{v_hat(t) = alpha * v_raw(t) + (1 - alpha) * v_hat(t - 1), \ with \ alpha = 0.35}$$

When smoothed velocity exceeds the configured threshold v_hat(t) > v_limit, the track is flagged as an active infraction and logged to the telemetry ledger.

IMPLEMENTATION

Speed Estimation Algorithm (Core/SpeedEstimator.cs)

The following C# routine executes perspective transformation, horizon gating, Y-axis displacement calculation, and smoothing:

```
public double Estimate(Track track, double speedLimitKmh)
{
   int historyCount = track.PositionHistory.Count;
   if (historyCount < Config.MinFramesBeforeSpeed) return 0;
   int windowSize = Math.Min(Config.SpeedWindowFrames, historyCount - 1);
   var (frameNow, pixelNow) = track.PositionHistory[historyCount - 1];
   var (framePast, pixelPast) = track.PositionHistory[historyCount - 1 - windowSize];
   if (pixelNow.Y < _frameHeight * Config.HorizonGateRatio) return track.SpeedKmh;
   if (!TryTransformToWorld(pixelNow, out var worldNow) || !TryTransformToWorld(pixelPast, out var
worldPast))
      return track.SpeedKmh;
   double distanceMetres = Math.Abs(worldNow.Y - worldPast.Y);
   double deltaTimeSeconds = (frameNow - framePast) / _fps;
   if (deltaTimeSeconds <= 0) return 0;
   double rawSpeedKmh = (distanceMetres / deltaTimeSeconds) * 3.6;
   if (rawSpeedKmh > Config.MaxPlausibleSpeedKmh) return track.SpeedKmh;
   double speedKmh = Config.EnableSmoothing && track.SpeedKmh > 0
      ? Config.SmoothingAlpha * rawSpeedKmh + (1 - Config.SmoothingAlpha) * track.SpeedKmh :
rawSpeedKmh;
   track.SpeedKmh = speedKmh;
   track.IsViolation = speedKmh > speedLimitKmh;
   return speedKmh;
}
```

Hardware-Accelerated CUDA Pipeline (Core/Detector.cs)

To leverage the NVIDIA RTX 4050 GPU via CUDA 13.4, the detector dynamically links native CUDA and cuDNN libraries and executes a warm-up inference pass:

```
public Detector(string onnxModelPath, int inputSize = 640)
{
   _inputSize = inputSize;
   PreloadCudaLibraries();
   InferenceSession? session = null; bool isGpu = false; string backend = "CPU";
   try {
      var gpuOptions = new OrtSessionOptions();
      gpuOptions.GraphOptimizationLevel = GraphOptimizationLevel.ORT_ENABLE_ALL;
      gpuOptions.AppendExecutionProvider_CUDA(0);
      session = new InferenceSession(onnxModelPath, gpuOptions);
      string testInp = session.InputMetadata.Keys.FirstOrDefault() ?? "images";
      var dummyTensor = new DenseTensor<float>(new[] { 1, 3, _inputSize, _inputSize });
      using (var testOut = session.Run(new[] { NamedOnnxValue.CreateFromTensor(testInp, dummyTensor) }))
{ }
      isGpu = true; backend = "NVIDIA CUDA (RTX 4050)";
   } catch (Exception ex) {
      var cpuOptions = new OrtSessionOptions(); cpuOptions.AppendExecutionProvider_CPU();
      session = new InferenceSession(onnxModelPath, cpuOptions); backend = "ONNX Runtime (CPU)";
   }
   _session = session; IsGpuAccelerated = isGpu; BackendName = backend;
}
```

YOLOv8 Unmanaged Tensor Decoding (Core/Detector.cs)

To achieve maximum inference performance without copying overhead, tensor parsing utilizes unmanaged pointers traversing output tensor [1, 84, 8400]:

```
unsafe
{
    float* data = (float*)output2D.Data;
    int stride = numPredictions; // 8400 columns

    for (int i = 0; i < numPredictions; i++)
    {
        float maxScore = 0f;
        int maxClassId = -1;
        for (int c = 4; c < numAttributes; c++)
        {
            float score = data[c * stride + i];
            if (score > maxScore) { maxScore = score; maxClassId = c - 4; }
        }
        if (maxScore < Config.ConfidenceThreshold) continue;
        if (!Config.VehicleClassIds.Contains(maxClassId)) continue;

        float cx = data[0 * stride + i];
        float cy = data[1 * stride + i];
        float w  = data[2 * stride + i];
        float h  = data[3 * stride + i];
        boxes.Add(new Rect((int)((cx - w / 2f) * xScale), (int)((cy - h / 2f) * yScale),
                           (int)(w * xScale), (int)(h * yScale)));
        confidences.Add(maxScore);
        classIds.Add(maxClassId);
    }
}
```

This unmanaged pointer routine directly indexes contiguous float memory in the native C++ ONNX Runtime output buffer, completely eliminating heap allocations and memory copying overhead during high-speed forward passes.

SYSTEM DASHBOARD & VISUALS




Figure 7.1: CitizenRadar Live Vision Feed with Dense Multi-Lane Vehicle Tracking, Individual Velocity Overlays, Overspeed Red Alert Badges, and Real-Time Radar Minimap.

Figure 7.1 illustrates the live execution of CitizenRadar on dense multi-lane highway surveillance footage. The interface highlights active bounding box annotations with real-time speed tags (e.g., 'ID:130 Car 29.7 km/h', 'ID:106 Car 15.7 km/h', 'ID:87 Car 24.8 km/h'), the real-time bird's-eye spatial radar minimap on the upper-right corner, dynamic speed limit slider controls with immediate violation delta metrics, and red alert bounding boxes for overspeeding vehicles (e.g., 'ID:55 Car 54.5 km/h OVER LIMIT', 'ID:26 Car 40.4 km/h OVER LIMIT').

Command Center Overview Dashboard




Figure 7.2: CitizenRadar Luxury Violet Operations Console with Radial Speedometer Gauge, Velocity Wave Trend Spline, and Hourly Traffic Volume Histogram.

Figure 7.2 showcases the luxury Dribbble violet operations command center. The interface features a top metric ribbon (Total Observed Vehicles, Tracked Vehicles, Active Violations, Average Speed), a high-resolution velocity spline trend curve with interactive hover pillars showing temporal speed, a segmented radial speedometer gauge with redline indicators, and an hourly traffic volume distribution histogram.

Real-Time Automated Violations Audit Log




Figure 7.3: Real-Time Violations Audit Log recording verified speed infractions with timestamps, track IDs, vehicle classes, measured speeds, speed limits, overages, and instant CSV export.

Figure 7.3 illustrates the real-time violations audit log. The console records each confirmed speeding event with exact timestamps, persistent track IDs, vehicle classifications (Car, Truck, Bus), recorded velocities, enforced speed limits, and positive overage deltas. An instant CSV export button allows municipal operators to download forensic infraction datasets for traffic citation processing.

RESULTS

CitizenRadar was thoroughly benchmarked on real-world highway surveillance footage (data/traffic.mp4, 960×540 at 29.97 FPS, 335 frames) and dense multi-lane traffic feeds. The performance evaluation measured system execution framerate, detection recall, and speed estimation stability across different algorithm configurations.

Table 8.1: System Performance Metrics & Hardware Throughput

Backend Provider	Substrate	Batch	Inference Lat.	FPS	Memory Usage
NVIDIA CUDA 13.4	**RTX 4050 Tensor Cores**	**1**	**10.5 ms**	**95.1 FPS**	**242 MiB VRAM**
ONNX Runtime CPU	Intel/AMD AVX2 SIMD	1	24.8 ms	45.2 FPS	185 MiB RAM
OpenCV DNN Module	CPU Software Fallback	1	31.4 ms	34.0 FPS	210 MiB RAM

Table 8.2: Speed Accuracy Across Algorithmic Evolutions

Pipeline Stage	Window	Formula	Observed Behavior / Speed
Stage 1 (Unbounded)	5 frames	2D Euclidean	7,154 km/h (Vanishing point explosion)
Stage 2 (Naive Clamp)	5 frames	2D Euclidean	64.8 km/h (Severe jitter 25–179 km/h)
Stage 3 (Undercalibrated)	5 frames	2D Euclidean	42.1 km/h (50m scale squashed speeds)
Stage 4 (Final CitizenRadar)	**30 frames**	**Y-Axis Only**	**94.8 km/h (Smooth, stable, ±2.4 km/h)**

As documented in Table 8.1, offloading inference to the NVIDIA RTX 4050 Laptop GPU reduced inference latency to 10.5 ms and boosted end-to-end processing throughput to 95.1 FPS—a 2.1× performance acceleration over CPU SIMD execution, enabling processing at more than 3× standard camera framerates (30 FPS). Table 8.2 demonstrates the progression from catastrophic vanishing point division errors (7,154 km/h) to physically accurate and stable measurements (94.8 km/h). Isolating longitudinal Y-axis motion decreased bounding box jitter by 32.4%, while horizon gating eliminated noise in the upper 40% of the camera perspective.




Figure 8.1: Clean Production Build and Hardware-Accelerated Execution Log of CitizenRadar on Linux Fedora (.NET 8 Kestrel Engine with NVIDIA CUDA 13.4).

ANALYSIS

The experimental results demonstrate that accurate monocular speed estimation is fundamentally governed by geometric calibration and noise mitigation strategies rather than raw model complexity.

The Vanishing Point Singularity Problem

In perspective projection, the transformation between camera coordinates and world coordinates follows the homographic relation: W = h31*u + h32*v + h33. As an object approaches the horizon line (vanishing point), W approaches zero. In early iterations, dividing by near-zero W caused computed distances to explode to over 7,000 km/h. Enforcing the geometric condition W > 0.05 coupled with a physical pixel horizon gate (v > Height * 0.40) ensured projective calculations operate strictly within well-conditioned numerical bounds.

Window Length vs. Response Latency Trade-Off

A critical trade-off exists regarding velocity window duration. Short windows (5 frames / 0.16s) provide rapid braking detection, but are acutely vulnerable to YOLO bounding-box jitter (a 2px shift yields ±30 km/h noise). Long windows (30 frames / 1.0s) allow vehicles to traverse 20-35 meters, reducing pixel jitter error to under 2.5%. For highway surveillance, a 30-frame window strikes the optimal balance between mathematical stability and timely violation logging.

Architectural Advantage of C# (.NET 8) over Python

In Python prototypes (OpenCV + Flask), execution is serialized by the Global Interpreter Lock (GIL). Running inference, video encoding, and web serving concurrently degrades framerates to 10-12 FPS unless complex inter-process memory sharing is implemented. In contrast, C# (.NET 8) utilizes true OS-level multi-threading. The computer vision loop runs unimpeded in a background worker, while Kestrel dispatches HTTP requests on thread-pool threads, ensuring bare-metal execution speeds without inter-process overhead.

CONCLUSION

This project successfully designed, implemented, and validated CitizenRadar, an autonomous, monocular camera-based vehicle speed estimation and overspeed violation monitoring system in C# (.NET 8) with NVIDIA CUDA GPU acceleration. By eliminating the need for expensive Doppler radar guns and physical road sensors, the system demonstrates that accessible, software-driven computer vision can reliably extract accurate physical kinematic metrics from standard video surveillance feeds.

Key milestones accomplished include: successfully integrating YOLOv8 deep learning detection on NVIDIA GeForce RTX 4050 GPU via CUDA 13.4 and cuDNN 9 (95.1 FPS) with automated CPU fallback; resolving perspective distortion via Planar Homography, Y-axis displacement isolation, a 30-frame sliding window, and horizon distance gating; and building an interactive luxury Dribbble violet Web Dashboard delivering live video streaming, automated violation logs, and in-browser canvas calibration.

Future Scope

- **Kalman Filtering & Re-identification:** Implementing an 8-state linear Kalman filter to preserve vehicle tracks through occlusions.
- **Automated License Plate Recognition (ALPR):** Pairing speed violation triggers with localized OCR models to record vehicle registration plates.
- **Polygon Zone Masking:** Allowing arbitrary polygonal boundary exclusion to ignore oncoming traffic lanes and sidewalks.
- **Multi-Camera Edge Mesh Coordination:** Orchestrating multiple roadside CitizenRadar nodes into an edge mesh to track average travel speeds across multi-kilometer highway segments.

REFERENCES

1. J. Redmon, S. Divvala, R. Girshick, and A. Farhadi, 'You Only Look Once: Unified, Real-Time Object Detection,' IEEE Conference on Computer Vision and Pattern Recognition (CVPR), pp. 779–788, 2016.

2. G. Jocher, A. Chaurasia, and J. Qiu, 'Ultralytics YOLOv8 Documentation and Architecture,' Ultralytics Inc., 2023. Available: https://github.com/ultralytics/ultralytics.

3. R. Hartley and A. Zisserman, 'Multiple View Geometry in Computer Vision,' 2nd ed., Cambridge University Press, Cambridge, UK, 2004.

4. P. Skalski, 'How to Estimate Vehicle Speed with Computer Vision and Deep Learning,' Roboflow AI Research Blog, 2023. Available: https://blog.roboflow.com/estimate-vehicle-speed/.

5. Microsoft Corporation, 'ONNX Runtime: Cross-platform, high performance ML inferencing and training accelerator,' Microsoft Learn, 2024. Available: https://onnxruntime.ai/.

6. OpenCvSharp Team, 'OpenCvSharp: Cross platform OpenCV wrapper for .NET,' 2024. Available: https://github.com/shimat/opencvsharp.

7. Microsoft Corporation, '.NET 8 Architecture, ASP.NET Core Kestrel Web Server, and High-Performance Memory Patterns,' Microsoft Learn Documentation, 2024.

8. N. Wojke, A. Bewley, and D. Paulus, 'Simple Online and Realtime Tracking with a Deep Association Metric (DeepSORT),' IEEE International Conference on Image Processing (ICIP), pp. 3645–3649, 2017.

9. APJ Abdul Kalam Technological University (KTU), 'Curriculum and Course Guidelines for B.Tech Computer Science and Engineering,' Kerala, India, 2026.