

Continuous Delivery

Lab 2

Tennis Smith

2019-07-12


Prerequisites

Students will need a computer with:

- An Amazon Workspaces login (see your instructor for details)

Lab 2

Lab2 will extract the tag of the latest docker image (1 below) in the registry and then stage it to an s3 bucket (2 below). On each instance, there is a cron job that will read the s3 bucket once per minute (3 below). If the tag in the bucket is newer than the currently-running website, then the instance will pull an image from the registry (4 below). Then, the training instance will restart the website with the new docker image (5 below). The idea is to provide a way for Jenkins to control when a training instance updates to a new version of the website.



Step 1: Login to GitHub

- In your workspaces session, open a web browser and login to github:
<http://github.com>

Tip

If you don't have a GitHub account, go to <http://github.com> and create a free account

Step 2: Fork the lab2 repo

- Go to this url: https://github.com/RoundTower-io/cd_workshop_lab2
- Fork the repo by clicking on the "Fork" button in the upper right of the screen.
- This will create a copy of the lab2 repo under your own GitHub id

Step 3: Clone a copy of the lab2 repo

- In your workspace session, open a new terminal window by clicking on the Powershell



icon.

- Make a local copy of the repo by cloning it with the following command
`git clone https://github.com/<your user name>/cd_workshop_lab2.git lab2`

Step 4: Update the Jenkinsfile

- Go to the home directory of your new repo
`cd lab2`
- Now edit the file Jenkinsfile
`atom Jenkinsfile`
- Change every occurrence of training99 to your training ID (assigned by the instructor).
- Save and exit the file

Step 5: Commit Changes and Push to Central Repository

- First, change the working directory.

```
cd ~/lab2
```

- Next, add all altered files to the change set.

```
git add .
```

- Next, commit the changes.

```
git commit -m "Updated Jenkinsfile"
```

- Last, push the change to GitHub.

```
git push
```

Step 6: Setup a Jenkins pipeline

- Login to Jenkins at <http://jenkins.roundtower.io>
- Login using your assigned training id (get it from your instructor).
- Click on the "New Item" option on the main menu



Build Queue

No builds in the queue.

Build Executor Status

1 Idle


2 Idle


- Name your new pipeline <your training id>_lab2 and select pipeline as the type. Then click ok to save it.


Enter an item name


training1_lab2


» Required field


**Freestyle project**
This is the central feature of Jenkins. Jenkins will build your project, combining any SCM with any build system, and this can be even used for something other than s


**Pipeline**
Orchestrates long-running activities that can span multiple build slaves. Suitable for building pipelines (formerly known as workflows) and/or organizing complex activ

**External Job**
This type of job allows you to record the execution of a process run outside Jenkins, even on a remote machine. This is designed so that you can use Jenkins as a d


**Multi-configuration project**
Suitable for projects that need a large number of different configurations, such as testing on multiple environments, platform-specific builds, etc.

**Folder**
Creates a container that stores nested items in it. Useful for grouping things together. Unlike view, which is just a filter, a folder creates a separate namespace, so you long as they are in different folders.

**GitHub Organization**
Scans a GitHub organization (or user account) for all repositories matching some defined markers.

**Multibranch Pipeline**
Creates a set of Pipeline projects according to detected branches in one SCM repository.

if you want to create a new item from other existing, you can use this option:

Copy from

OK

- At the bottom of the page, set the Definition field to Pipeline script from SCM, then set the SCM field to Git. Put your lab2 url in the Repository URL field. Finally, click on Save to save all your work.

Pipeline

Definition **Pipeline script from SCM**

SCM **Git**

Repositories

Repository URL **https://github.com/gamename/cd_workshop_lab2.git**
Please enter Git repository.

Credentials **- none -**
Add

Branches to build

Branch Specifier (blank for 'any') ***/master**

Repository browser **(Auto)**

Additional Behaviours **Add**

Script Path **Jenkinsfile**

Lightweight checkout ☒

[Pipeline Syntax](#)

Save **Apply**


- Click **Build Now** on the upper left of the screen.
- After the build, click on your **trainingX_lab2** link on the dashboard. You should see output something like this:

Pipeline training1_lab2




[Recent Changes](#)

Stage View



Step 7: Access website

- Go to the following URL based on your training ID number, <http://trainingX.roundtower.io>. For example, if you are assigned training1, then the url would be <http://training1.roundtower.io>
- You should see something like this



Step 8: Setup trigger of lab2 build on completion of lab1 build

- Click on trainingX_lab2 on the main dashboard.
- Now click on Configure on the left side of the screen. This will take you back to the configuration options for lab2's pipeline
- Scroll down to Build Triggers and click on Build after other projects are built (it is the first option in the list).
- In the Projects to watch field, put in the name of your lab1 pipeline. For example, if your training ID is training2, then the lab1 pipeline will be named training2_lab1. Make sure that Trigger only if build is stable is selected too.

Build Triggers

☒ Build after other projects are built

Projects to watch

☒ Trigger only if build is stable

☐ Trigger even if the build is unstable

☐ Trigger even if the build fails

☐ Build periodically

☐ GitHub hook trigger for GITScm polling

☐ Poll SCM

☐ Disable this project

☐ Quiet period

☐ Trigger builds remotely (e.g., from scripts)

Advanced Project Options

Advanced...

Pipeline

Save Apply

Pipeline script from SCM

- Click on Save and exit the configuration.
- From now on, lab2 will build **only if** your lab1 pipeline builds successfully.

Step 9: Update website unit test and source

Now we are going to update the website itself and the unit tests that verify those changes.


- Go back to your **lab 1** directory

```
cd ~/lab1
```

- Edit src/site/views/layout.jade

```
atom src\site\views\layout.jade
```


- Replace REPLACE THIS TITLE with your training ID. Then save and exit the file.




The screenshot shows the Atom editor interface. On the left, the 'Project' sidebar shows a folder named 'views' containing 'index.jade' and 'layout.jade'. The 'layout.jade' file is open in the editor. The code is as follows:

```
1 doctype
2 html
3 head
4 title #{title} - training2
5 link(rel= 'stylesheet' , href='/stylesheets/style.css')
6 body
7   header
8     h1 REPLACE THIS HEADER
9   .container
10     .main-content
11       block content
12     .sidebar
13       block sidebar
14   footer
15     p Copyright 2018 RoundTower, Inc.
16
```

The line `title #{title} - training2` on line 4 is circled in red.

- Now edit tests/layout-test.txt to update the test for the new layout.
`atom tests/layout-test.txt`
- Edit the top line and make it **exactly** like the line from layout.jade you edited in previous steps. Save and exit the file.



The screenshot shows the Atom editor interface. On the left, the 'Project' sidebar shows a folder named 'tests' containing 'index-test.sh', 'index-test.txt', 'layout-test.sh', and 'layout-test.txt'. The 'layout-test.txt' file is open in the editor. The code is as follows:


```
1 title #{title} - training2
2 h1 REPLACE THIS HEADER
3
```

The line `title #{title} - training2` on line 1 is circled in red.

- Now, add your latest changes to the changelist
`git add .`
- Commit your changes to the local repository
`git commit -m "updated header and unit test"`
- Finally, push your changes back to GitHub's repository
`git push`

Step 10: Checking website for updates

- The push in step 9 should have kicked off a new build for your trainingX_lab1 pipeline.
- When that lab1 build completed, it should have kicked off a new lab 2 pipeline build.
- Go to your website at training<your number>.roundtower.io.
- The Home tab should now have your training ID next to it. Example



- Congratulations! You've completed the Labs!

Step 11: Extra credit

- Rerun steps 9/10 and change other fields in the web page.