ACADEMIC CENTRAL

PRACTICE EXAMINATION

NC(V) LEVEL 3

INTRODUCTION TO TECHNICAL PROGRAMMING

PRACTICE EXAM 8 (PAPER 2) · MARKING GUIDELINE

MARKS: 100

Marking guideline for the Academic Central NC(V) Level 3 Introduction to Technical Programming practice exam 8 (paper 2).

Written by Academic Central for practice, following the NC(V) subject guidelines for NC(V) Level 3. It is not a Department of Higher Education and Training marking guideline.

How to mark: each ✓ is one mark. Programs are not marked strictly on syntax: give marks for correct logic, correct variables and correct output. Accept other variable names, other prompts and other correct ways of solving the problem.

QUESTION 1

1.1 Project created and named correctly ✓ (1)

1.2 Suitable sprite ✓ (1)

1.3 Suitable backdrop ✓ (1)

1.4 Variables created ✓✓✓ (percent, level, aps) and set to 0 ✓✓✓ (6)

1.5 repeat 6 ✓ around the subject blocks ✓ (2)

1.6 ask block ✓; set percent to answer ✓ (2)

1.7 Correct conditions for levels 7 ✓, 6 ✓, 5 ✓, 4 ✓, 3 ✓ and 2 ✓; level 1 in the last else ✓; correct nesting of if … else ✓✓; boundaries correct (e.g. 80 gives 7, 79 gives 6) ✓ (10)

1.8 change aps by level ✓✓ (2)

1.9 say the level ✓ joined with text ✓ (2)

1.10 say the total APS after the loop ✓✓ (2)

1.11 Levels 7, 6, 5, 4, 3, 2 ✓✓; APS = 27 ✓ (3)

```
when green flag clicked
set [percent] to 0
set [level] to 0
set [aps] to 0
repeat 6
    ask [Enter the percentage for a subject] and wait
    set [percent] to (answer)
    if < (percent) > 79 > then
        set [level] to 7
    else
        if < (percent) > 69 > then
            set [level] to 6
        else
            if < (percent) > 59 > then
                set [level] to 5
            else
                if < (percent) > 49 > then
                    set [level] to 4
                else
                    if < (percent) > 39 > then
                        set [level] to 3
                    else
                        if < (percent) > 29 > then
                            set [level] to 2
                        else
                            set [level] to 1
```

```
    say (join [Level: ] (level)) for 2 seconds
    change [aps] by (level)
end repeat
say (join [Your APS is ] (aps)) for 3 seconds
```

[32]

QUESTION 2

2.1 File created and named correctly ✓ (1)

2.2 #include <iostream> ✓; using namespace std; ✓ (2)

2.3 int main() ✓; units, amount, vat, total declared as double ✓✓ and set to 0 ✓ (4)

2.4 Prompt and cin ✓✓; if units < 0 ✓ show "Invalid units" and return / end ✓ (4)

2.5 if (units <= 350) ✓✓ amount = units * 2.50 ✓✓; else ✓ amount = 350 * 2.50 + (units − 350) * 3.10 ✓✓✓ (8)

2.6 vat = amount * 0.15 ✓✓; total = amount + vat ✓ (3)

2.7 Amount ✓, VAT ✓ and total ✓ displayed with R (3)

```
// YourName - Question 2
#include <iostream>
using namespace std;

int main() {
    double units = 0, amount = 0, vat = 0, total = 0;

    cout << "Enter the units used (kWh): ";
    cin >> units;
    if (units < 0) {
        cout << "Invalid units" << endl;
        return 0;
    }

    if (units <= 350) {
        amount = units * 2.50;
    } else {
        amount = 350 * 2.50 + (units - 350) * 3.10;
    }
    vat = amount * 0.15;
    total = amount + vat;

    cout << "Amount before VAT: R" << amount << endl;
    cout << "VAT: R" << vat << endl;
    cout << "Total to pay: R" << total << endl;
    return 0;
}
```

[25]

QUESTION 3

3.1 File created and named correctly ✓ (1)

3.2 #include <iostream> ✓; using namespace std; ✓ (2)

3.3 int main() ✓; number of students ✓; total and average (double) ✓; highest, lowest and pass counter ✓ (4)

3.4 Prompt ✓ and cin ✓ in a loop ✓ that repeats while n < 1 or n > 40 ✓ (4)

3.5 int (or double) array ✓ of size 40 ✓ declared before use ✓ (3)

3.6 for loop over the students ✓✓; prompt with the student number ✓; cin into marks[i] ✓; inner loop / check ✓ that repeats while the mark is below 0 or above 100 ✓ with an error message ✓; correct index use ✓ (8)

3.7 Total set to 0 and each mark added ✓✓; average = total / n ✓✓ (with a decimal result) (4)

3.8 highest and lowest start at marks[0] ✓✓; loop through the array ✓; if marks[i] > highest ✓ then highest = marks[i] ✓; if marks[i] < lowest ✓ then lowest = marks[i] ✓; correct results ✓ (8)

3.9 Counter set to 0 ✓; if marks[i] >= 50 ✓ the counter increases ✓ inside the loop ✓ (4)

3.10 Average ✓, highest ✓, lowest ✓ and passes ✓ displayed with labels ✓ (5)

```
// YourName - Question 3
#include <iostream>
using namespace std;

int main() {
    int n = 0, marks[40], highest = 0, lowest = 0, passed = 0;
    double total = 0, average = 0;

    do {
        cout << "How many students wrote (1-40)? ";
        cin >> n;
    } while (n < 1 || n > 40);

    for (int i = 0; i < n; i++) {
        cout << "Mark for student " << i + 1 << ": ";
        cin >> marks[i];
        while (marks[i] < 0 || marks[i] > 100) {
            cout << "Mark must be from 0 to 100." << endl;
            cout << "Mark for student " << i + 1 << ": ";
            cin >> marks[i];
        }
    }

    highest = marks[0];
    lowest = marks[0];
    for (int i = 0; i < n; i++) {
        total = total + marks[i];
        if (marks[i] > highest) highest = marks[i];
        if (marks[i] < lowest) lowest = marks[i];
        if (marks[i] >= 50) passed++;
    }
    average = total / n;

    cout << "Class average: " << average << endl;
    cout << "Highest mark: " << highest << endl;
    cout << "Lowest mark: " << lowest << endl;
    cout << "Students who passed: " << passed << endl;
    return 0;
}
```

[43]

TOTAL: 100

END OF MARKING GUIDELINE