

Security of distributed Model Predictive Control under False Data injection or How I Learned to Stop and Worry about Everything

Rafael Accácio NOGUEIRA

December 12, 2022




<https://bit.ly/3g3S6X4>




Context

Requirements evolve with time



Context

Requirements evolve with time



Context

Requirements evolve with time



Context

Requirements evolve with time



Context

Requirements evolve with time



Context

Requirements evolve with time



- Electricity Distribution System
- Heat distribution
- Water distribution
- Traffic management
- (include your problem here)

Context

Requirements evolve with time



- Electricity Distribution System
 - Heat distribution
 - Water distribution
 - Traffic management
- (include your problem here)

Context

Requirements evolve with time



- Electricity Distribution System
- Heat distribution
- Water distribution
- Traffic management

(include your problem here)

Context

Requirements evolve with time



- Electricity Distribution System
 - Heat distribution
 - Water distribution
 - Traffic management
- (include your problem here)

Context

Requirements evolve with time



- Multiple systems interacting
- Coupled by constraints
- Optimization objectives
 - Minimize energy consumption
 - Maximize user satisfaction
 - Follow a trajectory
 - ...
- Solution \rightarrow MPC

Context

Requirements evolve with time



- Multiple systems interacting
- Coupled by constraints
- Optimization objectives
 - Minimize energy consumption
 - Maximize user satisfaction
 - Follow a trajectory
 - ...
- Solution \rightarrow MPC

Context

Requirements evolve with time



- Multiple systems interacting
- Coupled by constraints
- Optimization objectives
 - Minimize energy consumption
 - Maximize user satisfaction
 - Follow a trajectory
 - ...
- Solution \rightarrow MPC

Context

Requirements evolve with time



- Multiple systems interacting
- Coupled by constraints
- Optimization objectives
 - Minimize energy consumption
 - Maximize user satisfaction
 - Follow a trajectory
 - ...
- Solution \rightarrow MPC

Context

Requirements evolve with time



- Multiple systems interacting
- Coupled by constraints
- Optimization objectives
 - Minimize energy consumption
 - Maximize user satisfaction
 - Follow a trajectory
 - ...
- Solution \rightarrow MPC

Context

Requirements evolve with time



- Multiple systems interacting
- Coupled by constraints
- Optimization objectives
 - Minimize energy consumption
 - Maximize user satisfaction
 - Follow a trajectory
- ...
- Solution \rightarrow MPC

Context

Requirements evolve with time



- Multiple systems interacting
- Coupled by constraints
- Optimization objectives
 - Minimize energy consumption
 - Maximize user satisfaction
 - Follow a trajectory
 - ...
- Solution → MPC

Context

Requirements evolve with time



- Multiple systems interacting
- Coupled by constraints
- Optimization objectives
 - Minimize energy consumption
 - Maximize user satisfaction
 - Follow a trajectory
 - ...
- Solution \rightarrow MPC

Model-based Predictive Control

Find best control sequence using predictions based on a model.

- Objective function to optimize
- System's Model (states and inputs)
- Other constraints to respect (QoS, technical restrictions, ...)



Find best control sequence using predictions based on a model.

- Objective function to optimize
- System's Model (states and inputs)
- Other constraints to respect (QoS, technical restrictions, ...)

Model-based Predictive Control

Find **best** control sequence using predictions based on a model.

- Objective function to optimize
- System's Model (states and inputs)
- Other constraints to respect (QoS, technical restrictions, ...)



Model-based Predictive Control

Find optimal control sequence using predictions based on a model.

- Objective function to optimize
- System's Model (states and inputs)
- Other constraints to respect (QoS, technical restrictions, ...)



Model-based Predictive Control

Find optimal control sequence using predictions based on a model.

- Objective function to optimize
- System's Model (states and inputs)
- Other constraints to respect (QoS, technical restrictions, ...)

minimize
 $\mathbf{u}[0:N-1|k]$

$$J(\mathbf{x}[0|k], \mathbf{u}[0 : N - 1|k])$$

subject to

$$\left. \begin{array}{l} \mathbf{x}[\xi|k] = f(\mathbf{x}[\xi - 1|k], \mathbf{u}[\xi - 1|k]) \\ g_i(\mathbf{x}[\xi - 1|k], \mathbf{u}[\xi - 1|k]) \leq 0 \\ h_j(\mathbf{x}[\xi - 1|k], \mathbf{u}[\xi - 1|k]) = 0 \end{array} \right\} \begin{array}{l} \forall \xi \in \{1, \dots, N\} \\ \forall i \in \{1, \dots, m\} \\ \forall j \in \{1, \dots, p\} \end{array}$$



Model-based Predictive Control

Find optimal control sequence using predictions based on a model.

- Objective function to optimize
- System's Model (states and inputs)
- Other constraints to respect (QoS, technical restrictions, ...)

minimize
 $\mathbf{u}[0:N-1|k]$

$$J(\mathbf{x}[0|k], \mathbf{u}[0 : N - 1|k])$$

subject to

$$\left. \begin{array}{l} \mathbf{x}[\xi|k] = f(\mathbf{x}[\xi - 1|k], \mathbf{u}[\xi - 1|k]) \\ g_i(\mathbf{x}[\xi - 1|k], \mathbf{u}[\xi - 1|k]) \leq 0 \\ h_j(\mathbf{x}[\xi - 1|k], \mathbf{u}[\xi - 1|k]) = 0 \end{array} \right\} \begin{array}{l} \forall \xi \in \{1, \dots, N\} \\ \forall i \in \{1, \dots, m\} \\ \forall j \in \{1, \dots, p\} \end{array}$$



Model-based Predictive Control

Find optimal control sequence using predictions based on a model.

- Objective function to optimize
- System's Model (states and inputs)
- Other constraints to respect (QoS, technical restrictions, ...)

minimize
 $\mathbf{u}[0:\textcolor{red}{N}-1|k]$

$$J(\mathbf{x}[0|k], \mathbf{u}[0 : \textcolor{red}{N} - 1|k])$$

subject to

$$\left. \begin{array}{l} \mathbf{x}[\xi|k] = f(\mathbf{x}[\xi-1|k], \mathbf{u}[\xi-1|k]) \\ g_i(\mathbf{x}[\xi-1|k], \mathbf{u}[\xi-1|k]) \leq 0 \\ h_j(\mathbf{x}[\xi-1|k], \mathbf{u}[\xi-1|k]) = 0 \end{array} \right\} \begin{array}{l} \forall \xi \in \{1, \dots, N\} \\ \forall i \in \{1, \dots, m\} \\ \forall j \in \{1, \dots, p\} \end{array}$$



Model-based Predictive Control

Find optimal control sequence using predictions based on a model.

- Objective function to optimize
- System's Model (states and inputs)
- Other constraints to respect (QoS, technical restrictions, ...)

minimize
 $\mathbf{u}[0:N-1|k]$

$$J(\mathbf{x}[0|k], \mathbf{u}[0 : N - 1|k])$$

subject to

$$\left. \begin{array}{l} \mathbf{x}[\xi|k] = f(\mathbf{x}[\xi - 1|k], \mathbf{u}[\xi - 1|k]) \\ g_i(\mathbf{x}[\xi - 1|k], \mathbf{u}[\xi - 1|k]) \leq 0 \\ h_j(\mathbf{x}[\xi - 1|k], \mathbf{u}[\xi - 1|k]) = 0 \end{array} \right\} \begin{array}{l} \forall \xi \in \{1, \dots, N\} \\ \forall i \in \{1, \dots, m\} \\ \forall j \in \{1, \dots, p\} \end{array}$$



Model-based Predictive Control

Find optimal control sequence using predictions based on a model.

- Objective function to optimize
- System's Model (states and inputs)
- Other constraints to respect (QoS, technical restrictions, ...)

$$\begin{array}{ll} \underset{\mathbf{u}[0:N-1|k]}{\text{minimize}} & J(\mathbf{x}[0|k], \mathbf{u}[0 : N - 1|k]) \\ \text{subject to} & \left. \begin{array}{l} \mathbf{x}[\xi|k] = f(\mathbf{x}[\xi - 1|k], \mathbf{u}[\xi - 1|k]) \\ g_i(\mathbf{x}[\xi - 1|k], \mathbf{u}[\xi - 1|k]) \leq 0 \\ h_j(\mathbf{x}[\xi - 1|k], \mathbf{u}[\xi - 1|k]) = 0 \end{array} \right\} \begin{array}{l} \forall \xi \in \{1, \dots, N\} \\ \forall i \in \{1, \dots, m\} \\ \forall j \in \{1, \dots, p\} \end{array} \end{array}$$



Model-based Predictive Control

Find optimal control sequence using predictions based on a model.

- Objective function to optimize
- System's Model (**states** and inputs)
- Other constraints to respect (QoS, technical restrictions, ...)

$$\begin{array}{ll} \underset{\mathbf{u}[0:N-1|k]}{\text{minimize}} & J(\mathbf{x}[0|k], \mathbf{u}[0 : N - 1|k]) \\ \text{subject to} & \left. \begin{array}{l} \mathbf{x}[\xi|k] = f(\mathbf{x}[\xi - 1|k], \mathbf{u}[\xi - 1|k]) \\ g_i(\mathbf{x}[\xi - 1|k], \mathbf{u}[\xi - 1|k]) \leq 0 \\ h_j(\mathbf{x}[\xi - 1|k], \mathbf{u}[\xi - 1|k]) = 0 \end{array} \right\} \begin{array}{l} \forall \xi \in \{1, \dots, N\} \\ \forall i \in \{1, \dots, m\} \\ \forall j \in \{1, \dots, p\} \end{array} \end{array}$$



Model-based Predictive Control

Find optimal control sequence using predictions based on a model.

- Objective function to optimize
- System's Model (states and **inputs**)
- Other constraints to respect (QoS, technical restrictions, ...)

$$\begin{array}{ll} \underset{\mathbf{u}[0:N-1|k]}{\text{minimize}} & J(\mathbf{x}[0|k], \mathbf{u}[0 : N - 1|k]) \\ \text{subject to} & \left. \begin{array}{l} \mathbf{x}[\xi|k] = f(\mathbf{x}[\xi - 1|k], \mathbf{u}[\xi - 1|k]) \\ g_i(\mathbf{x}[\xi - 1|k], \mathbf{u}[\xi - 1|k]) \leq 0 \\ h_j(\mathbf{x}[\xi - 1|k], \mathbf{u}[\xi - 1|k]) = 0 \end{array} \right\} \begin{array}{l} \forall \xi \in \{1, \dots, N\} \\ \forall i \in \{1, \dots, m\} \\ \forall j \in \{1, \dots, p\} \end{array} \end{array}$$



Model-based Predictive Control

Find optimal control sequence using predictions based on a model.

- Objective function to optimize
- System's Model (states and inputs)
- Other constraints to respect (QoS, technical restrictions, ...)

$$\begin{array}{ll} \underset{\mathbf{u}[0:N-1|k]}{\text{minimize}} & J(\mathbf{x}[0|k], \mathbf{u}[0 : N - 1|k]) \\ \text{subject to} & \left. \begin{array}{l} \mathbf{x}[\xi|k] = f(\mathbf{x}[\xi - 1|k], \mathbf{u}[\xi - 1|k]) \\ g_i(\mathbf{x}[\xi - 1|k], \mathbf{u}[\xi - 1|k]) \leq 0 \\ h_j(\mathbf{x}[\xi - 1|k], \mathbf{u}[\xi - 1|k]) = 0 \end{array} \right\} \begin{array}{l} \forall \xi \in \{1, \dots, N\} \\ \forall i \in \{1, \dots, m\} \\ \forall j \in \{1, \dots, p\} \end{array} \end{array}$$



Model-based Predictive Control

Find optimal control sequence using predictions based on a model.

- Objective function to optimize
- System's Model (states and inputs)
- Other constraints to respect (QoS, technical restrictions, ...)



$$\begin{array}{ll} \underset{\mathbf{u}[0:N-1|k]}{\text{minimize}} & J(\mathbf{x}[0|k], \mathbf{u}[0 : N - 1|k]) \\ \text{subject to} & \left. \begin{array}{l} \mathbf{x}[\xi|k] = f(\mathbf{x}[\xi - 1|k], \mathbf{u}[\xi - 1|k]) \\ g_i(\mathbf{x}[\xi - 1|k], \mathbf{u}[\xi - 1|k]) \leq 0 \\ h_j(\mathbf{x}[\xi - 1|k], \mathbf{u}[\xi - 1|k]) = 0 \end{array} \right\} \begin{array}{l} \forall \xi \in \{1, \dots, N\} \\ \forall i \in \{1, \dots, m\} \\ \forall j \in \{1, \dots, p\} \end{array} \end{array}$$



Model Predictive Control

In a nutshell

Find optimal control sequence





CentraleSupélec

Model Predictive Control

In a nutshell

Find optimal control sequence





CentraleSupélec

Model Predictive Control

In a nutshell



Find optimal control sequence, apply first element



Model Predictive Control

In a nutshell



Find optimal control sequence, apply first element, rinse repeat



Model Predictive Control

In a nutshell



Find optimal control sequence, apply first element, rinse repeat → Receding Horizon



Model Predictive Control


In a nutshell

Find optimal control sequence, apply first element, rinse repeat → Receding Horizon




Distributed Model Predictive Control

- Problem: Complexity depends on N, m, p and sizes of x and u
- Solution: Divide and Conquer¹



Distributed Model Predictive Control


- Problem: Complexity depends on N, m, p and sizes of x and u
- Solution: Divide and Conquer¹



¹  *Distributed Model Predictive Control made easy*

Distributed Model Predictive Control


- Problem: Complexity depends on N, m, p and sizes of x and u
- Solution: Divide and Conquer¹



¹  *Distributed Model Predictive Control made easy*

Distributed Model Predictive Control


Optimization Frameworks



- Agents solve local problems
 - Variables are updated
- } Until
Convergence

Distributed Model Predictive Control


Optimization Frameworks



- Agents solve local problems
 - Variables are updated
- } Until
Convergence

Distributed Model Predictive Control

Optimization Frameworks



- Agents solve local problems
 - Variables are updated
- } Until
Convergence

Negotiation works if agents comply.

But what if some agents are ill-intentioned and attack the system?

- What are the consequences of an attack?
- Can we mitigate the effects?



Negotiation works if agents comply.

But what if some agents are ill-intentioned and attack the system?

- What are the consequences of an attack?
- Can we mitigate the effects?

Negotiation works if agents comply.

But what if some agents are ill-intentioned and attack the system?

- What are the consequences of an attack?
- Can we mitigate the effects?

Negotiation works if agents comply.

But what if some agents are ill-intentioned and attack the system?

- What are the consequences of an attack?
- Can we mitigate the effects?

State of art

	Decomposition	Present vulnerabilities?	Resilient/Robust	Detection	Mitigation
[Vel+17a] [Mae+21]	Dual	Yes	Robust (Scenario)	NA	NA
[Vel+17b] [Vel+18]	Dual	Yes	Robust (f-robust)	NA	NA
[CMI18]	Jacobi-Gauß	Yes	–	–	–
[Ana+18] [Ana+19] [Ana+20]	Dual	Yes	Resilient	Analyt./Learn.	Disconnect (Robustness)
Our	Primal	Yes	Resilient	Active Analyt./Learn.	Data reconstruction



State of art

	Decomposition	Present vulnerabilities?	Resilient/Robust	Detection	Mitigation
[Vel+17a] [Mae+21]	Dual	Yes	Robust (Scenario)	NA	NA
[Vel+17b] [Vel+18]	Dual	Yes	Robust (f-robust)	NA	NA
[CMI18]	Jacobi-Gauß	Yes	–	–	–
[Ana+18] [Ana+19] [Ana+20]	Dual	Yes	Resilient	Analyt./Learn.	Disconnect (Robustness)
Our	Primal	Yes	Resilient	Active Analyt./Learn.	Data reconstruction



- ① Vulnerabilities in distributed MPC based on Primal Decomposition
- ② Resilient Primal Decomposition-based dMPC for deprived systems
- ③ Resilient Primal Decomposition-based dMPC using Artificial Scarcity

- ① Vulnerabilities in distributed MPC based on Primal Decomposition
- ② Resilient Primal Decomposition-based dMPC for deprived systems
- ③ Resilient Primal Decomposition-based dMPC using Artificial Scarcity

- ① Vulnerabilities in distributed MPC based on Primal Decomposition
- ② Resilient Primal Decomposition-based dMPC for deprived systems
- ③ Resilient Primal Decomposition-based dMPC using Artificial Scarcity

Outline

① Vulnerabilities in distributed MPC based on Primal Decomposition

What is the Primal Decomposition?

How can an agent attack?

Consequences



Distributed Model Predictive Control

Primal Decomposition | Quantity Decomposition | Resource Allocation

Decompose original problem using primal problem



Distributed Model Predictive Control

Primal Decomposition | Quantity Decomposition | Resource Allocation

Decompose **original problem** using primal problem

$$\begin{array}{ll}
 \underset{\mathbf{u}[0:N-1|k]}{\text{minimize}} & J(\mathbf{x}[0|k], \mathbf{u}[0 : N - 1|k]) \\
 \text{subject to} & \left. \begin{array}{l} \mathbf{x}[\xi|k] = f(\mathbf{x}[\xi - 1|k], \mathbf{u}[\xi - 1|k]) \\ g_i(\mathbf{x}[\xi - 1|k], \mathbf{u}[\xi - 1|k]) \leq 0 \\ h_j(\mathbf{x}[\xi - 1|k], \mathbf{u}[\xi - 1|k]) = 0 \end{array} \right\} \begin{array}{l} \forall \xi \in \{1, \dots, N\} \\ \forall i \in \{1, \dots, m\} \\ \forall j \in \{1, \dots, p\} \end{array}
 \end{array}$$

Distributed Model Predictive Control

Primal Decomposition | Quantity Decomposition | Resource Allocation

Decompose **original problem** using primal problem

$$\begin{aligned}
 & \underset{\mathbf{u}[0:N-1|k]}{\text{minimize}} && \sum_{i \in \mathcal{M}} \sum_{\xi \in \mathcal{N}} \left[\|\mathbf{v}_i[\xi|k]\|_{Q_i}^2 + \|\mathbf{u}_i[\xi-1|k]\|_{R_i}^2 \right] \\
 & \text{subject to} && \left. \begin{aligned} \mathbf{x}[\xi|k] &= f(\mathbf{x}[\xi-1|k], \mathbf{u}[\xi-1|k]) \\ g_i(\mathbf{x}[\xi-1|k], \mathbf{u}[\xi-1|k]) &\leq 0 \\ h_j(\mathbf{x}[\xi-1|k], \mathbf{u}[\xi-1|k]) &= 0 \end{aligned} \right\} \begin{aligned} &\forall \xi \in \{1, \dots, N\} \\ &\forall i \in \{1, \dots, m\} \\ &\forall j \in \{1, \dots, p\} \end{aligned}
 \end{aligned}$$



Distributed Model Predictive Control

Primal Decomposition | Quantity Decomposition | Resource Allocation

Decompose original problem using primal problem

E.g. $v_i = w_i - x_i$

$$\begin{aligned}
 & \underset{\mathbf{u}[0:N-1|k]}{\text{minimize}} && \sum_{i \in \mathcal{M}} \sum_{\xi \in \mathcal{N}} \left[\|\mathbf{v}_i[\xi|k]\|_{Q_i}^2 + \|\mathbf{u}_i[\xi-1|k]\|_{R_i}^2 \right] \\
 & \text{subject to} && \left. \begin{aligned} \mathbf{x}[\xi|k] &= f(\mathbf{x}[\xi-1|k], \mathbf{u}[\xi-1|k]) \\ g_i(\mathbf{x}[\xi-1|k], \mathbf{u}[\xi-1|k]) &\leq 0 \\ h_j(\mathbf{x}[\xi-1|k], \mathbf{u}[\xi-1|k]) &= 0 \end{aligned} \right\} \begin{aligned} &\forall \xi \in \{1, \dots, N\} \\ &\forall i \in \{1, \dots, m\} \\ &\forall j \in \{1, \dots, p\} \end{aligned}
 \end{aligned}$$



Distributed Model Predictive Control

Primal Decomposition | Quantity Decomposition | Resource Allocation

Decompose original problem using primal problem

$$\begin{aligned}
 & \underset{\mathbf{u}[0:N-1|k]}{\text{minimize}} && \sum_{i \in \mathcal{M}} \sum_{\xi \in \mathcal{N}} \left[\|\mathbf{v}_i[\xi|k]\|_{Q_i}^2 + \|\mathbf{u}_i[\xi-1|k]\|_{R_i}^2 \right] \\
 & \text{subject to} && \left. \begin{aligned} \mathbf{x}[\xi|k] &= A\mathbf{x}[\xi-1|k] + B\mathbf{u}[\xi-1|k] \\ g_i(\mathbf{x}[\xi-1|k], \mathbf{u}[\xi-1|k]) &\leq 0 \\ h_j(\mathbf{x}[\xi-1|k], \mathbf{u}[\xi-1|k]) &= 0 \end{aligned} \right\} \begin{aligned} &\forall \xi \in \{1, \dots, N\} \\ &\forall i \in \{1, \dots, m\} \\ &\forall j \in \{1, \dots, p\} \end{aligned}
 \end{aligned}$$



Distributed Model Predictive Control

Primal Decomposition | Quantity Decomposition | Resource Allocation

Decompose original problem using primal problem

$$\begin{aligned}
 & \underset{\mathbf{u}[0:N-1|k]}{\text{minimize}} && \sum_{i \in \mathcal{M}} \sum_{\xi \in \mathcal{N}} \left[\|\mathbf{v}_i[\xi|k]\|_{Q_i}^2 + \|\mathbf{u}_i[\xi-1|k]\|_{R_i}^2 \right] \\
 & \text{subject to} && \left. \begin{aligned} \mathbf{x}[\xi|k] &= A_i \mathbf{x}[\xi-1|k] + B_i \mathbf{u}[\xi-1|k] \\ \sum_{i \in \mathcal{M}} \Gamma_i \mathbf{u}_i[\xi|k] &\leq \mathbf{u}_{\max} \end{aligned} \right\} \forall \xi \in \mathcal{N}
 \end{aligned}$$

Distributed Model Predictive Control

Primal Decomposition | Quantity Decomposition | Resource Allocation

Decompose original problem using primal problem

$$\begin{array}{ll} \underset{\mathbf{U}_1[k], \dots, \mathbf{U}_M[k]}{\text{minimize}} & \sum_{i \in \mathcal{M}} \left[\frac{1}{2} \|\mathbf{U}_i[k]\|_{H_i}^2 + \mathbf{f}_i[k]^T \mathbf{U}_i[k] \right] \\ \text{subject to} & \sum_{i \in \mathcal{M}} [\bar{\Gamma}_i \mathbf{U}_i[k]] \leq \mathbf{U}_{\max} \end{array}$$

Distributed Model Predictive Control

Primal Decomposition | Quantity Decomposition | Resource Allocation

Decompose original problem using primal problem

$$\underset{\mathbf{U}_1[k]}{\text{minimize}} \quad \frac{1}{2} \|\mathbf{U}_1[k]\|_{H_1}^2 + \mathbf{f}_1[k]^T \mathbf{U}_1[k]$$

$$\text{subject to} \quad \bar{\Gamma}_1 \mathbf{U}_1[k] \leq \boldsymbol{\theta}_1[k] : \boldsymbol{\lambda}_1[k]$$

$$\vdots$$

$$\underset{\mathbf{U}_M[k]}{\text{minimize}} \quad \frac{1}{2} \|\mathbf{U}_M[k]\|_{H_M}^2 + \mathbf{f}_M[k]^T \mathbf{U}_M[k]$$

$$\text{subject to} \quad \bar{\Gamma}_M \mathbf{U}_M[k] \leq \boldsymbol{\theta}_M[k] : \boldsymbol{\lambda}_M[k]$$

$$\boldsymbol{\theta}[k]^{(p+1)} = \text{Proj}^{\mathcal{S}}(\boldsymbol{\theta}[k]^{(p)} + \rho^{(p)} \boldsymbol{\lambda}[k]^{(p)})$$



Distributed Model Predictive Control

Primal Decomposition | Quantity Decomposition | Resource Allocation

Decompose original problem using primal problem

$$\mathcal{S} = \{\boldsymbol{\theta}[k] \mid I_c^M \boldsymbol{\theta}[k] \leq \mathbf{U}_{\max}\}$$

$$\begin{aligned} & \underset{\mathbf{U}_1[k]}{\text{minimize}} && \frac{1}{2} \|\mathbf{U}_1[k]\|_{H_1}^2 + \mathbf{f}_1[k]^T \mathbf{U}_1[k] \\ & \text{subject to} && \bar{\Gamma}_1 \mathbf{U}_1[k] \leq \boldsymbol{\theta}_1[k] : \boldsymbol{\lambda}_1[k] \end{aligned}$$

$$\begin{aligned} & \vdots \\ & \underset{\mathbf{U}_M[k]}{\text{minimize}} && \frac{1}{2} \|\mathbf{U}_M[k]\|_{H_M}^2 + \mathbf{f}_M[k]^T \mathbf{U}_M[k] \\ & \text{subject to} && \bar{\Gamma}_M \mathbf{U}_M[k] \leq \boldsymbol{\theta}_M[k] : \boldsymbol{\lambda}_M[k] \end{aligned}$$

$$\boldsymbol{\theta}[k]^{(p+1)} = \text{Proj}^{\mathcal{S}}(\boldsymbol{\theta}[k]^{(p)} + \rho^{(p)} \boldsymbol{\lambda}[k]^{(p)})$$



Distributed Model Predictive Control

Primal Decomposition | Quantity Decomposition | Resource Allocation

Decompose original problem using primal problem

$$\mathcal{S} = \{\boldsymbol{\theta}[k] \mid I_c^M \boldsymbol{\theta}[k] \leq \mathbf{U}_{\max}\}$$

$$\underset{\mathbf{U}_1[k]}{\text{minimize}} \quad \frac{1}{2} \|\mathbf{U}_1[k]\|_{H_1}^2 + \mathbf{f}_1[k]^T \mathbf{U}_1[k]$$

$$\text{subject to} \quad \bar{\Gamma}_1 \mathbf{U}_1[k] \leq \boldsymbol{\theta}_1[k] : \boldsymbol{\lambda}_1[k]$$

$$\vdots$$


$$\underset{\mathbf{U}_M[k]}{\text{minimize}} \quad \frac{1}{2} \|\mathbf{U}_M[k]\|_{H_M}^2 + \mathbf{f}_M[k]^T \mathbf{U}_M[k]$$

$$\text{subject to} \quad \bar{\Gamma}_M \mathbf{U}_M[k] \leq \boldsymbol{\theta}_M[k] : \boldsymbol{\lambda}_M[k]$$


$$\boldsymbol{\theta}[k]^{(p+1)} = \text{Proj}^{\mathcal{S}}(\boldsymbol{\theta}[k]^{(p)} + \rho^{(p)} \boldsymbol{\lambda}[k]^{(p)})$$




Quantity Decomposition | Resource Allocation




Quantity Decomposition | Resource Allocation




Quantity Decomposition | Resource Allocation




Quantity Decomposition | Resource Allocation




Quantity Decomposition | Resource Allocation





Quantity Decomposition | Resource Allocation



Quantity Decomposition | Resource Allocation



Quantity Decomposition | Resource Allocation



How can a non-cooperative agent attack?

Literature

- [Vel+17a; CMI18] present some kinds of attacks
 - Objective function
 - Selfish Attack
 - Fake weights
 - Fake reference
 - Fake constraints
 - Liar agent (use different control)
- Deception Attacks
(False Data Injection)



How can a non-cooperative agent attack?

Literature

- [Vel+17a; CMI18] present some kinds of attacks
 - Objective function
 - Selfish Attack
 - Fake weights
 - Fake reference
 - Fake constraints
 - Liar agent (use different control)
- Deception Attacks
(False Data Injection)



How can a non-cooperative agent attack?

Literature

- [Vel+17a; CMI18] present some kinds of attacks
 - Objective function
 - Selfish Attack
 - Fake weights
 - Fake reference
 - Fake constraints
 - Liar agent (use different control)
- Deception Attacks
(False Data Injection)



How can a non-cooperative agent attack?

Literature

- [Vel+17a; CMI18] present some kinds of attacks
 - Objective function
 - Selfish Attack
 - Fake weights
 - Fake reference
 - Fake constraints
 - Liar agent (use different control)
- Deception Attacks
(False Data Injection)



How can a non-cooperative agent attack?

Literature

- [Vel+17a; CMI18] present some kinds of attacks
 - Objective function
 - Selfish Attack
 - Fake weights
 - Fake reference
 - Fake constraints
 - Liar agent (use different control)
- Deception Attacks
(False Data Injection)



How can a non-cooperative agent attack?

Literature

- [Vel+17a; CMI18] present some kinds of attacks
 - Objective function
 - Selfish Attack
 - Fake weights
 - Fake reference
 - Fake constraints
 - Liar agent (use different control)

Deception Attacks
(False Data Injection)



How can a non-cooperative agent attack?

Literature

- [Vel+17a; CMI18] present some kinds of attacks
 - Objective function
 - Selfish Attack
 - Fake weights
 - Fake reference
 - Fake constraints
 - Liar agent (use different control)

Deception Attacks
(False Data Injection)



How can a non-cooperative agent attack?

Literature

- [Vel+17a; CMI18] present some kinds of attacks
 - Objective function
 - Selfish Attack
 - Fake weights
 - Fake reference
 - Fake constraints
 - Liar agent (use different control)
- Deception Attacks
(False Data Injection)



How can a non-cooperative agent attack?

Our approach

- λ_i is the only interface with coordination
- λ_i depends on the parameters of the system
- Malicious agent sends a different λ_i



How can a non-cooperative agent attack?

Our approach

- λ_i is the only interface with coordination
- λ_i depends on the parameters of the system
- Malicious agent sends a different λ_i

How can a non-cooperative agent attack?

Our approach

- λ_i is the only interface with coordination
- λ_i depends on the parameters of the system
- Malicious agent sends a different λ_i



How can a non-cooperative agent attack?

Our approach

- λ_i is the only interface with coordination
- λ_i depends on the parameters of the system
- Malicious agent sends a different λ_i

$$\tilde{\lambda}_i = \gamma_i(\lambda_i)$$



Example

Let's suppose $\gamma_i(\lambda_i) = T_i \lambda_i$



Example

Let's suppose $\gamma_i(\lambda_i) = T_i \lambda_i$

4 distinct agents

- Agent 1 is non-cooperative
- It uses $\tilde{\lambda}_1 = \gamma_1(\lambda_1) = \tau_1 I \lambda_1$

Example

Let's suppose $\gamma_i(\lambda_i) = T_i \lambda_i$

4 distinct agents

- Agent 1 is non-cooperative
- It uses $\tilde{\lambda}_1 = \gamma_1(\lambda_1) = \tau_1 I \lambda_1$



Example

Let's suppose $\gamma_i(\lambda_i) = T_i \lambda_i$


4 distinct agents

- Agent 1 is non-cooperative
- It uses $\tilde{\lambda}_1 = \gamma_1(\lambda_1) = \tau_1 I \lambda_1$



Example

Let's suppose $\gamma_i(\lambda_i) = T_i \lambda_i$




4 distinct agents

- Agent 1 is non-cooperative
- It uses $\tilde{\lambda}_1 = \gamma_1(\lambda_1) = \tau_1 I \lambda_1$

Example

Let's suppose $\gamma_i(\lambda_i) = T_i \lambda_i$




4 distinct agents

- Agent 1 is non-cooperative
- It uses $\tilde{\lambda}_1 = \gamma_1(\lambda_1) = \tau_1 I \lambda_1$

Example

Let's suppose $\gamma_i(\lambda_i) = T_i \lambda_i$



4 distinct agents

- Agent 1 is non-cooperative
- It uses $\tilde{\lambda}_1 = \gamma_1(\lambda_1) = \tau_1 I \lambda_1$


Mitigating

There are vulnerabilities



Mitigating

There are vulnerabilities




Original minimum.




Mitigating

There are vulnerabilities



Original minimum.



Minimum after attack.


Mitigating

There are vulnerabilities
“Great”. But what can we do?



Mitigating

There are vulnerabilities
“Great”. But what can we do?




Ignore attacker.




Mitigating

There are vulnerabilities
“Great”. But what can we do?



Ignore attacker.




Recover original behavior.




Mitigating

There are vulnerabilities
“Great”. But what can we do?



Ignore attacker.



Recover original behavior.



Strategy

- Recover original behavior
 - Invert effects of function $\gamma_i(\lambda_i)$
- Is $\gamma_i(\lambda_i)$ invertible?
 - Not necessarily, but let's reason



Strategy

- Recover original behavior
 - Invert effects of function $\gamma_i(\lambda_i)$
- Is $\gamma_i(\lambda_i)$ invertible?
 - Not necessarily, but let's reason



Strategy

- Recover original behavior
 - Invert effects of function $\gamma_i(\lambda_i)$
- Is $\gamma_i(\lambda_i)$ invertible?
 - Not necessarily, but let's reason




Strategy

- Recover original behavior
 - Invert effects of function $\gamma_i(\lambda_i)$
- Is $\gamma_i(\lambda_i)$ invertible?
 - Not necessarily, but let's reason



Is $\gamma_i(\lambda_i)$ invertible?

Unidimensional Case




- $\lambda \geq 0$ means dissatisfaction
- $\lambda = 0$ means complete satisfaction
 - $\gamma(\lambda) = 0 \Leftrightarrow \lambda = 0$

Assumptions

- Attacker is greedy $\gamma(\lambda) > \lambda$
- But not smart
 - $\lambda_b > \lambda_a \rightarrow \gamma(\lambda_b) > \gamma(\lambda_a)$

Is $\gamma_i(\lambda_i)$ invertible?

Unidimensional Case




- $\lambda \geq 0$ means dissatisfaction
- $\lambda = 0$ means complete satisfaction
 - $\gamma(\lambda) = 0 \Leftrightarrow \lambda = 0$

Assumptions

- Attacker is greedy $\gamma(\lambda) > \lambda$
- But not smart
 - $\lambda_b > \lambda_a \rightarrow \gamma(\lambda_b) > \gamma(\lambda_a)$

Is $\gamma_i(\lambda_i)$ invertible?

Unidimensional Case




- $\lambda \geq 0$ means dissatisfaction
- $\lambda = 0$ means complete satisfaction
 - $\gamma(\lambda) = 0 \Leftrightarrow \lambda = 0$

Assumptions

- Attacker is greedy $\gamma(\lambda) > \lambda$
- But not smart
 - $\lambda_b > \lambda_a \rightarrow \gamma(\lambda_b) > \gamma(\lambda_a)$

Is $\gamma_i(\lambda_i)$ invertible?

Unidimensional Case




- $\lambda \geq 0$ means dissatisfaction
- $\lambda = 0$ means complete satisfaction
 - $\gamma(\lambda) = 0 \Leftrightarrow \lambda = 0$

Assumptions

- Attacker is greedy $\gamma(\lambda) > \lambda$
- But not smart
 - $\lambda_b > \lambda_a \rightarrow \gamma(\lambda_b) > \gamma(\lambda_a)$

Is $\gamma_i(\lambda_i)$ invertible?

Unidimensional Case




- $\lambda \geq 0$ means dissatisfaction
- $\lambda = 0$ means complete satisfaction
 - $\gamma(\lambda) = 0 \Leftrightarrow \lambda = 0$

Assumptions

- Attacker is greedy $\gamma(\lambda) > \lambda$
- But not smart
 $\lambda_b > \lambda_a \rightarrow \gamma(\lambda_b) > \gamma(\lambda_a)$

Is $\gamma_i(\lambda_i)$ invertible?

Unidimensional Case




- $\lambda \geq 0$ means dissatisfaction
- $\lambda = 0$ means complete satisfaction
 - $\gamma(\lambda) = 0 \Leftrightarrow \lambda = 0$

Assumptions

- Attacker is greedy $\gamma(\lambda) > \lambda$
 - But not smart
- $\lambda_b > \lambda_a \rightarrow \gamma(\lambda_b) > \gamma(\lambda_a)$

Is $\gamma_i(\lambda_i)$ invertible?

Unidimensional Case




- $\lambda \geq 0$ means dissatisfaction
- $\lambda = 0$ means complete satisfaction
 - $\gamma(\lambda) = 0 \Leftrightarrow \lambda = 0$

Assumptions

- Attacker is greedy $\gamma(\lambda) > \lambda$
- But not smart
$$\lambda_b > \lambda_a \rightarrow \gamma(\lambda_b) > \gamma(\lambda_a)$$

Is $\gamma_i(\lambda_i)$ invertible?

Unidimensional Case




- $\lambda \geq 0$ means dissatisfaction
- $\lambda = 0$ means complete satisfaction
 - $\gamma(\lambda) = 0 \Leftrightarrow \lambda = 0$

Assumptions

- Attacker is greedy $\gamma(\lambda) > \lambda$
- But not smart
$$\lambda_b > \lambda_a \rightarrow \gamma(\lambda_b) > \gamma(\lambda_a)$$

Is $\gamma_i(\lambda_i)$ invertible?

Unidimensional Case




- $\lambda \geq 0$ means dissatisfaction
- $\lambda = 0$ means complete satisfaction
 - $\gamma(\lambda) = 0 \Leftrightarrow \lambda = 0$

Assumptions

- Attacker is greedy $\gamma(\lambda) > \lambda$
- But not smart
 $\lambda_b > \lambda_a \rightarrow \gamma(\lambda_b) > \gamma(\lambda_a)$

Is $\gamma_i(\lambda_i)$ invertible?

Unidimensional Case



- $\lambda \geq 0$ means dissatisfaction
- $\lambda = 0$ means complete satisfaction
 - $\gamma(\lambda) = 0 \Leftrightarrow \lambda = 0$

Assumptions

- Attacker is greedy $\gamma(\lambda) > \lambda$
- But not smart
 $\lambda_b > \lambda_a \rightarrow \gamma(\lambda_b) > \gamma(\lambda_a)$

Is $\gamma_i(\lambda_i)$ invertible?

Linear Multidimensional Case

- $\gamma(\lambda) = T\lambda$
- $T\lambda = 0 \Leftrightarrow \lambda = 0 \rightarrow \exists T^{-1}$
- Each agent could choose different T_i each time



Is $\gamma_i(\lambda_i)$ invertible?

Linear Multidimensional Case

- $\gamma(\lambda) = T\lambda$
- $T\lambda = 0 \Leftrightarrow \lambda = 0 \rightarrow \exists T^{-1}$
- Each agent could choose different T_i each time

Is $\gamma_i(\lambda_i)$ invertible?

Linear Multidimensional Case

- $\gamma(\lambda) = T\lambda$
- $T\lambda = 0 \Leftrightarrow \lambda = 0 \rightarrow \exists T^{-1}$
- Each agent could choose different T_i each time



Is $\gamma_i(\lambda_i)$ invertible?

Linear Multidimensional Case

- $\gamma(\lambda) = T\lambda$
- $T\lambda = 0 \Leftrightarrow \lambda = 0 \rightarrow \exists T^{-1}$
- Each agent could choose different T_i each time



Is $\gamma_i(\lambda_i)$ invertible?

Linear Multidimensional Case

- $\gamma(\lambda) = T\lambda$
- $T\lambda = 0 \Leftrightarrow \lambda = 0 \rightarrow \exists T^{-1}$
- Each agent could choose different T_i each time $\rightarrow T_i[k]$

Strategy

- Recover original behavior
 - Invert effects of function $\gamma_i(\lambda_i) \rightarrow \text{Estimate } T_i[k]^{-1}$
- But how? Analyzing the system



Strategy

- Recover original behavior
 - Invert effects of function $\gamma_i(\lambda_i) \rightarrow \text{Estimate } T_i[k]^{-1}$
- But how? Analyzing the system



Strategy

- Recover original behavior
 - Invert effects of function $\gamma_i(\lambda_i) \rightarrow \text{Estimate } T_i[k]^{-1}$
- But how? Analyzing the system



Strategy

- Recover original behavior
 - Invert effects of function $\gamma_i(\lambda_i) \rightarrow \text{Estimate } T_i[k]^{-1}$
- But how? Analyzing the system



Outline

② Resilient Primal Decomposition-based dMPC for deprived systems

- Analyzing deprived systems

- Building an algorithm

- Applying mechanism



What are deprived systems?

$$\begin{aligned} & \underset{\mathbf{U}_i[k]}{\text{minimize}} && \frac{1}{2} \|\mathbf{U}_i[k]\|_{H_i}^2 + \mathbf{f}_i[k]^T \mathbf{U}_i[k] \\ & \text{subject to} && \bar{\Gamma}_i \mathbf{U}_i[k] \leq \boldsymbol{\theta}_i[k] : \boldsymbol{\lambda}_i[k] \end{aligned}$$

- Unconstrained solution $\dot{\mathbf{U}}_i^*[k] = -H_i^{-1} \mathbf{f}_i[k]$
- Deprived if constraints are active $\rightarrow \bar{\Gamma}_i \dot{\mathbf{U}}_i^*[k] > \boldsymbol{\theta}_i[k], \forall k$
 - Solution projected onto boundaries (equality constraints)

What are deprived systems?

$$\begin{aligned} & \underset{\mathbf{U}_i[k]}{\text{minimize}} && \frac{1}{2} \|\mathbf{U}_i[k]\|_{H_i}^2 + \mathbf{f}_i[k]^T \mathbf{U}_i[k] \\ & \text{subject to} && \bar{\Gamma}_i \mathbf{U}_i[k] \leq \boldsymbol{\theta}_i[k] : \boldsymbol{\lambda}_i[k] \end{aligned}$$

- Unconstrained solution $\hat{\mathbf{U}}_i^*[k] = -H_i^{-1} \mathbf{f}_i[k]$
- Deprived if constraints are active $\rightarrow \bar{\Gamma}_i \hat{\mathbf{U}}_i^*[k] > \boldsymbol{\theta}_i[k], \forall k$
 - Solution projected onto boundaries (equality constraints)



What are deprived systems?

$$\begin{aligned} & \underset{\mathbf{U}_i[k]}{\text{minimize}} && \frac{1}{2} \|\mathbf{U}_i[k]\|_{H_i}^2 + \mathbf{f}_i[k]^T \mathbf{U}_i[k] \\ & \text{subject to} && \bar{\Gamma}_i \mathbf{U}_i[k] \leq \boldsymbol{\theta}_i[k] : \boldsymbol{\lambda}_i[k] \end{aligned}$$

- Unconstrained solution $\dot{\mathbf{U}}_i^*[k] = -H_i^{-1} \mathbf{f}_i[k]$
- Deprived if constraints are active $\rightarrow \bar{\Gamma}_i \dot{\mathbf{U}}_i^*[k] > \boldsymbol{\theta}_i[k], \forall k$
 - Solution projected onto boundaries (equality constraints)



What are deprived systems?

$$\begin{aligned} & \underset{\mathbf{U}_i[k]}{\text{minimize}} && \frac{1}{2} \|\mathbf{U}_i[k]\|_{H_i}^2 + \mathbf{f}_i[k]^T \mathbf{U}_i[k] \\ & \text{subject to} && \bar{\Gamma}_i \mathbf{U}_i[k] \leq \boldsymbol{\theta}_i[k] : \boldsymbol{\lambda}_i[k] \end{aligned}$$

- Unconstrained solution $\mathring{\mathbf{U}}_i^\star[k] = -H_i^{-1} \mathbf{f}_i[k]$
- Deprived if constraints are active $\rightarrow \bar{\Gamma}_i \mathring{\mathbf{U}}_i^\star[k] > \boldsymbol{\theta}_i[k], \forall k$
 - Solution projected onto boundaries (equality constraints)

What are deprived systems?

$$\begin{aligned} & \underset{\mathbf{U}_i[k]}{\text{minimize}} && \frac{1}{2} \|\mathbf{U}_i[k]\|_{H_i}^2 + \mathbf{f}_i[k]^T \mathbf{U}_i[k] \\ & \text{subject to} && \bar{\Gamma}_i \mathbf{U}_i[k] \leq \boldsymbol{\theta}_i[k] : \boldsymbol{\lambda}_i[k] \end{aligned}$$


- Unconstrained solution $\mathring{\mathbf{U}}_i^\star[k] = -H_i^{-1} \mathbf{f}_i[k]$
- Deprived if constraints are active $\rightarrow \bar{\Gamma}_i \mathring{\mathbf{U}}_i^\star[k] > \boldsymbol{\theta}_i[k], \forall k$
 - Solution projected onto boundaries (equality constraints)



What are deprived systems?

$$\begin{aligned} & \underset{\mathbf{U}_i[k]}{\text{minimize}} && \frac{1}{2} \|\mathbf{U}_i[k]\|_{H_i}^2 + \mathbf{f}_i[k]^T \mathbf{U}_i[k] \\ & \text{subject to} && \bar{\Gamma}_i \mathbf{U}_i[k] \leq \boldsymbol{\theta}_i[k] : \boldsymbol{\lambda}_i[k] \end{aligned}$$


- Unconstrained solution $\dot{\mathbf{U}}_i^*[k] = -H_i^{-1} \mathbf{f}_i[k]$
- Deprived if constraints are active $\rightarrow \bar{\Gamma}_i \dot{\mathbf{U}}_i^*[k] > \boldsymbol{\theta}_i[k], \forall k$
 - Solution projected onto boundaries (equality constraints)



What are deprived systems?

$$\begin{aligned} & \underset{\mathbf{U}_i[k]}{\text{minimize}} && \frac{1}{2} \|\mathbf{U}_i[k]\|_{H_i}^2 + \mathbf{f}_i[k]^T \mathbf{U}_i[k] \\ & \text{subject to} && \bar{\Gamma}_i \mathbf{U}_i[k] \leq \boldsymbol{\theta}_i[k] : \boldsymbol{\lambda}_i[k] \end{aligned}$$


- Unconstrained solution $\dot{\mathbf{U}}_i^*[k] = -H_i^{-1} \mathbf{f}_i[k]$
- Deprived if constraints are active $\rightarrow \bar{\Gamma}_i \dot{\mathbf{U}}_i^*[k] > \boldsymbol{\theta}_i[k], \forall k$
 - Solution projected onto boundaries (equality constraints)



What are deprived systems?

$$\begin{aligned} & \underset{\mathbf{U}_i[k]}{\text{minimize}} && \frac{1}{2} \|\mathbf{U}_i[k]\|_{H_i}^2 + \mathbf{f}_i[k]^T \mathbf{U}_i[k] \\ & \text{subject to} && \bar{\Gamma}_i \mathbf{U}_i[k] \leq \boldsymbol{\theta}_i[k] : \boldsymbol{\lambda}_i[k] \end{aligned}$$

- Unconstrained solution $\dot{\mathbf{U}}_i^*[k] = -H_i^{-1} \mathbf{f}_i[k]$
- Deprived if constraints are active $\rightarrow \bar{\Gamma}_i \dot{\mathbf{U}}_i^*[k] > \boldsymbol{\theta}_i[k], \forall k$
 - Solution projected onto boundaries (equality constraints)



Deprived Systems

But why?

- No Scarcity \rightarrow All constraints satisfied $\rightarrow \lambda_i = 0 \rightarrow$ No coordination needed
- Scarcity \rightarrow Competition \rightarrow Consensus/Compromise (or cheating 🏰)



Deprived Systems

But why?

- No Scarcity \rightarrow All constraints satisfied $\rightarrow \lambda_i = 0 \rightarrow$ No coordination needed
- Scarcity \rightarrow Competition \rightarrow Consensus/Compromise (or cheating 🏰)



Deprived Systems

But why?

- No Scarcity \rightarrow All constraints satisfied $\rightarrow \lambda_i = 0 \rightarrow$ No coordination needed
- Scarcity \rightarrow Competition \rightarrow Consensus/Compromise (or cheating 🏰)



Deprived Systems

But why?

- No Scarcity \rightarrow All constraints satisfied $\rightarrow \lambda_i = 0 \rightarrow$ No coordination needed
- Scarcity \rightarrow Competition \rightarrow Consensus/Compromise (or cheating 🏰)



Deprived Systems

But why?

- No Scarcity \rightarrow All constraints satisfied $\rightarrow \lambda_i = 0 \rightarrow$ No coordination needed
- Scarcity \rightarrow Competition \rightarrow Consensus/Compromise (or cheating 🏰)



Deprived Systems

But why?

- No Scarcity \rightarrow All constraints satisfied $\rightarrow \lambda_i = 0 \rightarrow$ No coordination needed
- Scarcity \rightarrow Competition \rightarrow Consensus/Compromise (or cheating 🤖)



Deprived Systems

But why?

- No Scarcity \rightarrow All constraints satisfied $\rightarrow \lambda_i = 0 \rightarrow$ No coordination needed
- Scarcity \rightarrow Competition \rightarrow Consensus/Compromise (or cheating 🤖)



Deprived Systems

But why?

- No Scarcity \rightarrow All constraints satisfied $\rightarrow \lambda_i = 0 \rightarrow$ No coordination needed
- Scarcity \rightarrow Competition \rightarrow Consensus/Compromise (or cheating 🧑🏻)



Deprived Systems

Analysis

- We can transform inequality constraints into equality ones²
- Solution is analytical and trivial.
 - If we solve for λ_i

$$\begin{aligned} & \underset{\mathbf{U}_i[k]}{\text{minimize}} && \frac{1}{2} \|\mathbf{U}_i[k]\|_{H_i}^2 + \mathbf{f}_i[k]^T \mathbf{U}_i[k] \\ & \text{subject to} && \bar{\Gamma}_i \mathbf{U}_i[k] \geq \boldsymbol{\theta}_i[k] : \boldsymbol{\lambda}_i[k] \end{aligned}$$

$$\boldsymbol{\lambda}_i[k] = -P_i \boldsymbol{\theta}_i[k] - \mathbf{s}_i[k],$$

$$\text{where } P_i = (\bar{\Gamma}_i H_i^{-1} \bar{\Gamma}_i^T)^{-1} \text{ and } \mathbf{s}_i[k] = P_i \bar{\Gamma}_i H_i^{-1} \mathbf{f}_i[k].$$

²Under some conditions

Deprived Systems

Analysis

- We can transform inequality constraints into equality ones²
- Solution is analytical and trivial.
 - If we solve for λ_i

$$\begin{aligned} & \underset{\mathbf{U}_i[k]}{\text{minimize}} && \frac{1}{2} \|\mathbf{U}_i[k]\|_{H_i}^2 + \mathbf{f}_i[k]^T \mathbf{U}_i[k] \\ & \text{subject to} && \bar{\Gamma}_i \mathbf{U}_i[k] = \boldsymbol{\theta}_i[k] : \boldsymbol{\lambda}_i[k] \end{aligned}$$

$$\boldsymbol{\lambda}_i[k] = -P_i \boldsymbol{\theta}_i[k] - \mathbf{s}_i[k],$$

$$\text{where } P_i = (\bar{\Gamma}_i H_i^{-1} \bar{\Gamma}_i^T)^{-1} \text{ and } \mathbf{s}_i[k] = P_i \bar{\Gamma}_i H_i^{-1} \mathbf{f}_i[k].$$

²Under some conditions [▶ see here](#)

Deprived Systems

Analysis

- We can transform inequality constraints into equality ones²
- Solution is analytical and trivial.
 - If we solve for λ_i

$$\begin{aligned} & \underset{\mathbf{U}_i[k]}{\text{minimize}} && \frac{1}{2} \|\mathbf{U}_i[k]\|_{H_i}^2 + \mathbf{f}_i[k]^T \mathbf{U}_i[k] \\ & \text{subject to} && \bar{\Gamma}_i \mathbf{U}_i[k] = \boldsymbol{\theta}_i[k] : \boldsymbol{\lambda}_i[k] \end{aligned}$$

$$\boldsymbol{\lambda}_i[k] = -P_i \boldsymbol{\theta}_i[k] - \mathbf{s}_i[k],$$

$$\text{where } P_i = (\bar{\Gamma}_i H_i^{-1} \bar{\Gamma}_i^T)^{-1} \text{ and } \mathbf{s}_i[k] = P_i \bar{\Gamma}_i H_i^{-1} \mathbf{f}_i[k].$$

²Under some conditions [▶ see here](#)

Deprived Systems

Analysis

- We can transform inequality constraints into equality ones²
- Solution is analytical and trivial.
 - If we solve for λ_i

$$\begin{aligned} & \underset{\mathbf{U}_i[k]}{\text{minimize}} && \frac{1}{2} \|\mathbf{U}_i[k]\|_{H_i}^2 + \mathbf{f}_i[k]^T \mathbf{U}_i[k] \\ & \text{subject to} && \bar{\Gamma}_i \mathbf{U}_i[k] = \boldsymbol{\theta}_i[k] : \boldsymbol{\lambda}_i[k] \end{aligned}$$

$$\boldsymbol{\lambda}_i[k] = -P_i \boldsymbol{\theta}_i[k] - \mathbf{s}_i[k],$$

$$\text{where } P_i = (\bar{\Gamma}_i H_i^{-1} \bar{\Gamma}_i^T)^{-1} \text{ and } \mathbf{s}_i[k] = P_i \bar{\Gamma}_i H_i^{-1} \mathbf{f}_i[k].$$

²Under some conditions [▶ see here](#)

Deprived Systems

Analysis

- We can transform inequality constraints into equality ones²
- Solution is analytical and trivial.
 - If we solve for λ_i

$$\begin{aligned} & \underset{\mathbf{U}_i[k]}{\text{minimize}} && \frac{1}{2} \|\mathbf{U}_i[k]\|_{H_i}^2 + \mathbf{f}_i[k]^T \mathbf{U}_i[k] \\ & \text{subject to} && \bar{\Gamma}_i \mathbf{U}_i[k] = \boldsymbol{\theta}_i[k] : \boldsymbol{\lambda}_i[k] \end{aligned}$$

$$\boldsymbol{\lambda}_i[k] = -P_i \boldsymbol{\theta}_i[k] - \mathbf{s}_i[k],$$

$$\text{where } P_i = (\bar{\Gamma}_i H_i^{-1} \bar{\Gamma}_i^T)^{-1} \text{ and } \mathbf{s}_i[k] = P_i \bar{\Gamma}_i H_i^{-1} \mathbf{f}_i[k].$$

²Under some conditions [▶ see here](#)

Deprived Systems

Analysis

- We can transform inequality constraints into equality ones²
- Solution is analytical and trivial.
 - If we solve for λ_i

$$\begin{aligned} & \underset{\mathbf{U}_i[k]}{\text{minimize}} && \frac{1}{2} \|\mathbf{U}_i[k]\|_{H_i}^2 + \mathbf{f}_i[k]^T \mathbf{U}_i[k] \\ & \text{subject to} && \bar{\Gamma}_i \mathbf{U}_i[k] = \boldsymbol{\theta}_i[k] : \boldsymbol{\lambda}_i[k] \end{aligned}$$

$$\boldsymbol{\lambda}_i[k] = -P_i \boldsymbol{\theta}_i[k] - \mathbf{s}_i[k],$$

$$\text{where } P_i = (\bar{\Gamma}_i H_i^{-1} \bar{\Gamma}_i^T)^{-1} \text{ and } \mathbf{s}_i[k] = P_i \bar{\Gamma}_i H_i^{-1} \mathbf{f}_i[k].$$

²Under some conditions [▶ see here](#)

Deprived Systems

Analysis

- We can transform inequality constraints into equality ones²
- Solution is analytical and trivial.
 - If we solve for λ_i

$$\begin{aligned} & \underset{\mathbf{U}_i[k]}{\text{minimize}} && \frac{1}{2} \|\mathbf{U}_i[k]\|_{H_i}^2 + \mathbf{f}_i[k]^T \mathbf{U}_i[k] \\ & \text{subject to} && \bar{\Gamma}_i \mathbf{U}_i[k] = \boldsymbol{\theta}_i[k] : \boldsymbol{\lambda}_i[k] \end{aligned}$$

$$\boldsymbol{\lambda}_i[k] = -P_i \boldsymbol{\theta}_i[k] - \mathbf{s}_i[k],$$

$$\text{where } P_i = (\bar{\Gamma}_i H_i^{-1} \bar{\Gamma}_i^T)^{-1} \text{ and } \mathbf{s}_i[k] = P_i \bar{\Gamma}_i H_i^{-1} \mathbf{f}_i[k].$$

²Under some conditions [▶ see here](#)

Deprived Systems

Analysis

- We can transform inequality constraints into equality ones²
- Solution is analytical and trivial.
 - If we solve for λ_i

$$\begin{aligned} & \underset{\mathbf{U}_i[k]}{\text{minimize}} && \frac{1}{2} \|\mathbf{U}_i[k]\|_{H_i}^2 + \mathbf{f}_i[k]^T \mathbf{U}_i[k] \\ & \text{subject to} && \bar{\Gamma}_i \mathbf{U}_i[k] = \boldsymbol{\theta}_i[k] : \boldsymbol{\lambda}_i[k] \end{aligned}$$

$$\boldsymbol{\lambda}_i[k] = -P_i \boldsymbol{\theta}_i[k] - \mathbf{s}_i[k],$$

$$\text{where } P_i = (\bar{\Gamma}_i H_i^{-1} \bar{\Gamma}_i^T)^{-1} \text{ and } \mathbf{s}_i[k] = P_i \bar{\Gamma}_i H_i^{-1} \mathbf{f}_i[k].$$

²Under some conditions [▶ see here](#)

Deprived Systems

Analysis (Continued)

$$\mathcal{S} = \{\boldsymbol{\theta}[k] \mid I_c^M \boldsymbol{\theta}[k] \leq \mathbf{U}_{\max}\}$$

$$\boldsymbol{\theta}[k]^{(p+1)} = \text{Proj}^{\mathcal{S}}(\boldsymbol{\theta}[k]^{(p)} + \rho^{(p)} \boldsymbol{\lambda}[k]^{(p)})$$



Deprived Systems


Analysis (Continued)

$$\mathcal{S} = \{\boldsymbol{\theta}[k] \mid I_c^M \boldsymbol{\theta}[k] = \mathbf{U}_{\max}\}$$

$$\boldsymbol{\theta}_i^{(p+1)} = \boldsymbol{\theta}_i^{(p)} + \rho^{(p)} \left(\boldsymbol{\lambda}_i^{(p)} - \frac{1}{M} \sum_{j=1}^M \boldsymbol{\lambda}_j^{(p)} \right), \forall i \in \mathcal{M}$$

Deprived Systems

Analysis (Continued)

$$\mathcal{S} = \{\boldsymbol{\theta}[k] \mid I_c^M \boldsymbol{\theta}[k] = \mathbf{U}_{\max}\}$$
$$\boldsymbol{\theta}_i^{(p+1)} = \boldsymbol{\theta}_i^{(p)} + \rho^{(p)} \left(\lambda_i^{(p)} - \frac{1}{M} \sum_{j=1}^M \lambda_j^{(p)} \right), \forall i \in \mathcal{M}$$


Deprived Systems

Analysis (Continued)

$$\begin{aligned}
 \mathcal{S} &= \{\boldsymbol{\theta}[k] \mid I_c^M \boldsymbol{\theta}[k] = \mathbf{U}_{\max}\} \\
 \boldsymbol{\theta}_i^{(p+1)} &= \boldsymbol{\theta}_i^{(p)} + \rho^{(p)} \left(\boldsymbol{\lambda}_i^{(p)} - \frac{1}{M} \sum_{j=1}^M \boldsymbol{\lambda}_j^{(p)} \right), \forall i \in \mathcal{M} \\
 \boldsymbol{\lambda}_i[k] &= -P_i \boldsymbol{\theta}_i[k] - \mathbf{s}_i[k]
 \end{aligned}$$

Deprived Systems

Analysis (Continued)

$$\lambda_i[k] = -P_i \theta_i[k] - s_i[k]$$

$$\mathcal{S} = \{\theta[k] \mid I_c^M \theta[k] = \mathbf{U}_{\max}\}$$

$$\theta_i^{(p+1)} = \theta_i^{(p)} + \rho^{(p)} \left(\lambda_i^{(p)} - \frac{1}{M} \sum_{j=1}^M \lambda_j^{(p)} \right), \forall i \in \mathcal{M}$$

$$\theta^{(p+1)} = \mathcal{A}_\theta \theta^{(p)} + \mathcal{B}_\theta[k] \quad \text{▶ see here}$$



Deprived Systems

Under attack!

- Normal behavior

$$\lambda_i[k] = -P_i \theta_i[k] - s_i[k],$$

- Under attack

$$\tilde{\lambda}_i = T_i[k] \lambda_i = -T_i P_i \theta_i[k] - T_i s_i[k]$$

$$\tilde{\lambda}_i = -\tilde{P}_i[k] \theta_i[k] - \tilde{s}_i[k]$$



Deprived Systems

Under attack!

- Normal behavior

$$\lambda_i[k] = -P_i \theta_i[k] - s_i[k],$$

- Under attack

$$\tilde{\lambda}_i = T_i[k] \lambda_i = -T_i P_i \theta_i[k] - T_i s_i[k]$$

$$\tilde{\lambda}_i = -\tilde{P}_i[k] \theta_i[k] - \tilde{s}_i[k]$$



Deprived Systems

Under attack!

- Normal behavior

$$\lambda_i[k] = -P_i \theta_i[k] - s_i[k],$$

- Under attack

$$\tilde{\lambda}_i = T_i[k] \lambda_i = -T_i P_i \theta_i[k] - T_i s_i[k]$$

$$\tilde{\lambda}_i = -\tilde{P}_i[k] \theta_i[k] - \tilde{s}_i[k]$$



Deprived Systems

Under attack!

- Normal behavior

$$\lambda_i[k] = -P_i \theta_i[k] - s_i[k],$$

- Under attack

$$\tilde{\lambda}_i = T_i[k] \lambda_i = -T_i P_i \theta_i[k] - T_i s_i[k]$$

$$\tilde{\lambda}_i = -\tilde{P}_i[k] \theta_i[k] - \tilde{s}_i[k]$$



Deprived Systems

Under attack!

- Normal behavior

$$\lambda_i[k] = -P_i \theta_i[k] - s_i[k],$$

- Under attack

$$\tilde{\lambda}_i = T_i[k] \lambda_i = -T_i P_i \theta_i[k] - T_i s_i[k]$$

$$\tilde{\lambda}_i = -\tilde{P}_i[k] \theta_i[k] - \tilde{s}_i[k]$$

$$\theta^{(p+1)} = \tilde{\mathcal{A}}_\theta[k] \theta^{(p)} + \tilde{\mathcal{B}}_\theta[k]$$



Deprived Systems

Under attack!

- Normal behavior

$$\lambda_i[k] = -P_i \theta_i[k] - s_i[k],$$

- Under attack

$$\tilde{\lambda}_i = T_i[k] \lambda_i = -T_i P_i \theta_i[k] - T_i s_i[k]$$

$$\tilde{\lambda}_i = -\tilde{P}_i[k] \theta_i[k] - \tilde{s}_i[k]$$

$$\theta^{(p+1)} = \tilde{\mathcal{A}}_\theta[k] \theta^{(p)} + \tilde{\mathcal{B}}_\theta[k]$$



Detection Mechanism

Assumption

We know nominal \bar{P}_i

Assumption

*Attacker chooses $\tilde{\lambda}_i = \gamma_i(\lambda_i) = T_i(k)\lambda_i$
 $-T_i(k)P_i\theta_i - T_i(k)s_i(k) \rightarrow -\tilde{P}_i\theta_i - \tilde{s}_i(k)$*

- We can estimate¹ \hat{P}_i and $\hat{\tilde{s}}_i(k)$ such as:

$$\tilde{\lambda}_i = \gamma_i(\lambda_i(\theta_i)) = -\hat{\tilde{P}}_i(k)\theta_i - \hat{\tilde{s}}_i(k)$$

- If $\hat{\tilde{P}}_i(k) \neq \bar{P}_i \rightarrow \text{Attack}$

¹Using Recursive Least Squares

Detection Mechanism

Assumption

We know nominal \bar{P}_i

Assumption

Attacker chooses $\tilde{\lambda}_i = \gamma_i(\lambda_i) = T_i(k)\lambda_i$
 $-T_i(k)P_i\theta_i - T_i(k)s_i(k) \rightarrow -\tilde{P}_i\theta_i - \tilde{s}_i(k)$

- We can estimate¹ \hat{P}_i and $\hat{\tilde{s}}_i(k)$ such as:

$$\tilde{\lambda}_i = \gamma_i(\lambda_i(\theta_i)) = -\hat{\tilde{P}}_i(k)\theta_i - \hat{\tilde{s}}_i(k)$$

- If $\hat{\tilde{P}}_i(k) \neq \bar{P}_i \rightarrow \text{Attack}$

¹Using Recursive Least Squares

Detection Mechanism

Assumption

We know nominal \bar{P}_i

Assumption

*Attacker chooses $\tilde{\lambda}_i = \gamma_i(\lambda_i) = T_i(k)\lambda_i$
 $-T_i(k)P_i\theta_i - T_i(k)s_i(k) \rightarrow -\tilde{P}_i\theta_i - \tilde{s}_i(k)$*

- We can estimate¹ \hat{P}_i and $\hat{\tilde{s}}_i(k)$ such as:

$$\tilde{\lambda}_i = \gamma_i(\lambda_i(\theta_i)) = -\hat{\tilde{P}}_i(k)\theta_i - \hat{\tilde{s}}_i(k)$$

- If $\hat{\tilde{P}}_i(k) \neq \bar{P}_i \rightarrow \text{Attack}$

¹Using Recursive Least Squares

Detection Mechanism

Assumption

We know nominal \bar{P}_i

Assumption

*Attacker chooses $\tilde{\lambda}_i = \gamma_i(\lambda_i) = T_i(k)\lambda_i$
 $-T_i(k)P_i\theta_i - T_i(k)s_i(k) \rightarrow -\tilde{P}_i\theta_i - \tilde{s}_i(k)$*

- We can estimate¹ \hat{P}_i and $\hat{\tilde{s}}_i(k)$ such as:

$$\tilde{\lambda}_i = \gamma_i(\lambda_i(\theta_i)) = -\hat{\tilde{P}}_i(k)\theta_i - \hat{\tilde{s}}_i(k)$$

- If $\hat{\tilde{P}}_i(k) \neq \bar{P}_i \rightarrow \text{Attack}$

¹Using Recursive Least Squares

Detection Mechanism

Assumption

We know nominal \bar{P}_i

Assumption

*Attacker chooses $\tilde{\lambda}_i = \gamma_i(\lambda_i) = T_i(k)\lambda_i$
 $-T_i(k)P_i\theta_i - T_i(k)s_i(k) \rightarrow -\tilde{P}_i\theta_i - \tilde{s}_i(k)$*

- We can estimate¹ \hat{P}_i and $\hat{\tilde{s}}_i(k)$ such as:

$$\tilde{\lambda}_i = \gamma_i(\lambda_i(\theta_i)) = -\hat{\tilde{P}}_i(k)\theta_i - \hat{\tilde{s}}_i(k)$$

- If $\hat{\tilde{P}}_i(k) \neq \bar{P}_i \rightarrow \text{Attack}$

¹Using Recursive Least Squares

Detection

In detail

- Error $E_i(k) = \|\hat{\tilde{P}}_i(k) - \bar{P}_i\|_F$
- Create threshold ϵ_P
- Indicator $d_i \in \{0, 1\}$ detects the attack in agent i .
- $d_i = 1$ if $E_i(k) > \epsilon_P$, 0 otherwise



Detection

In detail

- Error $E_i(k) = \|\hat{\bar{P}}_i(k) - \bar{P}_i\|_F$
- Create threshold ϵ_P
- Indicator $d_i \in \{0, 1\}$ detects the attack in agent i .
- $d_i = 1$ if $E_i(k) > \epsilon_P$, 0 otherwise



Detection

In detail

- Error $E_i(k) = \|\hat{\bar{P}}_i(k) - \bar{P}_i\|_F$
- Create threshold ϵ_P
- Indicator $d_i \in \{0, 1\}$ detects the attack in agent i .
- $d_i = 1$ if $E_i(k) > \epsilon_P$, 0 otherwise



Detection

In detail

- Error $E_i(k) = \|\hat{\bar{P}}_i(k) - \bar{P}_i\|_F$
- Create threshold ϵ_P
- Indicator $d_i \in \{0, 1\}$ detects the attack in agent i .
- $d_i = 1$ if $E_i(k) > \epsilon_P$, 0 otherwise



Detection

In detail

- Error $E_i(k) = \|\hat{\bar{P}}_i(k) - \bar{P}_i\|_F$
- Create threshold ϵ_P
- Indicator $d_i \in \{0, 1\}$ detects the attack in agent i .
- $d_i = 1$ if $E_i(k) > \epsilon_P$, 0 otherwise



Estimating $\hat{\tilde{P}}_i[k]$

- We estimate \hat{P}_i and $\hat{\tilde{s}}_i(k)$ simultaneously using Recursive Least Squares
- Problem: Estimation during negotiation fails
 - Consecutive λ_i^p and θ_i^p are linearly dependent \rightarrow low input excitation
- Solution: Send sequence of random values of θ_i until estimates converge



Estimating $\hat{\tilde{P}}_i[k]$

- We estimate \hat{P}_i and $\hat{\tilde{s}}_i(k)$ simultaneously using Recursive Least Squares
- Problem: Estimation during negotiation fails
 - Consecutive λ_i^p and θ_i^p are linearly dependent \rightarrow low input excitation
- Solution: Send sequence of random values of θ_i until estimates converge

Estimating $\hat{\tilde{P}}_i[k]$

- We estimate \hat{P}_i and $\hat{\tilde{s}}_i(k)$ simultaneously using Recursive Least Squares
- Problem: Estimation during negotiation fails
 - Consecutive λ_i^p and θ_i^p are linearly dependent \rightarrow low input excitation
- Solution: Send sequence of random values of θ_i until estimates converge



Estimating $\hat{\tilde{P}}_i[k]$

- We estimate \hat{P}_i and $\hat{\tilde{s}}_i(k)$ simultaneously using Recursive Least Squares
- Problem: Estimation during negotiation fails
 - Consecutive λ_i^p and θ_i^p are linearly dependent \rightarrow low input excitation
- Solution: Send sequence of random values of θ_i until estimates converge



Mitigation mechanism

- Main idea: Reconstruct λ_i and use in negotiation

Assumption

We suppose $\tilde{\lambda}_i = 0$ only if $\lambda_i = 0$, which implies $T_i(k)$ invertible.

- Estimate the inverse of $T_i(k)$

$$\widehat{T_i(k)^{-1}} = \bar{P}_i \widehat{\tilde{P}_i(k)^{-1}}$$

- Reconstruct λ_i

$$\lambda_{i\text{rec}} = \widehat{T_i(k)^{-1}} \tilde{\lambda}_i = -\bar{P}_i \theta_i - \widehat{T_i(k)^{-1}} \hat{\tilde{s}}_i(k)$$



Mitigation mechanism

- Main idea: Reconstruct λ_i and use in negotiation

Assumption

We suppose $\tilde{\lambda}_i = \mathbf{0}$ only if $\lambda_i = \mathbf{0}$, which implies $T_i(k)$ invertible.

- Estimate the inverse of $T_i(k)$

$$\widehat{T_i(k)^{-1}} = \bar{P}_i \widehat{\tilde{P}_i(k)^{-1}}$$

- Reconstruct λ_i

$$\lambda_{i\text{rec}} = \widehat{T_i(k)^{-1}} \tilde{\lambda}_i = -\bar{P}_i \theta_i - \widehat{T_i(k)^{-1}} \hat{\tilde{s}}_i(k)$$



Mitigation mechanism

- Main idea: Reconstruct λ_i and use in negotiation

Assumption

We suppose $\tilde{\lambda}_i = \mathbf{0}$ only if $\lambda_i = \mathbf{0}$, which implies $T_i(k)$ invertible.

- Estimate the inverse of $T_i(k)$

$$\widehat{T_i(k)^{-1}} = \bar{P}_i \widehat{\tilde{P}_i(k)^{-1}}$$

- Reconstruct λ_i

$$\lambda_{i\text{rec}} = \widehat{T_i(k)^{-1}} \tilde{\lambda}_i = -\bar{P}_i \theta_i - \widehat{T_i(k)^{-1}} \hat{s}_i(k)$$



Mitigation mechanism

- Main idea: Reconstruct λ_i and use in negotiation

Assumption

We suppose $\tilde{\lambda}_i = 0$ only if $\lambda_i = 0$, which implies $T_i(k)$ invertible.

- Estimate the inverse of $T_i(k)$


$$\widehat{T_i(k)^{-1}} = \bar{P}_i \widehat{\tilde{P}_i(k)^{-1}}$$

- Reconstruct λ_i

$$\lambda_{i\text{rec}} = \widehat{T_i(k)^{-1}} \tilde{\lambda}_i = -\bar{P}_i \theta_i - \widehat{T_i(k)^{-1}} \hat{\tilde{s}}_i(k)$$




Complete Mechanism



Two phases:

- ① Detect which agents are non-cooperative
- ② Reconstruct λ_i and use in negotiation


Complete Mechanism



Two phases:

- 1 Detect which agents are non-cooperative
- 2 Reconstruct λ_i and use in negotiation


Complete Mechanism



Two phases:

- 1 Detect which agents are non-cooperative
- 2 Reconstruct λ_i and use in negotiation

Complete Mechanism




Two phases:

- 1 Detect which agents are non-cooperative
- 2 Reconstruct λ_i and use in negotiation


Complete algorithm

RPdMPC-DS




Complete algorithm

RPdMPC-DS




Complete algorithm

RPdMPC-DS




Complete algorithm

RPdMPC-DS




Complete algorithm

RPdMPC-DS




Complete algorithm

RPdMPC-DS




Complete algorithm

RPdMPC-DS




Complete algorithm

RPdMPC-DS




Complete algorithm

RPdMPC-DS




Complete algorithm

RPdMPC-DS




Complete algorithm

RPdMPC-DS




Complete algorithm

RPdMPC-DS




Complete algorithm

RPdMPC-DS



Complete algorithm

RPdMPC-DS



Example

District Heating of 4 Distinct Houses Under Power Scarcity

- 4 distinct rooms modeled using 3R-2C
- Initial temperature under 20°C
- Not enough power to achieve setpoint $\left(\sum_{i=1}^4 u_i(k) \leq 4\text{kW}\right)$
- Simulated for a period of 5h
- ZOH $T_s = 0.25\text{h}$
- 3 scenarios
 - ① Nominal
 - ② Agent I non cooperative from $k>6$ with $T=4^{\circ}\text{C}$
 - ③ Similar but with secure algorithm

Example

District Heating of 4 Distinct Houses Under Power Scarcity

- 4 distinct rooms modeled using 3R-2C
- Initial temperature under 20°C
- Not enough power to achieve setpoint $\left(\sum_{i=1}^4 u_i(k) \leq 4\text{kW}\right)$
- Simulated for a period of 5h
- ZOH $T_s = 0.25\text{h}$
- 3 scenarios
 - ① Nominal
 - ② Agent 1 non cooperative from $k>6$ with $T=4^{\circ}\text{C}$
 - ③ Similar but with secure algorithm

Example

District Heating of 4 Distinct Houses Under Power Scarcity

- 4 distinct rooms modeled using 3R-2C
- Initial temperature under 20°C
- Not enough power to achieve setpoint $\left(\sum_{i=1}^4 u_i(k) \leq 4\text{kW}\right)$
- Simulated for a period of 5h
- ZOH $T_s = 0.25\text{h}$
- 3 scenarios
 - ① Nominal
 - ② Agent I non cooperative from $k>6$ with $T=4^{\circ}\text{C}$
 - ③ Similar but with secure algorithm



Example

District Heating of 4 Distinct Houses Under Power Scarcity

- 4 distinct rooms modeled using 3R-2C
- Initial temperature under 20°C
- Not enough power to achieve setpoint $\left(\sum_{i=1}^4 u_i(k) \leq 4\text{kW}\right)$
- Simulated for a period of 5h
- ZOH $T_s = 0.25\text{h}$
- 3 scenarios
 - ① Nominal
 - ② Agent 1 non cooperative from $k>6$ with $T=4^{\circ}\text{C}$
 - ③ Similar but with secure algorithm



Example

District Heating of 4 Distinct Houses Under Power Scarcity

- 4 distinct rooms modeled using 3R-2C
- Initial temperature under 20°C
- Not enough power to achieve setpoint $\left(\sum_{i=1}^4 u_i(k) \leq 4\text{kW}\right)$
- Simulated for a period of 5h
- ZOH $T_s = 0.25\text{h}$
- 3 scenarios
 - ① Nominal
 - ② Agent 1 non cooperative from $k>6$ with $T=4^{\circ}\text{C}$
 - ③ Similar but with secure algorithm



Example

District Heating of 4 Distinct Houses Under Power Scarcity

- 4 distinct rooms modeled using 3R-2C
- Initial temperature under 20°C
- Not enough power to achieve setpoint $\left(\sum_{i=1}^4 u_i(k) \leq 4\text{kW}\right)$
- Simulated for a period of 5h
- ZOH $T_s = 0.25\text{h}$
- 3 scenarios
 - ① Nominal
 - ② Agent I non cooperative from $k>6$ with $T=4^{\circ}\text{C}$
 - ③ Similar but with secure algorithm

Example

District Heating of 4 Distinct Houses Under Power Scarcity

- 4 distinct rooms modeled using 3R-2C
- Initial temperature under 20°C
- Not enough power to achieve setpoint $\left(\sum_{i=1}^4 u_i(k) \leq 4\text{kW}\right)$
- Simulated for a period of 5h
- ZOH $T_s = 0.25\text{h}$
- 3 scenarios
 - ① Nominal
 - ② Agent 1 non cooperative from $k>6$ with $T=4^{\circ}\text{C}$
 - ③ Similar but with secure algorithm



Results

Temporal

- N Nominal
- S Selfish behavior
- C selfish behavior with Correction



Results

Temporal

- N Nominal
- S Selfish behavior
- C selfish behavior with Correction



Results

Table 1: Comparison of costs J_i^N and J_G^N

Agent	Nominal	Selfish	Selfish + correction
I	103	64	104
II	73	91	73
III	100	123	101
IV	132	154	131
Global	408	442	409

Results

Table 1: Comparison of costs J_i^N and J_G^N

Agent	Nominal	Selfish	Selfish + correction
I	103	64	104
II	73	91	73
III	100	123	101
IV	132	154	131
Global	408	442	409

Outline

③ Resilient Primal Decomposition-based dMPC using Artificial Scarcity

- Relaxing some assumptions

- Adapting the algorithm

- Results



Analysing

$$\lambda_i[k] = \begin{cases} -P_i^{(0)} \theta_i[k] - s_i^{(0)}[k], & \text{if } \theta_i[k] \in \mathcal{R}_{\lambda_i}^n \\ \vdots & \vdots \\ -P_i^{(2^{n_{\text{ineq}}}-1)} \theta_i[k] - s_i^{(2^{n_{\text{ineq}}}-1)}[k], & \text{if } \theta_i[k] \in \mathcal{R}_{\lambda_i}^{2^{n_{\text{ineq}}}-1} \end{cases}. \quad (1)$$



Artificial Scarcity




Figure 1: Ball $\mathcal{B}(\theta_i, r)$.




Figure 2: Ball $\mathcal{B}(\theta_i, r)$ traversing zones.

Expectation Maximization




Figure 3: Gaussian Mixture for a 1D PWA function with 2 modes.

Expectation Maximization

Algorithm





Figure 4: Gaussian Mixture for a 1D PWA function with 2 modes.


Complete algorithm

RPdMPC-AS




Complete algorithm

RPdMPC-AS




Complete algorithm

RPdMPC-AS




Complete algorithm

RPdMPC-AS




Complete algorithm

RPdMPC-AS




Complete algorithm

RPdMPC-AS




Complete algorithm

RPdMPC-AS




Complete algorithm

RPdMPC-AS




Complete algorithm

RPdMPC-AS




Complete algorithm

RPdMPC-AS




Complete algorithm

RPdMPC-AS




Complete algorithm

RPdMPC-AS




Complete algorithm

RPdMPC-AS



Complete algorithm

RPdMPC-AS



Thank you!

Repository

<https://github.com/Accacio/thesis>



Contact

rafael.accacio.nogueira@gmail.com



For Further Reading I



José M Maestre, Rudy R Negenborn, et al. *Distributed Model Predictive Control made easy*. Vol. 69. Springer, 2014. ISBN: 978-94-007-7005-8.



Wicak Ananduta et al. “Resilient Distributed Model Predictive Control for Energy Management of Interconnected Microgrids”. In: *Optimal Control Applications and Methods* 41.1 (2020), pp. 146–169. DOI: 10.1002/oca.2534. URL: <https://onlinelibrary.wiley.com/doi/pdf/10.1002/oca.2534>.



José M. Maestre et al. “Scenario-Based Defense Mechanism Against Vulnerabilities in Lagrange-Based Dmpc”. In: *Control Eng Pract* 114 (2021), p. 104879. ISSN: 0967-0661. DOI: 10.1016/j.conengprac.2021.104879.



For Further Reading II



Pablo Velarde et al. “Vulnerabilities in Lagrange-Based Distributed Model Predictive Control”. In: *Optimal Control Applications and Methods* 39.2 (Sept. 2018), pp. 601–621. DOI: [10.1002/oca.2368](https://doi.org/10.1002/oca.2368).



Wicak Ananduta et al. “Resilient Distributed Energy Management for Systems of Interconnected Microgrids”. In: *2018 IEEE Conference on Decision and Control (CDC)*. 2018, pp. 3159–3164. DOI: [10.1109/CDC.2018.8619548](https://doi.org/10.1109/CDC.2018.8619548).



Wicak Ananduta et al. “A Resilient Approach for Distributed MPC-Based Economic Dispatch in Interconnected Microgrids”. In: *2019 18th European Control Conference (ECC)*. 2019, pp. 691–696. DOI: [10.23919/ECC.2019.8796208](https://doi.org/10.23919/ECC.2019.8796208).



For Further Reading III



P. Chanfreut, J. M. Maestre, and H. Ishii. “Vulnerabilities in Distributed Model Predictive Control based on Jacobi-Gauss Decomposition”. In: *2018 European Control Conference (ECC)*. June 2018, pp. 2587–2592. DOI: [10.23919/ECC.2018.8550239](https://doi.org/10.23919/ECC.2018.8550239).



Pablo Velarde et al. “Scenario-based defense mechanism for distributed model predictive control”. In: *2017 IEEE 56th Annual Conference on Decision and Control (CDC)*. IEEE. Dec. 2017, pp. 6171–6176. DOI: [10.1109/CDC.2017.8264590](https://doi.org/10.1109/CDC.2017.8264590).



Pablo Velarde et al. “Vulnerabilities in Lagrange-Based DMPC in the Context of Cyber-Security”. In: *2017 IEEE International Conference on Autonomic Computing (ICAC)*. July 2017, pp. 215–220. DOI: [10.1109/ICAC.2017.53](https://doi.org/10.1109/ICAC.2017.53).



One way to ensure this, is to make the original constraint (??) to have at most as many rows as columns, i.e., $\# \mathbf{u}_{\max} \leq n_u$, although it may be a little restrictive.

$$\theta^{(p+1)} = \mathcal{A}_\theta \theta^{(p)} + \mathcal{B}_\theta[k]$$

where

$$\mathcal{A}_\theta = \begin{bmatrix} I - \frac{M-1}{M} \rho^{(p)} P_1 & \frac{1}{M} \rho^{(p)} P_2 & \dots & \frac{1}{M} \rho^{(p)} P_M \\ \frac{1}{M} \rho^{(p)} P_1 & I - \frac{M-1}{M} \rho^{(p)} P_2 & \dots & \frac{1}{M} \rho^{(p)} P_M \\ \vdots & \vdots & \ddots & \vdots \\ \frac{1}{M} \rho^{(p)} P_1 & \frac{1}{M} \rho^{(p)} P_2 & \dots & I - \frac{M-1}{M} \rho^{(p)} P_M \end{bmatrix}$$
$$\mathcal{B}_\theta[k] = \begin{bmatrix} -\frac{M-1}{M} \rho^{(p)} \mathbf{s}_1[k] + \frac{1}{M} \rho^{(p)} \mathbf{s}_2[k] \dots - \frac{1}{M} \rho^{(p)} \mathbf{s}_M[k] \\ \frac{1}{M} \rho^{(p)} \mathbf{s}_1[k] - \frac{M-1}{M} \rho^{(p)} \mathbf{s}_2[k] \dots - \frac{1}{M} \rho^{(p)} \mathbf{s}_M[k] \\ \vdots \\ \frac{1}{M} \rho^{(p)} \mathbf{s}_1[k] + \frac{1}{M} \rho^{(p)} \mathbf{s}_2[k] \dots - \frac{M-1}{M} \rho^{(p)} \mathbf{s}_M[k] \end{bmatrix}$$