

OSPS TELECOM SERVICES PVT. LTD. (AN ISO 9001 : 2008 Company) F-1, 4th Floor, Hyderabad Business Centre, Hyderguda, Hyderabad - 500 029 Tel : 040-66832324, 23296123, Fax 040-66832325.

-		***	-	
D	Δ	ш	E	٠

JOINT MEASUREMENT SHEET BSNL / GBT/RTT

R/RL- 2794325 INDUS ID: 1054281 SITE NAME: Wankhade Nagar

Description of Material fabrication, installation and painting of GSM / MW / RRU antenna mount poles gth and 88 mm dia including brackets as per drawings and specifications. additional Anteena Mount (fixture) [New adjustable GI fixture 1'-5.5" length & including bracket, Nutbolts as per drawing as specifications] for 3G Sites in 3G Bracket ibrication, galvanizing, painting and installation of 450 mm wide external cable respecifications. In 1 mtr. X 1 mtr., RCC / PCC / Fabricate illier/ Cabinet / PIU / BTS foundation RTT site (1.5 Mtr. X 1.5 Mtr.) PCC ital illier Cabinet / PIU / BTS foundation GBT site pe 40mm Reinforced 1" flecxible pipe ing strip down conductors with GI strip of 25X3 mm including insulators at 2 ft fixing of 1 nos. copper strip of size 300 x75 x 3 mm on epoxy insulators to be ital / EGB. 10 nos. of holes to be made on each plates and SS nuts & bolts with spring washers to be supplied. DB inps 1 pole / 13 Amps. 1 Pole / 6 Amps. 1 Pole, 63 Amp. 1 Pole MCB single core multistrand copper cable mm , Single Core copper conductor , unarmoured flexible multistrand power ding providing thimbles (Red)	No Pair Per Site Per/mtr No No No Per/mtr Mtr No No No Per/mtr Per/mtr Per/mtr Per/mtr Per/mtr	01 Nos 04 Nos
fabrication, installation and painting of GSM / MW / RRU antenna mount poles gth and 88 mm dia including brackets as per drawings and specifications. additional Anteena Mount (fixture) [New adjustable GI fixture 1'-5.5" length & including bracket, Nutbolts as per drawing as specifications] for 3G Sites in 3G Bracket abrication, galvanizing, painting and installation of 450 mm wide external cable specifications. In 1 mtr. X 1 mtr., RCC / PCC / Fabricate iller/ Cabinet / PIU / BTS foundation RTT site (1.5 Mtr. X 1.5 Mtr.) PCC all iller Cabinet / PIU / BTS foundation GBT site pe 40mm Reinforced 1" flecxible pipe ng strip down conductors with GI strip of 25X3 mm including insulators at 2 ft fixing of 1 nos. copper strip of size 300 x75 x 3 mm on epoxy insulators to be iB / EGB. 10 nos. of holes to be made on each plates and SS nuts & bolts with spring washers to be supplied. DB pps 1 pole / 13 Amps. 1 Pole / 6 Amps. 1 Pole, 63 Amp. 1 Pole MCB single core multistrand copper cable mm , Single Core copper conductor , unarmoured flexible multistrand power	Pair Per Site Per/mtr No No No Per/mtr Per/mtr Mtr No No No	01 405
including bracket, Nutbolts as per drawing as specifications] for 3G Sites in 3G Bracket ibrication, galvanizing, painting and installation of 450 mm wide external cable is specifications. In 1 mtr. X 1 mtr., RCC / PCC / Fabricate iller/ Cabinet / PIU / BTS foundation RTT site (1.5 Mtr. X 1.5 Mtr.) PCC is all iller Cabinet / PIU / BTS foundation GBT site In 40 mm Reinforced 1" flecxible pipe Ing strip down conductors with GI strip of 25X3 mm including insulators at 2 ft In 5 may a mm on epoxy insulators to be in 6 made on each plates and SS nuts & bolts with spring washers to be supplied. In 5 may 1 pole / 13 Amps. 1 Pole / 6 Amps. 1 Pole, 63 Amp. 1 Pole MCB In 5 single core multistrand copper cable In 5 mm, Single Core copper conductor, unarmoured flexible multistrand power	Per Site Per/mtr No No No Per/mtr Per/mtr Mtr No No No No	
n 3G Bracket brication, galvanizing, painting and installation of 450 mm wide external cable specifications. In 1 mtr. X 1 mtr., RCC / PCC / Fabricate filler/ Cabinet / PIU / BTS foundation RTT site (1.5 Mtr. X 1.5 Mtr.) PCC filler Cabinet / PIU / BTS foundation GBT site filler Cabinet / PIU / BTS foundat	Per/mtr No No No Per/mtr Per/mtr Mtr No No No	
In 1 mtr. X 1 mtr., RCC / PCC / Fabricate iller/ Cabinet / PIU / BTS foundation RTT site (1.5 Mtr. X 1.5 Mtr.) PCC iller Cabinet / PIU / BTS foundation GBT site pe 40mm Reinforced 1" flecxible pipe ng strip down conductors with GI strip of 25X3 mm including insulators at 2 ft fixing of 1 nos. copper strip of size 300 x75 x 3 mm on epoxy insulators to be iB / EGB. 10 nos. of holes to be made on each plates and SS nuts & bolts with spring washers to be supplied. DB ips 1 pole / 13 Amps. 1 Pole / 6 Amps. 1 Pole, 63 Amp. 1 Pole MCB single core multistrand copper cable mm , Single Core copper conductor , unarmoured flexible multistrand power	No No No Per/mtr Per/mtr Mtr No No	
iiller/ Cabinet / PIU / BTS foundation RTT site (1.5 Mtr. X 1.5 Mtr.) PCC sal iiller Cabinet / PIU / BTS foundation GBT site pe 40mm Reinforced 1" flecxible pipe ng strip down conductors with GI strip of 25X3 mm including insulators at 2 ft fixing of 1 nos. copper strip of size 300 x75 x 3 mm on epoxy insulators to be B / EGB. 10 nos. of holes to be made on each plates and SS nuts & bolts with spring washers to be supplied. DB Inps 1 pole / 13 Amps. 1 Pole / 6 Amps. 1 Pole, 63 Amp. 1 Pole MCB single core multistrand copper cable mm , Single Core copper conductor , unarmoured flexible multistrand power	No No Per/mtr Per/mtr Mtr No No	
iiller/ Cabinet / PIU / BTS foundation RTT site (1.5 Mtr. X 1.5 Mtr.) PCC sal iiller Cabinet / PIU / BTS foundation GBT site pe 40mm Reinforced 1" flecxible pipe ng strip down conductors with GI strip of 25X3 mm including insulators at 2 ft fixing of 1 nos. copper strip of size 300 x75 x 3 mm on epoxy insulators to be B / EGB. 10 nos. of holes to be made on each plates and SS nuts & bolts with spring washers to be supplied. DB Inps 1 pole / 13 Amps. 1 Pole / 6 Amps. 1 Pole, 63 Amp. 1 Pole MCB single core multistrand copper cable mm , Single Core copper conductor , unarmoured flexible multistrand power	No Per/mtr Per/mtr Mtr No No	
Reinforced 1" flecxible pipe ng strip down conductors with GI strip of 25X3 mm including insulators at 2 ft fixing of 1 nos. copper strip of size 300 x75 x 3 mm on epoxy insulators to be BB / EGB. 10 nos. of holes to be made on each plates and SS nuts & bolts with spring washers to be supplied. DB nps 1 pole / 13 Amps. 1 Pole / 6 Amps. 1 Pole, 63 Amp. 1 Pole MCB single core multistrand copper cable mm , Single Core copper conductor , unarmoured flexible multistrand power	Per/mtr Per/mtr Mtr No No No	
Reinforced 1" flecxible pipe ng strip down conductors with GI strip of 25X3 mm including insulators at 2 ft fixing of 1 nos. copper strip of size 300 x75 x 3 mm on epoxy insulators to be BB / EGB. 10 nos. of holes to be made on each plates and SS nuts & bolts with spring washers to be supplied. DB nps 1 pole / 13 Amps. 1 Pole / 6 Amps. 1 Pole, 63 Amp. 1 Pole MCB single core multistrand copper cable mm , Single Core copper conductor , unarmoured flexible multistrand power	Per/mtr Mtr No No No	
Reinforced 1" flecxible pipe ng strip down conductors with GI strip of 25X3 mm including insulators at 2 ft fixing of 1 nos. copper strip of size 300 x75 x 3 mm on epoxy insulators to be BB / EGB. 10 nos. of holes to be made on each plates and SS nuts & bolts with spring washers to be supplied. DB ps 1 pole / 13 Amps. 1 Pole / 6 Amps. 1 Pole, 63 Amp. 1 Pole MCB single core multistrand copper cable mm , Single Core copper conductor , unarmoured flexible multistrand power	Per/mtr Mtr No No No	
fixing of 1 nos. copper strip of size 300 x75 x 3 mm on epoxy insulators at 2 ft fixing of 1 nos. copper strip of size 300 x75 x 3 mm on epoxy insulators to be 6B / EGB. 10 nos. of holes to be made on each plates and SS nuts & bolts with spring washers to be supplied. DB nps 1 pole / 13 Amps. 1 Pole / 6 Amps. 1 Pole, 63 Amp. 1 Pole MCB single core multistrand copper cable mm , Single Core copper conductor , unarmoured flexible multistrand power	Mtr No No No	
B / EGB. 10 nos. of holes to be made on each plates and SS nuts & bolts with spring washers to be supplied. DB nps 1 pole / 13 Amps. 1 Pole / 6 Amps. 1 Pole, 63 Amp. 1 Pole MCB single core multistrand copper cable mm , Single Core copper conductor , unarmoured flexible multistrand power	No No	
nps 1 pole / 13 Amps. 1 Pole / 6 Amps. 1 Pole, 63 Amp. 1 Pole MCB single core multistrand copper cable mm , Single Core copper conductor , unarmoured flexible multistrand power	No No	
nps 1 pole / 13 Amps. 1 Pole / 6 Amps. 1 Pole, 63 Amp. 1 Pole MCB single core multistrand copper cable mm , Single Core copper conductor , unarmoured flexible multistrand power	No	
single core multistrand copper cable mm , Single Core copper conductor , unarmoured flexible multistrand power		
mm , Single Core copper conductor , unarmoured flexible multistrand power	1 01/110	1
ding providing trimibles (red)	Per/mtr	03 NO
mm , Single Core copper conductor , unarmoured flexible multistrand power ding providing thimbles (Black)	Per/mtr	03 1/6
qmm single core cu condutor, unarmoured flexible multistand power cable roviding glands & thimbles (Green)	Per/mtr	
qmm single core cu condutor, unarmoured flexible multistand power cable roviding glands & thimbles (Red)	Per/mtr	
qmm single core cu condutor, unarmoured flexible multistand power cable roviding glands & thimbles (Black)	Per/mtr	
lation, RRU / MW / GSM	Nos.	
lation	Nos.	
stallation	Nos	
tner 12mm, 4 inch	No	
0 mm SDPE	Mtr.	
ingle Core Mutistand Flexible Cable	Mtr.	OTMA
q	Per Site	01201
1	Alation, RRU/MW/GSM Ilation Installation Installation Installation I	Illation Nos. Installation Nos Installation No Installation No Installation No Installation No Installation Mtr. Installation Mtr. Installation Mtr. Installation Mtr. Installation Per Site

ay 9913872978

OSPS-EIGENEER:

TECHNICIAN SIGNATURE:

FSE SIGNATURE: