ROBOCOPY ONLY — Canonical Module Notice

Document status: Informative
Applies to: `/modules` directory
Audience: Facilitators, operators, maintainers, auditors

Purpose of this note

This document explains the role of the files contained in the `/modules` directory and provides explicit instructions on how they are to be handled.

The files in this directory are the **original canonical modules** for the Access-mode framework. They are retained for record-keeping, provenance, and authoritative reference.

Table of Contents

- Canonical Status of `/modules`
- How Canonical Modules Are Used
- Creating a New Custom Mode
- Record-Keeping Principle
- Summary of Canonical vs Derived Folders
- PS7 Robocopy Prompt
- Post-Creation Housekeeping for New Modes
- Mode Difference Documentation
- README Requirements for New Modes

Canonical Status

The modules in `/modules` are:

- **Authoritative**
- **Unmodified**
- **Mode-agnostic**
- **Preserved for traceability**

These files represent the original source material from which all Access-mode configurations are derived.

Do not edit these files directly.
Any modification risks breaking consistency across modes and undermining audit integrity.

How canonical modules are used

Canonical modules are used as **source inputs only**.

They may be:

- copied into a new mode folder,
- renamed with a mode suffix (e.g. `_ID_4`), and
- extended or adapted **only in the destination folder**.

Canonical modules must never be:

- edited in place,
- partially copied,
- selectively modified, or
- overwritten.

Creating a new custom mode

When a new Access-mode configuration is required (for example, `ID_4`), the correct process is:

1. **Create a new mode directory** under `/modes`
2. **Copy all canonical modules** from `/modules` using `robocopy` – provided below
3. **Apply mode-specific changes only** in the new folder

This ensures:

- provenance is preserved,
- differences between modes are explicit,
- rollback is possible, and
- audit review remains straightforward.

Record-Keeping Principle

The `/modules` directory functions as a **source-of-truth archive**.

Think of it as:

- a reference library, not a working directory;
- a master copy, not a draft space.

All experimentation, facilitation variants, or standards-specific adaptations belong in `/modes`, never here.

Summary

- `/modules` = canonical, read-only, authoritative
- `/modes` = derived, contextual, editable
- **Robocopy is the recommended and approved method** for creating new modes from canonical modules

---

PS7 robocopy prompt

This prompt safely creates a new **custom mode ID_4** by copying *all* canonical modules.

Assumptions

- Source (canonical):
  `C:\v1.0-Access-mode\modules`
- Destination (new mode):
  `C:\v1.0-Access-mode\modes\ID_4_custom\modules`

PowerShell 7 command – Copy/paste In PS7 – Hit enter

```
# Create destination folder if it does not exist
New-Item -ItemType Directory `
  -Path "C:\v1.0-Access-mode\modes\ID_4_custom\modules" `
  -Force | Out-Null

# Robocopy canonical modules into new custom mode
robocopy `
  "C:\v1.0-Access-mode\modules" `
  "C:\v1.0-Access-mode\modes\ID_4_custom\modules" `
  *.md `
  /E `
  /COPY:DAT `
  /DCOPY:T `
  /R:0 `
  /W:0 `
  /NFL `
  /NDL `
  /NJH `
  /NJS `
  /NP
```

What this does (plain English)

- Copies **all `.md` files only**
- Preserves timestamps and attributes
- Does **not** retry or wait on errors
- Produces minimal console noise
- Leaves canonical modules untouched

After this step, you may:

- rename files to include `_ID_4`
- modify content **only** inside `ID_4_custom`
- add mode-specific README or notes – below.

Post-creation housekeeping for new modes (ID_4 and beyond)

Once a new mode directory has been created (for example, `ID_4_custom`), perform the following **mandatory housekeeping steps** before making any content changes.

Name the mode folder deliberately

Rename or confirm the mode folder name using a clear, descriptive suffix.

Examples:

- `ID_4_custom`
- `ID_4_internal_review`
- `ID_4_sector_trial`
- `ID_4_experimental`

Avoid generic names such as `test`, `temp`, or `new`.

The folder name becomes part of the audit trail.

Create supporting folders for records and working material

Inside the new mode folder, create the following sub-folders to mirror existing modes (ID_1, ID_2, ID_3):

- `drafts` — for working versions, experiments, and in-progress edits
- `notes` — for facilitator notes, review comments, or decision records

These folders are **mode-local** and must not exist in `/modules`.

Create a README.md for the new mode

Every new mode **must include a README.md file** at the root of the mode folder.

The README documents:

- the purpose of the mode,
- how it differs from other modes, and
- any constraints or intended audience.

This ensures that future reviewers can understand *why* the mode exists, not just *how* it was built.

Begin edits only after housekeeping is complete

Only after:

- the folder is named,
- `drafts` and `notes` exist, and
- a README.md is present,

may module files be renamed (e.g. `_ID_4`) or edited **within the mode folder**.

Mode difference documentation

Prior to creating a new mode folder, maintain a Mode Difference Note in the `/modes` root directory

(e.g. `MODE_DIFF_NOTE.md`).

This file records:

- why a new mode is being considered,
- how it differs from existing modes (ID_1–ID_3), and
- any intended scope or constraints.

The MODE_DIFF_NOTE.md **supports design intent and review clarity.**

It does not replace the README.md that will later be created inside the mode folder.

README.md template for the new ID_4 mode

Suggested file location

```
C:\v1.0-Access-mode\modes\ID_4_custom\README.md
```

Template (copy-paste) below in notepad

```
# Mode ID_4 — Custom Mode

**Status:** Draft
**Derived from:** Canonical modules in `/modules`
**Created via:** Robocopy (no in-place modification)

## Purpose of this mode

Describe why this mode exists and the specific governance posture, audience,
or use case it is intended to support.

This mode was created to:
- [reason about …]
- [support …]
- [experiment with …]

## Relationship to other modes

This mode is:
- different from ID_1 because …
- different from ID_2 because …
- different from ID_3 because …

This mode does not replace or supersede any existing mode.

## What this mode includes

- Copies of canonical modules with `_ID_4` suffix
- Mode-specific edits and extensions (where applicable)
- Supporting drafts and notes for record-keeping

## What this mode does NOT do

- It does not modify canonical source files
- It does not imply certification, compliance, or approval
- It does not change HASH KEY 1–10 semantics

## Record-keeping notes

- Canonical source remains `/modules`
- All changes are local to this mode folder
- Differences should be reviewable by file comparison
```

save as type – **all files** and name file: **README.md** - save in the new mode\ folder.