
CLICKLOCK - CLICKLOCK MACOS KILL LOOP

Repeated termination of core GUI processes used to coerce credential entry.



PRODUCTION CANDIDATE

CONFIDENCE: MEDIUM

REPORT TYPE
campaign

STATUS
Untested implementation sketch

PRIMARY PLATFORM
Microsoft Defender XDR on macOS

OPERATIONAL VALUE
9 / 10

01

Executive Assessment

Decision-grade summary with explicit evidence boundaries.

ASSESSMENT

DECISION

Retain this package as a production candidate and migrate it to the canonical visual and evidence contract without changing query conditions. Treat every result as an investigative lead until local schema, field population, benign overlap and the legacy claim provenance are reviewed.

LEGACY EVIDENCE RECORD

- The retained legacy source ledger contains 2 normalized references; claim-to-source mapping remains...

ANALYST ASSESSMENT

- The existing logic is retained at production-candidate maturity; repository migration is not...
- The folder and query header map the package to T1562.001 / T1056.002 / T1543.001; operation...

DETECTION ASSUMPTIONS

- The named telemetry is collected across the intended asset or identity scope with adequate...
- Projected fields preserve their expected semantics in the target connector and parser. [C002]
- Approved activity, owners and change records are available to analysts during disposition. [C003]

KEY FINDINGS

FINDING 1

The original query conditions and source ledger were preserved during layout migration; legacy PDF SHA-256 6c5680beb3dd22f3... is recorded for traceability. [C001]

FINDING 2

The principal observable is Evaluate DeviceProcessEvents for clicklock macos kill loop using the existing source-derived conditions while preserving projected investigation context. [C002]

FINDING 3

The evidence boundary remains explicit: a match does not prove that a credential prompt was shown, credentials were captured or the activity belongs to ClickLock. [C003]

EVIDENCE BOUNDARY

A matching result does not prove that a credential prompt was shown, credentials were captured or the activity belongs to ClickLock. Target-environment field population, benign prevalence, parser behavior and operational ownership have not been validated by this repository migration.

02

Threat Mechanics

Technical mechanism, observable transitions and supported scope.

ATTACK FLOW

TECHNICAL BACKGROUND

The retained dossier links Clicklock to the detection opportunity described as clicklock macos kill loop. The v2 migration preserves the query exactly and exposes its match boundary, but does not reinterpret legacy source claims as laboratory evidence. Evaluate DeviceProcessEvents for clicklock macos kill loop using the existing source-derived conditions while preserving projected investigation context. [C001][C002]

1

THREAT CONTEXT

Repeated termination of core GUI processes used to coerce credential entry. Observable: Context retained from the legacy dossier and source ledger.

2

OBSERVABLE CANDIDATE

Evaluate DeviceProcessEvents for clicklock macos kill loop using the existing source-derived conditions while preserving projected investigation context. Observable: Events from DeviceProcessEvents and projected fields.

3

CONTEXTUAL ENRICHMENT

Resolve asset, identity, process, ownership and change context before disposition. Observable: Raw event, surrounding timeline, inventory and authorized-change evidence.

4

DECISION GATE

Escalate only when corroborating evidence closes the documented non-claim boundary. Observable: Controlled validation, explainable negatives and analyst-readable evidence.

03

Telemetry & Evidence Model

Minimum data contract and known visibility gaps.

DATA CONTRACT

PRIMARY PLATFORM

Microsoft Defender XDR on macOS. Evaluate DeviceProcessEvents for clicklock macos kill loop using the existing source-derived conditions while preserving projected investigation context.

FIELD / TABLE	STATUS	PURPOSE
DeviceProcessEvents	**Required**	Primary event source selected by the unchanged query logic.
Event time and entity identifiers	**Required**	Chronology, deduplication, scoping and investigation pivots.
Raw projected context	**Required**	Preserve the fields emitted by the query before normalization or tuning.
Asset, identity and change inventory	**Enrichment**	Separate authorized activity and define operational ownership.

KNOWN VISIBILITY GAPS

Unvalidated local schema Missing projected fields Incomplete retention or asset scope Mutable attacker behavior Legacy claim provenance review pending

04

Primary Detection Logic

Native query, explicit condition evidence and match meaning.

KQL

```
// Rule: [T1562.001][T1056.002][T1543.001] Clicklock - Clicklock macOS Kill Loop
// MITRE ATT&CK: T1562.001, T1056.002, T1543.001
// Classification: Production candidate
// Status: Untested implementation sketch
// Primary platform: Microsoft Defender XDR on macOS
// Required telemetry: DeviceProcessEvents
// Purpose: Repeated termination of core GUI processes used to coerce credential entry.
// Logic: Evaluate DeviceProcessEvents for clicklock macos kill loop using the existing source-derived conditions while preserving projected invest
// A match proves: A match indicates repeated process-termination activity compatible with the source-described coercion loop.
// A match does not prove: that a credential prompt was shown, credentials were captured or the activity belongs to ClickLock.
// Expected false positives: authorized administration, approved software, testing, or benign artifact collisions.
// Coverage limits: local schema, field population, retention, collection scope, and attacker variation require validation.
// Evidence claims: C001, C002, C003
//
// Title: ClickLock macOS Repeated Process-Termination Loop
// Status: Production candidate - untested threshold
// Confidence: Medium
// Platform: Microsoft Defender XDR on macOS
// Telemetry: DeviceProcessEvents
// Purpose: Detect dense bursts of pkill/killall commands targeting macOS GUI
// components involved in the ClickLock credential-coercion behavior.
// ATT&CK: T1562.001, T1056.002, T1543.001
// Assumption: MDE captures enough short-lived processes and command-line data.

DeviceProcessEvents
| where FileName in~ ("pkill", "killall")
| where ProcessCommandLine has_any (
    "Finder",
    "Dock",
    "SystemUIServer",
    "NotificationCenter"
)
| summarize
    FirstSeen = min(Timestamp),
    LastSeen = max(Timestamp),
    TerminationAttempts = count(),
    Commands = make_set(ProcessCommandLine, 20),
    Parents = make_set(InitiatingProcessFileName, 10)
  by DeviceId, DeviceName, AccountName, bin(Timestamp, 1m)
| where TerminationAttempts >= 20
```

WHAT A MATCH PROVES

A match indicates repeated process-termination activity compatible with the source-described coercion loop.

WHAT IT DOES NOT PROVE

that a credential prompt was shown, credentials were captured or the activity belongs to ClickLock.

MATURITY

Production candidate - Untested implementation sketch. Evaluate DeviceProcessEvents for clicklock macos kill loop using the existing source-derived conditions while preserving projected investigation context.

05

Triage & Hunting Playbook

Evidence-preserving workflow from match to disposition.

WORKFLOW

01

Preserve the complete raw matching event, query version, timestamp, connector or sensor version and stable entity identifiers.

02

Confirm the event originated from the intended Microsoft Defender XDR on macOS data source and verify the semantics of every condition used by the query.

03

Resolve asset, identity, process, software and destination ownership against authoritative inventories and approved change records.

04

Build the surrounding endpoint, identity, network or appliance timeline and seek an independent evidence layer before escalation.

05

Classify benign overlap explicitly; tune only with durable ownership or provenance controls, never by suppressing the core behavior globally.

06

Escalate only when corroborating evidence establishes malicious or unauthorized activity beyond the documented match boundary.

DISPOSITION RULE

Escalate only when the evidence establishes the behavior described by the query. that a credential prompt was shown, credentials were captured or the activity belongs to ClickLock.

06

False Positives & Validation

Overlap model, controlled checks and promotion gate.

QUALITY GATE

AUTHORIZED ADMINISTRATION OR SOFTWARE

Require owner, purpose, approved change and expected execution or configuration provenance.

BENIGN ARTIFACT OR COMMAND COLLISION

Require the full condition set plus an independent evidence layer or stable provenance.

PARSER, INVENTORY OR RETENTION AMBIGUITY

Reproduce a controlled event and reconcile raw fields, collection scope and authoritative inventory.

VALIDATION SEQUENCE

- Generate an authorized controlled equivalent of the primary observable without using live malicious infrastructure.
- Verify each query condition and projected field against retained raw telemetry.
- Run representative approved and near-match negative controls.
- Measure historical prevalence and classify every returned owner or workflow.
- Record parser, connector, retention and asset-scope dependencies with the test evidence.

SUCCESS

The controlled positive produces a complete, explainable row and representative negatives are separable through durable context.

REJECTION

Reject promotion when field semantics, collection scope, benign ownership or the core behavior cannot be established reproducibly.

PROMOTION GATE

Require claim-level source review, a retained controlled positive, representative negatives, measured prevalence and an accountable operational owner.

07

Analyst Assessment & References

Coverage statement, open questions and source record.

FINAL

CONCLUSION

This package now uses the canonical v2 layout and evidence contract while preserving the original detection.kql conditions. It remains a production candidate at medium confidence. The visual migration is complete; claim-level provenance and target-environment execution remain explicit promotion gates.

MITRE ATT&CK

T1562.001 / T1056.002 / T1543.001

PRIMARY AND AUTHORITATIVE REFERENCES

S001 group-ib.com - ClickLock Stealer: Paste Once, Lose Everything (undated)

hxxps://www[.]group-ib[.]com/blog/clicklock-stealer-macos-malware/

S002 Microsoft Learn - DeviceProcessEvents table in the advanced hunting schema (undated)

hxxps://learn[.]microsoft[.]com/en-us/defender-xdr/advanced-hunting-deviceprocessevents-table

OPEN QUESTIONS

A matching result does not prove that a credential prompt was shown, credentials were captured or the activity belongs to ClickLock. Target-environment field population, benign prevalence, parser behavior and operational ownership have not been validated by this repository migration.

DOCUMENT CONTROL

Schema 2.0 | Layout 2.0 | Maturity production-candidate | Confidence Medium | No customer data | Evidence ledger required