ChatGPT

PCAP Files Explained

You

what are networking events how to identify them from pcap file

ChatGPT

Networking events: What are they, and how do you identify them in a PCAP file?

To understand networking events, imagine that your computer is communicating with a website. Your computer sends packets, receives responses, establishes connections, looks up domain names, and exchanges data.

A networking event is an identifiable activity or occurrence during network communication. Examples include a DNS lookup, a TCP connection attempt, a successful connection, a failed connection, a file transfer, or a suspicious communication attempt.

When you analyze a PCAP file, you examine captured packets to identify these events and understand what happened on the network.

This is an important skill in network troubleshooting, cybersecurity, intrusion detection, and malware analysis.

1. What are networking events?

A networking event is something meaningful that happens during communication between devices.

For example, when you open a website, several networking events may occur in sequence:

Event 1: DNS query

Your computer looks up a domain name.

Take your curiosity further
Scan to get the ChatGPT app

Event 2: TCP connection

Your computer attempts to establish a connection.

Event 3: TLS handshake

The client negotiates secure communication for HTTPS.

Event 4: Data exchange

The client and server exchange application data.

Event 5: Connection closure

The connection may close normally or terminate unexpectedly.

A PCAP does not necessarily contain a separate record explicitly labelled "DNS event" or "connection event." Instead, the event is often inferred by examining one packet or a sequence of packets.

For example, one TCP SYN packet indicates a connection attempt. A SYN followed by SYN-ACK and ACK indicates a completed TCP handshake.

2. Common networking events you can identify in a PCAP

Here are the main types of events you should learn first.

Networking event	What it means	What to look for
DNS query	A device looks up a domain	DNS query packets
DNS response	A DNS server answers a query	DNS response and answer records

Take your curiosity further
Scan to get the ChatGPT app


TCP connection attempt	A device attempts to connect	TCP SYN flag
TCP connection established	A TCP handshake completes	SYN, SYN-ACK, ACK sequence
Connection failure	A connection cannot be established or is rejected	RST, repeated SYNs, ICMP errors, or timeouts
HTTP request	A client requests a web resource	HTTP methods such as GET or POST
TLS handshake	A client and server negotiate encryption	Client Hello, Server Hello, and other TLS messages
Data transfer	Data is exchanged	Payload-bearing packets and byte counts
Connection termination	A TCP connection closes	FIN or RST flags
Port scanning	A host probes multiple ports	Repeated connection attempts to different ports
Possible data exfiltration	Data may be leaving a network unexpectedly	Unusual outbound transfers, destinations, or traffic volumes
Possible beaconing	A host repeatedly contacts a destination	Regularly spaced connections or similar requests

Important: These are observed events or indicators, not automatic proof of malicious activity. For example, a TCP RST may be completely legitimate, and repeated connections may be normal application behavior.

3. How to identify networking events in Wireshark

Wireshark is one of the easiest tools for inspecting PCAP files because it decodes packets into readable protocol fields.

Take your curiosity further
Scan to get the ChatGPT app



Step 1: Open the PCAP file

1. Open Wireshark.
2. Select **File → Open**.
3. Choose your `.pcap` or `.pcapng` file.
4. Look at the packet list.

The packet list typically contains these columns:

Column	Meaning
No.	Packet number
Time	When the packet was captured
Source	Device sending the packet
Destination	Device receiving the packet
Protocol	Protocol Wireshark identifies
Length	Packet length

Take your curiosity further
Scan to get the ChatGPT app

Info Brief summary of the packet

For example, you might see:

```
No.  Time      Source          Destination      Protocol  Info
1    0.000     192.168.1.10    192.168.1.1      DNS       Standard query
2    0.025     192.168.1.1     192.168.1.10     DNS       Standard query response
3    0.040     192.168.1.10    93.184.216.34    TCP       51524 → 443 [SYN]
4    0.060     93.184.216.34   192.168.1.10     TCP       443 → 51524 [SYN, ACK]
5    0.061     192.168.1.10    93.184.216.34    TCP       51524 → 443 [ACK]
```

These are illustrative packets. They show a DNS exchange followed by a TCP connection handshake.

Step 2: Use display filters

Wireshark's display filter bar allows you to show only packets relevant to the event you want to investigate.

Select an event to see its filter.

- DNS activity
- All TCP packets
- Connection attempts (SYN)
- TCP resets
- HTTP traffic
- TLS traffic
- Network errors and diagnostics
- Traffic for a particular host

Wireshark display filter

```
dns
```

Take your curiosity further
Scan to get the ChatGPT app

Copy filter

Show DNS queries and responses. Examine the queried name, response code, and answer records.

Enter the filter in Wireshark's display filter bar and press Enter. These are **display filters**, not capture filters; they narrow the displayed packets without deleting other packets from the capture.

Step 3: Inspect packet details

Click a packet to expand its protocol layers.

For a TCP packet, you might inspect:

- Source and destination IP addresses
- Source and destination ports
- TCP flags
- Sequence and acknowledgment numbers
- TCP payload length

For a DNS packet, inspect:

- Query name
- Query type, such as A or AAAA
- Response code
- Answer records and returned IP addresses

The fields tell you what happened in an individual packet. To identify the larger networking event, correlate it with related packets before and after it.

4. How to identify the most important networking events

Event 1: DNS query and response

DNS translates domain names into information such as IP addresses.

Take your curiosity further
Scan to get the ChatGPT app

Suppose your computer wants to access `example.com`.

You may see:

```
192.168.1.10 → 192.168.1.1
DNS Query: example.com, Type A

192.168.1.1 → 192.168.1.10
DNS Response: example.com, Type A
Answer: 93.184.216.34
```

How to identify this event:


1. Apply the filter `dns`.
2. Find a query and its corresponding response.
3. Inspect the queried domain and response code.
4. Examine the answer records.
5. Check whether a subsequent connection goes to an address returned by the response.

A successful response is not guaranteed. A DNS response can return an error, no answers, or a redirected address.

Cybersecurity use: Unexpected domains, unusually frequent DNS requests, and suspicious patterns in DNS responses can be worth investigating. An unusual domain alone does not prove malware.

Event 2: TCP connection establishment

TCP commonly establishes a connection through a three-way handshake.



Take your curiosity further
Scan to get the ChatGPT app



Conceptual TCP handshake. Each arrow represents a packet traveling between endpoints.

The three packets are:

1. Client → Server: `SYN`
2. Server → Client: `SYN, ACK`
3. Client → Server: `ACK`

Useful filter:

```
tcp.flags.syn == 1
```

This shows SYN packets, including SYN-ACK packets. To show initial SYN packets only, use:

```
tcp.flags.syn == 1 && tcp.flags.ack == 0
```

To establish that a connection succeeded, inspect the related packets and verify that the handshake completed. A SYN packet alone proves only an attempt, not a successful connection.

Event 3: Failed or rejected TCP connection

Suppose a client tries to connect to a server, but no connection is established.

You might observe:

```
Client → Server    SYN
Client → Server    SYN retransmission
Client → Server    SYN retransmission
```

Take your curiosity further
Scan to get the ChatGPT app

Possible interpretation: the client did not receive the expected response. Reasons could include packet loss, filtering, a server that is down, or a capture that missed the response.

Another pattern:

```
Client → Server    SYN
Server → Client    RST, ACK
```

This can indicate that the connection was actively rejected or that the destination port was not accepting connections.

Useful filters:

```
tcp.flags.reset == 1
```

```
tcp.analysis.retransmission
```

Important: A timeout or missing response is harder to prove from a PCAP than a visible rejection. The capture may be incomplete, or the response may have taken a different route.

Event 4: HTTP requests and responses

HTTP is used for web communication. When it is unencrypted, a PCAP may reveal the request and response contents.

Example:

```
GET /index.html HTTP/1.1
Host: example.com
User-Agent: ExampleBrowser
```

You can identify:

- **GET:** A request to retrieve a resource.
- **POST:** A request commonly used to submit data.

Take your curiosity further
Scan to get the ChatGPT app

- **HTTP status code:** For example, 200, 301, 403, or 404.
- **Host header:** The requested hostname in HTTP/1.1.
- **Request URI:** The resource being requested.

Useful filter:

```
http
```

If you want to examine the entire conversation, right-click a packet and choose **Follow → TCP Stream** when that option is available.

With HTTPS, ordinary application data is encrypted. You generally cannot see the HTTP request path or response body merely by filtering for TLS traffic.

Event 5: TLS handshake

When a browser connects to an HTTPS website, TLS is normally used to negotiate secure communication.

You may see:

```
Client → Server    TLS Client Hello
Server → Client    TLS Server Hello
Client ↔ Server    Additional handshake messages
Client ↔ Server    Encrypted application data
```

Useful filter:

```
tls
```

Look for:

- Client Hello
- Server Hello
- Negotiated TLS version and cipher suite, where available
- Certificate-related messages, depending on the TLS version

Take your curiosity further
Scan to get the ChatGPT app

- Alerts or handshake failures

TLS 1.3 encrypts more of the handshake than earlier TLS versions. Consequently, some handshake details are not visible in an ordinary capture.

A TLS handshake does not necessarily prove that a website was successfully loaded. The handshake may fail, or the application may subsequently return an error.

Event 6: Connection termination

TCP connections commonly terminate using FIN and ACK packets.

For example:

```
Client → Server    FIN, ACK
Server → Client    ACK
Server → Client    FIN, ACK
Client → Server    ACK
```

This is an illustrative graceful TCP shutdown.

A connection can also terminate abruptly with an RST packet.

Useful filters:

```
tcp.flags.fin == 1
```

```
tcp.flags.reset == 1
```

Look at the packet sequence to determine whether the connection closed gracefully or was reset. A FIN or RST in isolation may not tell you the complete reason for the closure.

Take your curiosity further
Scan to get the ChatGPT app

5. How to identify suspicious networking events

In cybersecurity, you often want to know whether the observed activity is normal or potentially malicious.

Here are four useful patterns.

A. Possible port scanning

What you might observe

```
10.0.0.5 → 10.0.0.20:22    SYN
10.0.0.5 → 10.0.0.20:80    SYN
10.0.0.5 → 10.0.0.20:443   SYN
10.0.0.5 → 10.0.0.20:445   SYN
```

One host tries several ports on the same destination in a short period.

How to investigate: Filter for the source IP and TCP SYN packets. Examine the number of distinct destination ports, response patterns, and timing. A vulnerability scanner or legitimate monitoring system can generate similar traffic.

B. Possible beaconing

What you might observe

```
10:00:00  Host → External server
10:01:00  Host → External server
10:02:00  Host → External server
10:03:00  Host → External server
```

A host contacts the same destination at regular intervals.

How to investigate: Compare timestamps, destinations, ports, connection durations, and byte counts. Repeated communication may be normal polling, a health check, or a scheduled job, so timing alone does not establish malicious beaconing.

Take your curiosity further
Scan to get the ChatGPT app

C. Possible data exfiltration

What you might observe

```
Internal host → External destination
Many packets sent outbound
Unusually large total byte count
```

A device sends an unexpectedly large amount of data to an external endpoint.

How to investigate: Check which host initiated the connection, the amount and direction of transferred data, the duration, and whether the destination is expected. Encrypted traffic can still expose traffic volume, but not necessarily the content being transferred.

D. DNS anomalies

What you might observe

```
Host → DNS server
Unusually frequent DNS queries
Repeated failures or unusual domain names
```

A device makes many DNS requests, including requests for unusual domains or requests that repeatedly fail.

How to investigate: Review query frequency, response codes, domain patterns, returned addresses, and the originating host. Consider legitimate software behavior and the possibility of encrypted DNS bypassing the visible DNS traffic.

These are examples of **network indicators**. Reliable incident detection requires context, comparison with normal traffic, and corroborating evidence.

6. How do you turn packets into a timeline of events?

This is one of the most important PCAP analysis skills.

A packet is a single captured unit of communication. A networking event may involve one packet or hundreds of related packets. Your job is to group related packets and infer the sequence of activities.

Take your curiosity further
Scan to get the ChatGPT app

For example:

Time	Observation	Possible event
0.000 s	DNS query for a domain	Name lookup begins
0.020 s	DNS response with an address	Name lookup completes
0.040 s	TCP SYN to that address	Connection attempt
0.060 s	TCP SYN-ACK	Server responds
0.061 s	TCP ACK	TCP handshake completes
0.080 s	TLS Client Hello	Secure session negotiation begins
0.120 s	Encrypted application data	Application communication may be underway
1.500 s	TCP FIN	Connection begins graceful closure

This timeline illustrates how you can reconstruct the communication process. Actual timings and packet order depend on the network and application.

A good analyst asks:

1. Which device initiated the activity?
2. What was the destination?
3. What happened first?
4. Did the destination respond?
5. Was the communication successful?
6. What happened after the connection was established?
7. Does the sequence appear normal for this device and application?

7. Practical workflow: Analyze any PCAP for networking events

Follow this sequence when you receive a PCAP file for a networking or cybersecurity investigation.

1. **Understand the capture.** Check its time range, packet count, capture interfaces if available, and whether packets appear truncated or missing.

Take your curiosity further
Scan to get the ChatGPT app

2. **Identify the main hosts.** In Wireshark, open Statistics → Endpoints and Statistics → Conversations to see which devices communicate most frequently.
3. **Find DNS activity.** Use `dns` to identify domain lookups, answers, and failures.
4. **Find connection attempts.** Use `tcp.flags.syn == 1 && tcp.flags.ack == 0` and examine whether the handshakes completed.
5. **Inspect application protocols.** Examine HTTP, TLS, DNS, and other protocols relevant to the traffic.
6. **Look for anomalies.** Investigate unusual destinations, repeated connection failures, scanning patterns, or unexpected data volumes.
7. **Build an event timeline.** Correlate packets by timestamp, source and destination addresses, ports, and connection or stream identifiers.
8. **Document your findings.** Record the observed packets, your interpretation, alternative explanations, and any limitations of the capture.

Optional: Identify events with command-line tools

If you install Wireshark, you can also use its command-line companion, `tshark`.

For example, to list packet timestamps, endpoints, and protocols:

```
tshark -r capture.pcap \
  -T fields \
  -e frame.time \
  -e ip.src \
  -e ip.dst \
  -e _ws.col.Protocol \
  -e _ws.col.Info
```

To examine DNS packets:

```
tshark -r capture.pcap -Y "dns"
```

To examine initial TCP connection attempts:

Take your curiosity further
Scan to get the ChatGPT app


```
tshark -r capture.pcap \
  -Y "tcp.flags.syn == 1 && tcp.flags.ack == 0"
```

To identify TCP resets:

```
tshark -r capture.pcap -Y "tcp.flags.reset == 1"
```

Replace `capture.pcap` with your actual file path. These commands display matching packets; they do not automatically determine whether an activity is malicious.

8. Check your understanding

1. **You see a TCP SYN packet but no response. What can you conclude?**

   The connection definitely succeeded

   A connection was attempted, but success is not established

   The server definitely contains malware

2. **Which Wireshark filter helps you find DNS queries and responses?**

   http

   dns

   tcp.flags.fin == 1

3. **A host contacts the same external IP every 60 seconds. What is the correct conclusion?**

   It is definitely malware

   It is definitely harmless

   It may be periodic beaconing, but more evidence is needed

Take your curiosity further
Scan to get the ChatGPT app

4. What is the best way to identify a successful TCP handshake?

Look for any single SYN packet

Correlate SYN, SYN-ACK, and the final ACK

Look only at the destination port

Reset quiz

What I recommend next

The best way to learn networking events is to examine an actual PCAP rather than memorizing filters.

If you have a PCAP file, upload it here. I can help you examine the packets and build a clear, step-by-step event timeline showing:

- Which devices communicated
- Which DNS queries occurred
- Which TCP connections were attempted or established
- Which protocols were used
- Which events appear unusual and why
- What can and cannot be concluded from the available evidence

Remove or sanitize sensitive traffic before sharing a capture. PCAP files may contain private communications, session tokens, and other confidential information.

You

what are the errors that might happen in these networking events and how to identify them from pcap files

Take your curiosity further
Scan to get the ChatGPT app

ChatGPT

Networking errors: What can go wrong, and how do you identify them in a PCAP file?

When computers communicate over a network, many things can go wrong. A DNS server might fail to resolve a domain, a TCP connection might never be established, packets might be lost, a TLS handshake might fail, or a server might return an HTTP error.

A PCAP file helps you investigate these problems by showing the packets exchanged, their timestamps, protocol fields, and any errors or unusual sequences that can be observed.

The most important skill is learning to connect three things:

1. **What went wrong?** The networking error or failure.
2. **What does it look like?** The packets and fields that indicate the problem.
3. **How do you identify it?** The Wireshark filter and the packet sequence you need to inspect.

Let's go through this step by step, from beginner level to practical troubleshooting.

1. The main categories of networking errors

DNS errors
A domain cannot be resolved, the server returns an error, or the response never arrives.

TCP connection errors
Connection attempts fail, are rejected, or repeatedly time out.

Packet delivery and transport problems
Retransmissions, duplicate acknowledgments, out-of-order packets, and zero-window conditions.

TLS and HTTP errors
Secure handshakes fail, certificates are rejected, or web servers return error responses.

Take your curiosity further
Scan to get the ChatGPT app

IP and network-layer errors
Routing failures, unreachable destinations, fragmentation problems, or address-resolution issues.

One important distinction: a **protocol error** is not always a network failure. For example, an HTTP 404 response means the server returned a valid HTTP response indicating that the requested resource was not found. The network connection may have worked perfectly.

Also, some errors are explicitly reported in packets, while others must be inferred from missing responses or abnormal packet sequences.

2. DNS errors: Domain name resolution failures

DNS translates a domain name such as `example.com` into information such as an IP address.

Error A: DNS server returns NXDOMAIN

Suppose a client asks for a domain that does not exist.

Example:

```
Client → DNS Server
Query: unknown-example.test

DNS Server → Client
Response: NXDOMAIN
```

`NXDOMAIN` means that the queried domain name does not exist, according to the DNS response.

How to identify it in Wireshark:

1. Apply the filter `dns`.
2. Select the DNS response.
3. Expand **Domain Name System**.
4. Find the response code, usually displayed as `Name Error (3)`.

Take your curiosity further
Scan to get the ChatGPT app

Useful filter:

```
dns.flags.rcode == 3
```

Interpretation: the DNS server returned NXDOMAIN. This could result from a typo, a nonexistent domain, or an intentionally generated query; it does not by itself indicate a network malfunction or attack.

Error B: DNS server failure

A DNS response may indicate a server failure.

Example:

```
Client → DNS Server
Query: example.com

DNS Server → Client
Response: SERVFAIL
```

Useful filter:

```
dns.flags.rcode == 2
```

`SERVFAIL` means the server could not successfully process the query. Possible causes include upstream resolution problems, DNSSEC validation failures, or server configuration issues.

Error C: DNS timeout

Example:

```
10:00:00.000  Client → DNS Server  Query
10:00:01.000  Client → DNS Server  Retry
10:00:03.000  Client → DNS Server  Retry
                 No visible response
```

Take your curiosity further
Scan to get the ChatGPT app

This may indicate a DNS timeout.


To investigate:

- Filter with `dns`.
- Find queries with no matching response.
- Compare transaction IDs, query names, query types, and timestamps.
- Check whether responses were received from another DNS server.

There is no universal Wireshark display filter that conclusively identifies every DNS timeout. A query with no visible response may mean the response was lost, the capture missed it, or the response occurred outside the capture window.

3. TCP errors: Connection establishment failures

TCP establishes a connection using a three-way handshake.



If this sequence fails, the PCAP may help you determine where the connection attempt stopped.

Error A: Connection timeout

Example packet sequence:

```
Time       Source          Destination       Info
0.000 s    192.168.1.10    93.184.216.34     SYN
```

Take your curiosity further
Scan to get the ChatGPT app


```
1.000 s    192.168.1.10    93.184.216.34    SYN retransmission
3.000 s    192.168.1.10    93.184.216.34    SYN retransmission
           No visible response
```

What does it mean?

The client is attempting to establish a connection but is not receiving the expected response.

Possible causes:

- The server is offline.
- A firewall silently drops the traffic.
- A routing problem prevents delivery.
- The server or network is overloaded.
- The capture does not include the response.

Wireshark filter:

```
tcp.flags.syn == 1 && tcp.flags.ack == 0
```

To find likely retransmissions:

```
tcp.analysis.retransmission
```

Inspect the packets in the same TCP conversation and look for repeated SYN packets without a corresponding SYN-ACK.

Error B: Connection refused

Example:

```
Client → Server    SYN
Server → Client    RST, ACK
```

The server, or a device acting on its behalf, actively rejects the connection.

Take your curiosity further
Scan to get the ChatGPT app

Useful filter:

```
tcp.flags.reset == 1
```

Possible causes include:

- Nothing is listening on the destination port.
- A firewall or other network device actively rejects the connection.
- The server application has stopped accepting connections.

A reset is not automatically an error. Applications can use TCP resets legitimately to terminate connections.

Error C: TCP handshake does not complete

Example:

```
Client → Server    SYN
Server → Client    SYN, ACK
Client             No visible final ACK
```

The server responded, but the expected final handshake packet is not visible.

Possible explanations include packet loss, filtering, a client-side problem, or an incomplete capture.

How to investigate: Find the TCP stream and inspect the sequence around the handshake. Do not conclude that the client definitely failed if the final ACK might have been missed by the capture.

4. TCP data-transfer errors: Retransmissions and packet ordering

A TCP connection can be established successfully and still experience problems while transferring data.

Take your curiosity further
Scan to get the ChatGPT app

Error A: TCP retransmission

TCP retransmission occurs when data is sent again because the sender believes that previously transmitted data may not have been acknowledged.

Example:

```
Time       Direction     Observation
0.100 s    Client → S    TCP segment, Seq=1000
0.200 s    Client → S    Retransmission, Seq=1000
0.300 s    Server → C    ACK
```

This is an illustrative sequence.

Possible causes include packet loss, congestion, delayed acknowledgments, or other network conditions. Wireshark may also mark retransmissions when capture artifacts or missing packets confuse its analysis.

Useful filter:

```
tcp.analysis.retransmission
```

What to inspect:

1. Identify the affected TCP stream.
2. Check which packets are retransmitted.
3. Examine the acknowledgments and timing.
4. Determine whether retransmissions are isolated or frequent.
5. Compare the pattern with other streams and the surrounding traffic.

Frequent retransmissions can indicate poor network performance, but one retransmission does not necessarily mean something is seriously wrong.

Error B: Duplicate TCP acknowledgments

Example:

Take your curiosity further
Scan to get the ChatGPT app

```
Server → Client    ACK 2000
Server → Client    ACK 2000
Server → Client    ACK 2000
```

Repeated acknowledgments with the same acknowledgment number may indicate that the receiver is waiting for missing data.

Useful filter:

```
tcp.analysis.duplicate_ack
```

This can be associated with packet loss or out-of-order delivery. TCP uses duplicate acknowledgments as part of its loss-detection and recovery mechanisms.

Error C: Out-of-order TCP packets

TCP segments may arrive in a different order from the order in which they were sent.

Useful filter:

```
tcp.analysis.out_of_order
```

Wireshark may flag this when it detects an out-of-order sequence.

Possible causes include different network paths, packet reordering, congestion, or capture artifacts.

Out-of-order packets are not necessarily lost packets. TCP can reorder received data and deliver it to the application in the correct sequence.

Error D: TCP zero-window condition

Example:

```
Server → Client
TCP Window Size: 0
```

Take your curiosity further
Scan to get the ChatGPT app

A zero receive window means the receiver is temporarily telling the sender that it cannot accept more TCP data.

Useful filter:

```
tcp.analysis.zero_window
```

Possible causes include:

- The receiving application is not reading data quickly enough.
- The receiving system has limited buffer capacity.
- The receiver is overloaded.

A zero window is a flow-control signal, not necessarily a network fault. Investigate whether it persists and whether the receiver later advertises a nonzero window.

5. TLS errors: Secure connection failures

TLS is commonly used to protect HTTPS traffic. A TLS handshake can fail even when the underlying TCP connection succeeds.

Common TLS failure patterns

Error or symptom	What to look for
TLS handshake failure	TLS Alert messages or an incomplete handshake
Certificate validation problem	Certificate details and client-side validation errors, when observable
Protocol or cipher incompatibility	Handshake alerts or a failed negotiation
Connection closed during handshake	TCP FIN/RST or a missing continuation
TLS timeout	Handshake messages with no visible expected response

Useful Wireshark filter:

Take your curiosity further
Scan to get the ChatGPT app


```
tls
```

For TLS alerts:

```
tls.alert_message
```

Wireshark's available fields can vary by version, so if a filter is not recognized, use **Analyze → Display Filter Expression** or inspect the TLS fields shown for a selected packet.

An example of a failed handshake might look like this:

```
Client → Server    TCP SYN
Server → Client    TCP SYN, ACK
Client → Server    TCP ACK
Client → Server    TLS Client Hello
Server → Client    TLS Alert
```

The TLS alert may provide clues about why the handshake failed.

However, not every TLS failure produces a visible alert. The connection might simply time out or close, and some handshake information is encrypted, particularly in TLS 1.3.

Also, a PCAP may show a certificate but cannot always establish whether the client trusted or rejected it. Certificate validation is often performed locally by the client, so application or system logs may be needed to confirm the exact error.

6. HTTP errors: Web server and application problems

HTTP errors differ from transport errors. An HTTP response may indicate a problem even when DNS, TCP, and TLS all worked.

Common HTTP status codes

Status code	Meaning	What to investigate

Take your curiosity further
Scan to get the ChatGPT app

400	Bad Request	Invalid request or malformed input
401	Unauthorized	Authentication is required or failed
403	Forbidden	Access is denied
404	Not Found	Requested resource was not found
429	Too Many Requests	Rate limiting
500	Internal Server Error	Server-side application error
502	Bad Gateway	Gateway received an invalid upstream response
503	Service Unavailable	Service temporarily unavailable
504	Gateway Timeout	Gateway did not receive a timely upstream response

These status codes are defined by HTTP semantics, but their precise operational meaning depends on the server and application.

For unencrypted HTTP, use:

```
http.response.code >= 400
```

This shows HTTP responses with status codes of 400 or higher.

For example:

```
GET /login HTTP/1.1
Host: example.com

HTTP/1.1 503 Service Unavailable
```

This indicates that the server returned a service-unavailable response.

Important: An HTTP 500 or 503 does not automatically mean the network is broken. The request reached an HTTP-speaking endpoint, which returned an application-level error.

Take your curiosity further
Scan to get the ChatGPT app

With HTTPS, the HTTP status code is normally encrypted. You need authorized TLS decryption or suitable application logs to inspect it.

7. IP-layer and routing errors

Sometimes the problem occurs before TCP or the application can communicate successfully.

Error A: Destination unreachable

An ICMP message may indicate that a destination or network cannot be reached.

Example:

```
Client → Router     ICMP Echo Request
Router → Client     ICMP Destination Unreachable
```

Useful filter for IPv4:

```
icmp.type == 3
```

For IPv6, relevant errors include Destination Unreachable messages:

```
icmpv6.type == 1
```

Inspect the ICMP code and any quoted original packet information. Depending on the code, the problem may relate to an unreachable network, unreachable host, unreachable port, or another delivery issue.

An ICMP error can identify where a failure was reported, but it does not always identify the ultimate root cause.

Error B: TTL exceeded

An IPv4 packet's TTL is reduced as it passes through routers. If it reaches zero, a router can return an ICMP Time Exceeded message.

Take your curiosity further
Scan to get the ChatGPT app

Useful filter:

```
icmp.type == 11
```

This can occur during traceroute or when a routing loop causes packets to circulate too long.

For IPv6, the corresponding ICMPv6 message is Time Exceeded, type 3.

Error C: Fragmentation or MTU problems

IP packets that are too large for a network path can encounter fragmentation or Path MTU Discovery problems.

For IPv4, an ICMP Destination Unreachable message with the "fragmentation needed" code can indicate that a packet exceeds the path MTU and cannot be fragmented under the applicable conditions.

Useful starting filter:

```
icmp.type == 3 && icmp.code == 4
```

For IPv6, Packet Too Big is:

```
icmpv6.type == 2
```

Possible symptoms include connections that establish but stall when larger amounts of data are transferred.

Be aware that a packet capture alone may not always reveal the full path MTU problem, particularly if ICMP messages are filtered or the capture occurs at only one endpoint.

Take your curiosity further
Scan to get the ChatGPT app

8. ARP errors: Problems finding a local device

ARP (Address Resolution Protocol) is used on IPv4 local networks to find the MAC address associated with an IPv4 address.

Suppose your computer wants to send traffic to a local gateway at `192.168.1.1`.

It may send:

```
Who has 192.168.1.1?
Tell 192.168.1.10
```

The gateway should normally reply with its MAC address.

Possible ARP problem

```
10:00:00  Who has 192.168.1.1?
10:00:01  Who has 192.168.1.1?
10:00:03  Who has 192.168.1.1?
          No visible ARP reply
```

This could indicate that the device is unavailable, the address is incorrect, the local network has a problem, or the reply was not captured.

Wireshark filter:

```
arp
```

Look for repeated ARP requests that have no matching reply.

Another issue is a possible IP address conflict: multiple devices may appear to claim the same IPv4 address. Duplicate-address indications and conflicting ARP replies can be clues, but investigate the packet details before concluding there is a conflict.

ARP applies to IPv4 address resolution on local networks; IPv6 uses Neighbor Discovery instead.

Take your curiosity further
Scan to get the ChatGPT app

9. Quick reference: Which Wireshark filter should you use?

This is a practical cheat sheet you can use while investigating a PCAP.

- All filters
- DNS
- TCP
- TLS
- HTTP
- IP, ICMP, and ARP

DNS errors

DNS responses with nonzero response codes.

```
dns.flags.rcode != 0
```

DNS traffic

All recognized DNS queries and responses.

```
dns
```

Initial TCP connection attempts

Initial SYN packets.

```
tcp.flags.syn == 1 && tcp.flags.ack == 0
```

TCP retransmissions

Packets Wireshark identifies as retransmissions.

Take your curiosity further
Scan to get the ChatGPT app

```
tcp.analysis.retransmission
```

Duplicate ACKs

Duplicate TCP acknowledgments.

```
tcp.analysis.duplicate_ack
```

TCP resets

TCP packets with RST set.

```
tcp.flags.reset == 1
```

Zero window

TCP zero-window indications.

```
tcp.analysis.zero_window
```

TLS traffic

Recognized TLS packets.

```
tls
```

HTTP error responses

HTTP responses with status codes of 400 or above, when HTTP is visible.

```
http.response.code >= 400
```

IPv4 unreachable messages

ICMP Destination Unreachable messages.

```
icmp.type == 3
```

Take your curiosity further
Scan to get the ChatGPT app



IPv4 TTL exceeded

ICMP Time Exceeded messages.

```
icmp.type == 11
```

IPv4 fragmentation needed

ICMP messages reporting that fragmentation is needed.

```
icmp.type == 3 && icmp.code == 4
```

IPv6 destination unreachable

ICMPv6 Destination Unreachable messages.

```
icmpv6.type == 1
```

ARP traffic

ARP requests and replies.

```
arp
```

These are Wireshark display filters. They show packet patterns, not necessarily confirmed root causes. Some fields depend on the protocol being decoded.

10. A real-world example: How do you investigate a website that will not load?

Imagine a user reports that a website is not opening. You have their PCAP file.

Here is how you can narrow down the problem.

Start: Website fails to load

↓

1. Check DNS

Take your curiosity further
Scan to get the ChatGPT app



Does the query receive a valid response?

- No response: investigate possible timeout or capture gaps.
- NXDOMAIN or SERVFAIL: investigate the DNS response.

↓

2. Check TCP

Does the connection handshake complete?

- Repeated SYNs: investigate missing responses.
- RST: investigate an actively rejected connection.
- Completed handshake: continue to the next layer.

↓

3. Check TLS

Does secure negotiation proceed?

- Visible TLS alert: inspect its details.
- Handshake stalls: investigate timeouts, missing packets, and client/server logs.

↓

4. Check HTTP, if observable

Does the server return an application error?

- 4xx: investigate the request or access conditions.
- 5xx: investigate server or gateway behavior.
- Encrypted HTTPS: use authorized decryption or application logs if the HTTP status is needed.

Correlate the evidence and identify the most likely cause

This approach is called **layer-by-layer troubleshooting**. It prevents you from blaming the wrong component. For example, an HTTP 503 and a DNS timeout are very different failures and require different investigations.

Take your curiosity further
Scan to get the ChatGPT app



11. What a PCAP cannot tell you by itself

This is just as important as knowing the filters.

- A missing response does not prove that a server is down.
- A retransmission does not prove that a packet was lost on the physical network.
- A TCP reset does not prove that an attacker interrupted the connection.
- An HTTP error does not necessarily indicate a network failure.
- Encrypted TLS traffic generally does not reveal the full HTTP content.
- A capture taken at only one endpoint may not show what happened elsewhere on the path.

For stronger conclusions, correlate the PCAP with endpoint logs, server logs, firewall logs, DNS logs, and the exact time of the reported problem.

Recommended next step

If you upload a PCAP file, I can help analyze it and produce a table like this:

Time	Observed packet or sequence	Likely event/error	Evidence	Confidence
10:00:00	DNS query without visible response	Possible DNS timeout	No matching response in the capture	Tentative
10:00:02	Repeated TCP SYN packets	Possible connection failure	No visible SYN-ACK	Tentative
10:00:05	TCP RST from destination	Connection reset/rejection	RST flag set	Observed reset; cause uncertain

The analysis can then distinguish **what the PCAP directly shows, what the evidence suggests, and what additional information is needed to confirm the root cause**.

You

How to resolve these common errors from networking events through pcap

Take your curiosity further
Scan to get the ChatGPT app



ChatGPT


How to resolve common networking errors using PCAP files

A PCAP file helps you **identify where a network problem occurs, understand its likely cause, and verify whether your fix worked**.


However, there is an important distinction: Wireshark analyzes captured traffic; it does not directly repair your network. You use evidence from the PCAP to decide what to change on the client, server, DNS resolver, firewall, or network infrastructure.

We'll go through the most common errors, how to diagnose them, how to resolve them, and how to verify the solution.

1. The complete troubleshooting workflow



Take your curiosity further
Scan to get the ChatGPT app



The following sections apply this workflow to real troubleshooting scenarios.

2. DNS errors and their solutions

DNS translates domain names into IP addresses. If DNS fails, a browser may report that a site cannot be found even when the network connection itself is working.

Case A: DNS query receives no response

Example PCAP pattern:

```
10.0.0.10 → 10.0.0.1    DNS query: example.com
10.0.0.10 → 10.0.0.1    DNS query retry
10.0.0.10 → 10.0.0.1    DNS query retry
                         No visible response
```

Useful Wireshark filter:

```
dns
```

Possible causes

- DNS resolver is unavailable.
- A firewall blocks DNS traffic.
- Routing to the resolver is broken.
- The resolver is overloaded.
- The response is missing from the capture.

How to resolve it

1. Check whether the configured DNS server is reachable.

Take your curiosity further
Scan to get the ChatGPT app

2. Verify the DNS server address on the client.
3. Check firewall rules for DNS traffic, commonly UDP port 53 and, where required, TCP port 53.
4. Inspect the resolver's logs and service status.
5. Test the lookup independently.

On Windows, for example:

```
ipconfig /all
nslookup example.com
```

These commands show the configured network settings and test DNS resolution.

If the resolver is incorrect, correct the client or DHCP configuration. If the resolver is failing, repair its service or upstream resolution path rather than changing the client unnecessarily.

Case B: DNS returns an error

Useful filters:

```
dns.flags.rcode == 3
```

This identifies NXDOMAIN responses.

```
dns.flags.rcode == 2
```

This identifies SERVFAIL responses.

How to resolve it

- For NXDOMAIN, check the spelling of the domain and whether the DNS record should exist.
- For SERVFAIL, inspect resolver logs, upstream DNS connectivity, DNSSEC validation, and zone configuration as applicable.
- If the response comes from an unintended resolver, investigate DHCP settings, VPN configuration, and network policy.

Take your curiosity further
Scan to get the ChatGPT app

Do not automatically replace your DNS server with a public resolver. First determine whether the failure is caused by a typo, a private internal domain, an incorrect resolver, or a genuine resolver outage.

How to verify the fix: Repeat the DNS query, capture it, and confirm that the response is appropriate and that the application can proceed to the next step.

3. TCP connection errors and their solutions

TCP is responsible for establishing a reliable connection between two endpoints.

Case A: Connection timeout

PCAP pattern:

```
Client → Server    SYN
Client → Server    SYN retransmission
Client → Server    SYN retransmission
                   No visible response
```

Wireshark filter:

```
tcp.flags.syn == 1 && tcp.flags.ack == 0
```

This filter shows initial TCP SYN packets. To identify likely retransmissions, also use:

```
tcp.analysis.retransmission
```

Possible causes and fixes

Possible cause	What to do
Server is offline	Check the server's status and listening service.
Firewall silently drops packets	Check firewall rules and logs along the path.

Take your curiosity further
Scan to get the ChatGPT app

Incorrect destination IP or port	Verify DNS resolution, destination address, and service port.
Routing problem	Check the route and router logs.
Server is overloaded	Inspect server health, connection limits, and service logs.
Capture misses return traffic	Capture at both endpoints or at a suitable network observation point.

On Windows, test whether a TCP service is reachable:

```
Test-NetConnection example.com -Port 443
```

Replace the hostname and port with the actual destination.

Important: If SYN packets leave the client but no response is visible, you cannot conclude from that capture alone that the server is offline. The response could be dropped elsewhere or missed by the capture.

Case B: Connection refused

PCAP pattern:

```
Client → Server    SYN
Server → Client    RST, ACK
```

Wireshark filter:

```
tcp.flags.reset == 1
```

Possible causes

- No application is listening on the destination port.
- The service is stopped.
- A firewall or intermediary actively rejects the connection.
- The application is configured to reject the request.

How to resolve it

Take your curiosity further
Scan to get the ChatGPT app

1. Verify the destination IP and port.
2. Check that the expected service is running.
3. Confirm that the service is listening on the correct network interface.
4. Review firewall and security-device rules.
5. Test again and capture the handshake.

For example, if a web server should listen on port 443 but is not listening there, restore the service or correct its configuration. Opening firewall ports unnecessarily will not fix a service that is not listening.

Case C: TCP handshake succeeds, but the application still fails

PCAP pattern:

```
Client → Server    SYN
Server → Client    SYN, ACK
Client → Server    ACK
                   Connection established
                   Application exchange stalls or fails
```

The TCP connection is established, so investigate the next layer instead of continuing to troubleshoot the initial handshake.

Possible fixes depend on the evidence:

- For TLS handshake failure, inspect TLS alerts and server/client configuration.
- For HTTP 4xx or 5xx responses, inspect the request and server application logs.
- For stalled transfers, investigate retransmissions, receive windows, MTU issues, and application behavior.

A successful TCP handshake proves that the handshake completed; it does not prove the application is healthy.

4. Packet loss, retransmissions, and slow connections

These problems often occur after a connection has been established.

Take your curiosity further
Scan to get the ChatGPT app

Case A: Excessive TCP retransmissions

Wireshark filter:

```
tcp.analysis.retransmission
```

Look for repeated transmissions of the same sequence range, acknowledgment patterns, and whether the retransmissions occur across one connection or many connections.

Possible causes

- Congestion or packet loss.
- Unstable Wi-Fi or a faulty network link.
- An overloaded router or network interface.
- A congested or overloaded server.
- Capture loss or packet offloading effects that distort the observed pattern.

How to resolve it

1. Capture at both the client and server if possible.
2. Compare the retransmissions at each capture point.
3. Check interface error counters, Wi-Fi signal quality, switch-port statistics, and router congestion.
4. Check whether the problem affects one connection or many devices.
5. Investigate server load if the issue is concentrated on one server.
6. Correct the identified bottleneck, then repeat the capture.

Do not immediately change TCP timeout or congestion-control settings. First establish whether the problem is actual packet loss, congestion, server delay, or an artifact of the capture.

Case B: Duplicate acknowledgments and out-of-order packets

Filters:

```
tcp.analysis.duplicate_ack
```

Take your curiosity further
Scan to get the ChatGPT app


```
tcp.analysis.out_of_order
```

What to do

- If packets are reordered or lost on a Wi-Fi network, test the wireless link and access point.
- If a particular switch or router interface shows errors, investigate that link.
- If only one server is affected, inspect its network interface, resource usage, and upstream path.
- If the capture is taken on the sending host, compare it with a capture on the receiving host before concluding that packets were lost in transit.

Reordering is not always a fault. TCP is designed to handle it, and a small number of out-of-order packets may be harmless.

Case C: TCP zero-window condition

Wireshark filter:

```
tcp.analysis.zero_window
```

A zero window means the receiving endpoint is temporarily unable to accept additional TCP data.

How to resolve it

1. Identify which endpoint advertises a zero window.
2. Check whether it later advertises a larger window.
3. Inspect the receiving application's processing speed.
4. Check memory pressure, socket buffers, and system resource usage.
5. Investigate whether the sender is overwhelming the receiver.

The correct fix is usually to address the receiver's capacity or processing bottleneck, not to disable TCP flow control.

Take your curiosity further
Scan to get the ChatGPT app

5. TLS and HTTPS errors

TLS protects data exchanged over HTTPS. The TCP connection may succeed even if TLS negotiation fails.

Example PCAP pattern:

```
TCP handshake completes
Client → Server    TLS Client Hello
Server → Client    TLS Alert
Connection closes
```

Useful Wireshark filters:

```
tls
```

```
tls.alert_message
```

The second filter shows TLS alert messages when Wireshark recognizes them. Some failures do not generate a visible alert.

Common causes and fixes

Possible cause	Resolution
Client and server cannot agree on TLS settings	Configure compatible, supported TLS versions and cipher suites.
Certificate expired	Renew the certificate and verify that the server serves the correct certificate.
Hostname mismatch	Configure the certificate for the correct hostname.
Certificate chain is incomplete or untrusted	Correct the certificate chain and trust configuration.
System clock is incorrect	Correct the clock and time synchronization.

Take your curiosity further
Scan to get the ChatGPT app

TLS interception or proxy issue	Inspect proxy configuration and authorized inspection-device logs.

How to investigate properly

1. Confirm that TCP establishment succeeded.
2. Inspect the TLS handshake and any visible alerts.
3. Identify which endpoint sent the alert.
4. Check certificate and TLS configuration on the relevant endpoint.
5. Review the client or server logs for the exact validation or handshake error.
6. Repeat the connection and verify that the handshake progresses normally.

A PCAP alone may not identify the exact certificate validation failure. The client may reject a certificate locally without sending a detailed error to the server, and TLS 1.3 encrypts more handshake information than older versions.

Never resolve certificate errors by permanently disabling certificate validation. Fix the certificate, hostname, trust chain, or clock problem instead.

6. HTTP errors and web application failures

HTTP status codes help you distinguish application-level errors from network-level errors.

For visible, unencrypted HTTP traffic, use:

```
http.response.code >= 400
```

HTTP 400 — Bad Request

Check malformed requests, incorrect headers, invalid parameters, and request formatting. Correct the client request or the component generating it.

HTTP 401 or 403 — Authentication or access problem

Take your curiosity further
Scan to get the ChatGPT app

Verify credentials, authentication tokens, permissions, and access-control rules. Do not bypass security controls to make the error disappear.

HTTP 500 or 503 — Server-side problem

Check application logs, service health, dependencies, resource exhaustion, and server configuration. Fix the underlying service issue.

HTTP 502 or 504 — Gateway or upstream problem

Check reverse-proxy settings, upstream availability, upstream timeouts, and the connection between the gateway and backend.

For example, a `504 Gateway Timeout` may occur because a reverse proxy cannot get a timely response from its backend.

The PCAP might show a client communicating successfully with the proxy, but you may need a separate capture or logs from the proxy-to-backend connection to determine the root cause.

HTTPS limitation: HTTP status codes and request contents are normally encrypted. Without authorized TLS decryption, inspect the visible TLS and TCP behavior and correlate it with web server or proxy logs.

7. ICMP, routing, and MTU errors

These problems can prevent packets from reaching their destinations or can cause large transfers to stall.

Case A: Destination unreachable

Wireshark filter:

```
icmp.type == 3
```

For IPv6:

Take your curiosity further
Scan to get the ChatGPT app


```
icmpv6.type == 1
```

Resolution steps

1. Inspect the ICMP type and code.
2. Determine which router or endpoint generated the message.
3. Check the destination address and route.
4. Inspect firewall rules and routing tables.
5. Correct the route, destination, or policy responsible for the failure.

An unreachable message might indicate an unreachable network, host, or port, depending on the code. Apply the fix to the actual failure rather than treating every ICMP error the same way.

Case B: TTL exceeded

Wireshark filter:

```
icmp.type == 11
```

This can occur during traceroute or when packets encounter a routing loop.

Resolution: Use traceroute or the equivalent platform tool to investigate the route, then inspect routing tables and configuration on the affected routers. Do not simply increase TTL without understanding the path.

Case C: Path MTU problems

Possible signs include small exchanges working while larger transfers stall, or ICMP messages reporting that a packet is too large.

IPv4 filter:

```
icmp.type == 3 && icmp.code == 4
```

IPv6 filter:

Take your curiosity further
Scan to get the ChatGPT app

```
icmpv6.type == 2
```

Resolution

- Check the MTU configured on the endpoints and network interfaces.
- Check whether the network permits the required ICMP Path MTU Discovery messages.
- Correct incorrect tunnel or VPN MTU settings.
- Verify that the network supports the packet sizes being transmitted.

Avoid arbitrarily lowering MTU across the entire network. Confirm the affected path and apply a targeted change.

8. ARP errors and local network connectivity

ARP is used on IPv4 local networks to discover the MAC address associated with an IPv4 address.

Wireshark filter:

```
arp
```

Example:

```
Who has 192.168.1.1?
Who has 192.168.1.1?
Who has 192.168.1.1?
No visible reply
```

This could mean that the gateway is unavailable, the local link is faulty, the address is incorrect, or the response was not captured.

How to resolve it

1. Check the client's IP address, subnet mask, and default gateway.
2. Verify that the gateway and local network are functioning.

Take your curiosity further
Scan to get the ChatGPT app

3. Inspect switch-port and wireless access-point connectivity.
4. Check for duplicate IPv4 addresses.
5. Verify the ARP reply using a fresh capture.

If two devices appear to claim the same IPv4 address, investigate the duplicate-address condition before clearing caches or changing IP assignments.

For IPv6, inspect Neighbor Discovery traffic rather than ARP.

9. A practical error-to-fix reference

Use this table when you need to decide what to investigate first.

PCAP observation	Likely problem	First action
DNS query with no visible response	Possible DNS timeout	Check resolver reachability and DNS logs
DNS response with NXDOMAIN	Domain does not exist according to DNS	Verify the name and expected DNS records
Repeated SYN packets, no visible reply	Possible TCP timeout	Check routing, firewalls, server, and capture point
SYN followed by RST	Connection rejected or reset	Check the destination port, service, and security rules
Frequent TCP retransmissions	Possible loss or congestion	Compare captures and inspect link statistics
TCP zero-window packets	Receiver cannot currently accept more data	Investigate receiver resources and application processing
TLS handshake alert	Secure negotiation problem	Inspect TLS settings and endpoint logs
HTTP 503	Service unavailable	Inspect server, proxy, and dependency health
ICMP destination unreachable	Delivery or reachability failure	Inspect ICMP code, route, and firewall
Repeated ARP requests without visible replies	Possible local network or address-resolution issue	Check gateway, local link, and address configuration

Take your curiosity further
Scan to get the ChatGPT app

These observations indicate where to start investigating; none automatically identifies the root cause in every situation.

10. How to verify that your fix worked

Never stop at applying a configuration change. Capture the traffic again and compare the before-and-after behavior.

Before the fix
Save the original PCAP, note the affected host, destination, timestamp, and error pattern.

Apply the fix
Correct the identified DNS, service, firewall, routing, TLS, or application configuration.

Capture again
Repeat the same operation under comparable conditions and collect a new PCAP.

Compare the results
Confirm that DNS responses arrive, TCP handshakes complete, retransmissions decrease where appropriate, TLS negotiation succeeds, and the application works.

For example, if the original capture showed repeated SYN packets without a visible response, the new capture should show the expected SYN, SYN-ACK, and ACK sequence if the connection is now succeeding.

If the handshake succeeds but the website still fails, continue investigating the TLS or HTTP layer rather than assuming the whole problem is resolved.

11. Practice: Select an error and learn how to fix it

Choose a networking problem

Take your curiosity further
Scan to get the ChatGPT app

TCP connection timeout

DNS resolution failure

TCP retransmissions

TLS handshake failure

HTTP 5xx error

TCP connection timeout

Repeated SYN packets without a visible SYN-ACK.

Wireshark filter

```
tcp.flags.syn == 1 && tcp.flags.ack == 0
```

Copy

Troubleshooting steps

1. Verify the destination IP and port.
2. Check server availability and listening services.
3. Inspect firewall rules, routes, and the capture point.
4. Capture again to verify the handshake.

Explain this error in depth

My recommendation

If your goal is to learn practical network troubleshooting or build a cybersecurity tool that detects errors from PCAP files, start with **DNS failures, TCP connection failures, TCP retransmissions, TLS handshake failures, and HTTP errors**.

Once you understand these patterns, you can automate their detection using Python and Scapy or TShark. The key is to classify each finding as an observed packet condition, a likely error, or a confirmed root cause—rather than treating every suspicious packet as a proven failure.

Take your curiosity further
Scan to get the ChatGPT app