

Audit Report for Project PasswordStore

May 14, 2025

Prepared by: [Gabriel Acero](#) Lead Security Researcher:

- Gabriel Acero

Table of Contents

- [Audit Report for Project PasswordStore](#)
- [Table of Contents](#)
- [Protocol Summary](#)
- [Disclaimer](#)
- [Risk Classification](#)
- [Audit Details](#)
 - [Scope](#)
 - [Roles](#)
 - [Issues found](#)
- [Findings](#)
 - [High](#)
 - [\[H-1\] Storing the password on-chain makes it visible to anyone, and no longer private.](#)
 - [\[H-2\] `PasswordStore::setPassword` has no access controls, meaning a non-owner could change the password.](#)
 - [Informational](#)
 - [\[I-1\] The `PasswordStore::getPassword` natspec indicates a parameter that doesn't exist, causing the natspec to be incorrect](#)

Protocol Summary

PasswordStore is a protocol dedicated to storage and retrieval of a user's passwords. The protocol is designed to be used by a single user, and is not designed to be used by multiple users. Only the owner should be able to set and access this password.

Disclaimer

Gabriel Acero makes all effort to find as many vulnerabilities in the code in the given time period, but holds no responsibilities for the findings provided in this document. A security audit by the team is not an endorsement of the underlying business or product. The audit was time-boxed and the review of the code was solely on the security aspects of the Solidity implementation of the contracts.

Risk Classification

Impact				
		High	Medium	Low
High		H	H/M	M
Likelihood	Medium	H/M	M	M/L
Low		M	M/L	L

I use the [CodeHawks](#) severity matrix to determine severity. See the documentation for more details.

Audit Details

```
2e8f81e263b3a9d18fab4fb5c46805ffc10a9990
```

Scope

```
./src/  
#-- PasswordStore.sol
```

Roles

- Owner: The user who can set the password and read the password.
- Outsiders: No one else should be able to set or read the password.

Issues found

Severity	Number of issues found
High	2
Medium	0
Low	0
Info	1
Total	3

Findings

High

[H-1] Storing the password on-chain makes it visable to anyone, and no longer private.

Description: All data stored on-chain is visible to anyone, and can be read directly from the blockchain. The `PasswordStore::s_password` variable is intended to be a private variable and only accessed through the `PasswordStore::s_password` function, which is intended to be only called by the owner of the contract.

We show one such method of reading any data off chain below

Impact: Anyone can read the private password, severely breaking the functionality of the protocol.

Proof of Concept: (Proof of Code)

The below test case shows how anyone can read the password directly from the blockchain.

Recommended Mitigation: Due to this, the overall architecture of the contract should be rethought. One could encrypt the password off-chain, and then store the encrypted password on-chain. This would require the user to remember another password off-chain to decrypt the password. However, you'd also likely want to remove the view function as you wouldn't want the user to accidentally send a transaction with the password that decrypts your password.

[H-2] `PasswordStore::setPassword` has no access controls, meaning a non-owner could change the password.

Description: The `PasswordStore::setPassword` function is set to be an `external` function, however, the natspec of the function and overall purpose of the smart contract is that `This function allows only the owner to set a new password.`

```
function setPassword(string memory newPassword) external {
@>    // @audit - There are no access controls
    s_password = newPassword;
    emit SetNetPassword();
}
```

Impact: Anyone can set/change the password of the contract, severely breaking the contract intended functionality.

Proof of Concept: Add the following to the `PasswordStore.t.sol` test file.

► Code

```
function test_anyone_can_set_password(address randomAddress) public {
    vm.assume(randomAddress != owner);
    vm.prank(randomAddress);
    string memory expectedPassword = "myNewPassword";
    passwordStore.setPassword(expectedPassword);

    vm.prank(owner);
    string memory actualPassword = passwordStore.getPassword();
    assertEq(actualPassword, expectedPassword);
}
```

Recommended Mitigation: Add an access control conditional to the `setPassword` function.

```
if (msg.sender != owner) {  
    revert PasswordStore_NotOwner();  
}
```

Informational

[I-1] The `PasswordStore::getPassword` natspec indicates a parameter that doesn't exist, causing the natspec to be incorrect

Description:

```
/*  
 * @notice This allows only the owner to retrieve the password.  
 // @audit there is no newPassword parameter!  
 * @param newPassword The new password to set.  
 */  
function getPassword() external view returns (string memory) {}
```

The `PasswordStore::getPassword` function signature is `getPassword()` which the natspec says it should be `getPassword(string)`.

Impact: The natspec is incorrect.

Recommended Mitigation: Remove the incorrect natspec line.

```
-    * @param newPassword The new password to set.
```