

Reference

Acetil, Xook.Vector, rafaelososotolopez

Today!

Contents

1	Language stuff	1		
1.1	Libraries and stuff	1		
1.2	Compiling	1		
1.3	String reading	1		
1.3.1	Reading lines	1		
1.3.2	String streams	1		
1.3.3	Appending to string	1		
2	Algorithms	2		
2.1	Segment tree	2		

1 Language stuff

1.1. Libraries and stuff

```
#include <bits/stdc++.h>
using namespace std;

// If no bits available
#include <iostream>
#include <algorithm>
#include <vector>
#include <map>
#include <set>
// iostream
#include <sstream>
// Math stuff
#include <cmath>

// fastio
#define fastio \
    ios::sync_with_stdio(0); \
    cin.tie(0);
```

1.2. Compiling

```
# For version
g++ --version

# To compile
# Or 17, 20...
g++ -std=c++21 -o main <source file>

# To pipe testcases to binary
./main < text.txt
```

1.3. String reading

1.3.1. Reading lines

```
#include <iostream>
using namespace std;
int main() {
    string line;
    // Stores the whole line in "line",
    // without the newline \n
    getline(cin, line);
    // ignore the newline in the buffer
    cin.ignore();
}
```

1.3.2. String streams

```
#include <sstream>
using namespace std;
int main() {
    string a;
    // Allows to put stuff into oss,
    // built from a
    ostringstream oss(a);

    oss << 5;

    string ans1 = oss.str();
}
```

1.3.3. Appending to string

```
#include <string>
using namespace std;
int main() {
    string s;
    string a;

    // joins two strings (appends)
    s.append(a);

    // puts a character
    s.push_back('a');
}
```

2 Algorithms

2.1. Segment tree

2.1.1. Recursive SegTree

```
#include <bits/stdc++.h>

using namespace std;

struct Node
{
    int value = INT_MAX;
};

Node operate(Node a, Node b)
{
    return {min(a.value, b.value)};
}

int n, q;
vector<Node> nums, tree;

void build(int index, int low, int high)
{
    if(low == high)
    {
        tree[index].value = nums[low].value;
        return;
    }

    int mid = low + (high - low)/2;
    build(index<<1, low, mid);
    build(index<<1^1, mid+1, high);

    tree[index] = operate(tree[index<<1], tree[index<<1^1]);
}

Node query(int a, int b, int index = 1, int low = 0, int high = n-1)
{
    if(high < a || b < low)
        return {INT_MAX};

    if(a <= low && high <= b)
        return tree[index];

    int mid = low + (high - low)/2;
    Node left = query(a, b, index<<1, low, mid);
    Node right = query(a, b, index<<1^1, mid+1, high);

    return operate(left, right);
}

void update(int pos, int val, int index = 1, int low = 0, int high = n-1)
{
    if(low == high)
    {
        tree[index].value = val;
        return;
    }

    int mid = low + (high - low)/2;

    if(pos <= mid)
        update(pos, val, index<<1, low, mid);
    else
        update(pos, val, index<<1^1, mid+1, high);

    tree[index] = operate(tree[index<<1], tree[index<<1^1]);
}

void _solve()
{
    int type; cin >> type;

    if(type == 1)
    {
        int k, u; cin >> k >> u;
        update(k-1, u);
    }
    else
    {
        int a, b; cin >> a >> b;

        Node ans = query(a-1, b-1);

        cout << ans.value << "\n";
    }
}
```

```
}

void solve()
{
    cin >> n >> q;

    nums.assign(n, {});
    tree.assign(4*n + 1, {INT_MAX});

    for(Node& i : nums) cin >> i.value;

    build(1, 0, n-1);

    while(q--)
        _solve();
}

int main()
{
    ios_base::sync_with_stdio(false);
    cin.tie(NULL);
    cout.tie(NULL);

    solve();

    return 0;
}
```

2.2. GCD

```
long long gcd(long long a, long long b)
{
    if(b == 0) return a;

    return gcd(b, a % b);
}
```

2.3. Binpow

```
const int MOD = 1e9 + 7;

long long binpow(long long x, long long n)
{
    long long ans = 1;

    while(n > 0)
    {
        if(n & 1)
            ans = (ans * x) % MOD;

        x = (x * x) % MOD;
        n >>= 2;
    }

    return ans % MOD;
}
```

2.4. Prim

```
#include <bitset>
#include <vector>
#include <queue>
using namespace std;
long long dijkstra(
    vector<vector<pair<int, int>>> const& adj
)
{
    long long ans = 0;
    priority_queue<
        pair<long long, int>,
        vector<pair<long long, int>>,
        greater<pair<long long, int>>>
    > next;
    next.push({0, 1});
    bitset<100005> visited;
    while (!next.empty())
    {
        auto [cost, node] = next.top();
        next.pop();
        if (visited[node])
            continue;
        visited.set(node);
        ans += cost;
    }
}
```

```

    for (auto [nc, nn] : adj[node])
    {
        if (visited[nn])
            continue;
        next.push({nc, nn});
    }
    return ans;
}

```

2.5. Dijkstra

```

#include <vector>
#include <queue>
#include <climits>
using namespace std;
long long dijkstra(
    vector<vector<pair<int, int>>> const& adj,
    int start, int goal
)
{
    int n = adj.size();
    vector<long long> distance(n+1, LLONG_MAX);

    priority_queue<
        pair<long long, long long>,
        vector<pair<long long, long long>>,
        greater<pair<long long, long long>>>
        next;
    // {cost, node}
    next.push({0, start});

    while (!next.empty())
    {
        auto [weight, node] = next.top();
        next.pop();

        if (weight >= distance[node])
            continue;

        distance[node] = weight;

        for (auto [nweight, nnode] : adj[node])
        {
            if (nweight + distance[node] >= distance[nnode])
                continue;
            next.push({nweight + distance[node], nnode});
        }
    }
    return distance[goal];
}

```

2.6. Kahn

```

#include <bits/stdc++.h>
using namespace std;
int V; // Number of vertices
int E; // Number of edges
vector<int> indegree(V+1, 0);

vector<int> kahn(vector<vector<int>> const& graph)
{
    vector<int> order, deg = indegree; // copy
    queue<int> q;
    for(int i = 1; i <= V; i++)
        if(deg[i] == 0)
            q.push(i);
    while(!q.empty()) {
        int u = q.front(); q.pop();
        order.push_back(u);
        for(int v : graph[u]) {
            deg[v]--;
            if(deg[v] == 0)
                q.push(v);
        }
    }
    return order;
};

```

3.1. DSU

```

#include <bits/stdc++.h>
using namespace std;
vector<int> parent;
vector<int> _size;

void make_set(int v) {
    parent[v] = v;
    _size[v] = 1;
}

int find_set(int v) {
    if (v == parent[v])
        return v;
    return parent[v] = find_set(parent[v]);
}

// Union by size/rank - small to large
void union_sets(int a, int b) {
    a = find_set(a);
    b = find_set(b);
    if (a != b) {
        if (_size[a] < _size[b])
            swap(a, b);
        parent[b] = a;
        _size[a] += _size[b];
    }
}

```

3.2. Ordered Set

```

// Common file
#include <ext/pb_ds/assoc_container.hpp>
// Including tree_order_statistics_node_update
#include <ext/pb_ds/tree_policy.hpp>

using namespace std;
using namespace __gnu_pbds;

typedef tree<
    int,
    nulltype,
    less<int>,
    rb_tree_tag,
    tree_order_statistics_node_update>
    ordered_set;

```

4.1. Sum of divisors

```

void sum_all_divisors(int n, vector<long long>& sigma)
{
    sigma.assign(n+1, 1);

    for(int i = 2; i <= n; i++)
        for(int j = i; j <= n; j += i)
            sigma[j] += i;
}

```

4.2. Hashing

$$H(s) = (s_i p^{i-1} + s_{i+1} p^i + \dots) \% M = \sum_{i=1}^{|s|} s_i p^{i-1} \% M$$

$$M_1 = 127657753, \quad p_1 = 137$$

$$M_2 = 987654319, \quad p_2 = 277$$