

操作系统第一次上机报告

姓名：刘晨旭 学号：20232241110 班级：软件2306

1. 目标

熟悉并掌握Linux pthread编程

熟练掌握pthread库的同步、互斥机制，并能应用来解决实际问题

熟悉Linux环境下pthread编程

完成示例代码的编译与执行：

- nosync-ex.c
- mutex-ex.c
- sem-ex.c

nosync-ex.c

```
#include <stdio.h>
#include <pthread.h>

int sum = 0;

void *thread(void *arg) {
    int i;
    for (i = 0; i < 1000000; i++) {
        sum++;
    }
}

int main(void) {
    pthread_t tid1, tid2;
    pthread_create(&tid1, NULL, thread, NULL);
    pthread_create(&tid2, NULL, thread, NULL);
    pthread_join(tid1, NULL);
    pthread_join(tid2, NULL);
    printf("1000000 + 1000000 = %d\n", sum);
    return 0;
}
```

使用下面的指令来编译

```
gcc -o nosync-ex nosync-ex.c -lpthread
```

输入下面的指令来运行

```
./nosync-ex
```

运行结果如下图所示

```
[acidbarium@localhost machineFirst]$ ./nosync-ex
1000000 + 1000000 = 1117746
[acidbarium@localhost machineFirst]$
```

由于这段代码有多线程对全局变量 `sum` 的竞态条件，导致结果不正确。

mutex-ex.c

代码如下

```
#include <pthread.h>
#include <stdio.h>

int sum = 0;
pthread_mutex_t mutex;

void* thread(void*arg) {
    int i;
    for (i = 0; i < 1000000; i++) {
        pthread_mutex_lock(&mutex);
        sum++;
        pthread_mutex_unlock(&mutex);
    }
}

int main(void) {
    pthread_t tid1, tid2;

    pthread_mutex_init(&mutex, NULL);

    pthread_create(&tid1, NULL, thread, NULL);
    pthread_create(&tid2, NULL, thread, NULL);

    pthread_join(tid1, NULL);
    pthread_join(tid2, NULL);

    printf("1000000 + 1000000 = %d\n", sum);

    pthread_mutex_destroy(&mutex);
    return 0;
}
```

使用下面的指令来编译

```
gcc -o mutex-ex mutex-ex.c -lpthread
```

输入下面的指令来运行

```
./mutex-ex
```

运行结果如下图所示

```
[acidbarium@localhost machineFirst]$ ./mutex-ex
1000000 + 1000000 = 2000000
[acidbarium@localhost machineFirst]$
```

这段代码用互斥锁保证了多线程对 sum 的互斥访问，避免了竞态条件，所以结果正确。

sem-ex.c

代码如下

```
#include <pthread.h>
#include <semaphore.h>
#include <stdio.h>

int sum = 0;
sem_t sem;

void* thread(void*arg) {
    int i;
    for (i = 0; i < 1000000; i++) {
        sem_wait(&sem);
        sum++;
        sem_post(&sem);
    }
}

int main(void) {
    pthread_t tid1, tid2;

    sem_init(&sem, 0, 1);

    pthread_create(&tid1, NULL, thread, NULL);
    pthread_create(&tid2, NULL, thread, NULL);

    pthread_join(tid1, NULL);
    pthread_join(tid2, NULL);

    printf("1000000 + 1000000 = %d\n", sum);

    sem_destroy(&sem);
    return 0;
}
```

使用下面的指令来编译

```
gcc -o sem-ex sem-ex.c -lpthread
```

输入下面的指令来运行

```
./sem-ex
```

运行结果如下图所示

```
[acidbarium@localhost machineFirst]$ ./sem-ex
1000000 + 1000000 = 2000000
[acidbarium@localhost machineFirst]$
```

这段代码用信号量实现了对 sum 的互斥访问，避免了竞态条件，所以结果正确。

基于示例中涉及到的线程同步API，实现生产者消费者问题（具体的生产、消费操作可自行设计），检查时需能清楚说明程序设计思路。

编写代码如下所示

```
#include <pthread.h>
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#include <time.h>
#include <semaphore.h>

int sum = 0;

pthread_mutex_t mutex = PTHREAD_MUTEX_INITIALIZER;
sem_t not_empty;

void* producer(void* arg) {
    while (1) {

        pthread_mutex_lock(&mutex);
        sum++;
        printf("Producer produced an item. Current sum: %d\n", sum);

        sem_post(&not_empty);
        pthread_mutex_unlock(&mutex);

        sleep(rand() % 2 + 1);
    }

    return NULL;
}

void* consumer(void* arg) {
    while (1) {
        sem_wait(&not_empty);

        pthread_mutex_lock(&mutex);

        sum--;
        printf("Consumer consumed an item. Current sum: %d\n", sum);

        pthread_mutex_unlock(&mutex);

        sleep(rand() % 2 + 2);
    }
}
```

```

    return NULL;
}

int main() {
    pthread_t producers[2], consumers[2];

    srand(time(0));

    sem_init(&not_empty, 0, 0);

    for (int i = 0; i < 2; i++) {
        pthread_create(&producers[i], NULL, producer, NULL);
        pthread_create(&consumers[i], NULL, consumer, NULL);
    }

    for (int i = 0; i < 2; i++) {
        pthread_join(producers[i], NULL);
        pthread_join(consumers[i], NULL);
    }

    sem_destroy(&not_empty);

    return 0;
}

```

主线程初始化:

初始化互斥锁和信号量，创建 2 个生产者线程和 2 个消费者线程。

生产者线程流程:

加锁，sum++ 表示生产一个物品。
 打印当前 sum。
 sem_post 增加信号量，通知有物品可消费。
 解锁，随机休眠 1~2 秒。

消费者线程流程:

sem_wait 等待信号量，确保有物品可消费。
 加锁，sum-- 表示消费一个物品。
 打印当前 sum。
 解锁，随机休眠 2~3 秒。

使用下面的指令来编译


```
gcc -o produceConsum produceConsum.c -lpthread
```

输入下面的指令来运行

```
./produceConsum
```

运行结果如下图所示

```
[acidbarium@localhost machineFirst]$ ./produceConsume
Producer produced an item. Current sum: 1
Producer produced an item. Current sum: 2
Consumer consumed an item. Current sum: 1
Consumer consumed an item. Current sum: 0
Producer produced an item. Current sum: 1
Consumer consumed an item. Current sum: 0
Producer produced an item. Current sum: 1
Consumer consumed an item. Current sum: 0
Producer produced an item. Current sum: 1
Consumer consumed an item. Current sum: 1
Producer produced an item. Current sum: 2
Consumer consumed an item. Current sum: 1
Producer produced an item. Current sum: 2
Consumer consumed an item. Current sum: 1
Producer produced an item. Current sum: 2
Producer produced an item. Current sum: 3
Producer produced an item. Current sum: 4
Consumer consumed an item. Current sum: 3
Consumer consumed an item. Current sum: 2
Producer produced an item. Current sum: 3
Producer produced an item. Current sum: 4
Producer produced an item. Current sum: 5
Consumer consumed an item. Current sum: 4
Consumer consumed an item. Current sum: 3
Producer produced an item. Current sum: 4
Producer produced an item. Current sum: 5
Producer produced an item. Current sum: 6
Producer produced an item. Current sum: 7
Consumer consumed an item. Current sum: 6
Consumer consumed an item. Current sum: 5
Producer produced an item. Current sum: 6
Producer produced an item. Current sum: 7
Consumer consumed an item. Current sum: 6
Consumer consumed an item. Current sum: 5
Producer produced an item. Current sum: 6
Producer produced an item. Current sum: 7
^C
[acidbarium@localhost machineFirst]$
```



代码阅读

pthread-ex01

```
#include <stdio.h>
#include <pthread.h>

void *thread(void *vargp) {
    pthread_exit((void *)42);
}

int main(){
    int i;
    pthread_t tid;
    pthread_create(&tid, NULL, thread, NULL);
    pthread_join(tid, (void **)&i);
    printf ("%d\n", i);
    return 0;
}
```

代码理解

主线程创建一个子线程，子线程运行后立即退出并返回 42，主线程通过 pthread_join 获取该返回值，并将其输出。

pthread-ex02

```
#include <stdio.h>
#include <stdlib.h>
#include <pthread.h>

void *thread(void *vargp) {
    exit(42);
}

int main(){
    int i;
```

```

pthread_t tid;
pthread_create(&tid, NULL, thread, NULL);
pthread_join(tid, (void **)&i);
printf ("%d\n", i);
return 0;
}

```

代码理解

该程序创建一个子线程，子线程在执行过程中调用 `exit(42)` 直接终止整个进程，导致主线程无法正常回收子线程的返回值,最终无法`printf`输出。

pthread-ex03

```

#include <stdio.h>
#include <pthread.h>

void *thread(void *vargp) {
    int *ptr = (int*)vargp;
    pthread_exit((void*)*ptr);
}

void *thread2(void *vargp) {
    int *ptr = (int*)vargp;
    *ptr = 0;
    pthread_exit((void*)31);
}

int main() {
    int i = 42;
    pthread_t tid, tid2;
    pthread_create(&tid, NULL, thread, (void*)&i);
    pthread_create(&tid2, NULL, thread2, (void*)&i);
    pthread_join(tid, (void **)&i);
    pthread_join(tid2, NULL);
    printf("%d\n",i);
}

```

代码理解

该程序创建了两个线程，其中第一个线程将传入的整数指针所指向的值作为返回值退出，而第二个线程修改了该整数值并退出；主线程在回收第一个线程时获取了该整数值作为返回值，最终打印该值。

pthread-ex-04

```

#include <stdio.h>
#include <stdlib.h>
#include <pthread.h>

void *thread(void *vargp) {
    pthread_detach(pthread_self());
    pthread_exit((void*)42);
}

```

```

int main() {
    int i = 0;
    pthread_t tid;
    pthread_create(&tid, NULL, thread, (void*)&i);
    pthread_join(tid, (void**)&i);
    printf("%d\n", i);
}

```

代码理解

由于未能正确回收子线程的返回值，i 的值无法预期，可能导致程序输出不确定的值或者程序崩溃。

pthread-ex-05

```

#include <stdio.h>
#include <pthread.h>

int i = 42;

void *thread(void *vargp) {
    printf("%d\n", i);
}

void *thread2(void *vargp) {
    i = 31;
}

int main() {
    pthread_t tid, tid2;
    pthread_create(&tid2, NULL, thread2, (void*)&i);
    pthread_create(&tid, NULL, thread, (void*)&i);
    pthread_join(tid, (void**)&i);
    pthread_join(tid2, NULL);
}

```

代码理解

该程序创建了两个线程，其中第一个线程打印全局变量 i 的值，第二个线程修改该变量的值；主线程等待两个子线程完成，但由于线程执行的并发性，i 的最终值在不同的执行情况下可能不同。

pthread-ex-06

```

#include <stdio.h>
#include <stdlib.h>
#include <pthread.h>

void *foo(void *vargp) {
    int myid;
    myid = *((int *)vargp);
    free(vargp);
    printf("Thread %d\n", myid);
}

```



```
int main() {
    pthread_t tid[2];
    int i, *ptr;
    for (i = 0; i < 2; i++) {
        ptr = malloc(sizeof(int));
        *ptr = i;
        pthread_create(&tid[i], 0, foo, ptr);
    }
    pthread_join(tid[0], 0);
    pthread_join(tid[1], 0);
}
```

代码理解

该程序创建了两个线程，每个线程接收一个动态分配的内存（包含线程编号），在执行时打印线程编号并释放该内存；主线程等待两个子线程完成后退出。

pthread-ex-07

```
#include <stdio.h>
#include <stdlib.h>
#include <pthread.h>

void *foo(void *vargp) {
    int myid;
    myid = *((int *)vargp);
    printf("Thread %d\n", myid);
}

int main() {
    pthread_t tid[2];
    int i;
    for (i = 0; i < 2; i++) {
        pthread_create(&tid[i], 0, foo, &i);
    }
    pthread_join(tid[0], 0);
    pthread_join(tid[1], 0);
}
```

代码理解

由于访问冲突和访问时间问题，输出可能会出现不可预测的结果。例如，两个线程可能都打印 Thread 1，因为它们都读取到了相同的 i 值；如果两个线程都稍微慢一些，有可能都输出 2。

理发师问题

编写代码如下所示

```
#include <pthread.h>
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#include <semaphore.h>

#define TOTAL_CUSTOMERS 20 //
```

```

pthread_mutex_t mutex = PTHREAD_MUTEX_INITIALIZER;
sem_t customer;

int customers_waiting = 0;
int total_customers = TOTAL_CUSTOMERS;

void* barber(void* arg) {
    while (1) {
        sem_wait(&customer); // 没顾客就阻塞
        pthread_mutex_lock(&mutex);

        customers_waiting--;
        printf("Barber: Cutting hair... Customers waiting: %d\n",
customers_waiting);
        total_customers--;

        pthread_mutex_unlock(&mutex);

        sleep(rand() % 2 + 1); // 理发时间

        if (total_customers == 0) {
            printf("Barber: All customers done, going to sleep.\n");
            break;
        }
    }
    return NULL;
}

void* client(void* arg) {
    pthread_mutex_lock(&mutex);
    customers_waiting++;
    printf("Customer arrived! Customers waiting: %d\n", customers_waiting);
    pthread_mutex_unlock(&mutex);

    sem_post(&customer); // 通知理发师
    return NULL;
}

int main() {
    pthread_t barber_tid, customer_tids[TOTAL_CUSTOMERS];
    srand(time(0));

    sem_init(&customer, 0, 0);

    pthread_create(&barber_tid, NULL, barber, NULL);

    for (int i = 0; i < TOTAL_CUSTOMERS; i++) {
        usleep((rand() % 1500000)); // 顾客随机到店, 单位微秒
        pthread_create(&customer_tids[i], NULL, client, NULL);
    }

    for (int i = 0; i < TOTAL_CUSTOMERS; i++) {
        pthread_join(customer_tids[i], NULL);
    }
}

```

```
pthread_join(barber_tid, NULL);

sem_destroy(&customer);
return 0;
}
```

运行结果如下图所示

```
Barber: Cutting hair... Customers waiting: 0
Customer arrived! Customers waiting: 1
Barber: Cutting hair... Customers waiting: 0
Barber: All customers done, going to sleep.
[acidbarium@localhost code]$ vim barber.c
[acidbarium@localhost code]$ gcc barber.c -o barber
[acidbarium@localhost code]$ ./barber
Customer arrived! Customers waiting: 1
Barber: Cutting hair... Customers waiting: 0
Customer arrived! Customers waiting: 1
Barber: Cutting hair... Customers waiting: 0
Customer arrived! Customers waiting: 1
Barber: Cutting hair... Customers waiting: 0
Customer arrived! Customers waiting: 1
Barber: Cutting hair... Customers waiting: 0
Customer arrived! Customers waiting: 1
Customer arrived! Customers waiting: 2
Barber: Cutting hair... Customers waiting: 1
Customer arrived! Customers waiting: 2
Customer arrived! Customers waiting: 3
Barber: Cutting hair... Customers waiting: 2
Customer arrived! Customers waiting: 3
Barber: Cutting hair... Customers waiting: 2
Customer arrived! Customers waiting: 3
Customer arrived! Customers waiting: 4
Barber: Cutting hair... Customers waiting: 3
Customer arrived! Customers waiting: 4
Customer arrived! Customers waiting: 5
Barber: Cutting hair... Customers waiting: 4
Customer arrived! Customers waiting: 5
Customer arrived! Customers waiting: 6
Customer arrived! Customers waiting: 7
Barber: Cutting hair... Customers waiting: 6
Customer arrived! Customers waiting: 7
Barber: Cutting hair... Customers waiting: 6
Customer arrived! Customers waiting: 7
Customer arrived! Customers waiting: 8
Barber: Cutting hair... Customers waiting: 7
Barber: Cutting hair... Customers waiting: 6
Barber: Cutting hair... Customers waiting: 5
Barber: Cutting hair... Customers waiting: 4
Barber: Cutting hair... Customers waiting: 3
Barber: Cutting hair... Customers waiting: 2
Barber: Cutting hair... Customers waiting: 1
Barber: Cutting hair... Customers waiting: 0
Barber: All customers done, going to sleep.
[acidbarium@localhost code]$
```



git 日志

部分git的记录如下所示

```
D:\githubRes\osHomework\machineFirst>git log
commit 3c45ecde461bffff2d6fb2ac182ecd3e2fbc2adf1 (HEAD -> main, origin/main,
origin/HEAD)
Author: Acidbarium <acidbarium@localhost.localdomain>
Date: Tue May 13 21:41:57 2025 +0800
```

修改代码

```
commit c719e63cf36eb5d1d3d3410db764976fc956c6ec
Author: Acidbarium <acidbarium@163.com>
Date: Tue May 13 22:55:21 2025 +0800
```

```
Update barber.c
```

```
commit ccf4157a8188e6912036d8380bf4bc6665d1eeaf
Author: Acidbarium <acidbarium@localhost.localdomain>
Date: Tue May 13 21:37:15 2025 +0800
```

编译

```
commit 786c87db168e94caa73608f883543475c59a4dd8
Author: Acidbarium <acidbarium@163.com>
```

Date: Tue May 13 22:51:10 2025 +0800

Update barber.c

commit bf25130aa8b3a0f4eaa5a073b97900fadec093ca
Author: Acidbarium <acidbarium@localhost.localdomain>
Date: Tue May 13 21:32:51 2025 +0800

修改理发师代码

:...skipping...
commit 3c45ecde461bfff2d6fb2ac182ecd3e2fbc2adf1 (HEAD -> main, origin/main, origin/HEAD)
Author: Acidbarium <acidbarium@localhost.localdomain>
Date: Tue May 13 21:41:57 2025 +0800

修改代码

commit c719e63cf36eb5d1d3d3410db764976fc956c6ec
Author: Acidbarium <acidbarium@163.com>
Date: Tue May 13 22:55:21 2025 +0800

Update barber.c

commit ccf4157a8188e6912036d8380bf4bc6665d1eeaf
Author: Acidbarium <acidbarium@localhost.localdomain>
Date: Tue May 13 21:37:15 2025 +0800

编译

commit 786c87db168e94caa73608f883543475c59a4dd8
Author: Acidbarium <acidbarium@163.com>
Date: Tue May 13 22:51:10 2025 +0800

Update barber.c

commit bf25130aa8b3a0f4eaa5a073b97900fadec093ca
Author: Acidbarium <acidbarium@localhost.localdomain>
Date: Tue May 13 21:32:51 2025 +0800

修改理发师代码

commit 61d71bf044ee64b77257ce2c621dc6df74feb8d4
Author: Acidbarium <acidbarium@163.com>
Date: Tue May 13 22:41:52 2025 +0800

Create barber.c

commit 962f84955722cc014c12d403d4c2c05bb4a4f3c4
Author: Acidbarium <acidbarium@163.com>
Date: Tue May 13 22:35:04 2025 +0800

移动代码到code文件夹

commit 960c5f8d88ceb09a484c6811f1abdbd258da339d
Author: Acidbarium <acidbarium@163.com>
Date: Tue May 13 22:32:04 2025 +0800

Create 第一次上机实验报告_软件2306_20232241110_刘晨旭.pdf

commit 7426b47b7de9bdf4d6107f438dfa03287a38ae32

Author: Acidbarium <acidbarium@163.com>

Date: Tue May 13 22:29:00 2025 +0800

仓库地址

仓库作业地址为: [github.com AcidBarium osHomework](https://github.com/AcidBarium/osHomework)