

# OSI Complete 7-Layer Architectural & Protocol Reference Guide

---

Comprehensive academic analysis of Layers 1 through 7: physical signaling, framing & trailers, IP routing & CIDR, transport state machines, session checkpoints, presentation syntax & TLS 1.3, and application protocols.

## 1. Layered Architecture & Protocol Data Units (PDUs)

---

Modern network communication organizes protocols into discrete hierarchical abstraction layers. As application data travels down the stack at the sending host, each layer wraps the payload with layer-specific control headers (and trailers), creating a distinct **Protocol Data Unit (PDU)**.

- **SDU (Service Data Unit):** The pure payload delivered from an upper layer before encapsulation.
- **PDU (Protocol Data Unit):** The encapsulated block (  $\text{PDU} = \text{Header} + \text{SDU} + \text{Trailer}$  ).
- **7-Layer Mnemonics:**
  - Top-to-Bottom (7 → 1): *"All People Seem To Need Data Processing"*
  - Bottom-to-Top (1 → 7): *"Please Do Not Throw Sausage Pizza Away"*
  - PDU Mnemonic (7 → 1): *"Don't Spill Peanut Flavor Bits"* → **D**ata (L7–5), **S**egments (L4), **P**ackets (L3), **F**rames (L2), **B**its (L1).

| OSI Layer                    | PDU Name                       | Addressing Scheme                             | Core Protocols                                             | Hardware & System Components                                     |
|------------------------------|--------------------------------|-----------------------------------------------|------------------------------------------------------------|------------------------------------------------------------------|
| <b>Layer 7: Application</b>  | Data / Application Message     | URLs, URIs, FQDNs, Email Addresses            | HTTP/1.1, HTTP/2, HTTP/3, DNS, DHCP, SSH, SMTP, IMAP       | Web browsers, Mail clients, DNS servers, Application daemons     |
| <b>Layer 6: Presentation</b> | Data / Formatted Record        | MIME types, Object Identifiers (OID)          | TLS 1.3 Record Layer, ASN.1 (BER/DER), Protobuf, XDR, JSON | OS serialization libraries, Crypto accelerators (AES-NI), Codecs |
| <b>Layer 5: Session</b>      | Data / Session PDU             | Session IDs, Connection Handles, SOCKS tokens | NetBIOS, RPC, SOCKS5, PPTP, SIP, TLS Resumption            | OS socket subsystems, RPC runtimes, Session border controllers   |
| <b>Layer 4: Transport</b>    | Segment (TCP) / Datagram (UDP) | Port Numbers (16-bit, 0–65535)                | TCP, UDP, SCTP, QUIC                                       | End hosts, L4 Content/Application Switches, Stateful firewalls   |
| <b>Layer 3: Network</b>      | Packet                         | Logical IP (IPv4 32-bit, IPv6 128-bit)        | IPv4, IPv6, ICMP, ICMPv6, ARP, OSPF, BGP                   | Routers, Layer 3 Multilayer Switches                             |
| <b>Layer 2: Data Link</b>    | Frame (with FCS Trailer)       | Physical MAC (48-bit hex)                     | Ethernet (802.3), Wi-Fi (802.11)                           | Layer 2 Switches, NICs, Bridges, WAPs                            |
| <b>Layer 1: Physical</b>     | Bits                           | None (Physical Signals)                       | 1000BASE-T, 10GBASE-SR, 802.11 RF                          | Hubs, Repeaters, Cabling, Transceivers, PHY chips                |

## 2. Layer 1: Physical Layer Architecture

Layer 1 coordinates the transmission of unstructured raw binary bitstreams across physical transmission media via electrical voltages, optical pulses, or radio frequencies.

- **Media Types:** Twisted-pair copper (Cat5e/6/6a UTP/STP), Fiber optic (Single-mode for long-haul lasers, Multimode for local LEDs/VCSELs), Wireless radio waves (2.4 GHz, 5 GHz, 6 GHz).
- **Line Encoding:** Converts binary 1s and 0s into media transitions (e.g. Manchester encoding for 10BASE-T, PAM-4 pulse amplitude modulation for 10Gbps Ethernet).
- **Cabling Standards:** TIA/EIA-568A and TIA/EIA-568B pinout configurations for RJ-45 connectors. Straight-through cables connect dissimilar devices (PC to Switch); Crossover cables connect similar devices (Switch to Switch). Modern switches support Auto-MDIX to eliminate crossover cable requirements.
- **Physical Topologies:**
  - **Star:** Central switch/hub. Most scalable; single cable failure affects only one host. Switch is single point of failure.
  - **Mesh:** Interconnected redundant paths. Highest fault tolerance; expensive cabling.
  - **Bus:** Single backbone terminated with resistors. A single break halts the whole segment.
  - **Ring:** Sequential token-passing loop. Single break halts communication unless dual-ring (FDDI).

### 3. Layer 2: Data Link Layer & Ethernet II Framing

Layer 2 manages local hop-to-hop communication within a single broadcast domain or subnet. It packages network packets into **frames**, governs media access (CSMA/CD on shared copper, CSMA/CA on Wi-Fi), and validates transmission integrity.

#### MAC Hardware Addressing (48 Bits / 6 Bytes)

Every NIC possesses a burned-in MAC address formatted as six pairs of hexadecimal digits (e.g., `00:1A:2B:3C:4D:5E`):

- **OUI (Organizationally Unique Identifier):** First 24 bits (3 octets) assigned by the IEEE to identify the hardware vendor.
- **Device ID / Extension Identifier:** Last 24 bits assigned uniquely by the vendor to the NIC.
- **Address Scopes:** Unicast (individual NIC), Multicast (starts with `01:00:5E` for IPv4), Broadcast (`FF:FF:FF:FF:FF:FF`).

#### Ethernet II Frame Specification (with FCS Trailer)

| Field Name                         | Length            | Offset           | Purpose & Description                                                                                                   |
|------------------------------------|-------------------|------------------|-------------------------------------------------------------------------------------------------------------------------|
| Preamble                           | 7 Bytes (56 bits) | Bytes -8 to -2   | Alternating <code>10101010</code> pattern for receiver clock synchronization.                                           |
| Start of Frame Delimiter (SFD)     | 1 Byte (8 bits)   | Byte -1          | Binary <code>10101011</code> ; signals the immediate start of destination MAC.                                          |
| Destination MAC                    | 6 Bytes (48 bits) | Bytes 0 to 5     | Physical address of destination interface on local link.                                                                |
| Source MAC                         | 6 Bytes (48 bits) | Bytes 6 to 11    | Physical address of sender interface. Inspected by switches to populate CAM table.                                      |
| EtherType                          | 2 Bytes (16 bits) | Bytes 12 to 13   | Identifies encapsulated L3 protocol: <code>0x0800</code> (IPv4), <code>0x86DD</code> (IPv6), <code>0x0806</code> (ARP). |
| Payload (L3 SDU)                   | 46 to 1500 Bytes  | Bytes 14 to 1513 | Encapsulated IP packet. Minimum 46 bytes (padded to ensure 64-byte minimum frame size).                                 |
| Frame Check Sequence (FCS Trailer) | 4 Bytes (32 bits) | Trailing 4B      | <b>32-bit Cyclic Redundancy Check (CRC-32) calculated across the entire frame.</b>                                      |

#### ★ Architectural Principle: Why Only Layer 2 Has a Physical Trailer

As bits stream serially out of a transmitting NIC, dedicated hardware shift-registers compute the CRC-32 polynomial continuously on the fly across the payload. Placing the FCS at the tail allows the receiving NIC to evaluate the CRC simultaneously as the last bit arrives over the wire. If a bit error occurred, the NIC hardware drops the corrupted frame immediately before spending CPU cycles or allocating host operating system RAM.

## MTU, VLAN Tagging, and Jumbo Frames

- **Standard MTU:** 1500 bytes (standard Ethernet frame: 64 to 1518 bytes).
- **VLAN Tagging (IEEE 802.1Q):** Inserts a 4-byte VLAN tag between Source MAC and EtherType, increasing maximum frame size to 1522 bytes.
- **Jumbo Frames:** Supported by enterprise data centers and SANs; allows MTUs up to 9,198 bytes to reduce CPU packet-processing overhead.

## Address Resolution Protocol (ARP - RFC 826)

Bridges Layer 2 and Layer 3 by resolving known IPv4 addresses to physical MAC addresses.

- **ARP Request:** Sent as a broadcast ( `FF:FF:FF:FF:FF:FF` ) asking "Who owns IP X.X.X.X? Tell my MAC."
- **ARP Reply:** Returned as a unicast directly to the requester containing the target's MAC address.
- **ARP Table:** Contains Dynamic entries (learned automatically via broadcasts, expired via aging timers) and Static entries (manually pinned with `arp -s` ).
- **Security Concerns:** Duplicate MAC addresses cause switch CAM table fluttering; ARP spoofing redirects traffic to an attacker by sending unsolicited ARP replies.

## 4. Layer 3: Network Layer, IP Addressing & Routing Architecture

Layer 3 provides logical host addressing and determines optimal end-to-end paths across interconnected networks (internetworking).

### IPv4 Header (RFC 791) — 20 to 60 Bytes

| Field              | Bits  | Description                                                                                  |
|--------------------|-------|----------------------------------------------------------------------------------------------|
| Version            | 4     | Always 0100 (4).                                                                             |
| IHL                | 4     | Internet Header Length in 32-bit words (minimum 5 words = 20 bytes).                         |
| DSCP / ECN         | 6 / 2 | Differentiated Services (QoS priority) and Explicit Congestion Notification.                 |
| Total Length       | 16    | Total packet size (header + data) in bytes (up to 65,535 bytes).                             |
| Identification     | 16    | Unique ID assigned to reassemble fragmented IP packets at the destination.                   |
| Flags              | 3     | Bit 0: Reserved (0), Bit 1: DF (Don't Fragment), Bit 2: MF (More Fragments).                 |
| Fragment Offset    | 13    | Offset of fragment relative to beginning of original datagram (in 8-byte units).             |
| Time to Live (TTL) | 8     | Hop limit decremented by 1 at every router hop. Prevents endless routing loops.              |
| Protocol           | 8     | Encapsulated L4 protocol: 1 (ICMP), 6 (TCP), 17 (UDP), 89 (OSPF).                            |
| Header Checksum    | 16    | 1's complement sum covering header only. Recalculated at every router hop as TTL decrements. |
| Source IP          | 32    | Originating host IPv4 address.                                                               |
| Destination IP     | 32    | Target host IPv4 address.                                                                    |

### IPv6 Header (RFC 8200) — Fixed 40 Bytes

Streamlined base header with fixed 40-byte length. Eliminates router fragmentation (handled by source) and eliminates the header checksum to accelerate hardware forwarding.

- **Key Fields:** Version (4b), Traffic Class (8b), Flow Label (20b, identifies real-time streaming flows), Payload Length (16b), Next Header (8b, points to L4 protocol or chained Extension Header), Hop Limit (8b, replaces TTL), Source IPv6 (128b), Destination IPv6 (128b).
- **Neighbor Discovery Protocol (NDP):** Replaces ARP and ICMP broadcast functions in IPv6 using multicast ICMPv6 messages (Router Solicitation/Advertisement, Neighbor Solicitation/Advertisement).

## IPv4 Address Classes & Special Scopes

| Class / Scope    | Address Range                             | Default CIDR        | Purpose & Characteristic                                     |
|------------------|-------------------------------------------|---------------------|--------------------------------------------------------------|
| Class A          | 1.0.0.0 – 126.255.255.255                 | /8 (255.0.0.0)      | 126 networks, 16.7M hosts/network.                           |
| Class B          | 128.0.0.0 – 191.255.255.255               | /16 (255.255.0.0)   | 16,384 networks, 65,534 hosts/network.                       |
| Class C          | 192.0.0.0 – 223.255.255.255               | /24 (255.255.255.0) | 2.09M networks, 254 hosts/network.                           |
| Class D          | 224.0.0.0 – 239.255.255.255               | N/A                 | Multicast traffic (delivering packets to subscribed groups). |
| Class E          | 240.0.0.0 – 254.255.255.255               | N/A                 | Experimental / Research.                                     |
| Loopback         | 127.0.0.1 – 127.255.255.254               | /8                  | Internal host self-reference.                                |
| APIPA            | 169.254.0.1 – 169.254.255.254             | /16                 | Self-assigned when DHCP server is unreachable.               |
| RFC 1918 Private | 10.0.0.0/8, 172.16.0.0/12, 192.168.0.0/16 | Various             | Non-routable on public Internet; requires NAT/PAT.           |

## Routing Protocols & Router Roles (Chapter 4)

- **Router Roles:**
  - *Core / Interior Routers:* Direct traffic within the interior of an Autonomous System (AS).
  - *Edge / Border Routers:* Positioned at AS perimeter to interface with external networks.
  - *Exterior Routers:* Direct traffic between separate Autonomous Systems across the Internet.
- **Multilayer Switching (Layer 3 Switches):** Routes packets via hardware ASICs at wire speed, offering greater throughput and lower latency than traditional software routers on campus LANs.
- **Routing Protocols:**
  - **RIP / RIPv2 (IGP):** Distance-vector; uses hop count metric (max 15 hops; 16 = unreachable). Periodic 30s broadcast updates.
  - **OSPF (IGP):** Link-state; uses Dijkstra's Shortest Path First (SPF) algorithm, areas, and bandwidth cost metric. Fast convergence, no hop limit.
  - **IS-IS (IGP):** Link-state; preferred by core ISPs for massive scalability and native IPv6 support.
  - **EIGRP (IGP):** Advanced distance-vector / hybrid; uses DUAL algorithm and composite metric (bandwidth + delay).
  - **BGP (EGP):** Path-vector; the "Protocol of the Internet", connecting Autonomous Systems using policies and AS-Path attributes.
- **Administrative Distance (AD):** Protocol trustworthiness rating (lower wins): Connected (0), Static (1), eBGP (20), EIGRP (90), OSPF (110), RIP (120).

## 5. Layer 4: Transport Layer, TCP vs. UDP & Sockets

Layer 4 enables end-to-end process-to-process communication between applications using port addressing. A **Socket** represents an endpoint process: `[IP Address] : [Port Number]` .

### IANA Port Number Ranges

- **Well-Known Ports (0–1023):** Assigned to core server processes (e.g., 20/21 FTP, 22 SSH, 23 Telnet, 25 SMTP, 53 DNS, 80 HTTP, 110 POP3, 443 HTTPS, 3389 RDP).
- **Registered Ports (1024–49151):** Registered for commercial applications (e.g., 1433 MSSQL, 3306 MySQL).
- **Dynamic / Private / Ephemeral Ports (49152–65535):** Assigned dynamically by client OSs for outbound sessions.

### TCP vs. UDP Deep Comparison

| Feature                   | TCP (Transmission Control Protocol)                  | UDP (User Datagram Protocol)                      |
|---------------------------|------------------------------------------------------|---------------------------------------------------|
| Connection State          | Connection-oriented (Requires 3-way Handshake)       | Connectionless (Fire-and-forget, no handshake)    |
| Reliability               | Guaranteed delivery (Retransmits lost segments)      | Best-effort (No loss detection or retransmission) |
| Ordering                  | Strictly ordered via 32-bit Sequence Numbers         | Packets may arrive out-of-order                   |
| Header Size               | 20 to 60 Bytes                                       | Fixed 8 Bytes                                     |
| Checksum                  | Mandatory (IPv4 & IPv6)                              | Optional in IPv4, Mandatory in IPv6               |
| Flow & Congestion Control | Sliding Windows, Slow Start, Congestion Avoidance    | None (Transmits at application rate)              |
| Primary Use Cases         | Web (HTTP/S), Email (SMTP), File Transfer (FTP), SSH | DNS queries, DHCP, VoIP, Live Video, Gaming       |

### TCP Segment Header Fields (20 to 60 Bytes)

- **Source & Destination Ports (16b each):** Identifies sending and receiving processes.
- **Sequence Number (32b):** Tracks byte stream position. Initial ISN randomized during handshake.
- **Acknowledgment Number (32b):** Next expected byte sequence number from peer when ACK flag is set.
- **Data Offset (4b):** Header length in 32-bit words (5 words = 20 bytes).
- **9 Control Flags (9b):** `SYN` (initiate connection), `ACK` (acknowledgment valid), `FIN` (graceful close), `RST` (reset connection), `PSH` (push data immediately to app), `URG` (urgent pointer valid), `ECE` / `CWR` (congestion notifications), `NS` (nonce sum).
- **Window Size (16b):** Flow control; number of bytes receiver can buffer without acknowledgment.
- **Checksum (16b):** Verifies pseudo-header (IPs, protocol), TCP header, and payload.

## TCP 3-Way Handshake & Graceful Teardown

```
Client (192.168.1.105:52144)          Server (93.184.216.34:80)
CLOSED                                LISTEN
|                                     |
| ----- [SYN] Seq=1000, Ack=0 -----> | (SYN-RCVD)
(SYN-SENT)                             |
| <----- [SYN, ACK] Seq=5000, Ack=1001 ----- |
|                                     |
(ESTABLISHED)                           |
| ----- [ACK] Seq=1001, Ack=5001 -----> | (ESTABLISHED)
|                                     |
| ===== Full-Duplex Data Transmission ===== |
|                                     |
| ----- [FIN, ACK] Seq=1025, Ack=5001 -----> | (CLOSE-WAIT)
(FIN-WAIT-1)                             |
| <----- [ACK] Seq=5001, Ack=1026 ----- |
(FIN-WAIT-2)                             |
| <----- [FIN, ACK] Seq=5001, Ack=1026 ----- | (LAST-ACK)
|                                     |
| ----- [ACK] Seq=1026, Ack=5002 -----> | (CLOSED)
(TIME-WAIT: 2MSL)                       |
|                                     |
(CLOSED)
```

## 6. Layer 5: Session Layer Architecture

---

Layer 5 establishes, manages, synchronizes, and gracefully terminates dialogues (sessions) between communicating applications on separate hosts. While modern TCP/IP implementations often embed session semantics within application protocols or transport security, the OSI model formally isolates session state management from transport delivery.

### Dialogue Control & Directionality

The session layer coordinates which endpoint is permitted to transmit at any given time:

- **Simplex:** Unidirectional data flow. One station transmits exclusively while the receiving station consumes data with no return channel (e.g., automated broadcast telemetry, radio sensor monitoring).
- **Half-Duplex:** Bidirectional transmission, but strictly alternating. Both endpoints can communicate, but only one direction is active at any single moment. The session layer employs software tokens (e.g., Data Token) to control turn-taking and prevent collisions (e.g., classic walkie-talkie communication, HTTP/1.1 request-response alternation).
- **Full-Duplex:** Simultaneous bidirectional communication. Both endpoints send and receive concurrently over independent channel paths without turn-taking (e.g., modern TCP sockets, WebSockets, VoIP calls).

### Checkpoint Synchronization & Fault Recovery

In long-duration data exchanges (such as multi-gigabyte file transfers or distributed database transactions), the session layer inserts synchronization points into the data stream:

- **Major Synchronization Points:** Atomically commit completed transaction phases. Explicit acknowledgement from the receiving entity is required before transmission continues across a major boundary.
- **Minor Synchronization Points:** Periodic interim checkpoints placed throughout a transfer. If a link disconnects or an error occurs, communicating endpoints roll back and resume transmission from the last verified minor checkpoint rather than restarting the entire transfer from byte zero.

#### Modern Implementation Note: Layer 5 in the TCP/IP Stack

In the Internet Protocol Suite, Layer 5 functionality is folded into application-layer frameworks and security protocols:

- **RPC (Remote Procedure Call, RFC 1831):** Manages client-server session state, parameter marshalling, and unique transaction XIDs.
- **SOCKS5 (RFC 1928):** Provides generic session-level authentication, proxy negotiation, and UDP/TCP circuit relaying.
- **TLS 1.3 Session Resumption:** Session Tickets and Pre-Shared Key (PSK) handshakes permit clients to resume previous sessions with 0-RTT latency without full re-authentication.
- **SIP (Session Initiation Protocol, RFC 3261):** Establishes, modifies, and terminates multimedia sessions (VoIP, video conferencing).

## 7. Layer 6: Presentation Layer Architecture

Layer 6 ensures that data transmitted from the application layer of one host can be parsed, interpreted, and understood by the application layer of another host across heterogeneous computer architectures, operating systems, and character sets.

### Abstract Syntax vs. Transfer Syntax

Layer 6 decouples the internal representation of data structures from their wire format:

- **Abstract Syntax:** The conceptual, platform-independent description of data structures (e.g., ASN.1 schemas, Protocol Buffer `.proto` definitions, or internal programming language object graphs).
- **Transfer Syntax:** The standardized, canonical byte-level encoding negotiated for physical transmission on the wire (e.g., ASN.1 BER/DER, Protobuf varint binary wire format, or Canonical XDR).

### Endianness & Network Byte Order

Heterogeneous CPU architectures store multibyte integer values with differing byte significance. To prevent misinterpretation of binary packet headers, standard network protocols enforce a canonical ordering:

- **Big-Endian (Network Byte Order):** The Most Significant Byte (MSB) is placed at the lowest memory address and transmitted first over the wire (standardized by RFC 1700 for all IP, TCP, and UDP headers).
- **Little-Endian (Host Byte Order):** The Least Significant Byte (LSB) is stored at the lowest memory address (standard in x86\_64 and ARM processors).
- **POSIX Standard Conversion Routines:** `htons()` (Host to Network Short, 16-bit), `htonl()` (Host to Network Long, 32-bit), `ntohs()` (Network to Host Short), `ntohl()` (Network to Host Long).

### Data Serialization & Encoding Comparison

| Format           | Encoding Type                 | Wire Efficiency                | Schema Requirement                     | Primary Use Cases                                       |
|------------------|-------------------------------|--------------------------------|----------------------------------------|---------------------------------------------------------|
| JSON             | Textual (UTF-8)               | Moderate (verbose string keys) | Optional (JSON Schema)                 | Public REST APIs, Web applications, configuration       |
| ASN.1 (DER)      | Binary (Type-Length-Value)    | High (deterministic, compact)  | Strict (ASN.1 Definition)              | X.509 Digital Certificates, TLS Handshake, Cryptography |
| Protocol Buffers | Binary (Varints & Field Tags) | Very High (minimal payload)    | Strict (Compiled <code>.proto</code> ) | gRPC microservices, internal high-throughput RPCs       |
| XDR (RFC 4506)   | Binary (4-Byte Aligned)       | High (fixed padding)           | Strict (RFC Specification)             | NFS (Network File System), Sun RPC                      |

### Cryptographic Presentation (TLS 1.3 Record Layer)

In modern secure architectures, encryption and data transformation are handled by the **TLS 1.3 Record Layer** (RFC 8446). Application plaintext is encapsulated into TLS records, encrypted via Authenticated Encryption with Associated Data (AEAD) ciphers (such as AES-256-GCM or ChaCha20-Poly1305), and tagged with a 16-byte authentication tag ensuring confidentiality, authenticity, and tamper detection.

## 8. Layer 7: Application Layer Protocols

Layer 7 interfaces directly with end-user software applications and human operators, exposing standardized protocols for web navigation, hierarchical domain resolution, automatic dynamic network configuration, remote administration, and electronic mail.

### Web Protocol Evolution Matrix

| Feature / Dimension   | HTTP/1.1 (RFC 2616)                          | HTTP/2 (RFC 7540)                         | HTTP/3 (RFC 9114)                            |
|-----------------------|----------------------------------------------|-------------------------------------------|----------------------------------------------|
| Transport Layer       | TCP                                          | TCP                                       | QUIC (UDP-based)                             |
| Framing Architecture  | Plaintext textual (CRLF delimited)           | Binary framing (Frames & Streams)         | Binary QUIC Streams                          |
| Multiplexing          | No (Pipelining causes Head-of-Line blocking) | Multiplexed streams over 1 TCP connection | Fully independent multiplexed streams        |
| Head-of-Line Blocking | Application-level blocking                   | TCP packet loss stalls all streams        | Zero Head-of-Line blocking (Stream-isolated) |
| Header Compression    | None (verbose repeated headers)              | HPACK (static & dynamic table)            | QPACK (out-of-order stream safe)             |
| Connection Handshake  | 1 RTT TCP + 1–2 RTT TLS                      | 1 RTT TCP + 1 RTT TLS 1.3                 | 0–1 RTT Unified QUIC + TLS 1.3               |

### Hierarchical DNS Resolution Architecture

The Domain Name System (DNS, RFC 1035) is a globally distributed, hierarchical database operating over UDP/TCP Port 53. Resolution proceeds through three primary tiers:

- **1. Root Nameserver Tier:** 13 logical root server IP addresses (named `a.root-servers.net` through `m.root-servers.net`), coordinated by ICANN and distributed worldwide across hundreds of Anycast nodes. Root servers direct queries to appropriate TLD servers.
- **2. Top-Level Domain (TLD) Tier:** Authoritative servers for generic TLDs ( `.com` , `.org` , `.net` ) and country-code ccTLDs ( `.us` , `.uk` , `.de` ).
- **3. Authoritative Nameserver Tier:** The definitive nameservers configured by the domain owner holding official zone resource records (A, AAAA, CNAME, MX, TXT, NS).

**Recursive vs. Iterative Queries:** In recursive resolution, the client delegates the full query task to a recursive resolver (e.g., ISP resolver, `1.1.1.1` , `8.8.8.8` ). The recursive resolver performs iterative queries, asking Root → TLD → Authoritative servers step-by-step until the final IP is returned.

### DHCP DORA 4-Way Transaction

Dynamic Host Configuration Protocol (DHCP, RFC 2131) automates IP configuration using a four-step transaction over UDP Port 67 (Server) and Port 68 (Client):

1. **D — Discover (Broadcast):** The unconfigured client broadcasts `DHCPDISCOVER` from `0.0.0.0:68` to `255.255.255.255:67` seeking an active DHCP server.

2. **O — Offer (Unicast / Broadcast):** A DHCP server reserves an available IP and replies with `DHCP OFFER` containing the proposed IP address ( `yiaddr` ), subnet mask, lease duration, default gateway, and DNS servers.
3. **R — Request (Broadcast):** The client broadcasts `DHCP REQUEST` formally requesting the offered lease. Broadcasting notifies the chosen server of acceptance and signals all other DHCP servers to release their reserved offers.
4. **A — Acknowledge (Unicast / Broadcast):** The server writes the lease to its active database and returns `DHCP ACK` , committing the configuration to the client.

### Email Architecture: Store-and-Forward Push vs. Pull

- **SMTP (Simple Mail Transfer Protocol, TCP 25/587):** A **push** protocol used by Mail User Agents (MUAs) to submit messages to an outgoing Mail Submission Agent (MSA) and by Mail Transfer Agents (MTAs) to relay mail across the Internet to destination servers.
- **IMAP (Internet Message Access Protocol, TCP 143 / 993 SSL):** A **pull** protocol that keeps mail stored on the remote mail server. Clients synchronize multiple folders, read status, and message flags dynamically across devices.
- **POP3 (Post Office Protocol v3, TCP 110 / 995 SSL):** A legacy **pull** protocol that downloads messages to a single local client and historically deletes them from the server.

## 9. Network Troubleshooting & Diagnostics Command Reference

| Command                            | OS Platform    | Layer      | Diagnostic Function                                                                                 |
|------------------------------------|----------------|------------|-----------------------------------------------------------------------------------------------------|
| <code>ping &lt;target&gt;</code>   | Cross-platform | Layer 3    | Sends ICMP Echo Requests to verify IP connectivity, NIC binding, and round-trip latency.            |
| <code>ifconfig / ip a</code>       | Linux          | Layer 2–3  | Displays interface link states, hardware MAC addresses, IP bindings, and packet statistics.         |
| <code>ipconfig /all</code>         | Windows        | Layer 2–3  | Full TCP/IP configuration, DHCP lease time, DNS servers, and link-local IPv6 addresses.             |
| <code>arp -a</code>                | Cross-platform | Layer 2    | Displays ARP cache table mapping destination IPv4 addresses to local hardware MAC addresses.        |
| <code>route print / route</code>   | Cross-platform | Layer 3    | Displays the host routing table, default gateway ( <code>0.0.0.0</code> ), and next-hop interfaces. |
| <code>netstat -tuln / ss</code>    | Cross-platform | Layer 4    | Lists all active listening TCP and UDP sockets with bound port numbers.                             |
| <code>tracert / traceroute</code>  | Cross-platform | Layer 3    | Traces hop-by-hop router path by transmitting packets with incrementing TTL values.                 |
| <code>pathping</code>              | Windows        | Layer 3    | Combines ping and tracert over 100+ seconds to isolate per-hop packet loss and latency.             |
| <code>tcpdump</code>               | Linux          | Layers 2–4 | CLI packet analyzer that captures live frame headers, handshakes, and payloads crossing a NIC.      |
| <code>curl [-I] &lt;url&gt;</code> | Cross-platform | Layer 7    | HTTP/1.1 and HTTP/2 client diagnostic tool; inspects HTTP response status codes and headers.        |
| <code>openssl s_client</code>      | Cross-platform | Layer 6    | Connects to TLS endpoints; dumps certificate chains, negotiated cipher suites, and AEAD tags.       |
| <code>dhclient -v</code>           | Linux          | Layer 7    | Forces DHCP client lease renewal, displaying full DORA broadcast exchange on the terminal.          |
| <code>ssh [-v] &lt;host&gt;</code> | Cross-platform | Layer 7    | Establishes encrypted interactive remote shell over TCP port 22 with key-exchange verification.     |

## 10. Complete 7-Layer Summary Checklist for CSCI 250 Examination

- **✓ Complete 7-Layer Sequence (7 → 1):** Application (L7) → Presentation (L6) → Session (L5) → Transport (L4) → Network (L3) → Data Link (L2) → Physical (L1).
- **✓ PDU Taxonomy:** Data / Messages (L7–5) → Segments/Datagrams (L4) → Packets (L3) → Frames (L2) → Bits (L1).
- **✓ Trailer Exclusivity:** Only Layer 2 uses an FCS trailer (CRC-32) because hardware NIC transceivers calculate CRC on-the-fly as bits stream across the wire.

- **✓ Layer 5 Dialogue:** Simplex (one-way), Half-Duplex (turn-taking with tokens), Full-Duplex (simultaneous both ways). Major checkpoints commit; minor checkpoints recover.
- **✓ Layer 6 Presentation:** Standardizes Network Byte Order (Big-Endian, MSB first) via `htons()` / `ntohl()`, serializes schemas (ASN.1 DER, Protobuf), and encrypts payloads via TLS 1.3 AEAD records.
- **✓ Layer 7 Evolution:** HTTP/1.1 (ASCII text, pipeline HOL blocking) → HTTP/2 (binary frames, single TCP stream multiplexing) → HTTP/3 (QUIC over UDP, zero transport HOL blocking).
- **✓ DNS Hierarchy:** Root Nameservers (13 clusters) → TLD Nameservers ( `.com` ) → Authoritative Nameservers. Iterative vs. recursive query models.
- **✓ DHCP DORA:** Discover (Broadcast) → Offer (Unicast/Broadcast) → Request (Broadcast) → Acknowledge (Unicast/Broadcast).
- **✓ Email Routing:** SMTP (TCP 25/587) pushes mail between servers; IMAP (TCP 993) pulls and synchronizes mailbox state across devices.
- **✓ Transport Differences:** TCP is connection-oriented, reliable, sequenced, and heavier (20–60B header); UDP is connectionless, lightweight (8B header), and fire-and-forget.
- **✓ Socket Composition:** `IP_Address` : `Port_Number` (e.g. `192.168.1.100:443` ).
- **✓ APIPA Range:** `169.254.0.0/16` automatically assigned when DHCP negotiation fails.
- **✓ Routing Classifications:** Distance-Vector (RIP, max 15 hops) vs. Link-State (OSPF, Dijkstra SPF algorithm, bandwidth metric) vs. Path-Vector (BGP, Autonomous Systems).