

The Proton utility can be deployed in several ways on Ubuntu 14:

1. Using a puppet master.

- Download the puppet folder for Proton, and work in the **puppet/modules/cep** folder there. You can download single folder from github using **svn**:
`svn checkout https://github.com/ishkin/Proton.git/trunk/puppet`
- We assume the puppet master environment is already installed and working.
- Change the files permissions: `chmod 644 ./manifests/*.pp ./files/*` and `chmod +x ./files/download_artifacts.ksh`.
- Install the APT module on your master (e.g. `puppet module install puppetlabs-apt`), make sure its location is accessible to the client (via the **modulepath** puppet settings). It is possible that you will need to copy, or make soft links to that location.
- Run once the script `./files/download_artifacts.ksh` on the puppet master - to get the updated version of CEP *.war files into the same folder, e.g. `./files/`.
- Add the CEP module to the client manifests (e.g. "include cep").
- The tomcat admin/manager passwords are randomly generated during the artifacts download stage (e.g. when running the `./files/download_artifacts.ksh` in the puppet master). They are used during the clients' deployment. Steps should be taken if different password for each machine is needed.
- Rerunning the `./files/download_artifacts.ksh` in the puppet master will download a new version of CEP which will be pushed to all the puppet clients.

2. Using a standalone puppet client

- Download the puppet folder for Proton (see fist bullet above, e.g. into the **/tmp/** folder, than work in the **puppet/modules/cep** folder).
- Install the **puppet-module-puppetlabs-apt** package (e.g. run `sudo apt-get install puppet-module-puppetlabs-apt`)
- Change the files permissions: `chmod 644 ./manifests/*.pp ./files/*` and `chmod +x ./files/download_artifacts.ksh`.
- Make sure the **/etc/hosts** file contain an entry with the local machine hostname
- Install CEP using puppet. Note that the <puppet_modules_path> should point to the full path of your newly created module folder (e.g. `"/tmp/puppet/modules"`):
`sudo /usr/bin/puppet apply --parser future --modulepath=<puppet_modules_path>:/etc/puppet/modules:/usr/share/puppet/modules -e 'include cep' --debug`

3. Install via a shell script:

- The user running the script should be able to run **sudo** commands without a password prompt.
- Download the **CEP_Install_via_puppet.sh** script file from gitub at *puppet/miscellaneous/* folder and execute it.
- The script will download all the necessary files to the same folder it's on, install and configure