

Cordova Test Suite User Guide

Version 1.0

Copyright © 2014 Intel Corporation. All rights reserved. No portions of this document may be reproduced without the written permission of Intel Corporation.

Intel is a trademark of Intel Corporation in the U.S. and/or other countries.

Linux is a registered trademark of Linus Torvalds.

Tizen® is a registered trademark of The Linux Foundation.

ARM is a registered trademark of ARM Holdings Plc.

*Other names and brands may be claimed as the property of others.

Any software source code reprinted in this document is furnished under a software license and may only be used or copied in accordance with the terms of that license.

Contents

1	Introduction.....	3
2	Cordova Web Testing Architecture	3
3	Install testkit-lite on Host.....	4
4	Crosswalk based Cordova System Requirements.....	4
5	Crosswalk based Cordova Developer Tools	4
6	Cordova Mobile Spec Test on Crosswalk based Cordova.....	5
7	Web Runtime and Web API Test on Crosswalk based Cordova	9


1 Introduction

This document provides method to run Crosswalk based Cordova Test Suite. Currently the target platform is Android only. You can use the following method to run it with testkit-lite. Testkit tool-chain includes 3 components:

- testkit-lite: a command-line interface application deployed on Host
- testkit-stub: a test stub application deployed on Device
- tinyweb: a web service application deployed on Device

2 Cordova Web Testing Architecture

- Cordova Web Testing on Android
- Architecture



There are two types of Webapi tests:

- Web service dependent

Client side is a stub test package which link to remote web runner, no local TCs and web runner, thus avoid cross origin issue.

Server side includes tinyweb, webrunner and TCs.

- Web service independent

Self contained test package which include all things - web runner, TCs.

3 Install testkit-lite on Host

- Deploy testkit-lite
 - Install dependency python-requests (version>1.0)
\$ sudo apt-get install python-pip
\$ sudo pip install requests
 - Install testkit-lite from source code in GitHub
\$ git clone git@github.com:testkit/testkit-lite.git
\$ cd testkit-lite && sudo python setup.py install

4 Crosswalk based Cordova System Requirements

- Java JDK 1.5 or greater
<http://www.oracle.com/technetwork/java/javase/downloads/index.html>
- Apache ANT 1.8.0 or greater <http://ant.apache.org/bindownload.cgi>
- Android SDK <http://developer.android.com>
- Python 2.7 or greater <https://www.python.org/download/>

5 Crosswalk based Cordova Developer Tools

The Cordova developer tooling is split between general tooling and project level tooling.

- General Commands

`./bin/create [path package activity]`

create the `./example` app or a cordova android project

`./bin/check_reqs`

checks that your environment is set up for cordova-android development

`./bin/update [path]`

updates an existing cordova-android project to the version of the framework

- Project Commands

`./cordova/clean`

cleans the project

`./cordova/build`

calls ``clean`` then compiles the project

`./cordova/log`

stream device or emulate logs to stdout

`./cordova/run`

calls ``build`` then deploys to a connected Android device. If no Android device is detected, will launch an emulator and deploy to it.

`./cordova/version`

returns the cordova-android version of the current project

6 Cordova Mobile Spec Test on Crosswalk based Cordova

- Build and run Cordova Mobile Spec test build (named as `cordova_mobile_spec-debug.apk`) on Android

1. Extract `XWalkCoreLibrary` in Crosswalk builds

Download crosswalk builds from

<https://download.01.org/crosswalk/releases/android-x86/canary/crosswalk-<version>-x86.zip>

<https://download.01.org/crosswalk/releases/android-arm/canary/crosswalk-<version>-arm.zip>

```
$ unzip crosswalk-<version>-arm.zip <path>/
```

```
$ tar zxvf /path/to/crosswalk-<version>-arm/xwalk_core_library.tar.gz
```

2. Checkout crosswalk-cordova-android

```
$ git clone https://github.com/crosswalk-project/crosswalk-cordova-android.git
```

3. Update branches when you test on target versions if needed, the default is the master branch.

```
$ cd crosswalk-cordova-android
```

```
$ git branch
```

Sometimes you may need to switch to targeted branches, if not, please use default branch.

```
$ git checkout -b crosswalk-4 origin/crosswalk-4
```

Please check the detailed available branch list via "git branch -a", the "crosswalk-4" etc., branches keep updating by developer.

4. Import XWalkCoreLibrary by linking it to framework folder of crosswalk-cordova-android

```
$ ln -s /path/to/xwalk_core_library /path/to/crosswalk-cordova-android/framework/
```

Make sure there is only one xwalk_core_library folder rather than xwalk_core_library/xwalk_core_library under /framework/.

5. Fetch Cordova Mobile Spec test cases:

```
$ git clone git@github.com:apache/cordova-mobile-spec.git
```

```
$ cd cordova-mobile-spec
```

```
$ git checkout -b 3.3.0 3.3.0
```

6. Create mobile spec app:

```
$ /path/to/crosswalk-cordova-android/bin/create mobilespeg org.apache.mobilespec  
mobilespec --shared
```

```
$ cd mobilespeg
```

```
$ cp -r /path/to/cordova-mobile-spec/* assets/www (Please don't accept to overwrite the cordova.js)
```

```
$ cp -r /path/to/cordova-mobile-spec/config.xml res/xml/config.xml
```

7. Set up Cordova Mobile Spec plugins environment. Recommend to use plugman to install plugins. You need to have [node.js](#) installed. Then install plugman by:

```
$ npm install -g plugman
```

8. Add Cordova Mobile Spec plugins for Crosswalk based Cordova, please refer to [full supported plugin list](#):

```
$ cd mobilespeg
```

```
$ plugman install --platform android --project ./ --plugin https://git-wip-us.apache.org/repos/asf/cordova-plugin-device.git#r0.2.5
```

```
$ plugman install --platform android --project ./ --plugin https://git-wip-us.apache.org/repos/asf/cordova-plugin-network-information.git#r0.2.5
```

```
$ plugman install --platform android --project ./ --plugin https://git-wip-us.apache.org/repos/asf/cordova-plugin-battery-status.git#r0.2.5
```

```
$ plugman install --platform android --project ./ --plugin https://git-wip-us.apache.org/repos/asf/cordova-plugin-device-motion.git#r0.2.4
```

```
$ plugman install --platform android --project ./ --plugin https://git-wip-us.apache.org/repos/asf/cordova-plugin-device-orientation.git#r0.3.3
```

```
$ plugman install --platform android --project ./ --plugin https://git-wip-us.apache.org/repos/asf/cordova-plugin-geolocation.git#r0.3.4
```

```
$ plugman install --platform android --project ./ --plugin https://git-wip-us.apache.org/repos/asf/cordova-plugin-media.git#r0.2.6
```

```
$ plugman install --platform android --project ./ --plugin https://git-wip-us.apache.org/repos/asf/cordova-plugin-file.git#r0.2.5
```

```
$ plugman install --platform android --project ./ --plugin https://git-wip-us.apache.org/repos/asf/cordova-plugin-file-transfer.git#r0.4.0
```

```
$ plugman install --platform android --project ./ --plugin https://git-wip-us.apache.org/repos/asf/cordova-plugin-dialogs.git#r0.2.4
```

```
$ plugman install --platform android --project ./ --plugin https://git-wip-us.apache.org/repos/asf/cordova-plugin-splashscreen.git#r0.2.5
```

```
$ plugman install --platform android --project ./ --plugin https://git-wip-
```

```
us.apache.org/repos/asf/cordova-plugin-console.git#r0.2.5
$ plugman install --platform android --project ./ --plugin https://git-wip-
us.apache.org/repos/asf/cordova-plugin-camera.git#r0.2.5
$ plugman install --platform android --project ./ --plugin https://git-wip-
us.apache.org/repos/asf/cordova-plugin-media-capture.git#r0.2.8
$ plugman install --platform android --project ./ --plugin https://git-wip-
us.apache.org/repos/asf/cordova-plugin-vibration.git#r0.3.5
$ plugman install --platform android --project ./ --plugin https://git-wip-
us.apache.org/repos/asf/cordova-plugin-globalization.git#r0.2.4
$ plugman install --platform android --project ./ --plugin https://git-wip-
us.apache.org/repos/asf/cordova-plugin-contacts.git#r0.2.5
$ plugman install --platform android --project ./ --plugin https://git-wip-
us.apache.org/repos/asf/cordova-plugin-inappbrowser.git#r0.2.4
$ plugman install --platform android --project ./ --plugin assets/www/cordova-plugin-
whitelist
```

9. According to [Splash Screen API](#) Spec, you may need to add following statement into the onCreate method of the class that extends DroidGap:

```
super.setIntegerProperty\("splashscreen", R.drawable.splash\);
in /path/to/mobilespec/src/org/apache/mobilespec/mobilespec.java
```

The .java file path maps to package activity etc., package parameters in step 6
"mobilespec org.apache.mobilespec mobilespec"

```
public void onCreate(Bundle savedInstanceState)
{
    super.onCreate(savedInstanceState);
    super.init();
    super.setIntegerProperty\("splashscreen", R.drawable.splash\);
    super.loadUrl(Config.getStartUrl());
}
```

10. Connect the Android test device to host (adb enabled), build and run:

```
$ cd /path/to/mobilespec
```



```
$ ./cordova/build
```

Add “--debug” switch if “remote debugging” feature is needed to run the test

```
$ ./cordova/build --debug
```

```
$ ./cordova/run
```

- The alternate way is copy test apk from /path/to/mobilespec/bin/mobile_spec-debug.apk to device, install it.
- Run Cordova API (Cordova Mobile Spec) test cases in app on test device.

7 Web Runtime and Web API Test on Crosswalk based Cordova

- Download Crosswalk binaries from:
<https://download.01.org/crosswalk/releases/android-x86/canary/crosswalk-<version>-x86.zip>
<https://download.01.org/crosswalk/releases/android-arm/canary/crosswalk-<version>-arm.zip>
- In Web Runtime testing, there are two methods to build test builds base on two kinds of test sources:

Build Crosswalk based Cordova app with cordova.tar.gz (there should be cordova.tar.gz in crosswalk-<version>-x86/arm.zip, but it's not ready in download.01.org)

1. Unzip cordova.tar.gz extracted from crosswalk-<version>-x86/arm.zip

```
tar zxvf /path/to/cordova.tar.gz
```

2. `/path/to/crosswalk-cordova-android/bin/create testapp com.example.testapp
testapp --shared`
3. `$ cd testapp`
4. Copy web source code (e.g. index.html with some contents) to assets/www
5. `./cordova/build`
6. `./cordova/run`

If you can't get cordova.tar.gz in decompressed crosswalk-<version>-x86/arm.zip, please refer to the steps as below:

1. Extract XWalkCoreLibrary in Crosswalk builds

Download crosswalk builds from

<https://download.01.org/crosswalk/releases/android-x86/canary/crosswalk-<version>-x86.zip>

<https://download.01.org/crosswalk/releases/android-arm/canary/crosswalk-<version>-arm.zip>

`$ unzip crosswalk-<version>-arm.zip <path>/`

`$ tar zxvf /path/to/crosswalk-<version>-arm/xwalk_core_library.tar.gz`

2. Checkout crosswalk-cordova-android

`$ git clone https://github.com/crosswalk-project/crosswalk-cordova-android.git`

11. Update branches when you test on target versions if needed, the default is the master branch.

`$ cd crosswalk-cordova-android`

`$ git branch`

Sometimes you may need to switch to targeted branches, if not, please use default branch.

`$ git checkout -b crosswalk-4 origin/crosswalk-4`

Please check the detailed available branch list via "git branch -a", the "crosswalk-4" etc., branches keep updating by developer.

3. Import XWalkCoreLibrary by linking it to framework folder of crosswalk-cordova-android

```
$ ln -s /path/to/xwalk_core_library /path/to/crosswalk-cordova-  
android/framework/
```

Make sure there is only one xwalk_core_library folder rather than xwalk_core_library/xwalk_core_library under /framework/.

The steps 1~4 are equal to unzipped cordova.tar.gz.

4. /path/to/crosswalk-cordova-android/bin/create testapp com.example.testapp testapp --shared
5. \$ cd testapp
6. Copy web source code (e.g. index.html with some contents) to assets/www
7. ./cordova/build
8. ./cordova/run

- Set Permissions

Some HTML5 APIs which access devices require developers to set appropriate permissions in AndroidManifest.xml to work correctly. For example, if your app calls getUserMedia, it needs to add

```
<uses-permission android:name="android.permission.RECORD_AUDIO" />  
<uses-permission android:name="android.permission.CAMERA" />
```

into AndroidManifest.xml in /path/to/testapp folder.

The Cordova Mobile Spec test doesn't need testkit-lite etc., tools to run the test, but for Web Runtime and Web API tests, please run the following steps:

- Deploy testkit-stub and launch it

- Make binary for testkit-stub from source code in GitHub

```
$ git clone git@github.com:testkit/testkit-stub.git
```

```
$ cd testkit-stub/android/jni/ && /path/to/android-ndk-dir/ndk-build
```

- Import project testkit-stub to Android developer Tool by location testkit-stub/android
- Build the project and install APK to android device
\$ adb install /path/to/testkit-stub/bin/testkit-stub.apk
- Launch testkit-stub by clicking the testkit-stub App icon in launcher

- Deploy tinyweb and launch it
 - Make binaries for tinyweb from source code in GitHub
\$ git clone git@github.com:testkit/tinyweb.git
\$ cd tinyweb/android/native/jni/ && /path/to/android-ndk-dir/ndk-build
 - Copy tinyweb/android/native/libs/ to folder testkit-stub/android/assets/system/libs/
 - Import project tinyweb to Android developer Tool by location tinyweb /android
 - Build the project and install APK to android device
\$ adb install /path/to/tinyweb/bin/tinywebservice.apk
 - Launch tinyweb by clicking the tinyweb app icon in launcher

- Pack test suite package
Please see ***Web_Test_Suite_Packaging_Guide***, Chapter 3.1 "*Pack Web Test Suite Packages for Android*", detailed steps for Cordova test suites package are added.
Note: For Android device, the default APK package mode of Crosswalk based Cordova is embedded mode.

- Install test suite on Android device
\$ unzip -o <test_suite_name>.apk.zip -d ~/ xwalk_suites/
\$ ~/xwalk_suites/opt/<test_suite_name>/inst.sh

- Launch web test with lite
\$ testkit-lite -f ~/ xwalk_suites/opt/<test_suite_name>/tests.xml --comm
androidmobile

- Uninstall test suite

```
$ ~/xwalk_suites/opt/<test_suite_name>/inst.sh -u
```